

# FCC Radio Test Report

## FCC ID: IR5DH8

**Report No.** : BTL-FCCP-2-2205T007  
**Equipment** : HANDHELD COMPUTER  
**Model Name** : DH8  
**Brand Name** : MilDef Crete Inc.  
**Applicant** : MilDef Crete Inc.  
**Address** : 7F, No.250, Sec.3, PeiShen Rd., Shen Keng District, New Taipei City, Taiwan

**Radio Function** : Bluetooth Low Energy 5.2

**FCC Rule Part(s)** : FCC CFR Title 47, Part 15, Subpart C  
**Measurement Procedure(s)** : ANSI C63.10-2013

**Date of Receipt** : 2022/5/16  
**Date of Test** : 2022/5/16 ~ 2022/6/10  
**Issued Date** : 2022/8/25

The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.

**Prepared by** : Eric Lee  
Eric Lee, Engineer

**Approved by** : Jerry Chuang  
Jerry Chuang, Supervisor

**BTL Inc.**

No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan

Tel: +886-2-2657-3299

Fax: +886-2-2657-3331

Web: [www.newbtl.com](http://www.newbtl.com)

**Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

**BTL's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

**BTL's** laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

**BTL** is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

**Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

**CONTENTS**

1	SUMMARY OF TEST RESULTS	5
1.1	TEST FACILITY	6
1.2	MEASUREMENT UNCERTAINTY	6
1.3	TEST ENVIRONMENT CONDITIONS	6
1.4	TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	6
2	GENERAL INFORMATION	7
2.1	DESCRIPTION OF EUT	7
2.2	TEST MODES	9
2.3	BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.4	SUPPORT UNITS	11
3	AC POWER LINE CONDUCTED EMISSIONS TEST	12
3.1	LIMIT	12
3.2	TEST PROCEDURE	12
3.3	DEVIATION FROM TEST STANDARD	12
3.4	TEST SETUP	13
3.5	TEST RESULT	13
4	RADIATED EMISSIONS TEST	14
4.1	LIMIT	14
4.2	TEST PROCEDURE	15
4.3	DEVIATION FROM TEST STANDARD	15
4.4	TEST SETUP	15
4.5	EUT OPERATING CONDITIONS	16
4.6	TEST RESULT – BELOW 30 MHZ	17
4.7	TEST RESULT – 30 MHZ TO 1 GHZ	17
4.8	TEST RESULT – ABOVE 1 GHZ	17
5	OUTPUT POWER TEST	18
5.1	LIMIT	18
5.2	TEST PROCEDURE	18
5.3	DEVIATION FROM STANDARD	18
5.4	TEST SETUP	18
5.5	EUT OPERATION CONDITIONS	18
5.6	TEST RESULTS	18
6	LIST OF MEASURING EQUIPMENTS	19
7	EUT TEST PHOTO	20
8	EUT PHOTOS	20
APPENDIX A	AC POWER LINE CONDUCTED EMISSIONS	21
APPENDIX B	RADIATED EMISSIONS - 30 MHZ TO 1 GHZ	26
APPENDIX C	RADIATED EMISSIONS - ABOVE 1 GHZ	29
APPENDIX D	OUTPUT POWER	46

**REVISION HISTORY**

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-2-2205T007	R00	Original Report.	2022/8/2	Invalid
BTL-FCCP-2-2205T007	R01	Revised report to address TCB's comments.	2022/8/25	Valid

## 1 SUMMARY OF TEST RESULTS

Test procedures according to the technical standards.

Standard(s) Section	Description	Test Result	Judgement	Remark
15.207	AC Power Line Conducted Emissions	APPENDIX A	Pass	-----
15.205 15.209 15.247(d)	Radiated Emissions	APPENDIX B APPENDIX C	Pass	-----
15.247(a)(2)	Bandwidth	NOTE (3)	Pass	-----
15.247(b)(3)	Output Power	APPENDIX D	Pass	-----
15.247(e)	Power Spectral Density	NOTE (3)	Pass	-----
15.247(d)	Antenna conducted Spurious Emission	NOTE (3)	Pass	-----
15.203	Antenna Requirement	-----	Pass	-----

**NOTE:**

- (1) "N/A" denotes test is not applicable in this Test Report.
- (2) The report format version is TP.1.1.1.
- (3) This is to request a Class II permissive change for FCC ID: IR5DH8 (This FCC ID is change ID based on Intel Mobile Communications, the original application information follow as model: AX210NGW, FCC ID: PD9AX210NG, approved on 05/25/2022)  
The major change filed under this application is disable RLAN 5 GHz (U-NII 2a, U-NII 2c, U-NII 3) and U-NII 6 GHz.  
Since the RF module has been certificated, after evaluation, above test items were criticized and reconfirmed in this report, for other test data can be refer report No.: 200611-03.TR04.
- (4) After spot check, this revision does not change original radio parameters.

### 1.1 TEST FACILITY

The test facilities used to collect the test data in this report:

No. 68-1, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

The test sites and facilities are covered under FCC RN: 674415 and DN: TW0659.

- C05       CB08       CB11       CB15       CB16  
 SR05

### 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k = 2$ , providing a level of confidence of approximately **95 %**. The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2. The BTL measurement uncertainty is less than the CISPR 16-4-2  $U_{cispr}$  requirement.

#### A. AC power line conducted emissions test:

Test Site	Method	Measurement Frequency Range	U (dB)
C05	CISPR	150 kHz ~ 30MHz	3.44

#### B. Radiated emissions test :

Test Site	Measurement Frequency Range	U,(dB)
CB15	0.03 GHz ~ 0.2 GHz	4.17
	0.2 GHz ~ 1 GHz	4.72
	1 GHz ~ 6 GHz	5.21
	6 GHz ~ 18 GHz	5.51
	18 GHz ~ 26 GHz	3.69
	26 GHz ~ 40 GHz	4.23

#### C. Conducted test :

Test Item	U,(dB)
Output Power	0.3669

#### NOTE:

Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

### 1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Environment Condition	Test Voltage	Tested by
AC Power Line Conducted Emissions	19 °C, 51 %	AC 120V	Ronald Kao
Radiated emissions below 1 GHz	Refer to data	AC 120V	Eddie Lee
Radiated emissions above 1 GHz	Refer to data	AC 120V	Eddie Lee
Output Power	22.3 °C, 52 %	AC 120V	Angela Wang

### 1.4 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

Test Software	DRTU V22.21090.0.0			
Modulation Mode	2402 MHz	2440 MHz	2480 MHz	Data Rate
BLE 5.2	36	36	36	1 Mbps
BLE 5.2	36	36	36	2 Mbps

## 2 GENERAL INFORMATION

### 2.1 DESCRIPTION OF EUT

Equipment	HANDHELD COMPUTER
Model Name	DH8
Brand Name	MilDef Crete Inc.
Model Difference	N/A
Power Source	#1 DC voltage supplied from External Power Supply. #2 Supplied from battery.
Power Rating	#1 I/P: 100-240V~50-60Hz 1.5A MAX. O/P: 5.0V---3.0A 15.0W or 9.0V---3.0A 27.0W or 12.0V---3.0A 36.0W or 15.0V---3.0A 45.0W or 20.0V---3.0A 60.0W #2 7.2V---2500mAh/18Wh
Products Covered	1 * Adapter: ADAPTER TECH / CDP060A1-P200 1 * Battery: BDH82A
WIFI+BT Module	Intel / AX210NGW
Operation Band	2400 MHz ~ 2483.5 MHz
Operation Frequency	2402 MHz ~ 2480 MHz
Maximum Output Power	1 Mbps: 9.66 dBm (0.0092 W) 2 Mbps: 9.96 dBm (0.0099 W)
Test Model	DH8
Sample Status	Engineering Sample
EUT Modification(s)	N/A

**NOTE:**

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

## (2) Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454
07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

## (3) Table for Filed Antenna:

Antenna	Manufacture	Part Number	Type	Connector	Frequency Range (MHz)	Gain (dBi)
WLAN&BT Antenna	N/A	G983190000	PIFA	N/A	2400	-1.46
					2450	2.33
					2500	0.19



**2.2 TEST MODES**

Test Items	Test mode	Channel	Note
AC power line conducted emissions	Normal/Idle	-	-
Transmitter Radiated Emissions (below 1GHz)	2 Mbps	19	-
Transmitter Radiated Emissions (above 1GHz)	1, 2 Mbps	00/39	Bandedge
	1, 2 Mbps	00/19/39	Harmonic
Output Power	1, 2 Mbps	00/19/39	-


**NOTE:**

- (1) The Radiated emissions test was verified based on the worst conducted power and Bandwidth test results reported in the original report.
- (2) For radiated emission band edge test, both Vertical and Horizontal are evaluated, but only the worst case (Horizontal) is recorded.
- (3) All X, Y and Z axes are evaluated, but only the worst case (X axis) is recorded.


**2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED**

Equipment letters and Cable numbers refer to item numbers described in the tables of clause 2.4.

AC Power Line Conducted Emissions Test



Radiated Emissions Test



**2.4 SUPPORT UNITS**

Item	Equipment	Brand	Model No.	Series No.	Remarks
A	Adapter	ADAPTER TECH	CDP060A1-P200	N/A	Supplied by test requester.

Item	Shielded	Ferrite Core	Length	Cable Type	Remarks
1	N/A	N/A	1.8m	Power Cord	Supplied by test requester.

### 3 AC POWER LINE CONDUCTED EMISSIONS TEST

#### 3.1 LIMIT

Frequency (MHz)	Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56 *	56 - 46 *
0.50 - 5.0	56	46
5.0 - 30.0	60	50

**NOTE:**

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.
- (3) The test result calculated as following:  
 Measurement Value = Reading Level + Correct Factor  
 Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor (if use)  
 Margin Level = Measurement Value – Limit Value  
 Calculation example:

Reading Level		Correct Factor		Measurement Value
38.22	+	3.45	=	41.67

Measurement Value		Limit Value		Margin Level
41.67	-	60	=	-18.33

The following table is the setting of the receiver.

Receiver Parameter	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

#### 3.2 TEST PROCEDURE

- a. The EUT was placed 0.8 m above the horizontal ground plane with the EUT being connected to the power mains through a line impedance stabilization network (LISN).  
 All other support equipment were powered from an additional LISN(s).  
 The LISN provides 50 Ohm/50uH of impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle to keep the cable above 40 cm.
- c. Excess I/O cables that are not connected to a peripheral shall be bundled in the center.  
 The end of the cable will be terminated, using the correct terminating impedance.  
 The overall length shall not exceed 1 m.
- d. The LISN is spaced at least 80 cm from the nearest part of the EUT chassis.
- e. For the actual test configuration, please refer to the related Item - EUT TEST PHOTO.


**NOTE:**

- (1) In the results, each reading is marked as Peak, QP or AVG per the detector used.  
 BW=9 kHz (6 dB Bandwidth)
- (2) All readings are Peak unless otherwise stated QP or AVG in column of Note. Both the QP and the AVG readings must be less than the limit for compliance.

#### 3.3 DEVIATION FROM TEST STANDARD

No deviation.

### 3.4 TEST SETUP



### 3.5 TEST RESULT

Please refer to the APPENDIX A.

## 4 RADIATED EMISSIONS TEST

### 4.1 LIMIT

In case the emission fall within the restricted band specified on 15.205, then the 15.209 limit in the table below has to be followed.

#### LIMITS OF RADIATED EMISSIONS MEASUREMENT (9 kHz to 1000 MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

#### LIMITS OF RADIATED EMISSIONS MEASUREMENT (Above 1000 MHz)

Frequency (MHz)	Radiated Emissions (dBuV/m)		Measurement Distance (meters)
	Peak	Average	
Above 1000	74	54	3

#### NOTE:

- (1) The limit for radiated test was performed according to FCC Part 15, Subpart C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following:

Measurement Value = Reading Level + Correct Factor

Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)

Margin Level = Measurement Value - Limit Value

Calculation example:

Reading Level		Correct Factor		Measurement Value
19.11	+	2.11	=	21.22

Measurement Value		Limit Value		Margin Level
21.22	-	54	=	-32.78

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average

Spectrum Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz~110KHz for QP detector
Start ~ Stop Frequency	110KHz~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector


#### 4.2 TEST PROCEDURE

- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m or 1.5 m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- i. For the actual test configuration, please refer to the related Item – EUT TEST PHOTO.


#### 4.3 DEVIATION FROM TEST STANDARD

No deviation.


#### 4.4 TEST SETUP



### 30 MHz to 1 GHz



### Above 1 GHz



#### 4.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.



**4.6 TEST RESULT – BELOW 30 MHZ**

There were no emissions found below 30 MHz within 20 dB of the limit.

**4.7 TEST RESULT – 30 MHZ TO 1 GHZ**

Please refer to the APPENDIX B.

**4.8 TEST RESULT – ABOVE 1 GHZ**

Please refer to the APPENDIX C.

**NOTE:**

- (1) No limit: This is fundamental signal, the judgment is not applicable.  
For fundamental signal judgment was referred to Peak output test.

## 5 OUTPUT POWER TEST

### 5.1 LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Maximum Output Power	1 watt or 30dBm	2400-2483.5	PASS


### 5.2 TEST PROCEDURE

- The EUT was directly connected to the power meter and antenna output port as show in the block diagram below.
- The maximum peak conducted output power was performed in accordance with method 9 b) of FCC KDB 558074 D01 DTS Meas Guidance.

### 5.3 DEVIATION FROM STANDARD

No deviation.

### 5.4 TEST SETUP



### 5.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

### 5.6 TEST RESULTS

Please refer to the APPENDIX D.

## 6 LIST OF MEASURING EQUIPMENTS

AC Power Line Conducted Emissions						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	TWO-LINE V-NETWORK	R&S	ENV216	101051	2022/3/29	2023/3/28
2	Test Cable	EMCI	EMCCFD300-BM-BMR-6000	170714	2022/5/2	2023/5/1
3	EMI Test Receiver	R&S	ESR 7	101433	2021/11/24	2022/11/23
4	Measurement Software	EZ	EZ EMC (Version NB-03A1-01)	N/A	N/A	N/A

Radiated Emissions						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Preamplifier	EMCI	EMC02325	980217	2022/4/6	2023/4/5
2	Preamplifier	EMCI	EMC012645B	980222	2022/4/6	2023/4/5
3	Preamplifier	EMCI	EMC001340	980555	2022/4/6	2023/4/5
4	Test Cable	EMCI	EMC104-SM-1000	180809	2022/4/6	2023/4/5
5	Test Cable	EMCI	EMC104-SM-SM-2500	160413	2022/4/6	2023/4/5
6	Test Cable	EMCI	EMC-SM-SM-7000	180408	2022/4/6	2023/4/5
7	Signal Analyzer	Agilent	N9010A	MY56480554	2021/8/25	2022/8/24
8	Loop Ant	Electro-Metrics	EMCI-LPA600	274	2021/6/1	2022/5/31
9	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D-1333	2021/11/18	2022/11/17
10	Horn Ant	Schwarzbeck	BBHA 9170	340	2021/7/9	2022/7/8
11	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	9168-352	2021/8/11	2022/8/10
12	5dB Attenuator	EMCI	EMCI-N-6-05	AT-N0625	2021/8/11	2022/8/10
13	Measurement Software	EZ	EZ EMC (Version NB-03A1-01)	N/A	N/A	N/A

Output Power						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Power Meter	Anritsu	ML2487A	6K00004714	2021/8/15	2022/8/14
2	Power Sensor	Anritsu	MA2491A	034138	2021/8/15	2022/8/14

Remark: "N/A" denotes no model name, no serial no. or no calibration specified.  
All calibration period of equipment list is one year.

**7 EUT TEST PHOTO**


Please refer to document Appendix No.: TP-2205T007-FCCP-1 (APPENDIX-TEST PHOTOS).

**8 EUT PHOTOS**

Please refer to document Appendix No.: EP-2205T007-1 (APPENDIX-EUT PHOTOS).

## **APPENDIX A AC POWER LINE CONDUCTED EMISSIONS**

Test Mode	Normal	Tested Date	2022/5/27
Test Frequency	-	Phase	Line




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1522	47.10	9.67	56.77	65.88	-9.11	QP	
2		0.1522	33.50	9.67	43.17	55.88	-12.71	AVG	
3		0.2220	29.60	9.67	39.27	62.74	-23.47	QP	
4		0.2220	5.80	9.67	15.47	52.74	-37.27	AVG	
5		0.2985	30.90	9.66	40.56	60.28	-19.72	QP	
6		0.2987	17.00	9.66	26.66	50.28	-23.62	AVG	
7		0.3997	24.80	9.67	34.47	57.86	-23.39	QP	
8		0.3997	12.90	9.67	22.57	47.86	-25.29	AVG	
9		2.5778	16.50	9.83	26.33	56.00	-29.67	QP	
10		2.5778	4.20	9.83	14.03	46.00	-31.97	AVG	
11		3.1514	16.70	9.86	26.56	56.00	-29.44	QP	
12		3.1514	3.60	9.86	13.46	46.00	-32.54	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	Normal	Tested Date	2022/5/27
Test Frequency	-	Phase	Neutral




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1522	47.10	9.67	56.77	65.88	-9.11	QP	
2		0.1522	34.00	9.67	43.67	55.88	-12.21	AVG	
3		0.1864	33.50	9.66	43.16	64.20	-21.04	QP	
4		0.1864	10.90	9.66	20.56	54.20	-33.64	AVG	
5		0.2513	31.00	9.65	40.65	61.71	-21.06	QP	
6		0.2513	18.30	9.65	27.95	51.71	-23.76	AVG	
7		0.3502	25.10	9.66	34.76	58.96	-24.20	QP	
8		0.3502	13.50	9.66	23.16	48.96	-25.80	AVG	
9		0.5595	18.70	9.69	28.39	56.00	-27.61	QP	
10		0.5595	9.10	9.69	18.79	46.00	-27.21	AVG	
11		2.6115	17.00	9.83	26.83	56.00	-29.17	QP	
12		2.6115	4.50	9.83	14.33	46.00	-31.67	AVG	

**REMARKS:**

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	Idle	Tested Date	2022/5/27
Test Frequency	-	Phase	Line




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1522	47.30	9.67	56.97	65.88	-8.91	QP	
2		0.1522	33.90	9.67	43.57	55.88	-12.31	AVG	
3		0.1995	37.80	9.67	47.47	63.63	-16.16	QP	
4		0.1995	23.70	9.67	33.37	53.63	-20.26	AVG	
5		0.3030	31.70	9.65	41.35	60.16	-18.81	QP	
6		0.3030	20.10	9.65	29.75	50.16	-20.41	AVG	
7		0.4087	24.70	9.67	34.37	57.67	-23.30	QP	
8		0.4087	12.60	9.67	22.27	47.67	-25.40	AVG	
9		0.6673	16.80	9.70	26.50	56.00	-29.50	QP	
10		0.6673	3.60	9.70	13.30	46.00	-32.70	AVG	
11		2.5013	15.10	9.83	24.93	56.00	-31.07	QP	
12		2.5013	4.20	9.83	14.03	46.00	-31.97	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.



Test Mode	Idle	Tested Date	2022/5/27
Test Frequency	-	Phase	Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1522	47.20	9.67	56.87	65.88	-9.01	QP	
2		0.1522	34.00	9.67	43.67	55.88	-12.21	AVG	
3		0.1793	36.30	9.66	45.96	64.52	-18.56	QP	
4		0.1793	14.00	9.66	23.66	54.52	-30.86	AVG	
5		0.2063	37.20	9.66	46.86	63.35	-16.49	QP	
6		0.2063	21.10	9.66	30.76	53.35	-22.59	AVG	
7		0.2962	30.50	9.65	40.15	60.35	-20.20	QP	
8		0.2962	15.30	9.65	24.95	50.35	-25.40	AVG	
9		0.6765	15.30	9.70	25.00	56.00	-31.00	QP	
10		0.6765	2.30	9.70	12.00	46.00	-34.00	AVG	
11		2.7938	18.00	9.84	27.84	56.00	-28.16	QP	
12		2.7938	5.50	9.84	15.34	46.00	-30.66	AVG	


**REMARKS:**

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

## **APPENDIX B RADIATED EMISSIONS - 30 MHZ TO 1 GHZ**

Test Mode	BLE 5.2 (1 Mbps)	Test Date	2022/5/26
Test Frequency	2440MHz	Polarization	Vertical
Temp	23°C	Hum.	67%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		112.7733	36.18	-11.93	24.25	43.50	-19.25	peak	
2		176.7933	35.29	-10.12	25.17	43.50	-18.33	peak	
3		305.8680	35.08	-8.10	26.98	46.00	-19.02	peak	
4		443.5433	33.41	-4.29	29.12	46.00	-16.88	peak	
5		563.7910	31.75	-2.20	29.55	46.00	-16.45	peak	
6	*	749.1257	30.04	1.49	31.53	46.00	-14.47	peak	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.2 (1 Mbps)	Test Date	2022/5/26
Test Frequency	2440MHz	Polarization	Horizontal
Temp	23°C	Hum.	67%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		112.7733	36.84	-11.93	24.91	43.50	-18.59	peak	
2		176.8902	38.44	-10.13	28.31	43.50	-15.19	peak	
3		329.7623	39.95	-7.54	32.41	46.00	-13.59	peak	
4		443.3816	36.93	-4.30	32.63	46.00	-13.37	peak	
5		755.3983	32.59	1.57	34.16	46.00	-11.84	peak	
6	*	831.8343	32.19	2.55	34.74	46.00	-11.26	peak	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

## **APPENDIX C RADIATED EMISSIONS - ABOVE 1 GHZ**

Test Mode	BLE 5.2 (1 Mbps)	Test Date	2022/5/24
Test Frequency	2402MHz	Polarization	Horizontal
Temp	22°C	Hum.	66%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2344.787	26.14	31.06	57.20	74.00	-16.80	peak	
2		2344.787	13.33	31.06	44.39	54.00	-9.61	AVG	
3	X	2402.000	72.69	31.24	103.93	74.00	29.93	peak	NoLimit
4	*	2402.000	72.04	31.24	103.28	54.00	49.28	AVG	NoLimit
5		2502.000	25.86	31.57	57.43	74.00	-16.57	peak	
6		2502.000	3.19	31.57	34.76	54.00	-19.24	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.2 (1 Mbps)	Test Date	2022/5/24
Test Frequency	2480MHz	Polarization	Horizontal
Temp	22°C	Hum.	66%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2388.127	26.26	31.20	57.46	74.00	-16.54	peak	
2		2388.127	2.88	31.20	34.08	54.00	-19.92	AVG	
3	X	2480.000	74.34	31.50	105.84	74.00	31.84	peak	NoLimit
4	*	2480.000	73.80	31.50	105.30	54.00	51.30	AVG	NoLimit
5		2490.767	27.61	31.53	59.14	74.00	-14.86	peak	
6		2490.767	14.26	31.53	45.79	54.00	-8.21	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.2 (2 Mbps)	Test Date	2022/5/27
Test Frequency	2402MHz	Polarization	Horizontal
Temp	24°C	Hum.	61%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2353.207	26.95	31.09	58.04	74.00	-15.96	peak	
2		2353.207	13.32	31.09	44.41	54.00	-9.59	AVG	
3	X	2402.000	71.76	31.24	103.00	74.00	29.00	peak	NoLimit
4	*	2402.000	70.97	31.24	102.21	54.00	48.21	AVG	NoLimit
5		2491.060	27.08	31.53	58.61	74.00	-15.39	peak	
6		2491.060	3.06	31.53	34.59	54.00	-19.41	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.



Test Mode	BLE 5.2 (2 Mbps)	Test Date	2022/5/27
Test Frequency	2480MHz	Polarization	Horizontal
Temp	24°C	Hum.	61%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2381.747	26.17	31.18	57.35	74.00	-16.65	peak	
2		2381.747	3.28	31.18	34.46	54.00	-19.54	AVG	
3	X	2480.000	74.16	31.50	105.66	74.00	31.66	peak	NoLimit
4	*	2480.000	72.69	31.50	104.19	54.00	50.19	AVG	NoLimit
5		2483.913	26.79	31.50	58.29	74.00	-15.71	peak	
6		2483.913	17.70	31.50	49.20	54.00	-4.80	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.2 (1 Mbps)	Test Date	2022/5/24
Test Frequency	2402MHz	Polarization	Vertical
Temp	22°C	Hum.	66%




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.000	45.48	-0.09	45.39	74.00	-28.61	peak	
2	*	4804.000	33.69	-0.09	33.60	54.00	-20.40	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.2 (1 Mbps)	Test Date	2022/5/24
Test Frequency	2402MHz	Polarization	Horizontal
Temp	22°C	Hum.	66%




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.000	44.30	-0.09	44.21	74.00	-29.79	peak	
2	*	4804.000	33.14	-0.09	33.05	54.00	-20.95	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.2 (1 Mbps)	Test Date	2022/5/24
Test Frequency	2440MHz	Polarization	Vertical
Temp	22°C	Hum.	66%




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4880.000	47.06	0.05	47.11	74.00	-26.89	peak	
2	*	4880.000	37.46	0.05	37.51	54.00	-16.49	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.2 (1 Mbps)	Test Date	2022/5/24
Test Frequency	2440MHz	Polarization	Horizontal
Temp	22°C	Hum.	66%




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4880.000	44.00	0.05	44.05	74.00	-29.95	peak	
2	*	4880.000	34.97	0.05	35.02	54.00	-18.98	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.2 (1 Mbps)	Test Date	2022/5/24
Test Frequency	2480MHz	Polarization	Vertical
Temp	22°C	Hum.	66%




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4960.000	44.44	0.20	44.64	74.00	-29.36	peak	
2	*	4960.000	35.15	0.20	35.35	54.00	-18.65	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.2 (1 Mbps)	Test Date	2022/5/24
Test Frequency	2480MHz	Polarization	Horizontal
Temp	22°C	Hum.	66%




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4960.000	44.86	0.20	45.06	74.00	-28.94	peak	
2	*	4960.000	34.05	0.20	34.25	54.00	-19.75	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.2 (2 Mbps)	Test Date	2022/5/27
Test Frequency	2402MHz	Polarization	Vertical
Temp	24°C	Hum.	61%




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.000	44.32	-0.09	44.23	74.00	-29.77	peak	
2	*	4804.000	34.39	-0.09	34.30	54.00	-19.70	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.



Test Mode	BLE 5.2 (2 Mbps)	Test Date	2022/5/27
Test Frequency	2402MHz	Polarization	Horizontal
Temp	24°C	Hum.	61%




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.000	44.55	-0.09	44.46	74.00	-29.54	peak	
2	*	4804.000	35.50	-0.09	35.41	54.00	-18.59	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.2 (2 Mbps)	Test Date	2022/5/27
Test Frequency	2440MHz	Polarization	Vertical
Temp	24°C	Hum.	61%




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4880.000	43.90	0.05	43.95	74.00	-30.05	peak	
2	*	4880.000	34.59	0.05	34.64	54.00	-19.36	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.2 (2 Mbps)	Test Date	2022/5/27
Test Frequency	2440MHz	Polarization	Horizontal
Temp	24°C	Hum.	61%




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4880.000	45.00	0.05	45.05	74.00	-28.95	peak	
2	*	4880.000	35.04	0.05	35.09	54.00	-18.91	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.2 (2 Mbps)	Test Date	2022/5/27
Test Frequency	2480MHz	Polarization	Vertical
Temp	24°C	Hum.	61%




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4960.000	46.06	0.20	46.26	74.00	-27.74	peak	
2	*	4960.000	34.06	0.20	34.26	54.00	-19.74	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.2 (2 Mbps)	Test Date	2022/5/27
Test Frequency	2480MHz	Polarization	Horizontal
Temp	24°C	Hum.	61%



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4960.000	44.37	0.20	44.57	74.00	-29.43	peak	
2	*	4960.000	34.30	0.20	34.50	54.00	-19.50	AVG	

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

## APPENDIX D OUTPUT POWER

Test Mode :	BLE 5.2 (1Mbps)	Tested Date	2022/5/30
-------------	-----------------	-------------	-----------

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	9.55	0.0090	30.00	1.0000	Pass
2440	9.60	0.0091	30.00	1.0000	Pass
2480	9.66	0.0092	30.00	1.0000	Pass

Test Mode :	BLE5.0 (2Mbps)	Tested Date	2022/5/30
-------------	----------------	-------------	-----------

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	9.88	0.0097	30.00	1.0000	Pass
2440	9.96	0.0099	30.00	1.0000	Pass
2480	9.84	0.0096	30.00	1.0000	Pass

**End of Test Report**