

APPENDIX: FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Standard Applicable

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength	Magnetic Field Strength	Power Density (mw/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Test Data

Predication of MPE limit at a given distance: $S = PG/4\pi R^2$

Where:

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Items	Value
Maximum peak output power at antenna input terminal:	18.72 (dBm)
Maximum peak output power at antenna input terminal:	74.47(mW)
Prediction distance:	>20 (cm)
Predication frequency:	2448 (MHz)
Antenna Gain (typical):	1.2 (dBi)
Maximum Antenna Gain:	1.32 (numeric)
MPE limit for general population exposure at prediction frequency:	1.0 (mW/cm ²)
The worst case power density at predication frequency at 20 cm:	0.0196 (mW/cm ²)

Result:

The predicted power density level at 20 cm is 0.0196 mw/cm² which is below the uncontrolled exposure limit of 1.0 mw/cm², The EUT is used at least 20 cm away from user's body. It is determined as mobile equipment and complies with the MPE limit.