







Fig.34 Conducted Spurious Emission (802.11b, CH6)





Fig.35 Conducted Spurious Emission (802.11b, CH11)



Fig.36 Conducted Spurious Emission (802.11g, CH1)

No. I18N00940-WLAN Page 37 of 66









Fig.38 Conducted Spurious Emission (802.11g, CH11)





Fig.39 Conducted Spurious Emission (802.11n HT20, CH1)



Fig.40 Conducted Spurious Emission (802.11n HT20, CH6)





Fig.41 Conducted Spurious Emission (802.11n HT20, CH11)



Fig.42 Conducted Spurious Emission (802.11n HT40, CH3)





Fig.43 Conducted Spurious Emission (802.11n HT40, CH6)



Fig.44 Conducted Spurious Emission (802.11n HT40, CH9)



A.6 Radiated Emission

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209 &	20dD below peok output nower
RSS-247 Section 5.5/RSS-Gen 6.13	200B below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission	Field atranath(u)//m)	Measurement
(MHz)	Field Strength(µV/III)	distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Condition:

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission	RBW/VBW	Sweep Time(s)
(MHz)		
30-1000	120kHz/300kHz	5
1000-4000	1MHz/3MHz	15
4000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

Note:

According to the performance evaluation, the radiated emission margin of EUT is over 20dB in the band below 30MHz. Therefore, the measurement starts from 30MHz to tenth harmonic. The measurement results include the horizontal polarization and vertical polarization measurements.



Measurement Results:

SISO	(Antenna	0):	
------	----------	-----	--

Mode	Channel	Frequency Range	Test Results	Conclusion
	CH 1	1 GHz ~18 GHz	Fig.45	Р
	CH 6	1 GHz ~18 GHz	Fig.46	Р
802.11b	CH 11	1 GHz ~18 GHz	Fig.47	Р
	Restricted Band (CH1)	2.38 GHz ~ 2.45 GHz	Fig.48	Р
	Restricted Band (CH11)	2.45 GHz ~ 2.5 GHz	Fig.49	Р
	CH 1	1 GHz ~18 GHz	Fig.50	Р
	CH 6	1 GHz ~18 GHz	Fig.51	Р
802.11g	CH 11	1 GHz ~18 GHz	Fig.52	Р
	Restricted Band (CH1)	2.38 GHz ~ 2.45 GHz	Fig.53	Р
	Restricted Band (CH11)	2.45 GHz ~ 2.5 GHz	Fig.54	Р
802.11n HT20	CH 1	1 GHz ~18 GHz	Fig.55	Р
	CH 6	1 GHz ~18 GHz	Fig.56	Р
	CH 11	1 GHz ~18 GHz	Fig.57	Р
	Restricted Band (CH1)	2.38 GHz ~ 2.45 GHz	Fig.58	Р
	Restricted Band (CH11)	2.45 GHz ~ 2.5 GHz	Fig.59	Р
	CH 3	1 GHz ~18 GHz	Fig.60	Р
000 11m	CH 6	1 GHz ~18 GHz	Fig.61	Р
002.110 UT40	CH 9	1 GHz ~18 GHz	Fig.62	Р
H140	Restricted Band (CH3)	2.38 GHz ~ 2.45 GHz	Fig.63	Р
	Restricted Band (CH9)	2.45 GHz ~ 2.5 GHz	Fig.64	Р
		9 kHz ~30 MHz	Fig.65	Р
/	All Channels	30 MHz ~1 GHz	Fig.66	Р
		18 GHz ~26.5 GHz	Fig.67	Р

MIMO:

Mode	Channel	Frequency Range	Test Results	Conclusion
	CH 1	1 GHz ~18 GHz	Fig.68	Р
802.11n	CH 6	1 GHz ~18 GHz	Fig.69	Р
	CH 11	1 GHz ~18 GHz	Fig.70	Р
п120	Restricted Band (CH1)	2.38 GHz ~ 2.45 GHz	Fig.71	Р
	Restricted Band (CH11)	2.45 GHz ~ 2.5 GHz	Fig.72	Р
802.11n	CH 3	1 GHz ~18 GHz	Fig.73	Р
	CH 6	1 GHz ~18 GHz	Fig.74	Р
	CH 9	1 GHz ~18 GHz	Fig.75	Р
П140	Restricted Band (CH3)	2.38 GHz ~ 2.45 GHz	Fig.76	Р
	Restricted Band (CH9)	2.45 GHz ~ 2.5 GHz	Fig.77	Р
		9 kHz ~30 MHz	Fig.78	Р
/	All Channels	30 MHz ~1 GHz	Fig.79	Р
		18 GHz ~26.5 GHz	Fig.80	Р



Worst-Case Result:

802.11b CH6 (1-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
13904.500000	55.51	74.00	18.49	V	20.8
14677.500000	56.05	74.00	17.95	Н	21.4
15566.500000	60.03	74.00	13.97	Н	23.5
15586.000000	62.02	74.00	11.98	V	23.9
17139.500000	62.79	74.00	11.21	V	26.7
17716.500000	62.94	74.00	11.06	V	27.7

Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
13910.500000	43.94	54.00	10.06	Н	21.1
14688.000000	44.46	54.00	9.54	Н	21.6
15574.000000	48.62	54.00	5.38	Н	23.7
15935.500000	49.98	54.00	4.02	V	24.9
16596.500000	50.86	54.00	3.14	Н	26.3
17705.000000	50.68	54.00	3.32	V	27.6

802.11g CH1 (1GHz-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
13935.500000	55.07	74.00	18.93	V	20.2
14677.500000	56.59	74.00	17.41	V	21.4
15571.000000	60.25	74.00	13.75	Н	23.6
16260.000000	61.49	74.00	12.51	Н	25.3
16605.000000	62.42	74.00	11.58	V	26.1
17718.000000	62.10	74.00	11.90	V	27.7

Frequency	Average	Limit	Margin	Pol	Corr.
(MHz)	(dBuV/m)	(dBuV/m)	(dB)		(dB)
13907.500000	43.40	54.00	10.60	V	21.0
14681.000000	44.27	54.00	9.73	V	21.5
15573.500000	48.45	54.00	5.55	Н	23.7
15937.500000	49.78	54.00	4.22	Н	24.9
17109.000000	50.66	54.00	3.34	Н	26.2
17708.000000	50.40	54.00	3.60	V	27.6

©Copyright. All rights reserved by SAICT



802.11n HT20 CH1 (1GHz-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
13948.000000	54.94	74.00	19.06	V	20.1
14645.000000	55.37	74.00	18.63	V	21.3
15221.500000	59.81	74.00	14.19	Н	22.8
15611.500000	61.22	74.00	12.78	Н	24.0
16583.500000	61.67	74.00	12.33	Н	26.4
17718.500000	61.20	74.00	12.80	Н	27.7

Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
13907.500000	42.80	54.00	11.20	Н	21.0
14656.000000	43.47	54.00	10.53	V	21.3
15570.000000	48.19	54.00	5.81	V	23.6
15936.000000	49.47	54.00	4.53	Н	24.9
16596.000000	50.50	54.00	3.50	V	26.3
17721.500000	49.94	54.00	4.06	V	27.6

802.11n HT40 CH1 (1GHz-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
13912.500000	54.08	74.00	19.92	Н	21.0
14599.500000	56.15	74.00	17.85	V	21.7
15567.500000	59.20	74.00	14.80	Н	23.5
15928.500000	62.03	74.00	11.97	V	24.8
16589.500000	63.01	74.00	10.99	Н	26.3
17731.500000	61.47	74.00	12.53	Н	27.2

Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
13911.000000	42.81	54.00	11.19	V	21.1
14681.000000	43.31	54.00	10.69	V	21.5
15574.000000	48.15	54.00	5.85	V	23.7
15938.500000	49.33	54.00	4.67	Н	24.9
16582.000000	50.42	54.00	3.58	V	26.4
17712.000000	50.07	54.00	3.93	Н	27.7



Note:

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and Antenna Factor, the gain of the preamplifier, the cable loss. P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result= P_{Mea} +Cable Loss +Antenna Factor-Gain of the preamplifier.

See below for test graphs. Conclusion: PASS





Fig.45 Radiated Spurious Emission (802.11b, CH1, 1 GHz-18GHz)



Fig.46 Radiated Spurious Emission (802.11b, CH6, 1 GHz-18GHz)





Fig.47 Radiated Spurious Emission (802.11b, CH11, 1 GHz-18GHz)



Fig.48 Radiated Restricted Band (802.11b, CH1, 2.38GHz~2.45GHz)





Fig.49 Radiated Restricted Band (802.11b, CH11, 2.45GHz~2.5GHz)



Fig.50 Radiated Spurious Emission (802.11g, CH1, 1 GHz-18 GHz)





Fig.51 Radiated Spurious Emission (802.11g, CH6, 1 GHz-18 GHz)



Fig.52 Radiated Spurious Emission (802.11g, CH11, 1 GHz-18 GHz)





Fig.53 Radiated Restricted Band (802.11g, CH1, 2.38GHz~2.45GHz)



Fig.54 Radiated Restricted Band (802.11g, CH11, 2.45GHz~2.5GHz)





Fig.55 Radiated Spurious Emission (802.11n HT20, CH1, 1 GHz-18 GHz)



Fig.56 Radiated Spurious Emission (802.11n HT20, CH6, 1 GHz-18 GHz)





Fig.57 Radiated Spurious Emission (802.11n HT20, CH11, 1 GHz-18 GHz)



Fig.58 Radiated Restricted Band (802.11n HT20, CH1, 2.38GHz~2.45GHz)





Fig.59 Radiated Restricted Band (802.11n HT20, CH11, 2.45GHz~2.5GHz)



Fig.60 Radiated Spurious Emission (802.11n HT40, CH3, 1 GHz-18 GHz)





Fig.61 Radiated Spurious Emission (802.11n HT40, CH6, 1 GHz-18 GHz)



Fig.62 Radiated Spurious Emission (802.11n HT40, CH9, 1 GHz-18 GHz)





Fig.63 Radiated Restricted Band (802.11n HT40, CH1, 2.38GHz~2.45GHz)



Fig.64 Radiated Restricted Band (802.11n HT40, CH11, 2.45GHz~2.5GHz)





Fig.65 Radiated Spurious Emission (All Channels, 9KHz-30 MHz)



Fig.66 Radiated Spurious Emission (All Channels, 30MHz-1 GHz)





Fig.67 Radiated Spurious Emission (All Channels, 18 GHz-26.5 GHz)









Fig.69 Radiated Spurious Emission (802.11n HT20, CH6, 1 GHz-18 GHz)



Fig.70 Radiated Spurious Emission (802.11n HT20, CH11, 1 GHz-18 GHz)









Fig.72 Radiated Restricted Band (802.11n HT20, CH11, 2.45GHz~2.5GHz)





Fig.73 Radiated Spurious Emission (802.11n HT40, CH3, 1 GHz-18 GHz)



Fig.74 Radiated Spurious Emission (802.11n HT40, CH6, 1 GHz-18 GHz)





Fig.75 Radiated Spurious Emission (802.11n HT40, CH9, 1 GHz-18 GHz)



Fig.76 Radiated Restricted Band (802.11n HT40, CH1, 2.38GHz~2.45GHz)





Fig.77 Radiated Restricted Band (802.11n HT40, CH11, 2.45GHz~2.5GHz)



Fig.78 Radiated Spurious Emission (All Channels, 9KHz-30 MHz)





Fig.79 Radiated Spurious Emission (All Channels, 30MHz-1 GHz)



Fig.80 Radiated Spurious Emission (All Channels, 18 GHz-26.5 GHz)



A.7 AC Power line Conducted Emission

Test Condition:

Voltage (V)	Frequency (Hz)
120	60

Measurement Result and limit:

WLAN (Quasi-peak Limit)

Frequency range	Quasi-peak	Result (dBμV)		Conclusion	
(MHz)	Limit (dBμV)	Traffic	Idle	Conclusion	
0.15 to 0.5	66 to 56				
0.5 to 5	56	Fig.81	Fig.82	Р	
5 to 30	60				

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)

Frequency range	Average-peak	Result (dBµV)		Conclusion		
(MHz)	Limit (dBµV)	Traffic	ldle	Conclusion		
0.15 to 0.5	56 to 46					
0.5 to 5	46	Fig 81	Fig 82	Р		
5 to 30	50					
NOTE: The limit degrapped linearly with the legentithm of the frequency in the range						

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Note: The measurement results include the L1 and N measurements.

See below for test graphs.

Conclusion: PASS





Fig.81 AC Power line Conducted Emission (Traffic)

Micasurement it		un				
Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	37.70	66.00	28.30	L1	ON	9.7
0.562000	32.42	56.00	23.58	L1	ON	9.7
0.874000	28.85	56.00	27.15	L1	ON	9.7
1.570000	30.19	56.00	25.81	L1	ON	9.7
3.398000	28.98	56.00	27.02	L1	ON	9.7
3.642000	28.45	56.00	27.55	L1	ON	9.7

Measurement Results: Quasi Peak

Measurement Results: Average

Frequency	Average	PE	Line	Corr.	Margin	Limit
(MHz)	(dBµV)			(dB)	(dB)	(dBµV)
0.550000	23.67	46.00	22.33	L1	ON	9.7
1.990000	20.11	46.00	25.89	L1	ON	9.7
3.366000	19.78	46.00	26.22	L1	ON	9.7
3.670000	19.14	46.00	26.86	L1	ON	9.7
17.342000	26.61	50.00	23.39	Ν	ON	10.2
17.778000	25.11	50.00	24.89	Ν	ON	10.2





Fig.82 AC Power line Conducted Emission (Idle)

Measurement Results: Quasi Peak

Frequency (MHz)	Quasi Peak (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.398000	34.72	57.90	23.17	Ν	ON	9.6
0.554000	34.85	56.00	21.15	Ν	ON	9.7
0.986000	31.60	56.00	24.40	Ν	ON	9.7
1.942000	31.25	56.00	24.75	L1	ON	9.7
3.398000	28.95	56.00	27.05	Ν	ON	9.7
3.674000	29.08	56.00	26.92	L1	ON	9.7

Measurement Results: Average

Frequency (MHz)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.554000	23.93	46.00	22.07	Ν	ON	9.7
1.222000	20.13	46.00	25.87	L1	ON	9.7
1.426000	20.98	46.00	25.02	L1	ON	9.7
3.382000	19.97	46.00	26.03	L1	ON	9.7
17.310000	26.85	50.00	23.15	Ν	ON	10.2
17.778000	24.44	50.00	25.56	Ν	ON	10.2

END OF REPORT