

Intertek  
731 Enterprise Drive  
Lexington, KY 40510

Tel 859 226 1000  
Fax 859 226 1040

[www.intertek.com](http://www.intertek.com)

# Lexmark International, Inc. MPE REPORT

**SCOPE OF WORK**

MPE CALCULATION  
ON THE LEX-M08-001 WIRELESS PRINT SERVER

**REPORT NUMBER**

103509456LEX-005

**ISSUE DATE**

7/2/2018

**[REVISED DATE]**

7/2/2018

**PAGES**

6

**DOCUMENT CONTROL NUMBER**

Non-Specific EMC Report Shell Rev. December 2017  
© 2017 INTERTEK



## TEST REPORT

**Report Number:** 103509456LEX-005

**Project Number:** G103509456

**Report Issue Date:** 7/2/2018

**Product Name:** Wireless Print Server

**Model:** LEX-M08-001


**FCC Standards:** FCC Part 1.1310 Limits for Maximum Permissible Exposure (MPE)

**Industry Canada Standards:** RSS-102 Issue 5

**Tested by:**  
Intertek Testing Services NA, Inc.  
731 Enterprise Drive  
Lexington, KY 40510

**Client:**  
Lexmark International, Inc.  
740 W New Circle Road, F61/004-2  
Lexington, KY 40511

Report prepared by



Bryan Taylor, Team Leader

Report reviewed by



Brian Lackey, Project Engineer

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.





# MPE Calculation

§ 1.1310: The criteria listed in table 1 shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

## Part 1.1310 Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

**RSS-102 Issue 5 Exposure Limits:****Table 4: RF Field Strength Limits for Devices Used by the General Public  
(Uncontrolled Environment)**

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Reference Period (minutes)
0.003-10 <sup>21</sup>	83	90	-	Instantaneous*
0.1-10	-	0.73/ <i>f</i>	-	6**
1.1-10	87/ <i>f</i> <sup>0.5</sup>	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ <i>f</i> <sup>0.25</sup>	0.1540/ <i>f</i> <sup>0.25</sup>	8.944/ <i>f</i> <sup>0.5</sup>	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 <i>f</i> <sup>0.3417</sup>	0.008335 <i>f</i> <sup>0.3417</sup>	0.02619 <i>f</i> <sup>0.6834</sup>	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ <i>f</i> <sup>1.2</sup>
150000-300000	0.158 <i>f</i> <sup>0.5</sup>	4.21 x 10 <sup>-4</sup> <i>f</i> <sup>0.5</sup>	6.67 x 10 <sup>-5</sup> <i>f</i>	616000/ <i>f</i> <sup>1.2</sup>
Note: <i>f</i> is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

**1.1 Test Procedure**

An MPE evaluation for was performed in order to show that the device was compliant with §2.1091. The maximum power density was calculated for each transmitter at a separation distance of 20cm. The calculation was performed using the maximum gain from the internal and external antennas declared by the manufacturer.

For each transmitter the maximum RF exposure at a 20 cm distance using the formula:

$$ConductedPower_{mW} = 10^{ConductedPower(dBm)/10}$$

$$PowerDensity = \frac{ConductedPower_{mW} \times Ant.Gain}{4\pi \times (20_{cm})^2}$$



**1.2 Results:**

802.11b (Internal Antenna)	Value	Unit	Comments
Frequency	2412	MHz	
Distance	20	cm	
Maximum Scaled Power	19.89	dBm	Measured conducted power
TX Antenna Gain	2.8	dBi	Internal Antenna
Source Based Duty Cycle	100	%	Percent of time transmitter is active
EIRP	<b>22.69</b>	<b>dBm</b>	Maximum Scaled Power x Antenna Gain
Source Based Output Power	<b>22.69</b>	<b>dBm</b>	EIRP x Duty Cycle
Power Density @ Distance	<b>0.0370</b>	<b>mW/cm<sup>2</sup></b>	(Source Based Output Power, mW) / (4π x (distance, cm) <sup>2</sup> )
FCC Limit	<b>1.0000</b>	<b>mW/cm<sup>2</sup></b>	1. x f0
Maximum Permissible Antenna Gain	<b>17.12</b>	<b>dBi</b>	((Limit, mW/cm <sup>2</sup> ) x 4π x (distance, cm) <sup>2</sup> ) / ((Maximum Scaled Power, mW) x Source Based Duty Cycle)

802.11b (External Antenna)	Value	Unit	Comments
Frequency	2412	MHz	
Distance	20	cm	
Maximum Scaled Power	19.89	dBm	Measured conducted power
TX Antenna Gain	2.5	dBi	External Antenna
Source Based Duty Cycle	100	%	Percent of time transmitter is active
EIRP	<b>22.39</b>	<b>dBm</b>	Maximum Scaled Power x Antenna Gain
Source Based Output Power	<b>22.39</b>	<b>dBm</b>	EIRP x Duty Cycle
Power Density @ Distance	<b>0.0345</b>	<b>mW/cm<sup>2</sup></b>	(Source Based Output Power, mW) / (4π x (distance, cm) <sup>2</sup> )
FCC Limit	<b>1.0000</b>	<b>mW/cm<sup>2</sup></b>	1. x f0
Maximum Permissible Antenna Gain	<b>17.12</b>	<b>dBi</b>	((Limit, mW/cm <sup>2</sup> ) x 4π x (distance, cm) <sup>2</sup> ) / ((Maximum Scaled Power, mW) x Source Based Duty Cycle)

802.11g (Internal Antenna)	Value	Unit	Comments
Frequency	2412	MHz	
Distance	20	cm	
Maximum Scaled Power	24.11	dBm	Measured conducted power
TX Antenna Gain	2.8	dBi	Internal Antenna
Source Based Duty Cycle	100	%	Percent of time transmitter is active
EIRP	<b>26.91</b>	<b>dBm</b>	Maximum Scaled Power x Antenna Gain
Source Based Output Power	<b>26.91</b>	<b>dBm</b>	EIRP x Duty Cycle
Power Density @ Distance	<b>0.0977</b>	<b>mW/cm<sup>2</sup></b>	(Source Based Output Power, mW) / (4π x (distance, cm) <sup>2</sup> )
FCC Limit	<b>1.0000</b>	<b>mW/cm<sup>2</sup></b>	1. x f0
Maximum Permissible Antenna Gain	<b>12.90</b>	<b>dBi</b>	((Limit, mW/cm <sup>2</sup> ) x 4π x (distance, cm) <sup>2</sup> ) / ((Maximum Scaled Power, mW) x Source Based Duty Cycle)

802.11g (External Antenna)	Value	Unit	Comments
Frequency	2412	MHz	
Distance	20	cm	
Maximum Scaled Power	24.11	dBm	Measured conducted power
TX Antenna Gain	2.5	dBi	External Antenna
Source Based Duty Cycle	100	%	Percent of time transmitter is active
EIRP	<b>26.61</b>	<b>dBm</b>	Maximum Scaled Power x Antenna Gain
Source Based Output Power	<b>26.61</b>	<b>dBm</b>	EIRP x Duty Cycle
Power Density @ Distance	<b>0.0911</b>	<b>mW/cm<sup>2</sup></b>	(Source Based Output Power, mW) / (4π x (distance, cm) <sup>2</sup> )
FCC Limit	<b>1.0000</b>	<b>mW/cm<sup>2</sup></b>	1. x f0
Maximum Permissible Antenna Gain	<b>12.90</b>	<b>dBi</b>	((Limit, mW/cm <sup>2</sup> ) x 4π x (distance, cm) <sup>2</sup> ) / ((Maximum Scaled Power, mW) x Source Based Duty Cycle)



802.11n (Internal Antenna)	Value	Unit	Comments
Frequency	2412	MHz	
Distance	20	cm	
Maximum Scaled Power	23.62	dBm	Measured conducted power
TX Antenna Gain	2.8	dBi	Internal Antenna
Source Based Duty Cycle	100	%	Percent of time transmitter is active
EIRP	26.42	dBm	Maximum Scaled Power x Antenna Gain
Source Based Output Power	26.42	dBm	EIRP x Duty Cycle
Power Density @ Distance	0.0872	mW/cm <sup>2</sup>	(Source Based Output Power, mW) / (4π x (distance, cm) <sup>2</sup> )
FCC Limit	1.0000	mW/cm <sup>2</sup>	1. x f0
Maximum Permissible Antenna Gain	13.39	dBi	((Limit, mW/cm <sup>2</sup> ) x 4π x (distance, cm) <sup>2</sup> ) / ((Maximum Scaled Power, mW) x Source Based Duty Cycle)
802.11n (External Antenna)	Value	Unit	Comments
Frequency	2412	MHz	
Distance	20	cm	
Maximum Scaled Power	23.62	dBm	Measured conducted power
TX Antenna Gain	2.5	dBi	External Antenna
Source Based Duty Cycle	100	%	Percent of time transmitter is active
EIRP	26.12	dBm	Maximum Scaled Power x Antenna Gain
Source Based Output Power	26.12	dBm	EIRP x Duty Cycle
Power Density @ Distance	0.0814	mW/cm <sup>2</sup>	(Source Based Output Power, mW) / (4π x (distance, cm) <sup>2</sup> )
FCC Limit	1.0000	mW/cm <sup>2</sup>	1. x f0
Maximum Permissible Antenna Gain	13.39	dBi	((Limit, mW/cm <sup>2</sup> ) x 4π x (distance, cm) <sup>2</sup> ) / ((Maximum Scaled Power, mW) x Source Based Duty Cycle)

The calculated maximum power density at 20cm distance is less that the limit for general population / uncontrolled exposure.