


Request for Modular Approval (MA)

Reference: FCCID: IYLM01002

Transmitter Module Requirements Identified in § 15.212

Item	Requirements	EUT
(a)(1)(i)	The radio elements of the modular transmitter must have their own shielding.	Comply
(a)(1)(ii)	Have Buffered modulation/data inputs (if such inputs are provided).	Comply
(a)(1)(iii)	The modular transmitter must have its own power supply regulation.	Comply
(a)(1)(iv)	The modular transmitter must comply with the antenna and transmission system requirements of §§15.203, 15.204(b) and 15.204(c).	Comply
(a)(1)(v)	Be tested in a stand-alone configuration and comply with the AC line conducted requirements found in §15.207.	Comply – refer to test photo exhibit and the test report.
(a)(1)(vi)	If using a permanently affixed label, the modular transmitter must be labeled with its own FCC identification number, and, if the FCC identification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.	Comply – reference label photo example exhibits.
(a)(1)(vii)	The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.	Comply – reference user guide
(a)(1)(viii)	The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	Comply – reference the MPE calculations exhibit.

March 17, 2009



Michael Klave
Regulatory Engineer