

TEST REPORT 02001337

2001-01-16

EQUIPMENT UNDER TEST:

| | |
|-----------------------------|--|
| Trade Name: | Marquardt Keyless Go W211 |
| Model: | Side Door Modul |
| Serial No: | none Prototype |
| Equipment Category: | Immobilizer |
| Manufacturer: | Marquardt GmbH |
| Address: | Schloßstrasse 16 D-78604 Rietheim-Weilheim Germany |
| Phone: | +49 (0)7424 / 99-1891 |
| Fax: | +49 (0)7424 / 99-2541 |
| E-mail: | Reinhardt.Neumann@marquardt.de |
| RELEVANT STANDARD: | 47 CFR Part 15C - Intentional Radiators |
| MEASUREMENT PROCEDURE USED: | ANSI C63.4-1992 |

TEST REPORT PREPARED

BY:

Ralf Trepper
m.dudde hochfrequenz-technik
Rottland 5a
D-51429 Bergisch Gladbach
Germany
Phone: +49 2207 96890
Fax : +49 2207 968920
E-mail: manfred.dudde@t-online.de


TEST PERSONNEL:

Ralf Trepper



SIGNATURE OF THE COMPANY OFFICIAL:

Manfried Dudde



CONTENTS

1 GENERAL INFORMATION 3

1.1 Purpose 3

1.2 Limits and Reservations 3

1.3 Test Location 3

1.4 Manufacturer 3

1.5 Dates 3

2 PRODUCT DESCRIPTION 4

2.1 Equipment Under Test (EUT)..... 4

2.2 EUT Peripherals 4

2.2.1 AC Adapter (power supply for EUT) 4

2.2.2 Notebook Computer 4

2.2.3 AC Adapter (for SONY Notebook) 4

2.3 Mode of Operation During Testing 4

2.4 Modifications Required for Compliance..... 5

3 TEST RESULTS SUMMARY 5

4 ANTENNA REQUIREMENT 6

4.1 Regulation 6

4.2 Result..... 6

5 RADIATED EMISSIONS 7

5.1 Regulation..... 7

5.2 Radiated Emissions Test, 9 kHz to 30 MHz (Magnetic Field Test)..... 10

5.2.1 Test Equipment 10

5.2.2 Test Procedures 10

5.2.3 Calculation of Field Strength Limits..... 11

5.2.4 Field Strength Calculation 11

5.2.5 Test Results..... 12

5.3 Radiated Emissions Test, 30 MHz to 2 GHz 13

5.3.1 Test Equipment 13

5.3.2 Test Procedures 13

5.3.3 Calculation of Field Strength Limits 14

5.3.4 Calculation of Average Correction Factor 14

5.3.5 Field Strength Calculation 14

5.3.6 Test Results..... 16

6 CONDUCTED EMISSIONS 17

6.1 Regulation..... 17

6.2 Test Equipment..... 17

6.3 Test Procedures 17

6.4 Test Results..... 18

7 MISCELLANEOUS COMMENTS AND NOTES 19

8 LIST OF ANNEXES 20

1 GENERAL INFORMATION

1.1 Purpose

The purpose of this report is to show compliance to the FCC regulations for unlicensed devices operating under section 15.209 of the Code of Federal Regulations title 47.

1.2 Limits and Reservations

The test results in this report apply only to the particular Equipment Under Test (EUT) as declared in this report. This test report shall not be reproduced except in full without the written permission of m.dudde hochfrequenz-technik.

1.3 Test Location

Company Name: m.dudde high frequency technology
Street: Rottland 5a
City: 51429 Bergisch Gladbach
Country: Germany
Laboratory:

FCC Registration Number: 699717

This site has been fully described in a report submitted to the FCC, and
accepted in the letter dated Registration Number .699717

Phone: +49-2207-9689-0
Fax: +49-2207-9689-20
Mail: manfred.dudde@t-online.de
Web: <http://www.dudde.com>

1.4 Manufacturer

Company Name: Marquardt GmbH
Street: Schloßstrasse 16
City: D-78604 Rietheim-Weilheim
Country: Germany

Name for contact purposes: Reinhardt Neumann

Phone: +49 (0)7424 / 99-1891
Fax: +49 (0)7424 / 99-2541
Mail: Reinhardt.Neumann@marquardt.de

1.5 Dates

Date of receipt of EUT: 2001 December 20
Test date: 2002 April 18 - 19

2 PRODUCT DESCRIPTION

2.1 Equipment Under Test (EUT)

Device: **Inductive system**
Trade Name: **Keyless Go W211 Side Door Module**
Model: **Side door control device BR211**
Serial Number: none (Prototype)
FCC ID: **IYZ3352**
Power: 12V DC
Transmit Frequency: 19.1kHz
Type of modulation: ASK
Interface: none
Variants:
Highest frequency generated or used in the device: 8 MHz

2.2 EUT Peripherals

The EUT was tested in a typical system consisting of:

2.2.1 DC Power supply (power supply for EUT)

Type:
Manufacturer: Rhode&Schwarz
Serial Number:

2.2.2 Notebook Computer *none*

Type:
Manufacturer:
Serial Number:

Highest frequency generated or used in the device:

2.2.3 AC Adapter *none*

Type:
Manufacturer:
Serial Number:

2.3 Mode of Operation During Testing

The *Side Door Module* was tested in a typical fashion. The Rhode&Schwarz DC Power supply was connected to the DC input port of the *Side Door Module* special connector. During preliminary emission tests the *Side Door Module* was operated in continuous READING mode for worst case emission mode investigation. READING mode was found to be the worst case emission mode. Therefore, final qualification testing was completed with *Side Door Module* operated in the continuous READING mode. All tests performed with standard vehicle electrical system voltage (12 Volts DC).

2.4 Modifications Required for Compliance

None.

3 TEST RESULTS SUMMARY

Summary of Test Results

| Requirement | CFR Section | Report Section | Test Result |
|---------------------|---------------|----------------|----------------|
| Antenna Requirement | 15.203 | 4 | Pass |
| Radiated Emissions | 15.209,15.109 | 5 | Pass |
| Conducted Emissions | 15.207 | 6 | not applicable |

The client has made the determination that EUT Condition, Characterization, and Mode of Operation are representative of production units, and meet the requirements of the specifications referenced herein.

Consistent with Industry practice, measurement and test equipment not directly involved in obtaining measurement results but having an impact on measurements (such as cable loss, antenna factors, etc.) are factored into the "Correction Factor" documented in certain test results. Instrumentation employed for testing meets tolerances consistent with known Industry Standards and Regulations.

The measurements contained in this report were made in accordance with the procedure ANSI C63.4 1992 and all applicable Public Notices received prior to the date of testing. All emissions from the device were found to be within the limits outlined in this report. The test results in this report apply only to the particular Equipment Under Test (EUT) as declared in this report.

Test Personnel: Ralf Trepper
Issuance Date: 2002 April 19

4 ANTENNA REQUIREMENT

Test Requirement: FCC CFR47, Part 15C

4.1 Regulation

15.203 An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of Part 15C. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31 (d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

4.2 Result

Device: **Inductive system**
Trade Name: **Keyless Go W211 Side Door Module**
Model: **Side door control device BR211**
Serial No: none (Prototype)

Antenna is a trace on the PCB.

The EUT meets the requirements of this section.

5 RADIATED EMISSIONS

Test Requirement: FCC CFR47, Part 15C

Test Procedure: ANSI C63.4:1992

5.1 Regulation

Section 15.31 (e) For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

Section 15.33 Frequency range of radiated measurements: (a) Unless otherwise noted in the specific rule section under which the equipment operates for an intentional radiator the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in this paragraph: (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

(4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation. (b) For unintentional radiators: (1) Except as otherwise indicated in paragraphs (b)(2) or (b)(3), for an unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a radiated emission limit is specified, up to the frequency shown in the following table:

| Highest frequency generated or used in the device or on which the device operates or tunes (MHz) | Upper frequency of measurement (MHz) |
|--|---|
| Below 1.705 | 30 |
| 1.705 -108 | 1000 |
| 108-500 | 2000 |
| 500-1000 | 5000 |
| Above 1000 | 5th harmonic of the highest frequency or 40 GHz, whichever is lower |

Section 15.35 Measurement detector functions and bandwidths. The conducted and radiated emission limits shown in this Part are based on the following, unless otherwise specified elsewhere in this Part: (a) On any frequency or frequencies below or equal to 1000 MHz, the limits shown are based on measuring equipment employing a CISPR quasi-peak detector function and related measurement bandwidths, unless otherwise specified. The specifications for the measuring instrument using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Interference (CISPR) of the International Electrotechnical Commission. As an alternative to CISPR quasi-peak measurements, the responsible party, at its option, may demonstrate compliance

with the emission limits using measuring equipment employing a peak detector function, properly adjusted for such factors as pulse desensitization, as long as the same bandwidths as indicated for CISPR quasi-peak measurements are employed.

Note: For pulse modulated devices with a pulse-repetition frequency of 20 Hz or less and for which CISPR quasi-peak measurements are specified, compliance with the regulations shall be demonstrated using measuring equipment employing a peak detector function, properly adjusted for such factors as pulse desensitization, using the same measurement bandwidths that are indicated for CISPR quasi-peak measurements.

(b) On any frequency of frequencies above 1000 MHz, the radiated limits shown are based upon the use of measurement instrumentation employing an average detector function. When average radiated emission measurements are specified in the regulations, including emission measurements below 1000 MHz, there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules in this part, e.g., see § 15.255. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1 MHz. Measurement of AC power line conducted emissions are performed using a CISPR quasipeak detector, even for devices for which average radiated emission measurements are specified.

(c) Unless otherwise specified, e.g. Section 15.255(b), when the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value. The exact method of calculating the average field strength shall be submitted with any application for certification or shall be retained in the measurement data file for equipment subject to notification or verification.

Section 15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |
| 30-88 | 100 | 3 |
| 88-216 | 150 | 3 |
| 216-960 | 200 | 3 |
| Above 960 | 500 | 3 |

(b) In the emission table above, the tighter limit applies at the band edges.

(c) The level of any unwanted emissions from an intentional radiator operating under these general provisions shall not exceed the level of the fundamental emission. For intentional radiators which operate under the provisions of other sections within this part and which are required to reduce their unwanted emissions to the limits specified in this table, the limits in this table are based on the frequency of the unwanted emission and not the fundamental frequency. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.

(d) The emission limits shown in the above table are based on measurements employing a CISPR quasi peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

(e) The provisions in §§ 15.31, 15.33, and 15.35 for measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

(f) In accordance with Section 15.33(a), in some cases the emissions from an intentional radiator must be measured to beyond the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator because of the incorporation of a digital device. If measurements above the tenth harmonic are so required, the radiated emissions above the tenth harmonic shall comply with the general radiated emission limits applicable to the incorporated digital device, as shown in Section 15.109 and as based on the frequency of the emission being measured, or, except for emissions contained in the restricted frequency bands shown in Section 15.205, the limit on spurious emissions specified for the intentional radiator, whichever is the higher limit. Emissions which must be measured above the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator and which fall within the restricted bands shall comply with the general radiated emission limits in Section 15.109 that are applicable to the incorporated digital device.

Section 15.109 Radiated emission limits. (a) Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

| Frequency (MHz) | Field Strength (microvolts/meter) |
|-----------------|-----------------------------------|
| 30-88 | 100 |
| 88-216 | 150 |
| 216-960 | 200 |
| Above 960 | 500 |

5.2 Radiated Emissions Test, 9 kHz to 30 MHz (Magnetic Field Test)

5.2.1 Test Equipment

| Type | Manufacturer/ | Dudde Device No. | Last Calibration | Next Calibration |
|------------------------------|-----------------------------|------------------|------------------|------------------|
| Receiver | Anritzu Spectrum Analyzer | MT74457 | 03/2002 | 03/2005 |
| (9 kHz –30 MHz) Receiver | MS 2601 (2) Rohde & Schwarz | 882902/007 | 01/2002 | 01/2005 |
| (9 kHz –30 MHz) Loop Antenna | ESH2 (22) Schwarzbeck | | | |
| Receiver | Anritzu Spectrum Analyzer | MT74457 | 03/2002 | 03/2005 |

5.2.2 Test Procedures

For tabletop equipment, the EUT is placed on a 1 meter by 1.5 meters wide and 0.8 meter high nonconductive table that sits on a flush mounted metal turntable. Floor standing equipment is placed directly on the flush mounted metal turntable. The EUT is connected to its associated peripherals with any excess I/O cabling bundled to approximately 1 meter.

Emissions from the unit are maximized by adjusting the orientation of the receive loop antenna and rotating the EUT on the turntable. Manipulating the system cables also maximizes EUT emissions. Refer to the photographs' section.

The EUT was tested in a typical fashion. The test distance was reduced to 3 m and 10 m, respectively. according to section 15.31 (f) (2). The initial step in collecting radiated data is a peak scan of the measurement range with an EMI test receiver. The significant peaks within a margin of 25 dB to the limit are then measured with quasi-peak and AV detector, respectively. Worst case radiated emissions are listed under chapter: test results.

| Radiated Emissions Test Characteristics (magnetic field test) | |
|--|--------------------------|
| Frequency range | 9 kHz - 30 MHz |
| Test distance | 3 m; 10 m* |
| Test instrumentation resolution bandwidth | 200 Hz (9 kHz - 150 kHz) |
| | 9 kHz (150 kHz - 30 MHz) |
| Test instrumentation detector | QP / AV, Peak |
| Receive antenna height | 1 m |
| Receive antenna orientation | 0-360° |

* Section 15.31 (f) (2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

5.2.3 Calculation of Field Strength Limits

Calculation: microvolts/meter to dB μ V/m

| Frequency (MHz) | Field Strength Limit according to Section 15.209 | | Measurement distance (meters) |
|--------------------|--|----------------|----------------------------------|
| | (μ V/m) | (dB μ V/m) | |
| 0.009-0.490 | 266.7-4.9 | 48.5-13.8 | 300 |
| 0.490-1.705 | 49.0-14.1 | 33.8-23.0 | 30 |
| 1.705-30.0 | 30 | 29.5 | 30 |

5.2.4 Field Strength Calculation

No special calculation for obtaining the field strength in dB μ V/m is necessary, because the EMI receiver and the active loop antenna operate as a system, where the reading gives directly the field strength result (dB μ V/m). The gain, antenna factors and cable losses are already taken into consideration.

For test distance other than what is specified, but fulfilling the requirements of Section 15.31 (f) (2) the field strength is calculated by adding additionally an extrapolation factor of 40 dB/decade (inverse lineardistance for field strength measurements). The basic equation with a sample calculation is as follows:

$$FS = RA + DF$$

where

FS = Field Strength in dB μ V/m

RA = Receiver Amplitude in dB μ V/m

DF = Distance Extrapolation Factor in dB,

where $DF = 20 \log (D_{test}/D_{spec})$ where D_{test} = Test Distance and D_{spec} = Specified Distance

Assume the tests performed at a reduced Test Distance of 3 m instead of the Specified Distance of 30 m giving a Distance Extrapolation Factor of $DF = 40 \log(3m/30m) = -40$ dB.

Assuming a receiver amplitude of 40.7 dB μ V/m is obtained. The distance factor of -40 dB are added, giving a field strength of 0.7 dB μ V/m. The 0.7 dB μ V/m value can be mathematically converted to its corresponding level in μ V/m.

$$FS = 40.7 - 40 = 0.7 \text{ [dB}\mu\text{V/m]}$$

Level in μ V/m Common Antilogarithm $(0.7/20) = 1.1$

5.2.5 Test Results

Device: **Inductive system**
Trade Name: **Keyless Go W211 Side Door Module**
Model: **Side door control device BR211**
Serial No: none (Prototype)

| PRODUCT EMISSIONS DATA 9 kHz - 30 MHz | | | | | | | | | |
|---------------------------------------|--------------------|-----------------------------|---------------|------------------|-------------------------------|-----------------------------|-------------------------------|----------|---------|
| No | Emission Frequency | Receiver Mode and BandWidth | Test Distance | Receiver Reading | Distance Extrapolation Factor | Result = Coneded Reading FS | Spec Limit @ Distance | Margin | Remarks |
| | [MHz] | [KHz] | [m] | RA [dBµV/m] | DF [dB] | [dBµV/m] | [dBµV/m] @ [m] | [dB] | |
| 1 | 0.0191 | QP/0.2kHz AV/0.2kHz | 10 | 60.2 59.6 | -59.1 | 1.1 0.5 | Pk51.9- @ 300 AV31.9 @ 300 | AV: 31.4 | |
| | | | | | | | | | |

Remark: * Peak Limit according to Section 15.35 (b).

The EUT meets the requirements of this section.

Test Personnel: Ralf Trepper
Test Date: 2002 April 18 , 19

5.3 Radiated Emissions Test, 30 MHz to 2 GHz

5.3.1 Test Equipment

| Type | Manufacturer/ Model No. | Dudde Device No. | Last Calibration | Next Calibration |
|-----------------------------------|---|---------------------|------------------|------------------|
| Receiver (30MHz - 1GHz) | Hewlett Packard Spectrum Analyzer (171) 8593 E | 3528U00990 | 02/2002 | 02/2004 |
| Pre-Amplifier (30MHz - 1GHz) | Hewlett Packard 8447 E (166a) | 1726°00705 | 04/2002 | 04/2006 |
| Antenna (30 MHz - 1 GHz) | Chase (Bilog) CBL 611A | 1517 | 04/2002 | 04/2008 |
| Receiver (1 GHz - 26.5 GHz) | Hewlett Packard Spectrum Analyzer (171) 8593 E | 3528U00990 | 02/2002 | 02/2004 |
| Antenna (1 GHz - 2 GHz) | Schwarzbeck BBHA 9120 – A/236 | | | |

5.3.2 Test Procedures

For tabletop equipment, the EUT is placed on a 1 meter by 1.5 meters wide and 0.8 meter high nonconductive table that sits on a flush mounted metal turntable. Floor standing equipment is placed directly on the flush mounted metal turntable [Remark.- Not applicable]. The EUT is connected to its associated peripherals with any excess I/O cabling bundled to approximately 1 meter.

Preview tests are performed to determine the "worst case" mode of operation. With the EUT operating in "worst case" mode, emissions from the unit are maximized by adjusting the polarization and height of the receive antenna and rotating the EUT on the turntable. Manipulating the system cables also maximizes EUT emissions. Refer to the photographs' section. The initial step in collecting radiated data is a peak scan of the measurement range with an EMI test receiver under closer distances as given in the rule. The significant peaks are then measured with the appropriate detectors (QP, AV and PK).

Worst case radiated emissions are listed under chapter: test results.

| Radiated Emissions Test Characteristics | |
|---|-------------------------------|
| Frequency range | 30 MHz - 2,000 MHz |
| Test distance | 3 m* |
| Test instrumentation resolution bandwidth | 120 kHz (30 MHz - 1,000 MHz) |
| | 1 MHz (1,000 MHz - 4,000 MHz) |
| Test instrumentation detector | QP (30 MHz - 1,000 MHz) |
| | AV (1,000 MHz - 2,000 MHz) |
| Receive antenna scan height | 1 m - 4 m |
| Receive antenna polarization | Vertical/Horizontal |

EUT: **Keyless Go W211 Side Door Modul**

* According to Section 15.31 (f)(1): At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. (...) When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

5.3.3 Calculation of Field Strength Limits

Calculation: microvolts/meter to dBµV/m

| Frequency (MHz) | Field Strength Limit acc. to section 15.209 and 15.109 (non-class A digital devices) | | Measurement distance (meters) |
|--------------------|--|----------|----------------------------------|
| | (microvolts/meter) | (dBµV/m) | |
| 30-88 | 100 | 40 | 3 |
| 88-216 | 150 | 43.5 | 3 |
| 216-960 | 200 | 46 | 3 |
| 960-2,000 | 500 | 54 | 3 |

5.3.4 Calculation of Average Correction Factor

The maximum correction factor to be applied is 20 dB per section 15.35 of the FCC rules. The relationship between average and peak mode reading has been confirmed by direct measurement using the receivers average and peak detectors. All emission measurements performed using the test receiver's average detector and the max. hold facility; i.e. the average value measured directly without the necessity of additional correction factor.

5.3.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

where

- FS = Field Strength in dBpV/m
- RA = Receiver Amplitude in dBµV
- AF = Antenna Factor in dB(1/m)
- CF = Cable Attenuation Factor in dB

Assume a receiver reading of 23.5 dBµV is obtained. The Antenna Factor of 7.4 dB(1/m) and a Cable Factor of 1.1 dB are added, giving a field strength of 32 dBµV/m. The 32 dBµV/m value can be mathematically converted to its corresponding level in µV/m.

$$FS = 23.5 + 7.4 + 1.1 = 32 [dBµV/m]$$

$$Level\ in\ pV/m = Common\ Antilogarithm\ (32/20) = 39.8$$

For test distance other than what is specified, but fulfilling the requirements of Section 15.31 (f)(1) the field strength is calculated by adding additionally an extrapolation factor of 20 dB/decade (inverse lineardistance for field strength measurements). The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF + DF$$

where

FS = Field Strength in dB μ V/m

RA = Receiver Amplitude in dB μ V

AF = Antenna Factor in dB(1/m)

CF = Cable Attenuation Factor in dB

DF = Distance Extrapolation Factor in dB,

where $DF = 20 \log(D_{test}/D_{spec})$ where D_{test} = Test Distance and D_{spec} = Specified Distance

Assume the tests performed at a reduced Test Distance of 1,5 m instead of the Specified Distance of 3 m giving a Distance Extrapolation Factor of $DF = 20 \log(1,5m/3m) = -6$ dB.

Assuming a receiver reading of 23.5 dB μ V is obtained. The Antenna Factor of 7.4 dB(1/m), the Cable Factor of 1.1 dB and the Distance Factor of -6 dB are added, giving a field strength of 26 dB μ V/m. The 26 dB μ V/m value can be mathematically converted to its corresponding level in μ V/m.

$$FS = 23.5 + 7.4 + 1.1 - 6 = 26 \text{ [dB}\mu\text{V/m]}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } (26/20) = 20$$

5.3.6 Test Results

Device: **Inductive system**
Trade Name: **Keyless Go W211 Side Door Module**
Model: **Side door control device BR211**
Serial No: none (Prototype)

| PRODUCT EMISSIONS DATA 30 MHz - 1000 MHz | | | | | | | | | | | |
|--|--------------------------|-----------------------------------|-------------------|----------------------------|------------------------------------|---------------------------------------|--|---------------------|----------------------|-------------|--------|
| No | Emission Frequency [MHz] | Receiver Mode and Bandwidth [kHz] | Test Distance [m] | Receiver Reading RA [dBµV] | Correction Factor AF+CF [dB(1/m)] | Distance Extrapolation Factor DF [dB] | Result = Corrected Reading FS [dBµV/m] | Spec Limit [dBµV/m] | Antenna Polarization | Margin [dB] | Remark |
| 1 | | QP/120 | 3 | | | 0 | | 40 | | | |
| 2 | | QP/120 | 3 | | | 0 | | 46 | | | |
| 3 | | QP/120 | 3 | | | 0 | | 46 | | | |
| 4 | | QP/120 | 3 | | | 0 | | 46 | | | |
| 5 | | QP/120 | 3 | | | 0 | | 46 | | | |
| 6 | | QP/120 | 3 | | | 0 | | 46 | | | |
| No emissions detected* ¹ | | | | | | | | | | | |
| PRODUCT EMISSIONS DATA 1000 MHz - 2000 MHz | | | | | | | | | | | |
| No | Emission Frequency [MHz] | Receiver Mode and Bandwidth [kHz] | Test Distance [m] | Receiver Reading RA [dBµV] | Correction Factor AF+CF [dB(1/ma)] | Distance Extrapolation Factor DF [dB] | Result = Corrected Reading FS [dBµV/m] | Spec Limit [dBµV/m] | Antenna Polarization | Margin [dB] | Remark |
| 1 | | AV/1000 Pk/1000 | 3 | | | 0 | | 54 74* ² | v | | |
| 2 | | AV/1000 Pk/1000 | 3 | | | 0 | | 54 74* ² | v | | |
| 3 | | AV/1000 Pk/1000 | 3 | | | 0 | | 54 74* | v | | |
| 4 | | AV/1000 Pk/1000 | 3 | | | 0 | | 54 74* | v | | |
| 5 | | AV/1000 Pk/1000 | 3 | | | 0 | | 54 74* ² | v | | |
| 6 | | AV/1000 | 3 | | | 0 | | 54 | v | | |
| No emissions detected* ¹ | | | | | | | | | | | |

Remark: *¹ Noise level of the measuring instrument
Remark: *² Peak Limit according to Section 15.35 (b).

The EUT meets the requirements of this section.

Test Personnel: Ralf Trepper
Test Date: 2002 April 18 , 19

6 CONDUCTED EMISSIONS

Test Requirement: FCC CFR47, Part 15C
Test Procedure: ANSI C63.4:1992

6.1 Regulation

Section 15.207 (a) For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 450 kHz to 30 MHz shall not exceed 250 microvolts. Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

Section 15.207 (d) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provision for, the use of battery chargers which permit operating while charging, AC adaptors or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

6.2 Test Equipment

| Type | Manufacturer/ Model No. | Serial No. | Last Calibration | Next Calibration | Remarks |
|--|----------------------------|------------|------------------|------------------|---------|
| Receiver (30 MHz - 1 GHz) | | | | | |
| Protector Limiter 9 kHz - 30MHz, 10 dB | | | | | |
| V-LISN 50 ohms/(50 uH+5 ohms) | | | | | |
| V-LISN 50 ohms/(50 uH+5 ohms) | | | | | |

6.3 Test Procedures

For tabletop equipment, the EUT is placed on a 1 meter by 1.5 meters wide and 0.8 meter high nonconductive table that is placed above the groundplane. Floor standing equipment is placed directly on the groundplane. Any supplemental grounding mechanisms are connected, if appropriate. The EUT is connected to its associated peripherals, with any excess I/O cabling bundled to approximately 1 meter. The EUT is connected to a dedicated LISN and all peripherals are connected to a second separate LISN circuit. The LISNs are bonded to the groundplane. Conducted measurements are made on each current carrying conductor with respect to ground.

EUT: Keyless Go W211 Side Door Modul

The initial step in collecting conducted data is a peak scan of the measurement range with an EMI test receiver. The significant peaks are then measured with quasi-peak detector. Worst case conducted emissions are listed under chapter: test results.

6.4 Test Results

Device: **Inductive system**
Trade Name: **Keyless Go W211 Side Door Module**
Model: **Side door control device BR211**
Serial No: none (Prototype)

| PRODUCT EMISSIONS QUASI PEAK DATA | | | | | | | |
|-----------------------------------|-------------|--------------------------|--------------------------|---------------|-------------------|-------------|---------|
| No | Tested Line | Emission Frequency [MHz] | Receiver Bandwidth [kHz] | Result [dBµV] | Spec Limit [dBµV] | Margin [dB] | Remarks |
| 1 | L1 | | 10 | | 48 | | |
| 2 | N | | 10 | | 48 | | |
| 3 | N | | 10 | | 48 | | |
| 4 | N | | 10 | | 48 | | |
| 5 | N | | 10 | | 48 | | |
| 6 | N | | 10 | | 48 | | |
| 7 | L1 | | 10 | | 48 | | |

* Not required, the EUT is directly connected to a car battery .

Test Personnel: Ralf Trepper

Test Date: 2002 April 2002

7 MISCELLANEOUS COMMENTS AND NOTES

None

8 LIST OF ANNEXES

The following Exhibits are separated annexes to this test report.

| Annex No. | Exhibit | Pages |
|-----------|--|-------|
| 1 | Photographs of Test Setups | 1 |
| 2 | External Photographs of the Equipment Under Test | 2 |
| 3 | Internal Photographs of the Equipment Under Test | 2 |
| 4 | Occupied Bandwith Plot | 1 |
| 5 | FCC ID Label Sample | 2 |
| 6 | Technical Description | 14 |
| 7 | Block diagram | 1 |
| 8 | Schematics | 2 |