| DEWOLONG. | | | | | | | | | | | |
|-----------|---------|--------------|------|----------|--|--|--|--|--|--|--|
| REV | ECO NO. | DESCRIPTIONS | DATE | APPROVED | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |

NOTES:

1. APPLICABLE STANDARDS/SPECIFICATIONS:
MIL-STD-100E, ENGINEERING DRAWING PRACTICES.
ANSI Y14.5M-82, DIMENSIONS AND TOLERANCES.

2. TYPE FACE: ARIAL ROUNDED MT BOLD

CHARACTER HEIGHT: 0.15 INCHES CHARACTER WIDTH: 0.06 INCHES

FCC ID: J26520006

<u>WARNING</u>: This device must comply with FCC-adopted RF exposure safety limits. This limit is satisfied if the device is at least 66 centimeters or 26 inches from any person while transmitting, when used with 24 dBi Antenna.

| | | l | ı | | | | | | |
|--|--------------------|---|-----------------|------------|----------------------------------|-------------------------------------|-----|--|--|
| | 1 | 1 | | 79969 | LAB | BEL, BLANK, POLY WHITE, 2.75 X 1.56 | | | |
| | ITEM QT NO. REG | | IDENTIFYING NO. | | | DESCRIPTION | | | |
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES | USED ON | | | ON | | | | | |
| TOLERANCES ARE: FRACTIONS DECIMALS ANGLES ±1/32 .XX ± .01 ±0°30' | | | USED | _ 520006-1 | | C+A | | | |
| | | | | | TITL | LABEL, MARKING, | | | |
| MATERIAL | | | | | LA | | | | |
| | DRAWN: | | | | FCC ID, TRX, STANDALONE, STD PWR | | | | |
| | CHECKED: | | | | | | | | |
| FINISH | ISSUED: | | | | | | | | |
| | | | | | SIZE | | REV | | |
| | | | | | Α | 6T925 | | | |
| DO NOT SCALE DRAWING | | | | | SCALE 1/1 | SHEET 1 OF 1 | | | |
| | I | | | | | WEIGHT | | | |

Form No: L11041/A