

品名 : ACA-5020-A2-MC-S Specification

History List

[illegible]

ACA-5020-A2-MC-S Specification

1. APPLIATION:

WLAN 802.11b/g, Bluetooth, etc...

2. Explanation of part number:


$\frac{AC}{(1)} \quad \frac{A}{(2)} - \frac{5020}{(3)} \quad \frac{A2}{(4)} - \frac{MC}{(5)} - \frac{S}{(6)} - \bar{(7)}$

- (1) Product Type : Chip Antenna
- (2) Center Frequency/Band Code : A--2.45G group
- (3) Size Code: 5.0mm(length) x 2.0mm(width)
- (4) Design Revision Code: A2= Rev. 2
- (5) MC= MONOPOLE Ceramics Type
- (6) Special Code: S=RoHS Compliant
- (7) Suffix For Special Requirements

3. ELECTRICAL SPECIFICATION:

Electrical Specification	
Frequency Range	2.4GHz~2.5GHz
Polarization	Linear
Patten	Omni-Directional
Reef Impedance	50 ohm
Gain	0 dBi (Peak)
Size	5.0mmX2.0mmX0.72mm
VSWR	≤ 2.0


4. DIMENSIONS:



Mark	L	W	H	a
Dimensions	5.0±0.2	2.0±0.2	0.72±0.2	0.50±0.2

UNLESS OTHER SPECIFIED TOLERANCES ON :			INPAQ TECHNOLOGY CO., LTD.	
X = ± X.X = ± X.XX =				
A N G L E S = ± H O L E D I A = ±				
SCALE :		UNIT : mm		THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION
DRAWN BY : 趙彥年 <i>Okston</i>		CHECKED BY : 楊奇峰 <i>Yang</i>		
DESIGNED BY : 陳威仁 <i>Allen</i>		APPROVED BY : 謝立庭 <i>Li</i>		
TITLE : ACA-5020-A2-MC-S Specification		DOCUMENT NO.	ENS000015390	SPEC REV. A2

5. RECOMMENDED PCB LAYOUT: (unit: mm)



6. APPEARANCE CONFIGURATION :

Top Layer:




Bottom Layer:




UNLESS OTHER SPECIFIED TOLERANCES ON :			INPAQ TECHNOLOGY CO., LTD.	
X = ± X.X = ± X.XX =				
A N G L E S = ± H O L E D I A = ±				
SCALE :	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION		
DRAWN BY : 趙彥年 <i>Okston</i>	CHECKED BY : 楊奇峰 <i>Yang</i>			
DESIGNED BY : 陳威仁 <i>Allen</i>	APPROVED BY : 謝立庭 <i>LT</i>			
TITLE : ACA-5020-A2-MC-S Specification		DOCUMENT NO.	ENS000015390	SPEC REV. A2

7. ELECTRICAL CHARACTERISTICS

Return Loss





VSWR




8. RADIATION PATTERN

The Gain pattern was measuring in INPAQ's FAR-field chamber. DUT will be placed on the table of rotator, a standard horn antenna and Vector Network Analyzer was using to collected data. (Please contact to INPAQ for more detail)


Measuring factors definition




2400MHZ



2450MHZ



2500MHZ



UNLESS OTHER SPECIFIED TOLERANCES ON :

X = ± X.X = ± X.XX =

ANGLES = ± HOLE DIA = ±

SCALE : UNIT : mm

DRAWN BY : 趙彥年 *Okazun* CHECKED BY : 楊奇峰 *Ke mng*

DESIGNED BY : 陳威仁 *Allen* APPROVED BY : 謝立庭 *LT*



INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : ACA-5020-A2-MC-S Specification

DOCUMENT NO.


ENS000015390

SPEC REV.
A2

9. Taping Package And Label Marking:


(1) Quantity/Reel: 3000pcs/Reel

(2) Plastic Tape: (unit: mm)




Type	W	A	B	K	t	F	P
5020	12±0.3	2.3±0.2	5.3±0.2	Max. 1.0	0.3±0.1	5.50±0.2	4.00±0.2

(3) Tape Packing




(4) Cover Tape Reel Off Force:

$$5g \cdot f \leq \text{Peel-Off Force} \leq 70g \cdot f$$



(5) Reel Dimensions: (unit: mm)

Reel Material: Polystyrene



W	A	B
12±0.5	178±1.0	13±0.5

UNLESS OTHER SPECIFIED TOLERANCES ON :			INPAQ TECHNOLOGY CO., LTD.			
X = ± X.X = ± X.XX =						
A N G L E S = ± H O L E D I A = ±						
SCALE :		UNIT : mm		THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION		
DRAWN BY : 趙彥年 <i>Okazaki</i>		CHECKED BY : 楊奇峰 <i>Yang Qifeng</i>				
DESIGNED BY : 陳威仁 <i>Allen</i>		APPROVED BY : 謝立庭 <i>Shieh Liting</i>				
TITLE : ACA-5020-A2-MC-S Specification				DOCUMENT NO.	ENS000015390	SPEC REV. A2

10. Environmental Performance

(1) Reliability Test

Item	Condition	Specification
Thermal shock	1. 30±3 minutes at -40°C±5°C, 2. Convert to +105°C (5 minutes) 3. 30±3 minutes at +105°C±5°C, 4. Convert to -40°C (5 minutes) 5. Total 24 continuous cycles	No apparent damage Fulfill the electrical spec. after test.
Humidity resistance	1. Humidity: 85% R.H. 2. Temperature: 85±5°C 3. Time: 500 hours.	No apparent damage Fulfill the electrical spec. after test.
High temperature resistance	1. Temperature: 150°C±5°C 2. Time: 1000 hours.	No apparent damage Fulfill the electrical spec. after test.
Low temperature resistance	1. Temperature: -40°C±5°C 2. Time: 1000 hours.	No apparent damage Fulfill the electrical spec. after test.
Soldering heat resistance	1. Solder bath temperature : 260±5°C 2. Bathing time: 10±1 seconds	No apparent damage
Solderability	The dipped surface of the terminal shall be at least 95% covered with solder after dipped in solder bath of 245±5°C for 3±1 seconds.	No apparent damage

(2) Storage condition

(a) At warehouse:

The temperature should be within 0 ~ 30°C and humidity should be less than 75% RH.

The product should be used within 1 year from the time of delivery.

(b) On board:


The temperature should be within -40~85°C and humidity should be less than 85% RH.

(3) Operating temperature range

Operating temperature range : -40°C to +105°C.

UNLESS OTHER SPECIFIED TOLERANCES ON :			INPAQ TECHNOLOGY CO., LTD.	
X = ± X.X = ± X.XX =				
A N G L E S = ± H O L E D I A = ±				
SCALE :		UNIT : mm		THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION
DRAWN BY : 趙彥年 <i>Okston</i>		CHECKED BY : 楊奇峰 <i>Kevin</i>		
DESIGNED BY : 陳威仁 <i>Allen</i>		APPROVED BY : 謝立庭 <i>LT</i>		
TITLE : ACA-5020-A2-MC-S Specification		DOCUMENT NO.	ENS000015390	SPEC REV. A2

11. Recommendable reflow soldering



(1) Soldering gun procedure

Note the follows, in case of using solder gun for replacement.

- (a) The tip temperature must be less than 350°C for the period within 3 seconds by using soldering gun under 30 W.
- (b) The soldering gun tip shall not touch this product directly.

(2) Soldering volume

Note that excess of soldering volume will easily get crack the body of this Product.

UNLESS OTHER SPECIFIED TOLERANCES ON :			INPAQ TECHNOLOGY CO., LTD.	
X = ± X.X = ± X.XX =				
A N G L E S = ± H O L E D I A = ±				
SCALE :	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION		
DRAWN BY : 趙彥年 <i>Okston</i>	CHECKED BY : 楊奇峰 <i>Ken</i>			
DESIGNED BY : 陳威仁 <i>Allen</i>	APPROVED BY : 謝立庭 <i>LT</i>			
TITLE : ACA-5020-A2-MC-S Specification		DOCUMENT NO.	ENS000015390	SPEC REV. A2