

2.2 OPERATIONAL DESCRIPTION

This device is transmitter of 2.4GHz Wireless Keyboard.

The device can transmit signal to associate USB dongle and control PC.

The device has one channel and operated in 2.420GHz with GFSK modulation.

Another information please refer to user's manual.

2.3 TEST MODES & EUT COMPONENTS DESCRIPTION

| EUT: 2.4GHz Wireless Keyboard, M/N: RK509C; ACC-RF-KBOTB | |
|--|-------------|
| Test Mode | Mode 1 |
| | Transmitter |

2.4 SUMMARY OF TEST PROCEDURE AND TEST RESULTS

| Test Item | Applied Standard Section | Test Result |
|---------------------|---|-----------------------------|
| Conduction Emission | 15.109, ANSI C63.4 Section 7 | Pass (refer to section 3.7) |
| Radiation Emission | 15.209, ANSI C63.4 Section 8 | Pass (refer to section 4.7) |
| Peak Power Output | 15.249(a), ANSI C63.4 Section 13 & Annex I | Pass (refer to section 4.7) |
| Band Edge | 15.249(d), ANSI C63.4 Section 13 & Annex I | Pass (refer to section 5.6) |

2.5 CONFIGURATION OF THE TESTED SYSTEM

The FCC IDs/Types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards, which have grants) are:

Non-test peripherals