

2.2 OPERATIONAL DESCRIPTION

This device is transceiver of wireless USB dongle included transmit and receive function.

The device can transmit signal to associate wireless keyboard or mouse and receive signal from wireless keyboard or mouse.

The device have 78 channel and operated in 2.402 to 2.479GHz with GFSK modulation.

Another information please refer to users manual.

2.3 TEST MODES & EUT COMPONENTS DESCRIPTION

EUT: Wireless Receiver, M/N: RX-635A	
Test Mode	Mode 1
	Transmitter

2.4 SUMMARY OF TEST PROCEDURE AND TEST RESULTS

Test Item	Applied Standard Section	Test Result
Conduction Emission	15.109, ANSI C63.4 Section 7	Pass (refer to section 3.7)
Radistion Emission	15.209, ANSI C63.4 Section 8	Pass (refer to section 4.7)
Peak Power Output	15.249(a), ANSI C63.4 Section 13 & Annex I	Pass (refer to section 4.7)
Band Edge	15.249(d) , ANSI C63.4 Section 13 & Annex I	Pass (refer to section 5.6)

2.5 CONFIGURATION OF THE TESTED SYSTEM

The FCC IDs/Types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards, which have grants) are:

Device	No.	Configuration
LCD MONITOR (DVI&D-SUB)	M01-061	Manufacturer : SONY Model Number : SDM-HS75P Serial Number : N/A BSMI ID : R33037 FCC ID : N/A DVI&D-SUB Cable : Non-Shielded, Detachable, 1.8m,cord POWER:AC INPUT :100-240V,50/60HZ Adapter Power Cord : Non-Shielded, Detachable, 3Pin, 1.8m
Modem	M03-028	Manufacturer : ACEEX Model Number : 1414V Serial Number : 0046183 BSMI ID : N/A FCC ID : IFAXDM1414 Data Cable : T Type:RS232, Shielded, Detachable, 1.2m Power Cord : Non-Shielded, Detachable, 1.5m Line : Type:RJ11(4P2C), Detachable, 1.8m Phone : Type:RJ11(4P2C), Detachable, 1.8m