

Qualcomm  
J9C-65VE239P2  
Request for transmitter modular approval

Transmitter Module Characteristics

Item	Requirements	EUT
1	Have its own RF shielding	<b>Device is equipped with metal shielding to cover RF section. Refer to external photos</b>
2	Have buffered modulation/data inputs (if such inputs are provided),	<b>All inputs to the modules are buffered through logic or microprocessor inputs.</b>
3	Have it own power supply regulation	<b>Internal 1.8V power regulator. Refer to Block diagram in the theory of operations</b>
4	Meet the antenna requirements of Section 15.203	<b>Device is equipped with unique antenna ( u.FL(v)-LP-040) connector. Refer to external photos</b>
5	Be tested in a stand-alone configuration, i.e., the antenna, AC or DC power and data input/output lines must be connected to the module but, the module must not be inside another case during testing	<b>Device was tested inside the laptop for limited modular approval. Refer to setup photos.</b>
6	Be labeled with its own FCC ID number, <b>and</b> if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.	<b>Two proposed FCC ID label format are included in the filing. One of label is to be placed on the module and the other label is to be placed on the outside of system. Refer to FCC ID label format and location file.</b>
7	The modular transmitter is manufactured so that the user cannot influence the operation of the transmitter that will operate outside of the scope of the regulations.	<b>Refer to “User’s Guide” Exhibit</b>
8	Compliance with RF exposure requirements is the responsibility of the grantee and will be addressed for all final host configurations.	<b>Refer to “Product Specification and Modular Installation” Exhibit</b>