

11.1 TEST DATA SUMMARY

Ambient TEMPERATURE (°C) _____ 23.0
Relative HUMIDITY (%) _____ 55.5
Atmospheric PRESSURE (kPa) _____ 96.2

Mixture Type: _____ Muscle _____

Dielectric Constant: _____ 54.2 _____

Conductivity: _____ 1.45 S/m _____

Closest Distance (between E-Probe & Phone Antenna): _____ 2.6 cm _____

Measurement Results

FREQUENCY		Modulation	POWER (W)	EAR Position	Antenna Position	SAR (W/kg)
MHz	Ch.					
1851.25	25	CDMA	0.35	Left	IN	1.0560
1851.25	25	CDMA	0.35	Left	OUT	1.3263
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak (Brain) Uncontrolled Exposure/General Population				1.6 W/kg (mW/g)		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. All modes of operation were investigated and the worst-case are reported.
2. Battery condition is fully charged for all readings.
3. Power measured: ☒ Conducted ☐ EIRP ☐ ERP


Randy Ortanez
President & Chief Engineer

PCTEST SEAL

DATE: _____ 06-25-98 _____