



# **Dell®/Gobi2000™ Collocated MPE Calculations**

**J9CGOBI2000-D**

**80-VR673-6 Rev. A**

**August 1, 2008**

---

**Submit technical questions at:  
<https://support.cdmatech.com>**

QUALCOMM is a registered trademark of QUALCOMM Incorporated in the United States and may be registered in other countries. Other product and brand names may be trademarks or registered trademarks of their respective owners. CDMA2000 is a registered certification mark of the Telecommunications Industry Association, used under license, ARM is a registered trademark of ARM Limited. QDSP is a registered trademark of QUALCOMM Incorporated in the United States and other countries.

Dell is a registered trademark of Dell, Inc.

This technical data may be subject to U.S. and international export, re-export, or transfer (“export”) laws. Diversion contrary to U.S. and international law is strictly prohibited.

**QUALCOMM Incorporated  
5775 Morehouse Drive  
San Diego, CA 92121-1714  
U.S.A.**

**Copyright © 2009 QUALCOMM Incorporated.  
All rights reserved.**

QUALCOMM®  
2009.08.06 at 13:22:29 PDT  
tina.chu-ccsemc.com

August 5, 2009

Dell®/Gobi2000™ Collocated MPE Calculations  
80-VR673-6 Rev. A

## Revision history

Revision	Date	Description
A	August 2009	Initial release

QUALCOMM®  
2009.08.06 at 13:22:29 PDT  
tina.chu-ccsemc.com

# 1 Introduction

This Maximum Permissible Exposure report demonstrates compliance with FCC CFR 47 §1.1310 and 2.1091 for collocated transmitters used in simultaneous conditions with the Gobi2000™ WWAN mPCIe installed in a host platform categorized as “mobile”. The mobile classification applies when 20 cm or more separation distance is maintained between the transmission antennas and the end-user.

The WWAN module is a Gobi2000 module authorized with FCC ID J9CGOBI2000-D.

Additional future collocated modules to be added to the host notebooks subsequent to this filing may be excluded from further submission, subject to the conditions of FCC KDB 447498, section 7.

## 1.1 Available Collocated WLAN Transmitters

Dell Inc. has provided the following list of initial WLAN FCC IDs that may be installed in Dell® notebook computers listed in Table 1:

- QDS-BRCM1030
- QDS-BRCM1031
- QDS-PRCM1041
- E2K512ANHMW
- E2K533ANH
- E2K622ANH
- E2K633ANH
- E2K625ANXH
- PPD-AR5BHB92
- PPD-AR5BXB63
- PD9512ANXHD
- QDS-BRCM1034
- QDS-BRCM1033
- QDS-BRCM1035
- T8YRTU7105-MOD-V3

Table 1 gives output power levels of each of the WLAN devices as given in their respective FCC grants. The maximum power levels are highlighted in boldface. The transmit powers used in collocated MPE calculations will be worst-case conservative values such that all collocated transmitters will have equal or less power. A Class II permissive change may be required to add a collocated transmitter if the new module exceeds values defined in the MPE calculations.

**Table 1 Dell Host Platforms**

Dell Model	Regulatory Model Number	Dell Model	Regulatory Model Number
Inspiron 13z	P06S-P06S001	Precision M6500	PP08X-PP08X001
Inspiron 1110	P03T-P03T001	Precision M6400	PP08X
		Precision M2400	PP27L
Latitude Z600	P01L-P01L001	Precision M4400	PP30L
Latitude E5400	PP23LA		
Latitude E4310	P05G-P05G001	Studio XPS 1340	PP17S
Latitude E4300	PP13S	Studio 1561	P06F-P06F001
Latitude E6500	PP30L	Studio 1458	P03G
Latitude E6400	PP27L	Studio 1745	P02E/P02E001
Latitude E6400 ATG	PP27L	Studio 1748	P02E/ TBD
Latitude E6400 XFR	P02G-P02G001	Studio XPS1645	PP35L

## 2 Transmitter Summary

Table 2 summarizes transmitter parameters associated with this permissive change application.

The WWAN modes of operation reflect the Gobi2000 module's parameters associated with FCC ID J9CGOBI2000-D.

The WLAN transmit power and antenna gain parameters represent the highest transmit power for a given frequency band from all of the WLAN/WPAN FCC IDs identified in Section 1.1.

Integration of a WLAN module that exceeds the parameters requires a new FCC authorization or permissive change application. A worst-case antenna gain of 5 dBi has been assumed for all WLAN antennas.

**Table 2 WWAN and Collocated Transmitter Declared Parameters**

FCC ID	Frequency (MHz)	Maximum Conducted Power (dBm)	Conducted Power (W)	Maximum Antenna Gain (dBi)
GPRS 2 UL	824	32.8	1.919	4.00
CDMA2000	824	24.6	0.29	4.00
UMTS	824	24.2	0.262	4.00
GPRS 2 UL	1850	29.4	0.875	3.50
CDMA2000	1850	24.6	0.291	3.50
UMTS	1850	24.1	0.256	3.50
WLAN	2402	6.33	0.004	5.00
WLAN	2412	26.4	0.438	5.00
WLAN	5180	16.7	0.047	5.00
WLAN	5260	23.7	0.23312	5.00
WLAN	5270	23.4	0.22039	5.00
WLAN	5500	22.2	0.16447	5.00
WLAN	5510	23.6	0.2278	5.00
WLAN	5725	26.4	0.441	5.00
WLAN	5745	25.5	0.352	5.00
WLAN	5755	25.1	0.325	5.00

### 3 RF Exposure Limits and Equations

According to FCC CFR 47 §1.1310, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

**Table 3 Limits for Maximum Permissible Exposure (MPE)**

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

Friis transmission formula:

$$P_d = \frac{P_{out} \times G}{4\pi R^2}$$

Where,

$P_d$  = power density (mW/cm<sup>2</sup>)

$P_{out}$  = output power to antenna (mW)

G = gain of antenna in linear scale

R = distance between observation point and center of the radiator (cm)

## 4 MPE Calculations

### 4.1 Stand Alone Transmitter Calculations

The MPE calculations for standalone transmitters at a separation distance of 20 cm are shown in Table 4 per the transmit power and antenna gain values declared in Table 2.

For frequency dependent limits, the lowest transmitter frequency was used to represent the lowest MPE limit (e.g. 824MHz = 0.549 mW/cm<sup>2</sup>).

The WLAN power levels listed represent the worst-case values for the corresponding frequency ranges associated with the grants listed in Section 1.1 *Available Collocated WLAN Transmitters*.

**Table 4 WWAN and WLAN Standalone MPE Calculations**

Technology	Frequency (MHz)	Maximum Conducted Power (dBm)	Conducted Power (W)	Maximum Antenna Gain (dBi)	Duty Cycle	Average EIRP (dBm)	Average EIRP (W)	Power Density @ 20cm (mW/cm <sup>2</sup> )	FCC MPE Limit (mW/cm <sup>2</sup> )
GPRS 2 UL	824 - 848	32.83	1.919	4.0	0.25	30.81	1.21	0.240	0.549
CDMA2000	826 - 846	24.18	0.262	4.0	1.00	28.18	0.66	0.131	0.549
UMTS	824 - 848	24.62	0.29	4.0	1.00	28.62	0.73	0.145	0.549
GPRS 2 UL	1850 - 1909	29.42	0.874	3.5	0.25	26.89	0.49	0.097	1.000
CDMA2000	1852 - 1907	24.08	0.256	3.5	1.00	27.58	0.57	0.114	1.000
UMTS	1851 - 1908	24.64	0.291	3.5	1.00	28.14	0.65	0.130	1.000
WLAN	2412 - 2462	29.00	0.794	5.0	1.00	34.0	2.51	0.500	1.000
WLAN	2496 - 2690	29.00	0.794	5.0	1.00	34.0	2.51	0.500	1.000
WLAN	3100 - 4800	29.00	0.794	5.0	1.00	34.0	2.51	0.500	1.000
WLAN	5180 - 5240	29.00	0.794	5.0	1.00	34.00	2.51	0.500	1.000
WLAN	5260 - 5320	29.00	0.794	5.0	1.00	34.00	2.51	0.500	1.000
WLAN	5470 - 5745	29.00	0.794	5.0	1.00	34.0	2.51	0.500	1.000
WLAN	5725 - 5850	29.00	0.794	5.0	1.00	34.0	2.51	0.500	1.000
WLAN	5755 - 5795	29.00	0.794	5.0	1.00	34.0	2.51	0.500	1.000
WLAN	6300 - 8000	29.00	0.794	5.0	1.00	34.0	2.51	0.500	1.000

## 4.2 Collocated MPE Calculations

Per OET 65, when RF sources have difference frequencies, the fraction of the FCC power density limited should be determined and the sum of all fractional components should be less than 1.

**Table 5 WWAN 850 MHz Collocation**

WLAN Band	(WLAN Pd) / (MPE Limit)	(WWAN 850 MHz) / MPE Limit)	(850 MHz WWAN fraction) + (WLAN fraction)	Limit	Pass/Fail
2412 - 2462	0.500	0.437	0.936	1	Pass
2496 - 2690	0.500	0.437	0.936	1	Pass
3100 - 4800	0.500	0.437	0.936	1	Pass
5180 - 5240	0.500	0.437	0.936	1	Pass
5260 - 5320	0.500	0.437	0.936	1	Pass
5470 - 5745	0.500	0.437	0.936	1	Pass
5725 - 5850	0.500	0.437	0.936	1	Pass
5755 - 5795	0.500	0.437	0.936	1	Pass
6300 - 8000	0.500	0.437	0.936	1	Pass

**Table 6 WWAN 1900 MHz Collocation**

WLAN Band	(WLAN Pd) / (MPE Limit)	(WWAN 1900 MHz) / MPE Limit)	(1900 MHz WWAN fraction) + (WLAN fraction)	Limit	Pass/Fail
2412 - 2462	0.500	0.130	0.629	1	Pass
2496 - 2690	0.500	0.130	0.629	1	Pass
3100 - 4800	0.500	0.130	0.629	1	Pass
5180 - 5240	0.500	0.130	0.629	1	Pass
5260 - 5320	0.500	0.130	0.629	1	Pass
5470 - 5745	0.500	0.130	0.629	1	Pass
5725 - 5850	0.500	0.130	0.629	1	Pass
5755 - 5795	0.500	0.130	0.629	1	Pass
6300 - 8000	0.500	0.130	0.629	1	Pass