

Exhibit 14 Frequency Stability

Frequency stability of the equipment versus temperature and power supply change was tested pursuant to FCC Part 2.1055. Measurement was conducted in CDMA transmitting mode without modulation on the carrier frequency. A CSZ Dimension Series 60 Chamber was used to stabilize a specific temperature and HP 8563E spectrum analyzer was used to monitor frequency stability

Test Equipment

| Equipment | Serial Number | Cal Date | Cal Due |
|---------------------------|---------------|--------------------|--------------------|
| Leader DC Power Supply | DE14268 | September 14, 2000 | September 14, 2001 |
| HP 8563 Spectrum Analyzer | 3412A00107 | February 1, 2001 | February 1, 2002 |

| Temperature (C) | CDMA Transmitter Carrier Frequency Deviation (ppm) | | | | | |
|-----------------|--|-------|-------|-------|-------|-------|
| | 10 | 11 | 12 | 14 | 16 | 18 |
| -30 | 0.11 | 0.53 | 0.80 | 0.57 | 0.02 | 0.68 |
| -20 | 0.17 | 0.74 | 0.98 | 0.75 | 0.87 | 0.73 |
| -10 | 0.07 | 0.10 | 1.10 | 0.69 | 0.35 | 0.93 |
| 0 | 0.19 | 0.44 | 0.50 | 0.21 | 0.18 | 0.32 |
| 10 | 0.53 | 0.09 | 0.58 | 0.44 | 0.06 | 0.04 |
| 20 | 0.13 | 0.03 | 0.21 | 0.14 | 0.15 | 0.18 |
| 30 | 0.05 | 0.17 | 0.31 | 0.21 | 0.10 | 0.13 |
| 40 | 0.11 | 0.10 | 0.13 | 0.03 | 0.04 | 0.03 |
| 50 | -0.74 | -0.75 | -1.10 | -0.43 | -0.38 | -0.04 |
| 60 | -1.69 | -1.16 | -1.72 | -0.44 | -0.29 | -0.46 |

