

Heptaband[™] Exterior Wireless Antennas



Heptaband external wireless antenna offers ultimate bandwidth with over seven frequency ranges

Laird Technologies Heptaband portable wireless antennas provide excellent radio transmission characteristics while offering the ultra flexibility of seven bands in one profile. With operating frequencies of 824 - 894 MHz, 880 - 960 MHz, 1575 MHz, 1710 - 1880MHz, 1850 - 1990 MHz, 1920 - 2170 MHz, 2400 - 2500 MHz, the antenna is the ideal choice when multiple band widths are required in various regional and global applications. Additionally, the blade style antenna features both knuckle and swivel snap-in or SMA/TNC/RPTNC connector options.

Features and Benefits:

- Operates simultaneously in more than seven frequency bands supporting - Cellular, Quadband GSM+UMTS/3G, GPS, AWS, WIFI, WLAN and WISP
- Available in knuckle swivel snap or SMA/TNC/RPTNC connector options.
- Blade style external antenna measures only 7.33"

Applications

 Wireless Terminal, Point-of-Sale, Machine to Machine, Automatic Meter Reading and Home Security

For sales information:

In the USA please telephone +1-800-323-3757

In Asia please telephone +886-2-2286-2828

In Europe please telephone +46-8-555-722-00


Laird TECHNOLOGIES®

Heptaband[™] Exterior Wireless Antennas


SPECIFICATIONS:

Electrical			
Frequency Range:	824-894 MHz, 880-960 MHz, 1575 MHz, 1710-1880 MHz, 1850-1990 MHz, 1920-2170 MHz, 2400-2500 MHz		
Gain	1 - 3 dBi		
VSWR	<2.5:1		
Polarization	Linear		
Azimuth (3dB beamwidth)	Omnidirectional		
Impedance	50 Ω		
Power	10 W		
Mounting Style	Snap-in/Captive, SMA, RPSMA, TNC, RPTNC		
Dimensions (mm)	6.3" x .36" (161 x 9.3)		

Model Number	Part Number	Mounting Style	Color
HEPTA-SM	MAF94300	SMA	Black
HEPTA-RSM	MAF94301	RP-SMA	Black
HEPTA-TN-G	MAF94302	TNC	Gray
HEPTA-RTN	MAF94303	RP-TNC	Black
HEPTA-IP04	MAF94304	SNAPIN/CAPTIVE, 100mm of RG178 coax with I-PEX connector	Black
НЕРТА-ММСХ04	MAF94305	SNAPIN/CAPTIVE, 100mm of RG178 coax MMCX connector	Black
HEPTA-FL04	MAF94306	SNAPIN/CAPTIVE, 100mm of RG178 coax flying lead	Black
HEPTA-TN	MAF94307	TNC	Black
HEPTA90-TN	MAF94309	TNC, Blade Angle - 90 degree	Black



Typical Azimuth Pattern



Typical Elevation Pattern

Any information furnished by Laird Technologies and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability, or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies domestic terms and conditions of sale in effect from time to time, a copy of which will be furnished upon request.

global solutions : local support .