

# 7.5 Spurious and Harmonic Emissions at Antenna Terminal §2.1051, §24.238(a), §27.53(h)

### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration.

# The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$ , where P is the transmitter power in Watts.

#### Test Procedure Used

KDB 971168 D01 v02r02 – Section 6.0 KDB 662911 D01 v02r01 – Section E)3)a)iii)

#### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to at least 10 \* the fundamental

frequency (separated into at least two plots per channel)

- 2. Detector = RMS
- 3. Trace mode = trace average for continuous emissions
- 4. Sweep time = auto couple
- 5. The trace was allowed to stabilize
- 6. Please see test notes below for RBW and VBW settings

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-4. Test Instrument & Measurement Setup

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager		
Test Report S/N:	Test Dates:	EUT Type:	Dego 61 of 105		
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 61 01 105		
© 2016 PCTEST Engineering Laboratory, Inc.					



### Test Notes

- 1. Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for frequencies less than 1 GHz and 1 MHz or greater for frequencies greater than 1 GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- Per 24.238(a) and 27.53(h), the spurious emission limit is -13dBm. Since this device transmits from two antennas simultaneously, applying the "Measure and add 10 log(N<sub>ant</sub>) dB", where N<sub>ant</sub> = 2, guidance from KDB 662911 D01 v02r01 yields an additional correction to the limit of -3dB. The correct out of band conducted emission limit is -13dBm + (-3dB) = **-16dBm**.

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager		
Test Report S/N:	Test Dates:	EUT Type:	Dega 62 of 105		
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 62 01 105		
© 2016 PCTEST Engineering Laboratory, Inc.					



#### Chain0







Plot 7-91. Conducted Spurious Plot (Band 4 – 5.0MHz QPSK – RB Size 6, Low Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager		
Test Report S/N:	Test Dates:	EUT Type:	Dege 62 of 105		
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 63 of 105		
© 2016 PCTEST Engineering Laboratory Inc.					



Agilent	Spectrum	Analyzei	r - Swept	SA								
L <mark>XI</mark> L		RF	50 Ω	DC	CORREC	SEN	VSE:INT		ALIGN AU	TO 03:23:13	MDec 29, 2015	Frequency
						Teles Free		Avg Type	RMS	TR/	CE 1 2 3 4 5 6	riequency
					PNO: Fast	Atten: 40	dB	Avg Hold:	100/100	, '		
					IFGain:Low	Atten. 40	40		_			
										Mkr1 4.07	2 8 GHz	Auto Tune
10 dE	3/div	Ref 3	0.00 d	IBm						-28.	547 dBm	
Log												
											⊥	Center Frea
20.0												5 01500000 GHz
											⊥	0.01000000000112
											⊥	
10.0											+	Otort From
											⊥	StartFreq
0.00												30.000000 MHz
											⊥	
											⊥	
-10.0											-13.00 dBm	Stop Freq
											⊥	10.00000000 GHz
-20.0												
						1					⊥	
											.	CF Step
-30.0						LUND BALL	and a she was	New John Constraint	a de la seco	ومانتكان والكروحاء وروادات	<mark>in philes dispersed the s</mark>	997.000000 MHz
			t s deux	الأخبران ار	na palanta di Victor	<b>New Parts</b>	MAA	New Joseph Contraction	يصبطره	line of a second based	the pathon of the second second	<u>Auto</u> Man
-40.0		<mark>i li na shik</mark>	allen i fisina m	لسريته ومعالى	and the second secon						<u> </u>	
	ning ingeningen ning ingeningen	and all a street	And Designed State								⊥	
-50.0												FreqOffset
-30.0											⊥	0 Hz
											⊥	
-60.0											<u> </u>	
											⊥	
Star	t 30 M	Hz								Stop 1	0.000 GHz	
#Res	SBW 1	.0 MH	Z		#VBW	3.0 MHz	*	S	weep	17.33 ms (	20001 pts)	
MSG									ST	ATUS		
	_		_	_						-		



Plot 7-92. Conducted Spurious Plot (Band 4 – 5.0MHz QPSK – RB Size 6, Mid Channel)

Plot 7-93. Conducted Spurious Plot (Band 4 – 5.0MHz QPSK – RB Size 6, Mid Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dege 64 of 105	
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 64 01 105	
© 2016 PCTEST Engineering Laboratory, Inc.				









Plot 7-95. Conducted Spurious Plot (Band 4 – 5.0MHz QPSK – RB Size 6, High Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager		
Test Report S/N:	Test Dates:	EUT Type:	Dage 65 of 105		
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 65 of 105		
© 2016 PCTEST Engineering Laboratory, Inc.					





Plot 7-96. Conducted Spurious Plot (Band 4 – 20.0MHz QPSK – RB Size 100, Low Channel)



Plot 7-97. Conducted Spurious Plot (Band 4 – 20.0MHz QPSK – RB Size 100, Low Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager		
Test Report S/N:	Test Dates:	EUT Type:	Dege 66 of 105		
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 66 01 105		
© 2016 PCTEST Engineering Laboratory, Inc.					





Plot 7-98. Conducted Spurious Plot (Band 4 – 20.0MHz QPSK – RB Size 100, Mid Channel)

Agilent	Spectrun	n Analyze	r - Swept	SA						_		
LXI L		RF	50 Ω	DC CC	RREC	SEN	ISE:INT	Avg Type	ALIGNAUTO	09:04:21 AF TRAC	4 Dec 30, 2015	Frequency
				F	NO: Fast 🔸	Trig: Free	Run	Avg Hold:	100/100	TYI		
				. IF	Gain:Low	Atten: 20	aD		D.41			Auto Tune
40.15		Def		Due					IALI	-36.6	44 dBm	
Log	siaia	Rel	19.00 0	вш								
												Center Freq
5.00												16.00000000 GHz
-5.00												Start From
											-13.00 dBm	10 00000000 GHz
-15.0												
-25.0												Stop Freq
-35.0									<b>≬</b> 1			22.000000000 GHz
							والمراجع والمراجع	anthantanathat	all all the state	A pair of pairs of the design of the	و به مارو الله الله ا	
-45.0	le classific	B. Jackson P.	en di statu di	all <sup>il</sup> stars date of	a <mark>iha inantanaki</mark>	in dit distant	A DE LA D	أمحاده وكالأروا ألغاب	احتبيه التظافين	and the states of the second		CF Step
-	a stand	iller and	N. Samana .	المراجع والمحافظ	. Alifentialisin planett	and the galaxies of the second se						Auto Man
-55.0												
												Freq Offset
-65.0												0 Hz
-75.0												
Stari	t 10.00	00 GH	z							Stop 22	.000 GHz	
#Res	s BW	1.0 MI	lz		#VBV	/ 3.0 MHz	¢	S	weep	20.80 ms (2	4001 pts)	
MSG									STAT	TUS		

Plot 7-99. Conducted Spurious Plot (Band 4 – 20.0MHz QPSK – RB Size 100, Mid Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dege 67 of 105	
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 67 01 105	
© 2016 PCTEST Engineering Laboratory, Inc.				





Plot 7-100. Conducted Spurious Plot (Band 4 - 20.0MHz QPSK - RB Size 100, High Channel)



Plot 7-101. Conducted Spurious Plot (Band 4 – 20.0MHz QPSK – RB Size 100, High Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dege 69 of 105	
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 68 01 105	
© 2016 PCTEST Engineering Laboratory, Inc.				



Chain1



Plot 7-102. Conducted Spurious Plot (Band 2 – 5.0MHz QPSK – RB Size 6, Low Channel)



Plot 7-103. Conducted Spurious Plot (Band 2 – 5.0MHz QPSK – RB Size 6, Low Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager		
Test Report S/N:	Test Dates:	EUT Type:	Dogo 60 of 105		
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Fage 09 01 105		
© 2016 PCTEST Engineering Laboratory, Inc.					









Plot 7-105. Conducted Spurious Plot (Band 2 - 5.0MHz QPSK - RB Size 6, Mid Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dego 70 of 105	
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 70 of 105	
© 2016 PCTEST Engineering Laboratory, Inc.				









Plot 7-107. Conducted Spurious Plot (Band 2 – 5.0MHz QPSK – RB Size 6, High Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 71 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 71 01 105
© 2016 PCTEST Engineering Laboratory, Inc.			





Plot 7-108. Conducted Spurious Plot (Band 2 - 20.0MHz QPSK - RB Size 100, Low Channel)



Plot 7-109. Conducted Spurious Plot (Band 2 – 20.0MHz QPSK – RB Size 100, Low Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dego 72 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 72 01 105
© 2016 PCTEST Engineering Laboratory, Inc. V			





Plot 7-110. Conducted Spurious Plot (Band 2 – 20.0MHz QPSK – RB Size 100, Mid Channel)



Plot 7-111. Conducted Spurious Plot (Band 2 – 20.0MHz QPSK – RB Size 100, Mid Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 72 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 75 01 105
© 2016 PCTEST Engineering Laboratory, Inc. V 3.3			





Plot 7-112. Conducted Spurious Plot (Band 2 - 20.0MHz QPSK - RB Size 100, High Channel)



Plot 7-113. Conducted Spurious Plot (Band 2 – 20.0MHz QPSK – RB Size 100, High Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dego 74 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 74 01 105
© 2016 PCTEST Engineering Laboratory, Inc.			



# 7.6 Peak-Average Ratio §24.232(d), §27.50(d)

## Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

#### Test Procedure Used

KDB 971168 v02r02 - Section 5.7.1

## Test Settings

- 1. The signal analyzer's CCDF measurement profile is enabled
- 2. Frequency = carrier center frequency
- 3. Measurement BW > Emission bandwidth of signal
- 4. The signal analyzer was set to collect one million samples to generate the CCDF curve
- 5. The measurement interval was set depending on the type of signal analyzed. For continuous

signals (>98% duty cycle), the measurement interval was set to 1ms.

## <u>Test Setup</u>

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-5. Test Instrument & Measurement Setup

## Test Notes

None

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Daga 75 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Fage 75 01 105
© 2016 PCTEST Engineering Laboratory. Inc. V 3.3			



#### Chain0







Plot 7-115. PAR Plot (Band 4 – 5.0MHz QPSK – RB Size 25, Mid Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 76 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 76 01 105
© 2016 PCTEST Engineering Laboratory, Inc.			





Plot 7-116. PAR Plot (Band 4 – 5.0MHz QPSK – RB Size 25, High Channel)



Plot 7-117. PAR Plot (Band 4 – 10.0MHz QPSK – RB Size 50, Mid Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dege 77 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 77 01 105
© 2016 PCTEST Engineering Laboratory, Inc. V			





Plot 7-118. PAR Plot (Band 4 – 15.0MHz QPSK – RB Size 75, Mid Channel)



Plot 7-119. PAR Plot (Band 4 – 20.0MHz QPSK – RB Size 50, Mid Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 79 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 76 01 105
© 2016 PCTEST Engineering Laboratory, Inc. V 3.			





Plot 7-120. PAR Plot (Band 2 - 5.0MHz QPSK - RB Size 25, Low Channel)



Plot 7-121. PAR Plot (Band 2 – 5.0MHz QPSK – RB Size 25, Mid Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Daga 70 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 79 01 105
© 2016 PCTEST Engineering Laboratory, Inc.			





Plot 7-122. PAR Plot (Band 2 – 5.0MHz QPSK – RB Size 25, High Channel)



Plot 7-123. PAR Plot (Band 2 – 10.0MHz QPSK – RB Size 50, Mid Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dege 90 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 60 01 105
© 2016 PCTEST Engineering Laboratory, Inc. V 3.			





Plot 7-124. PAR Plot (Band 2 – 15.0MHz QPSK – RB Size 75, Mid Channel)



Plot 7-125. PAR Plot (Band 2 – 20.0MHz QPSK – RB Size 50, Mid Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 91 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 61 01 105
© 2016 PCTEST Engineering Laboratory, Inc. V 3.			



#### Chain1



Plot 7-126. PAR Plot (Band 4 – 5.0MHz QPSK – RB Size 25, Low Channel)



Plot 7-127. PAR Plot (Band 4 – 5.0MHz QPSK – RB Size 25, Mid Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 92 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 62 01 105

© 2016 PCTEST Engineering Laboratory, Inc.





Plot 7-128. PAR Plot (Band 4 – 5.0MHz QPSK – RB Size 25, High Channel)



Plot 7-129. PAR Plot (Band 4 – 10.0MHz QPSK – RB Size 50, Mid Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 92 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 65 01 105
© 2016 PCTEST Engineering Laboratory, Inc.			





Plot 7-130. PAR Plot (Band 4 – 15.0MHz QPSK – RB Size 75, Mid Channel)



Plot 7-131. PAR Plot (Band 4 – 20.0MHz QPSK – RB Size 50, Mid Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dege 94 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 64 01 105
© 2016 PCTEST Engineering Laboratory, Inc.			









Plot 7-133. PAR Plot (Band 2 – 5.0MHz QPSK – RB Size 25, Mid Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 85 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 65 01 105
© 2016 PCTEST Engineering Laboratory, Inc.			





Plot 7-134. PAR Plot (Band 2 -5.0MHz QPSK - RB Size 25, High Channel)



Plot 7-135. PAR Plot (Band 2 – 10.0MHz QPSK – RB Size 50, Mid Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 96 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 60 01 105
© 2016 PCTEST Engineering Laboratory, Inc.			





Plot 7-136. PAR Plot (Band 2 – 15.0MHz QPSK – RB Size 75, Mid Channel)



Plot 7-137. PAR Plot (Band 2 – 20.0MHz QPSK – RB Size 50, Mid Channel)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dege 97 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 67 01 105
© 2016 PCTEST Engineering Laboratory, Inc.			



# 7.7 Frequency Stability / Temperature Variation §2.1055, §24.235, §27.54

## Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-D-2010. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 24 and Part 27, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

#### **Test Procedure Used**

ANSI/TIA-603-D-2010

#### Test Settings

- 1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
- 2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
- 3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

#### Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

#### Test Notes

None

FCC ID: J9CMTP9900LAA	<u> PCTEST</u>	FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 99 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Fage 66 01 105
© 2016 PCTEST Engineering Laboratory, Inc.			



# Band 4 Frequency Stability Measurements §2.1055, §27.54

OPERATING FREQUENCY:	2,132,500,000	Hz
REFERENCE VOLTAGE:	120.00	VAC

VOLTAGE (%)	POWER (VAC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %		+ 20 (Ref)	2,132,504,745	4,745	0.0002225
100 %		- 30	2,132,503,750	3,750	0.0001758
100 %		- 20	2,132,504,375	4,375	0.0002052
100 %	120.00	- 10	2,132,501,875	1,875	0.0000879
100 %		0	2,132,503,750	3,750	0.0001758
100 %		+ 10	2,132,502,500	2,500	0.0001172
100 %		+ 20	2,132,504,745	4,745	0.0002225
100 %		+ 30	2,132,501,875	1,875	0.0000879
100 %		+ 40	2,132,503,125	3,125	0.0001465
100 %		+ 50	2,132,503,750	3,750	0.0001758
85 %	102.00	+ 20	2,132,503,950	3,950	0.0001852
115 %	138.00	+ 20	2,132,503,575	3,575	0.0001676

 Table 7-2. Frequency Stability Data (Band 4)

## Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain inband when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Daga 90 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 69 01 105
© 2016 PCTEST Engineering Laboratory, Inc.			



# Band 2 Frequency Stability Measurements §2.1055, §24.235

OPERATING FREQUENCY:	1,960,000,000	Hz
REFERENCE VOLTAGE:	120.00	VAC

VOLTAGE (%)	POWER (VAC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %		+ 20 (Ref)	1,960,001,775	1,775	0.0000906
100 %		- 30	1,960,004,850	4,850	0.0002474
100 %		- 20	1,960,004,550	4,550	0.0002321
100 %	100.00	- 10	1,960,004,225	4,225	0.0002156
100 %		0	1,960,002,475	2,475	0.0001263
100 %	120.00	+ 10	1,960,001,550	1,550	0.0000791
100 %		+ 20	1,960,002,025	2,025	0.0001033
100 %		+ 30	1,960,001,745	1,745	0.0000890
100 %		+ 40	1,960,004,550	4,550	0.0002321
100 %		+ 50	1,960,003,675	3,675	0.0001875
85 %	102.00	+ 20	1,960,003,125	3,125	0.0001594
115 %	138.00	+ 20	1,960,003,625	3,625	0.0001849

 Table 7-3. Frequency Stability Data (Band 2)

## Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain inband when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 00 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Fage 90 01 105
© 2016 PCTEST Engineering Laboratory, Inc.			



# 7.8 Cabinet Radiated Spurious Emissions Measurements §2.1053, §24.238(a), §27.53(h)

### Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the outputs of the EUT terminated in 50 $\Omega$ . Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

#### **Test Procedures Used**

KDB 971168 v02r02 – Section 5.8 ANSI/TIA-603-D-2010 – Section 2.2.12

#### Test Settings

- 1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
- 2. VBW  $\geq$  3 x RBW
- 3. Span = 1.5 times the OBW
- 4. No. of sweep points  $\geq$  2 x span / RBW
- 5. Detector = Peak
- 6. Trace mode = max hold
- 7. The trace was allowed to stabilize

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dage 01 of 105	
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 91 01 105	
© 2016 PCTEST Engineering Laboratory, Inc.				



## Test Setup



The EUT and measurement equipment were set up as shown in the diagram below.

Figure 7-6. Test Instrument & Measurement Setup

## **Test Notes**

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning.
- 2) This unit was tested while powered by an AC power source.
- The EUT was evaluated for cabinet radiated spurious emissions with the antenna ports terminated in 50 $\Omega$ .
- 4) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 5) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 6) The wide spectrum spurious emissions plots shown on the following pages were measured at a 1m distance and are used only for the purpose of emission identification. There were no emissions detected in the 30MHz - 1GHz frequency range or above 18GHz, as shown in the subsequent plots.
- 7) The "-" shown in the "Antenna Height" and "Turntable Azimuth" columns of the following RSE tables are used to denote a noise floor measurement.
- 8) Cabinet radiated emissions were performed for two different test scenarios. In Test Scenario #1, Chain0 was active. In Test Scenario #2, Chain1 was active. Both scenarios were used to measure cabinet radiated emissions with the antenna ports terminated in 50  $\Omega$ . The test scenarios are labeled throughout this section.

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dega 02 of 105	
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 92 01 105	
© 2016 PCTEST Engineering Laboratory, Inc.				



## Test Scenario #1 - Chain0



Plot 7-138. Radiated Spurious Plot above 1GHz (LTE Band 4, 5MHz BW, Ch. 2175)



Plot 7-139. Radiated Spurious Plot above 1GHz (LTE Band 4, 20MHz BW, Ch. 2175)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dago 02 of 105	
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Fage 93 01 105	





Plot 7-140. Radiated Spurious Plot above 1GHz (LTE Band 2, 5MHz BW, Ch. 900)



Plot 7-141. Radiated Spurious Plot above 1GHz (LTE Band 2, 20MHz BW, Ch. 900)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dogo 04 of 105	
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 94 01 105	



## Test Scenario #2 – Chain1



Plot 7-142. Radiated Spurious Plot above 1GHz (LTE Band 4, 5MHz BW, Ch. 2175)



Plot 7-143. Radiated Spurious Plot above 1GHz (LTE Band 4, 20MHz BW, Ch. 2175)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager		
Test Report S/N:	Test Dates:	EUT Type:	Dogo 05 of 105		
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Fage 95 01 105		
@ 2016 DOTECT Engineering Lak					

© 2016 PCTEST Engineering Laboratory, Inc.









Plot 7-145. Radiated Spurious Plot above 1GHz (LTE Band 2, 20MHz BW, Ch. 900)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dago 06 of 105	
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Fage 90 01 105	
© 2016 PCTEST Engineering Laboratory, Inc.				



## Test Scenario #1 – Chain0

OPERATING FREQUENCY:	211	2.50 MHz
BANDWIDTH:	5.0	MHz
DISTANCE:	3	meters
LIMIT:	-13	dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1100.00	Н	-	-	-54.44	6.36	-48.09	-35.1
8673.00	Н	-	-	-50.44	11.07	-39.37	-26.4

Table 7-4. Radiated Spurious Data (Band 4 – Low Channel, 5MHz BW)

OPERATING FREQUENCY:	213	2.50 MHz
BANDWIDTH:	5.0	MHz
DISTANCE:	3	meters
LIMIT:	-13	dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3068.00	Н	-	-	-51.15	9.44	-41.72	-28.7
13446.00	Н	-	-	-49.02	12.38	-36.64	-23.6

Table 7-5. Radiated Spurious Data (Band 4 – Mid Channel, 5MHz BW)

OPERATING FREQUENCY:	215	2.50 MHz
BANDWIDTH:	5.0	MHz
DISTANCE:	3	meters
LIMIT:	-13	dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
2903.00	Н	-	-	-53.08	9.84	-43.24	-30.2
6654.00	Н	-	-	-44.86	11.89	-32.97	-20.0

 Table 7-6. Radiated Spurious Data (Band 4 – High Channel, 5MHz BW)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager		
Test Report S/N:	Test Dates:	EUT Type:	Dega 07 of 105		
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 97 01 105		
© 2016 PCTEST Engineering Laboratory, Inc.					



OPERATING FREQUENCY:	193	2.50 MHz
BANDWIDTH:	5.0	MHz
DISTANCE:	3	meters
LIMIT:	-13	dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1339.00	Н	1.25	257	-55.55	7.38	-48.17	-35.2
3865.00	Н	1.64	68	-35.10	9.22	-25.88	-12.9
13442.00	Н	-	-	-48.70	12.38	-36.32	-23.3

Table 7-7. Radiated Spurious Data (Band 2 – Low Channel, 5MHz BW)

OPERATING FREQUENCY:
BANDWIDTH:
DISTANCE:
LIMIT:

JENCY:	196	0.00	MHz
NIDTH:	5.0	MHz	
TANCE:	3	meters	
LIMIT:	-13	dBm	
		-	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1280.00	Н	1.11	302	-52.76	7.01	-45.76	-32.8
3240.00	Н	1.03	188	-50.55	9.49	-41.06	-28.1
3920.00	Н	1.15	117	-34.30	9.33	-24.97	-12.0
6650.00	Н	-	-	-46.16	11.90	-34.26	-21.3

Table 7-8. Radiated Spurious Data (Band 2 – Mid Channel, 5MHz BW)

OPERATING FREQUENCY:	198	7.50 MHz
BANDWIDTH:	5.0	MHz
DISTANCE:	3	meters
LIMIT:	-13	dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]	
1221.00	Н	2.54	27	-56.32	6.70	-49.62	-36.6	
3975.00	Н	2.50	304	-36.43	9.57	-26.86	-13.9	
13442.00	Н	-	-	-48.75	12.38	-36.37	-23.4	
	Table 7-9. Radiated Spurious Data (Band 2 – High Channel, 5MHz BW)							

	C PCTEST	FCC Pt. 24 & 27 LTE MEASUREMENT REPORT	Reviewed by:
TOO ID: JOOMITT SOULAA	THE RECEIPTING LABORATORY, INC.	(CERTIFICATION)	Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Daga 08 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 96 01 105
			110.0

© 2016 PCTEST Engineering Laboratory, Inc.



OPERATING FREQUENCY:	212	20.00 MHz
BANDWIDTH:	20.0	MHz
DISTANCE:	3	meters
LIMIT:	-13	dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
2740.00	Н	-	-	-53.88	9.87	-44.02	-31.0
7346.00	Н	-	-	-51.94	10.76	-41.18	-28.2

Table 7-10. Radiated Spurious Data (Band 4 – Low Channel, 20MHz BW)

OPERATING FREQUENCY:	2132.50		MHz
BANDWIDTH:	20.0	MHz	
DISTANCE:	3	meters	
LIMIT:	-13	dBm	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1280.00	Н	-	-	-55.45	7.01	-48.45	-35.4
3240.00	Н	-	-	-51.22	9.49	-41.73	-28.7
13446.00	Н	-	-	-47.92	12.38	-35.54	-22.5

Table 7-11. Radiated Spurious Data (Band 4 – Mid Channel, 20MHz BW)

OPERATING FREQUENCY:2145.00MHzBANDWIDTH:20.0MHzDISTANCE:3metersLIMIT:-13dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1326.00	Н	-	-	-58.24	7.29	-50.95	-38.0
7788.00	Н	-	-	-52.03	11.22	-40.81	-27.8

Table 7-12. Radiated Spurious Data (Band 4 – High Channel, 20MHz BW)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager		
Test Report S/N:	Test Dates:	EUT Type:	Dogo 00 of 105		
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 99 01 105		
© 2016 PCTEST Engineering Laboratory, Inc. V 3.3					



OPERATING FREQUENCY:	194	0.00 MHz
BANDWIDTH:	20.0	MHz
DISTANCE:	3	meters
LIMIT:	-13	dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1320.00	Н	1.98	245	-53.95	7.25	-46.70	-33.7
3880.00	Н	1.70	228	-37.27	9.23	-28.04	-15.0
7519.00	Н	-	-	-53.68	10.97	-42.71	-29.7

Table 7-13. Radiated Spurious Data (Band 2 – Low Channel, 20MHz BW)

OPERATING FREQUENCY:	
BANDWIDTH:	
DISTANCE:	
LIMIT:	

CY:	196	0.00	MHz
TH:	20.0	MHz	
CE:	3	meters	
1IT:	-13	dBm	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1280.00	Н	1.00	234	-42.14	7.01	-35.14	-22.1
3240.00	Н	-	-	-51.71	9.49	-42.22	-29.2
3920.00	Н	2.09	302	-40.73	9.33	-31.40	-18.4
13442.00	Н	1.18	360	-44.98	12.38	-32.60	-19.6

Table 7-14. Radiated Spurious Data (Band 2 – Mid Channel, 20MHz BW)

OPERATING FREQUENCY:	1980.00		MHz
BANDWIDTH:	20.0	MHz	
DISTANCE:	3	meters	
LIMIT:	-13	dBm	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]	
1221.00	Н	1.04	256	-49.62	6.70	-42.92	-29.9	
3960.00	Н	1.86	305	-37.26	9.51	-27.75	-14.8	
6653.00	Н	-	-	-47.43	11.89	-35.54	-22.5	
Table 7-15. Radiated Spurious Data (Band 2 – High Channel, 20MHz BW)								

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager			
Test Report S/N:	Test Dates:	EUT Type:	Dega 100 of 105			
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 100 01 105			

© 2016 PCTEST Engineering Laboratory, Inc.



## Test Scenario #2 – Chain1

OPERATING FREQUENCY:		2112.50	MHz
BANDWIDTH:	5.0	MHz	
DISTANCE:	3	meters	
LIMIT:	-13	dBm	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1100.00	Н	-	-	-55.60	6.36	-49.25	-36.2
8673.00	Н	-	-	-50.62	11.07	-39.55	-26.6

Table 7-16. Radiated Spurious Data (Band 4 – Low Channel, 5MHz BW)

OPERATING FREQUENCY:	213	2.50	MHz
BANDWIDTH:	5.0	MHz	
DISTANCE:	3	meters	
LIMIT:	-13	dBm	
		_	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3068.00	Н	-	-	-51.61	9.44	-42.18	-29.2
4265.00	Н	-	-	-48.44	10.62	-37.82	-24.8

Table 7-17. Radiated Spurious Data (Band 4 – Mid Channel, 5MHz BW)

OPERATING FREQUENCY:		2152.50	MHz
BANDWIDTH:	5.0	MHz	
DISTANCE:	3	meters	
LIMIT:	-13	dBm	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
2903.00	Н	-	-	-52.91	9.84	-43.07	-30.1
6654.00	Н	-	-	-45.53	11.89	-33.64	-20.6

Table 7-18. Radiated Spurious Data (Band 4 – High Channel, 5MHz BW)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 101 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 101 01 105
© 2016 PCTEST Engineering Lab	oratory, Inc.		V 3.3



OPERATING FREQUENCY:		MHz	
BANDWIDTH:	5.0	MHz	
DISTANCE:	3	meters	
LIMIT:	-13	dBm	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1339.00	Н	-	-	-55.35	7.38	-47.97	-35.0
3865.00	Н	1.00	32	-36.85	9.22	-27.63	-14.6
7230.00	Н	-	-	-48.26	12.38	-35.88	-22.9

Table 7-19. Radiated Spurious Data (Band 2 – Low Channel, 5MHz BW)

**OPERATING FREQUENCY** BANDWIDTH DISTANCE LIMIT

1:	196	0.00	MHz
1:	5.0	MHz	
:	3	meters	
Г:	-13	dBm	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1843.00	Н	-	-	-55.51	7.01	-48.51	-35.5
3240.00	Н	-	-	-46.00	9.49	-36.51	-23.5
3920.00	Н	-	-	-46.72	9.33	-37.39	-24.4
10446.00	Н	-	-	-47.14	11.90	-35.24	-22.2

Table 7-20. Radiated Spurious Data (Band 2 – Mid Channel, 5MHz BW)

OPERATING FREQUENCY:	198	87.50	MHz
BANDWIDTH:	5.0	MHz	
DISTANCE:	3	meters	
LIMIT:	-13	dBm	

Frequency [MHz]	, Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1221.00	Н	-	-	-55.90	6.70	-49.20	-36.2
3975.00	Н	-	-	-46.95	9.57	-37.38	-24.4
13442.00	Н	-	-	-48.86	12.38	-36.48	-23.5
-	Table 7	-21. Radia	ted Spuric	ous Data (Band 2	– High Channel,	5MHz BW)	

Table 7-21. Radiated	Spurious Data	(Band 2 – High	Channel,	5MHz B
			/	

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dega 102 of 105	
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 102 01 105	
© 2016 PCTEST Engineering Laboratory, Inc.				



OPERATING FREQUENCY:	212	0.00 MHz
BANDWIDTH:	20.0	MHz
DISTANCE:	3	meters
LIMIT:	-13	dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
2740.00	Н	-	-	-53.58	9.87	-43.72	-30.7
7346.00	Н	-	-	-50.90	10.76	-40.14	-27.1

Table 7-22. Radiated Spurious Data (Band 4 – Low Channel, 20MHz BW)

OPERATING FREQUENCY:		MHz	
BANDWIDTH:	20.0	MHz	
DISTANCE:	3	meters	
LIMIT:	-13	dBm	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1280.00	Н	-	-	-56.78	7.01	-49.78	-36.8
3240.00	Н	-	-	-50.61	9.49	-41.12	-28.1

Table 7-23. Radiated Spurious Data (Band 4 – Mid Channel, 20MHz BW)

OPERATING FREQUENCY:	2	145.00	MHz
BANDWIDTH:	20.0	MHz	
DISTANCE:	3	meters	
LIMIT:	-13	dBm	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1326.00	Н	-	-	-55.93	7.29	-48.64	-35.6
7788.00	Н	-	-	-51.88	11.22	-40.66	-27.7

 Table 7-24. Radiated Spurious Data (Band 4 – High Channel, 20MHz BW)

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager		
Test Report S/N:	Test Dates:	EUT Type:	Dage 102 of 105		
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 103 01 105		
© 2016 PCTEST Engineering Laboratory, Inc.					



OPERATING FREQUENCY:		MHz	
BANDWIDTH:	20.0	MHz	
DISTANCE:	3	meters	
LIMIT:	-13	dBm	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1320.00	Н	-	-	-55.56	7.25	-48.31	-35.3
3880.00	Н	2.14	121	-31.63	9.23	-22.40	-9.4
6650.00	Н	-	-	-51.43	10.97	-40.46	-27.5

Table 7-25. Radiated Spurious Data (Band 2 – Low Channel, 20MHz BW)

**OPERATING FREQUENCY:** BANDWIDTH: DISTANCE LIMIT

:	196	0.00	MHz
:	20.0	MHz	
:	3	meters	
:	-13	dBm	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1280.00	Н	1.00	241	-55.98	7.01	-48.98	-36.0
3240.00	Н	-	-	-49.90	9.49	-40.41	-27.4
3920.00	Н	1.01	21	-38.83	9.33	-29.50	-16.5
13442.00	Н	-	-	-49.63	12.38	-37.25	-24.3

Table 7-26. Radiated Spurious Data (Band 2 – Mid Channel, 20MHz BW)

OPERATING FREQUENCY:	19	MHz	
BANDWIDTH:	20.0	MHz	
DISTANCE:	3	meters	
LIMIT:	-13	dBm	

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [m]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]	
1221.00	Н	-	-	-56.46	6.70	-49.76	-36.8	
3960.00	Н	-	-	-48.64	9.51	-39.13	-26.1	
6653.00	Н	-	-	-46.38	11.89	-34.49	-21.5	
	Table 7-27. Radiated Spurious Data (Band 2 – High Channel, 20MHz BW)							

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dega 104 of 105	
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Page 104 01 105	
© 2016 PCTEST Engineering Laboratory Inc.				

© 2016 PCTEST Engineering Laboratory, Inc.



# 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Qualcomm LAA Release 13 Small Cell FCC ID: J9CMTP9900LAA** complies with all the requirements for LTE operation under Parts 24 & 27 of the FCC rules.

FCC ID: J9CMTP9900LAA		FCC Pt. 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dago 105 of 105
0Y1607131257-R2.J9C	12/23/2015-3/5/2016	LAA Release 13 Small Cell	Fage 105 01 105
© 2016 PCTEST Engineering Lab	poratory, Inc.		V 3.3