



UNDP-1 HP HSTNN-I71C Collocated RF Analysis

80-VH688-19 Rev. A

June 30, 2009

Submit technical questions at:
<https://support.cdmatech.com>

QUALCOMM is a registered trademark of QUALCOMM Incorporated in the United States and may be registered in other countries. Other product and brand names may be trademarks or registered trademarks of their respective owners. CDMA2000 is a registered certification mark of the Telecommunications Industry Association, used under license. ARM is a registered trademark of ARM Limited. QDSP is a registered trademark of QUALCOMM Incorporated in the United States and other countries.

This technical data may be subject to U.S. and international export, re-export, or transfer ("export") laws. Diversion contrary to U.S. and international law is strictly prohibited.

**QUALCOMM Incorporated
5775 Morehouse Drive
San Diego, CA 92121-1714
U.S.A.**

**Copyright © 2009 QUALCOMM Incorporated.
All rights reserved.**

June 30, 2009

UNDP-1 HP HSTNN-I71C Collocated RF Analysis

80-VH688-19 Rev. A

Revision history

Revision	Date	Description
A	May 2009	Initial release

1 Overview

This document provides collocated SAR analysis of the notebook model HSTNN-I71C in reference to KDB 616217.

The change filed under this application is adding notebook model HSTNN-I71C collocated with Bluetooth FCC IDs: QDS-BRCM1043 and QDS-BRCM1018, and WLAN FCC IDs: QDS-BRCM1041, PD9512ANHU, QDS-BRCM1030.

The analysis shows that notebook model HSTNN-I71C is compliant for all combinations of WWAN and WLAN modules based on the SAR summation of individual SAR measurement results.

1.1 Definitions

$$N_x = P_x / (60/f) - 1$$

P= average power

F= frequency in MHz

1.2 Collocation Calculations

Table 1-1 Antenna Separation Distances

Antenna	Distance (cm)
WLAN Main-to-user	16.5
WLAN Aux-to-user	16.5
WWAN main-to-user	16.5
WLAN Aux-to-WWAN main	7.7
WLAN main-to-WWAN main	15.1

Table 1-2 Individual Transmitter SAR Evaluation (Worst Case)

Technology	Freq (MHz)	Measured Burst Avg Pwr (GPRS only) (dBm)	Average Power (dBm)	Measured Average Power (mW)	60/F _(GHz) (mW)	n = (P / (60/f) - 1) cm	1/2*n (cm) per FCC Procedure	Minimum Antenna-User Separation Requirement (cm)	Actual Antenna-User Distance (cm)	Highest Measured SAR (mW/g 1g)
GPRS 850 MHz	824.2	31.4	25.38	345.1	72.8	3.7	2	7.0	5.2	0.047
UMTS 1900 MHz	1908.75		24.87	306.9	31.4	8.8	4	9	5.2	0.105
WLAN (QDS-BRCM1041)	5600		25.47	352.0	10.7	32	16	21	16.1	0.119
WLAN (PD9512ANHU)	5600		16.62	45.9	10.7	3	2	7	16.1	0.294
WLAN (QDS-BRCM1030)	2400		23.10	202.0	25.0	7	4	9	16.1	0.005

Table 1-3 Simultaneous Transmitter SAR Requirements

Mode	$(5 + 1/2 Nx + 1/2 Ny)$ cm	Actual Separation (cm)	Result
GPRS 850 MHz + WLAN Aux	23.0	7.7	SAR eval required. >5cm: Sum SAR
UMTS 1900 MHz + WLAN	25.0	15.1	SAR eval required. >5cm: Sum SAR

1.2.1 Collocation with QDS-BRCM1041

Table 1-4 Simultaneous SAR Summation QDS-BRCM1041

Mode	Highest Measured SAR (mW/g (1g))
WWAN 850 Max SAR (GPRS 850MHz)	0.047
WWAN 1900 MHz SAR (UMTS 1900MHz)	0.105
WLAN MAX SAR from QDS-BRCM1041 SAR report	0.119

WWAN 850MHz + WLAN (QDS-BRCM1041):

$$\text{WWAN 850 + WLAN SAR} = 0.047 \text{ mW/g} + 0.119 \text{ mW/g} = 0.166 \text{ mW/g (1g)}$$

WWAN 1900MHz + WLAN (QDS-BRCM1041):

$$\text{WWAN 1900 + WLAN SAR} = 0.105 \text{ mW/g} + 0.119 \text{ mW/g} = 0.224 \text{ mW/g (1g)}$$

1.2.2 Collocation with FCC ID PD9512ANHU

Table 1-5 Simultaneous SAR Summation PD9512ANHU

Mode	Highest Measured SAR (mW/g (1g))
WWAN 850 Max SAR (GPRS 850MHz)	0.047
WWAN 1900 MHz SAR (UMTS 1900MHz)	0.105
WLAN MAX SAR from PD9512ANHU SAR report	0.294

WWAN 850MHz + WLAN (PD9512ANHU):

$$\text{WWAN 850 + WLAN SAR} = 0.047 \text{ mW/g} + 0.294 \text{ mW/g} = 0.341 \text{ mW/g (1g)}$$

WWAN 1900MHz + WLAN (PD9512ANHU) :

$$\text{WWAN 1900 + WLAN SAR} = 0.105 \text{ mW/g} + 0.294 \text{ mW/g} = 0.339 \text{ mW/g (1g)}$$

1.2.3 Collocation with FCC ID QDS-BRCM1030

Table 1-6 Simultaneous SAR Summation QDS-BRCM1030

Mode	Highest Measured SAR (mW/g (1g))
WWAN 850 Max SAR (GPRS 850MHz)	0.047
WWAN 1900 MHz SAR (UMTS 1900MHz)	0.105
WLAN MAX SAR from PD9512ANHU SAR report	0.005

WWAN 850MHz + WLAN (PD9512ANHU):

WWAN 850 + WLAN SAR = 0.047 mW/g + 0.005 mW/g = **0.052 mW/g (1g)**

WWAN 1900MHz + WLAN (PD9512ANHU) :

WWAN 1900 + WLAN SAR = 0.105 mW/g + 0.005mW/g = **0.110 mW/g (1g)**

2 Permissive Change History

Table 2-1 summarizes the FCC permissive history for FCC ID J9CUNDP-1H.

Table 2-1 Permissive Change History for J9CUNDP-1H

Grant Date	Change Description	Hosts	WWAN FCC Category	WLAN FCC IDs
1/23/2008	Change of FCC ID from J9CUNDP-1			
5/16/2008	Mobile with end user install and simultaneous TX	Mobile hosts	Mobile	QDS-BRCM1036 QDS-BRCM1028
7/8/2008	Added portable host with collocation and end user install	HSTNN-W47C	Portable	QDS-BRCM1036 QDS-BRCM1028
7/30/2008	Add collocated WLAN modules to mobile configurations	Mobile hosts	Mobile	PD9533ANMU PD9512ANMU PD9512ANM QDS-BRCM1036 QDS-BRCM1028 PD9533ANM
10/21/2009	Add portable host + collocation	HP HSTNN-I57C	Portable	
4/23/2009	Add portable host + collocation	HSTNN-I70C	Portable	QDS-BRCM1010 QDS-BRCM1030
Pending	Add collocated WLAN modules to mobile configurations	Mobile hosts	Mobile	QDS-BRCM1031 QDS-BRCM1041 PPD-AR5BHB92-H PPD-AR5B95-H
	Add Portable Host + collocation	HSTNN-I71C	Portable	QDS-BRCM1043 QDS-BRCM1018 QDS-BRCM1041 PD9512ANHU QDS-BRCM1030