Over view

Model: CRD-BP1500U is the CD-RW Drive with Max. signal transfer rate: X40 speed. This device is provided USB2.0 interface and installed internal of the Personal Computer.

< *Specifications* >

Recording/playback speed

Recording	:	x2 ,x4,x8,x12,x16,x24(Write)
		x2 ,x4,x8,x10(Rewrite)
Playback & Data reading	:	x1 ~ x40 speed

Signal transfer rate

x1 speed (CLV)	: 150kB/s		
x2 speed (CLV)	: 300kB/s	x16 ~x40 speed(CAV)	: 2400kB/s~6000kB/s
x4 speed (CLV)	: 600kB/s		
x8 speed (CLV)	: 1200kB/s		
x12 speed (CLV)	: 1800kB/s		

Connectors

Interface connector	:	4-pin	
DC connector:	:	4-pin, +5V, +12V	(for Internal use)
	:	5-pin, +5V, +12V	(for External use)
Analog Audio connector	:	4-pin	(for Internal use)
(Line Out)		3.5mm stereo mini-jack	(for External use)
Digital Audio connector	:	2-pin	(for Internal use)
Headphone	:	3.5mm stereo mini-jack	

Audio

Headphone Output level	: 90mV (1kHz, 28dB)
Line Out Output level	: 70mV (1kHz, 70dB)

Loading method: Tray loading

Dimensions: (WxDxH) 146 x 188.5 x 41.3 mm

Weight: 1040g