



TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11b

Channel	Frequency (MHz)	Reading Power(dBm)	Factor (dB)	Output Power(dBm)	Output Power(W)	Limit(W)	Result
Low	2412	25.96	1	26.96	0.49659	1	PASS
Mid	2437	26.14	1	27.14	0.51761		PASS
High	2462	27.02	1	28.02	0.63387		PASS

Test mode: IEEE 802.11g

Channel	Frequency (MHz)	Reading Power(dBm)	Factor (dB)	Output Power(dBm)	Output Power(W)	Limit(W)	Result
Low	2412	24.36	1	25.36	0.34356	1	PASS
Mid	2437	24.54	1	25.54	0.35810		PASS
High	2462	25.38	1	26.38	0.43451		PASS



RADIO FREQUENCY EXPOSURE

LIMIT

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §15.247(i) and §1.1307(b)(1) of this chapter.

EUT Specification

EUT	Mini PCI Wireless Adapter
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input type="checkbox"/> Others
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <ul style="list-style-type: none"> <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
Max. output power	28.02dBm (633.87mW)
Antenna gain (Max)	4.5 dBi (Numeric gain: 2.8184)
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Remark:

1. The maximum output power is 28.02(633.87mW) at 2462MHz (with 2.8184 numeric antenna gain.)
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser.

TEST RESULTS

No non-compliance noted.



Calculation

Given $E = \sqrt{\frac{30 \times P \times G}{d}}$ & $S = \frac{E^2}{3770}$

Where $E =$ Field Strength in Volts / meter
 $P =$ Power in Watts
 $G =$ Numeric antenna gain
 $d =$ Distance in meters
 $S =$ Power Density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$d = \sqrt{\frac{30 \times P \times G}{3770 \times S}}$$

Changing to units of mW and cm, using:

$$P (mW) = P (W) / 1000 \text{ and}$$

$$d (cm) = 100 * d (m)$$

Yields

$$d = 100 \times \sqrt{\frac{30 \times (P / 1000) \times G}{3770 \times S}} = 0.282 \times \sqrt{\frac{P \times G}{S}}$$

Where $d =$ distance in cm
 $P =$ Power in mW
 $G =$ Numeric antenna gain
 $S =$ Power Density in mW / cm²

Substituting the logarithmic form of power and gain using:

$$P (mW) = 10 ^ (P (dBm) / 10) \text{ and}$$

$$G (numeric) = 10 ^ (G (dBi) / 10)$$

Yields

$$d = 0.282 \times \frac{10^{(P+G)/20}}{\sqrt{20}}$$

Equation 1

Where $d =$ MPE safe distance in cm
 $P =$ Power in dBm
 $G =$ Antenna Gain in dBi
 $S =$ Power Density Limit in mW / cm²



Maximum Permissible Exposure (2.4 GHz Band)

EUT output power = 633.8697mW

Antenna Gain = 2.818383 (Numeric gain)

S = 1.0 mW / cm² from 1.1310 Table 1

Substituting these parameters into the above Equation 1:

→ MPE Safe Distance = 12.03538cm

(For mobile or fixed location transmitters, the minimum separation distance is 20 cm, even if calculations indicate that the MPE distance would be less.)