

2.985 RF Power Output

Power output is measured and set at the RF antenna port of the transmitter using an HP-436A Power Meter with an HP-8481B High Power Sensor.

The transmit power is set at the desired level by adjusting the Power Amplifier Gain Adjust at the front of this module. The Power Amplifier has the following characteristics.

Alcatel Part Number	644-0327-xxx
Type Design	Solid State
DC Power Requirement	+10.5 Vdc @ 7.3A -12 Vdc @ 100mA -5 Vdc @ 100mA
Gain	46 dB typical
Output Power	+31 dBm transmit power at the antenna port.

2.987 MODULATION CHARACTERISTICS

The modulation employed in this equipment is 64 QAM (Quadrature Amplitude Modulation). This modulation was selected to achieve a good BER (bit error rate) performance while maintaining a high spectral efficiency.

The 64 QAM signal is generated by direct modulation of the RF carrier and its quadrature frequency component using the I and Q baseband signals. The I and Q baseband signals are fed to RF mixers in the modulator. The output of the transmit local oscillator is also fed to the RF mixers through a 90 degree hybrid coupler. Each baseband signal (I and Q) is applied to a double balanced mixer where it is translated to RF using the in-phase and quadrature components from the hybrid coupler. The translated I and Q spectrums are fed to a Wilkinson Combiner to form the suppressed carrier RF spectrum which is subsequently fed into the linear solid state power amplifier.

Overhead data is added to the traffic data to carry the framing and service channel information. The service channels are used to carry alarm reporting and voice order-wire data. They also provide a channel for microprocessor communication between radio transmitters and receivers.

DVR-6607-45 Broadcast Auxiliary Digital Radio FCC Type Notification

Radio Characteristics

FCC Identification	JF6-9802
Frequency Range	6875 – 7125 HHZ
RF Channel Bandwidth	10 MHz
Emission Designation	10M0D7W
Modulation Type	64 QAM
Data Rate	48.819 Mb/s
Baud Rate	9.96 Mbaud/s
Data Efficiency	4.9 Bits/Hz
Transmit Power	+37 dBm (5 Watts)
Transmit Frequency Stability	0.001% (-20 to +50 Degrees C)
Primary Voltage Range	24 – 48 Vdc (positive or negative) 120/240 Vac
Operating Temperature Range	0 to 45 Degrees C

Attached Support Documents

Equipment Photograph
FCC ID Label
FCC ID Label Position Drawing
2.985 RF Power Out
2.987 Modulation Characteristics
2.989 Occupied Bandwidth
2.993 Field Strength of Spurious Radiation
2.995 Frequency Stability