

DECLARATION OF COMPLIANCE SAR EVALUATION

<p><u>Test Lab</u></p> <p>CELLTECH LABS INC. Testing and Engineering Services 1955 Moss Court Kelowna, B.C. Canada V1Y 9L3 Phone: 250-448-7047 Fax: 250-448-7046 e-mail: info@celltechlabs.com web site: www.celltechlabs.com</p>	<p><u>Applicant Information</u></p> <p>ParkerVision Inc. 8493 Baymeadows Way Jacksonville, FL 32256</p>																										
<table style="width: 100%; border: none;"> <tr> <td style="width: 30%;">Rule Part(s):</td> <td>FCC 47 CFR §2.1093</td> </tr> <tr> <td>Test Procedure(s):</td> <td>FCC OET Bulletin 65, Supplement C (01-01)</td> </tr> <tr> <td>Device Classification:</td> <td>Digital Transmission System (DSS)</td> </tr> <tr> <td>Device Type:</td> <td>PCMCIA DSSS WLAN Card for Laptop PCs</td> </tr> <tr> <td>FCC ID:</td> <td>JFE-D2D00001</td> </tr> <tr> <td>Model Name / No.:</td> <td>HZ1500</td> </tr> <tr> <td>Tx Frequency Range:</td> <td>2412 - 2462 MHz</td> </tr> <tr> <td>Max. Output Power Tested:</td> <td>21.4 dBm Conducted (2437 MHz)</td> </tr> <tr> <td>Modulation:</td> <td>Direct Sequence Spread Spectrum (DSSS)</td> </tr> <tr> <td>Power Supply:</td> <td>from host Laptop PC</td> </tr> <tr> <td>Antenna Type:</td> <td>Internal</td> </tr> <tr> <td>Host Laptop PCs Tested:</td> <td>Toshiba Tecra; Compaq PP2130; Compaq PP2150</td> </tr> <tr> <td>Max. SAR Measured:</td> <td>0.483 W/kg (with Toshiba Tecra Laptop PC - Card Slot Side)</td> </tr> </table>		Rule Part(s):	FCC 47 CFR §2.1093	Test Procedure(s):	FCC OET Bulletin 65, Supplement C (01-01)	Device Classification:	Digital Transmission System (DSS)	Device Type:	PCMCIA DSSS WLAN Card for Laptop PCs	FCC ID:	JFE-D2D00001	Model Name / No.:	HZ1500	Tx Frequency Range:	2412 - 2462 MHz	Max. Output Power Tested:	21.4 dBm Conducted (2437 MHz)	Modulation:	Direct Sequence Spread Spectrum (DSSS)	Power Supply:	from host Laptop PC	Antenna Type:	Internal	Host Laptop PCs Tested:	Toshiba Tecra; Compaq PP2130; Compaq PP2150	Max. SAR Measured:	0.483 W/kg (with Toshiba Tecra Laptop PC - Card Slot Side)
Rule Part(s):	FCC 47 CFR §2.1093																										
Test Procedure(s):	FCC OET Bulletin 65, Supplement C (01-01)																										
Device Classification:	Digital Transmission System (DSS)																										
Device Type:	PCMCIA DSSS WLAN Card for Laptop PCs																										
FCC ID:	JFE-D2D00001																										
Model Name / No.:	HZ1500																										
Tx Frequency Range:	2412 - 2462 MHz																										
Max. Output Power Tested:	21.4 dBm Conducted (2437 MHz)																										
Modulation:	Direct Sequence Spread Spectrum (DSSS)																										
Power Supply:	from host Laptop PC																										
Antenna Type:	Internal																										
Host Laptop PCs Tested:	Toshiba Tecra; Compaq PP2130; Compaq PP2150																										
Max. SAR Measured:	0.483 W/kg (with Toshiba Tecra Laptop PC - Card Slot Side)																										

Celltech Labs Inc. declares under its sole responsibility that this wireless portable device was found to be in compliance with the Specific Absorption Rate (SAR) RF exposure requirements specified in FCC 47 CFR §2.1093. The device was tested in accordance with the measurement standards and procedures specified in FCC OET Bulletin 65, Supplement C (Edition 01-01) for the General Population / Uncontrolled Exposure environment. All measurements were performed in accordance with the SAR system manufacturer recommendations.

I attest to the accuracy of data. All measurements were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

This test report shall not be reproduced partially, or in full, without the prior written approval of Celltech Labs Inc. The results and statements contained in this report pertain only to the device(s) evaluated.



Russell Pipe
Senior Compliance Technologist
Celltech Labs Inc.



TABLE OF CONTENTS		
1.0	INTRODUCTION.....	3
2.0	DESCRIPTION OF DUT.....	3
3.0	SAR MEASUREMENT SYSTEM	4
4.0	MEASUREMENT SUMMARY.....	5
5.0	DETAILS OF SAR EVALUATION.....	6
6.0	EVALUATION PROCEDURES.....	6
7.0	PHANTOM REFERENCE POINT & DUT POSITIONING.....	7
8.0	SYSTEM PERFORMANCE CHECK.....	8
9.0	EQUIVALENT TISSUES.....	9
10.0	SAR LIMITS.....	9
11.0	SYSTEM SPECIFICATIONS.....	10
12.0	PROBE SPECIFICATION.....	11
13.0	SAM PHANTOM.....	11
14.0	PLANAR PHANTOM.....	11
15.0	DEVICE HOLDER.....	11
16.0	TEST EQUIPMENT LIST.....	12
17.0	MEASUREMENT UNCERTAINTIES.....	13-14
18.0	REFERENCES.....	15
	APPENDIX A - SAR MEASUREMENT DATA.....	16
	APPENDIX B - SYSTEM PERFORMANCE CHECK DATA.....	17
	APPENDIX C - SYSTEM VALIDATION.....	18
	APPENDIX D - PROBE CALIBRATION.....	19
	APPENDIX E - MEASURED FLUID DIELECTRIC PARAMETERS.....	20
	APPENDIX F - SAM PHANTOM CERTIFICATE OF CONFORMITY.....	21
	APPENDIX G - PLANAR PHANTOM CERTIFICATE OF CONFORMITY.....	22
	APPENDIX H - SAR TEST SETUP & DUT PHOTOGRAPHS.....	23

1.0 INTRODUCTION

This measurement report demonstrates that the ParkerVision Inc. Model: HZ1500 PCMCIA DSSS WLAN Card FCC ID: JFE-D2D00001 for Laptop PCs complies with the SAR (Specific Absorption Rate) RF exposure requirements specified in FCC 47 CFR §2.1093 (see reference [1]) for the General Population environment. The test procedures described in FCC OET Bulletin 65, Supplement C, Edition 01-01 (see reference [2]) were employed. A description of the product, operating configuration, detailed summary of the test results, methodology and procedures used in the evaluation, equipment used, and the various provisions of the rules are included within this test report.

2.0 DESCRIPTION of Device Under Test (DUT)


FCC Rule Part(s)	47 CFR §2.1093
Test Procedure(s)	FCC OET Bulletin 65, Supplement C (01-01)
FCC Device Classification	Digital Transmission System (DSS)
Device Type	PCMCIA DSSS WLAN Card for Laptop PCs
FCC ID	JFE-D2D00001
Model	HZ1500
Serial No.	Pre-production
Tx Frequency Range	2412 - 2462 MHz
Max. RF Output Power Tested	21.4 dBm Conducted (2437 MHz)
Antenna Type	Internal
Power Supply	from host Laptop PC
Host Laptop PCs Tested	Toshiba Tecra; Compaq PP2130; Compaq PP2150

3.0 SAR MEASUREMENT SYSTEM

Celltech Labs Inc. SAR measurement facility utilizes the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY4 measurement system is comprised of the robot controller, computer, near-field probe, probe alignment sensor, specific anthropomorphic mannequin (SAM) phantom, and various planar phantoms for brain and/or body SAR evaluations. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the DASY4 measurement server. The DAE4 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter and a command decoder and control logic unit. Transmission to the DASY4 measurement server is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. The sensor systems are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.



DASY4 SAR Measurement System with SAM Phantom



DASY4 SAR Measurement System with Planar Phantom

4.0 MEASUREMENT SUMMARY

The measurement results were obtained with the DUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum SAR location of the DUT are reported in Appendix A.

BODY SAR MEASUREMENT RESULTS

Freq. (MHz)	Test Mode	Laptop PC Battery Type	Conducted Power (dBm)		Phantom Type	Host Laptop PC	PCMCIA Card Slot Tested	Laptop PC Position to Planar Phantom	Separation Distance to Planar Phantom	Measured SAR 1g (W/kg)
			Before	After						
2437	DSSS	Lithium-ion	21.4	21.2	Planar	Toshiba Tecra	Lower	Bottom Side	0.0 cm (from PC)	0.171
2437	DSSS	Lithium-ion	21.4	21.3	Planar	Toshiba Tecra	Lower	Right Side	0.0 cm (from DUT)	0.483
2437	DSSS	Lithium-ion	21.4	21.3	Planar	Toshiba Tecra	Upper	Bottom Side	0.0 cm (from PC)	0.082
2437	DSSS	Lithium-ion	21.4	21.3	Planar	Toshiba Tecra	Upper	Right Side	0.0 cm (from DUT)	0.452
2437	DSSS	Lithium-ion	21.4	21.2	Planar	Compaq PP2130	Single	Bottom Side	0.0 cm (from PC)	0.152
2437	DSSS	Lithium-ion	21.4	21.3	Planar	Compaq PP2130	Single	Left Side	0.0 cm (from DUT)	0.419
2437	DSSS	Lithium-ion	21.4	21.2	Planar	Compaq PP2150	Single	Bottom Side	0.0 cm (from PC)	0.145
2437	DSSS	Lithium-ion	21.4	21.3	Planar	Compaq PP2150	Single	Left Side	0.0 cm (from DUT)	0.435

ANSI / IEEE C95.1 1992 - SAFETY LIMIT
BODY: 1.6 W/kg (averaged over 1 gram)
Spatial Peak - Uncontrolled Exposure / General Population

Test Date(s)	09/18/03		Relative Humidity	55 %
Measured Fluid Type	2450MHz Body		Atmospheric Pressure	101.8 kPa
Dielectric Constant ϵ_r	Target	Measured	Ambient Temperature	21.4 °C
	52.7 ±5%	50.8	Fluid Temperature	23.8 °C
Conductivity σ (mho/m)	Target	Measured	Fluid Depth	≥ 15 cm
	1.95 ±5%	1.99	ρ (Kg/m³)	1000

Note(s):

1. If the SAR measurements performed at the mid channel were ≥ 3 dB below the SAR limit, then SAR evaluation for the low and high channels was optional (per FCC OET Bulletin 65, Supplement C, Edition 01-01 (see reference [2])).
2. The ambient and fluid temperatures were measured prior to, and during, the fluid dielectric parameter check and the SAR evaluation. The temperatures listed in the table shown above were consistent for all measurement periods.
3. The dielectric properties of the simulated body fluid were measured prior to the evaluation using an 85070C Dielectric Probe Kit and an 8753E Network Analyzer (see Appendix E for printout of measured fluid dielectric parameters).

5.0 DETAILS OF SAR EVALUATION

The PARKERVISION INC. Model: HZ1500 PCMCIA WLAN Card FCC ID: JFE-D2D00001 for Laptop PCs was found to be compliant for localized Specific Absorption Rate (SAR) based on the following test provisions and conditions described below. The detailed test setup photographs are shown in Appendix H.

1. The DUT was tested for body SAR with the bottom side of the Toshiba Tecra Laptop PC placed parallel to, and touching, the surface of the planar phantom. The DUT was evaluated in both the lower and upper PCMCIA card slots.
2. The DUT was tested for body SAR with the right side of the Toshiba Tecra Laptop PC placed parallel to the surface of the planar phantom and the top edge of the DUT was touching the surface of the planar phantom. The DUT was evaluated in both the lower and upper PCMCIA card slots.
3. The DUT was tested for body SAR with the bottom side of the Compaq PP2130 Laptop PC placed parallel to, and touching, the surface of the planar phantom. The Compaq PP2130 Laptop PC contains a single PCMCIA card slot.
4. The DUT was tested for body SAR with the left side of the Compaq PP2130 Laptop PC placed parallel to the surface of the planar phantom and the top edge of the DUT was touching the surface of the planar phantom. The Compaq PP2130 Laptop PC contains a single PCMCIA card slot.
5. The DUT was tested for body SAR with the bottom side of the Compaq PP2150 Laptop PC placed parallel to, and touching, the surface of the planar phantom. The Compaq PP2150 Laptop PC contains a single PCMCIA card slot.
6. The DUT was tested for body SAR with the left side of the Compaq PP2150 Laptop PC placed parallel to the surface of the planar phantom and the top edge of the DUT was touching the surface of the planar phantom. The Compaq PP2150 Laptop PC contains a single PCMCIA card slot.
7. The conducted power levels were measured before and after each test using a Gigatronics 8652A Universal Power Meter according to the procedures described in FCC 47 CFR §2.1046.
8. The DUT was controlled in test mode via internal software and tested in modulated fixed frequency continuous transmit mode (100% duty cycle).
9. The DUT was tested with a fully charged battery in each host Laptop PC.
10. Due to the dimensions of the host Laptop PCs, a stack of low-density, low-loss dielectric foamed polystyrene was used in place of the device holder.

6.0 EVALUATION PROCEDURES

- (i) The evaluation was performed in the applicable area of the phantom depending on the type of device being tested. For devices held to the ear during normal operation, both the left and right ear positions were evaluated in accordance with FCC OET Bulletin 65, Supplement C (Edition 01-01) using the SAM phantom.
- (ii) For body-worn and face-held devices a planar phantom was used.
- b. The SAR was determined by a pre-defined procedure within the DASY4 software. Upon completion of a reference and optical surface check, the exposed region of the phantom was scanned near the inner surface with a grid spacing of 15mm x 15mm.

An area scan was determined as follows:


- c. Based on the defined area scan grid, a more detailed grid is created to increase the points by a factor of 10. The interpolation function then evaluates all field values between corresponding measurement points.
- d. A linear search is applied to find all the candidate maxima. Subsequently, all maxima are removed that are >2 dB from the global maximum. The remaining maxima are then used to position the cube scans.

A 1g and 10g spatial peak SAR was determined as follows:


1. Extrapolation is used to find the points between the dipole center of the probe and the surface of the phantom. This data cannot be measured, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.4 mm (see probe calibration document in Appendix D). The extrapolation was based on trivariate quadratics computed from the previously calculated 3D interpolated points nearest the phantom surface.
2. Interpolated data is used to calculate the average SAR over 1g and 10g cubes by spatially discretizing the entire measured cube. The volume used to determine the averaged SAR is a 1mm grid (42875 interpolated points).

7.0 PHANTOM REFERENCE POINT & DEVICE POSITIONING


Toshiba Tecra Host Laptop PC (Bottom Side)




Compaq PP2130/50 Host Laptop PC (Bottom Side)



Toshiba Tecra Host Laptop PC (Right Side)



Compaq PP2130/50 Host Laptop PC (Left Side)



8.0 SYSTEM PERFORMANCE CHECK

Prior to the SAR evaluation a system check was performed in the planar section of the SAM phantom with a 2450MHz dipole (see Appendix C for detailed system validation procedures). The dielectric parameters of the simulated brain tissue fluid were measured using an 85070C Dielectric Probe Kit and an 8753E Network Analyzer (see Appendix E for printout of measured fluid dielectric parameters). A forward power of 250 mW was applied to the dipole and the system was verified to a tolerance of $\pm 10\%$ (see Appendix B for system check test plot).

SYSTEM PERFORMANCE CHECK											
Test Date	2450MHz Equiv. Tissue	SAR 1g (W/kg)		Dielectric Constant ϵ_r		Conductivity σ (mho/m)		ρ (Kg/m ³)	Ambient Temp.	Fluid Temp.	Fluid Depth
		Target	Measured	Target	Measured	Target	Measured				
09/18/03	Brain	13.1 $\pm 10\%$	14.1 +7.6%	39.2 $\pm 5\%$	37.2	1.80 $\pm 5\%$	1.88	1000	21.2 °C	23.9 °C	≥ 15 cm




Figure 6. System Performance Check Setup Diagram



2450MHz System Performance Check Setup



2450MHz System Performance Check Setup



2450MHz Dipole

9.0 EQUIVALENT TISSUES

The 2450MHz brain and body simulated tissue fluids consist of Glycol-monobutyl, water, and salt (body fluid only). The fluid was prepared according to standardized procedures and measured for dielectric parameters (permittivity and conductivity).

SIMULATED EQUIVALENT TISSUE MIXTURES		
INGREDIENT	2450MHz Brain (System Performance Check)	2450MHz Body (DUT Evaluation)
Water	55.20 %	69.95 %
Glycol Monobutyl	44.80 %	30.00 %
Salt	-	0.05 %

10.0 SAR SAFETY LIMITS

EXPOSURE LIMITS	SAR (W/Kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1 g of tissue)	1.60	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0

Notes:

1. Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.
2. Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.

11.0 ROBOT SYSTEM SPECIFICATIONS

Specifications

POSITIONER: Stäubli Unimation Corp. Robot Model: RX60L
Repeatability: 0.02 mm
No. of axis: 6

Data Acquisition Electronic (DAE) System

Cell Controller

Processor: AMD Athlon XP 2400+
Clock Speed: 2.0 GHz
Operating System: Windows XP Professional

Data Converter

Features: Signal Amplifier, multiplexer, A/D converter, and control logic
Software: DASY4 software
Connecting Lines: Optical downlink for data and status info.
Optical uplink for commands and clock

DASY4 Measurement Server

Function: Real-time data evaluation for field measurements and surface detection
Hardware: PC/104 166MHz Pentium CPU; 32 MB chipdisk; 64 MB RAM
Connections: COM1, COM2, DAE, Robot, Ethernet, Service Interface

E-Field Probe

Model: ET3DV6
Serial No.: 1387
Construction: Triangular core fiber optic detection system
Frequency: 10 MHz to 6 GHz
Linearity: ± 0.2 dB (30 MHz to 3 GHz)

Phantom

Type 1: SAM V4.0C
Shell Material: Fiberglass
Thickness: 2.0 ± 0.1 mm
Volume: Approx. 20 liters

Type 2: Planar Phantom
Shell Material: Fiberglass
Thickness: 2.0 ± 0.1 mm
Volume: Approx. 72 liters

12.0 PROBE SPECIFICATION (ET3DV6)

Construction:	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g. glycol)
Calibration:	In air from 10 MHz to 2.5 GHz In brain simulating tissue at frequencies of 900 MHz and 1.8 GHz (accuracy $\pm 8\%$)
Frequency:	10 MHz to >6 GHz; Linearity: ± 0.2 dB (30 MHz to 3 GHz)
Directivity:	± 0.2 dB in brain tissue (rotation around probe axis) ± 0.4 dB in brain tissue (rotation normal to probe axis)
Dynamic Range:	5 μ W/g to >100 mW/g; Linearity: ± 0.2 dB
Surface Detect.:	± 0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces
Dimensions:	Overall length: 330 mm Tip length: 16 mm Body diameter: 12 mm Tip diameter: 6.8 mm Distance from probe tip to dipole centers: 2.7 mm
Application:	General dosimetry up to 3 GHz Compliance tests of mobile phone



ET3DV6 E-Field Probe

13.0 SAM PHANTOM V4.0C

The SAM phantom V4.0C is a fiberglass shell phantom with a 2.0 mm (+/-0.2 mm) shell thickness for left and right head and flat planar area integrated in a wooden table. The shape of the fiberglass shell corresponds to the phantom defined by SCC34-SC2. The device holder positions are adjusted to the standard measurement positions in the three sections (see Appendix F for specifications of the SAM phantom V4.0C).



SAM Phantom

14.0 PLANAR PHANTOM

The planar phantom is a fiberglass shell phantom with a 2.0 mm (+/-0.2mm) thick device measurement area at the center of the phantom for SAR evaluations of devices with a larger surface area such as Laptop PCs. The planar phantom is integrated in a wooden table (see Appendix G for dimensions and specifications of the planar phantom).



Planar Phantom

15.0 DEVICE HOLDER

The DASY4 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65°. The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections.



Device Holder

16.0 TEST EQUIPMENT LIST

TEST EQUIPMENT	SERIAL NO.	CALIBRATION DATE
Schmid & Partner DASY4 System	-	-
DASY4 Measurement Server	1078	N/A
-Robot	599396-01	N/A
-ET3DV6 E-Field Probe	1387	Feb 2003
-300MHz Validation Dipole	135	Oct 2002
-450MHz Validation Dipole	136	Oct 2002
-900MHz Validation Dipole	054	June 2003
-1800MHz Validation Dipole	247	June 2003
-2450MHz Validation Dipole	150	Sept 2003
-SAM Phantom V4.0C	N/A	N/A
-Barski Planar Phantom	N/A	N/A
HP 85070C Dielectric Probe Kit	N/A	N/A
Gigatronics 8651A Power Meter	8650137	April 2003
Gigatronics 8652A Power Meter	1835267	April 2003
Power Sensor 80701A	1833542	Feb 2003
Power Sensor 80701A	1833699	April 2003
HP E4408B Spectrum Analyzer	US39240170	Dec 2002
HP 8594E Spectrum Analyzer	3543A02721	April 2003
HP 8753E Network Analyzer	US38433013	May 2003
HP 8648D Signal Generator	3847A00611	May 2003
Amplifier Research 5S1G4 Power Amplifier	26235	N/A

17.0 MEASUREMENT UNCERTAINTIES

UNCERTAINTY BUDGET FOR DEVICE EVALUATION						
Error Description	Uncertainty Value ±%	Probability Distribution	Divisor	C_i 1g	Standard Uncertainty ±% (1g)	v_i or v_{eff}
Measurement System						
Probe calibration	± 4.8	Normal	1	1	± 4.8	∞
Axial isotropy of the probe	± 4.7	Rectangular	√3	(1- C_p)	± 1.9	∞
Spherical isotropy of the probe	± 9.6	Rectangular	√3	(C_p)	± 3.9	∞
Spatial resolution	± 0.0	Rectangular	√3	1	± 0.0	∞
Boundary effects	± 5.5	Rectangular	√3	1	± 3.2	∞
Probe linearity	± 4.7	Rectangular	√3	1	± 2.7	∞
Detection limit	± 1.0	Rectangular	√3	1	± 0.6	∞
Readout electronics	± 1.0	Normal	1	1	± 1.0	∞
Response time	± 0.8	Rectangular	√3	1	± 0.5	∞
Integration time	± 1.4	Rectangular	√3	1	± 0.8	∞
RF ambient conditions	± 3.0	Rectangular	√3	1	± 1.7	∞
Mech. constraints of robot	± 0.4	Rectangular	√3	1	± 0.2	∞
Probe positioning	± 2.9	Rectangular	√3	1	± 1.7	∞
Extrapolation & integration	± 3.9	Rectangular	√3	1	± 2.3	∞
Test Sample Related						
Device positioning	± 6.0	Normal	√3	1	± 6.7	12
Device holder uncertainty	± 5.0	Normal	√3	1	± 5.9	8
Power drift	± 5.0	Rectangular	√3		± 2.9	∞
Phantom and Setup						
Phantom uncertainty	± 4.0	Rectangular	√3	1	± 2.3	∞
Liquid conductivity (target)	± 5.0	Rectangular	√3	0.6	± 1.7	∞
Liquid conductivity (measured)	± 5.0	Rectangular	√3	0.6	± 1.7	∞
Liquid permittivity (target)	± 5.0	Rectangular	√3	0.6	± 1.7	∞
Liquid permittivity (measured)	± 5.0	Rectangular	√3	0.6	± 1.7	∞
Combined Standard Uncertainty					± 14.0	
Expanded Uncertainty (k=2)					± 28.0	

Measurement Uncertainty Table in accordance with IEEE Std 1528 (Draft - see Reference [3])

MEASUREMENT UNCERTAINTIES (Cont.)

UNCERTAINTY BUDGET FOR SYSTEM VALIDATION						
Error Description	Uncertainty Value ±%	Probability Distribution	Divisor	c_i 1g	Standard Uncertainty ±% (1g)	v_i OR v_{eff}
Measurement System						
Probe calibration	± 4.8	Normal	1	1	± 4.8	∞
Axial isotropy of the probe	± 4.7	Rectangular	√3	(1-c _p)	± 1.9	∞
Spherical isotropy of the probe	± 9.6	Rectangular	√3	(c _p)	± 3.9	∞
Spatial resolution	± 0.0	Rectangular	√3	1	± 0.0	∞
Boundary effects	± 5.5	Rectangular	√3	1	± 3.2	∞
Probe linearity	± 4.7	Rectangular	√3	1	± 2.7	∞
Detection limit	± 1.0	Rectangular	√3	1	± 0.6	∞
Readout electronics	± 1.0	Normal	1	1	± 1.0	∞
Response time	± 0.8	Rectangular	√3	1	± 0.5	∞
Integration time	± 1.4	Rectangular	√3	1	± 0.8	∞
RF ambient conditions	± 3.0	Rectangular	√3	1	± 1.7	∞
Mech. constraints of robot	± 0.4	Rectangular	√3	1	± 0.2	∞
Probe positioning	± 2.9	Rectangular	√3	1	± 1.7	∞
Extrapolation & integration	± 3.9	Rectangular	√3	1	± 2.3	∞
Dipole						
Dipole Axis to Liquid Distance	± 2.0	Rectangular	√3	1	± 1.2	∞
Input Power	± 4.7	Rectangular	√3	1	± 2.7	∞
Phantom and Setup						
Phantom uncertainty	± 4.0	Rectangular	√3	1	± 2.3	∞
Liquid conductivity (target)	± 5.0	Rectangular	√3	0.6	± 1.7	∞
Liquid conductivity (measured)	± 5.0	Rectangular	√3	0.6	± 1.7	∞
Liquid permittivity (target)	± 5.0	Rectangular	√3	0.6	± 1.7	∞
Liquid permittivity (measured)	± 5.0	Rectangular	√3	0.6	± 1.7	∞
Combined Standard Uncertainty					± 9.9	
Expanded Uncertainty (k=2)					± 19.8	

Measurement Uncertainty Table in accordance with IEEE Std 1528 (Draft - see Reference [3])

18.0 REFERENCES

- [1] Federal Communications Commission, "Radiofrequency radiation exposure evaluation: portable devices", Rule Part 47 CFR §2.1093: 1999.
- [2] Federal Communications Commission, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields", OET Bulletin 65, Supplement C (Edition 01-01), FCC, Washington, D.C.: June 2001.
- [3] IEEE Standards Coordinating Committee 34, Std 1528-200X, "DRAFT Recommended Practice for Determining the Spatial-Peak Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques".
- [4] W. Gander, *Computermathematick*, Birkhaeuser, Basel: 1992.

APPENDIX A - SAR MEASUREMENT DATA

Test Date: 09/18/03


DUT: ParkerVision Inc. FCC ID: JFE-D2D00001; Type: HZ1500 PCMCIA WLAN Card with Toshiba Tecra Laptop PC (Laptop PC Serial: 92098627PU)

Ambient Temp: 21.4 °C; Fluid Temp: 23.8 °C
Barometric Pressure: 101.8 kPa; Humidity: 55%

Communication System: DSSS
Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: M2450 ($\sigma = 1.99$ mho/m, $\epsilon_r = 50.8$, $\rho = 1000$ kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(4.6, 4.6, 4.6); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 19/05/2003
- Phantom: Planar back; Type: Barski Industries; Serial: 03-01
- Measurement SW: DAS4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 116

Bottom of Laptop 0 cm - Lower Slot/Area Scan (21x25x1): Measurement grid: dx=15mm, dy=15mm
Bottom of Laptop 0 cm - Lower Slot/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Peak SAR (extrapolated) = 0.334 W/kg
SAR(1 g) = 0.171 mW/g; SAR(10 g) = 0.096 mW/g
Reference Value = 1.78 V/m
Power Drift = -0.2 dB



Test Date: 09/18/03

DUT: ParkerVision Inc. FCC ID: JFE-D2D00001; Type: HZ1500 PCMCIA WLAN Card with Toshiba Tecra Laptop PC (Laptop PC Serial: 92098627PU)

Ambient Temp: 21.4 °C; Fluid Temp: 23.8 °C
Barometric Pressure: 101.8 kPa; Humidity: 55%

Communication System: DSSS
Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: M2450 ($\sigma = 1.99 \text{ mho/m}$, $\epsilon_r = 50.8$, $\rho = 1000 \text{ kg/m}^3$)

- Probe: ET3DV6 - SN1387; ConvF(4.6, 4.6, 4.6); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 19/05/2003
- Phantom: Planar back; Type: Barski Industries; Serial: 03-01
- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 116

Right Side of Laptop 0 cm - Lower Slot/Area Scan (6x25x1): Measurement grid: dx=15mm, dy=15mm


Right Side of Laptop 0 cm - Lower Slot/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Peak SAR (extrapolated) = 1.09 W/kg

SAR(1 g) = 0.483 mW/g; SAR(10 g) = 0.218 mW/g

Reference Value = 17.6 V/m

Power Drift = -0.1 dB





Test Date: 09/18/03


DUT: ParkerVision Inc. FCC ID: JFE-D2D00001; Type: HZ1500 PCMCIA WLAN Card with Toshiba Tecra Laptop PC (Laptop PC Serial: 92098627PU)

Ambient Temp: 21.4 °C; Fluid Temp: 23.8 °C
Barometric Pressure: 101.8 kPa; Humidity: 55%

Communication System: DSSS
Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: M2450 ($\sigma = 1.99$ mho/m, $\epsilon_r = 50.8$, $\rho = 1000$ kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(4.6, 4.6, 4.6); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 19/05/2003
- Phantom: Planar back; Type: Barski Industries; Serial: 03-01
- Measurement SW: DASy4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 116

Bottom of Laptop 0 cm - Upper Slot/Area Scan (21x25x1): Measurement grid: dx=15mm, dy=15mm
Bottom of Laptop 0 cm - Upper Slot/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Peak SAR (extrapolated) = 0.16 W/kg
SAR(1 g) = 0.082 mW/g; SAR(10 g) = 0.0488 mW/g
Reference Value = 2.13 V/m
Power Drift = -0.01 dB



Test Date: 09/18/03

DUT: ParkerVision Inc. FCC ID: JFE-D2D00001; Type: HZ1500 PCMCIA WLAN Card with Toshiba Tecra Laptop PC (Laptop PC Serial: 92098627PU)

Ambient Temp: 21.4 °C; Fluid Temp: 23.8 °C
Barometric Pressure: 101.8 kPa; Humidity: 55%

Communication System: DSSS
Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: M2450 ($\sigma = 1.99 \text{ mho/m}$, $\epsilon_r = 50.8$, $\rho = 1000 \text{ kg/m}^3$)

- Probe: ET3DV6 - SN1387; ConvF(4.6, 4.6, 4.6); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 19/05/2003
- Phantom: Planar back; Type: Barski Industries; Serial: 03-01
- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 116

Right Side of Laptop 0 cm - Upper Slot/Area Scan (6x25x1): Measurement grid: dx=15mm, dy=15mm


Right Side of Laptop 0 cm - Upper Slot/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 1 W/kg

SAR(1 g) = 0.452 mW/g; SAR(10 g) = 0.204 mW/g

Reference Value = 17.4 V/m

Power Drift = 0.06 dB



Test Date: 09/18/03


DUT: ParkerVision Inc. FCC ID: JFE-D2D00001; Type: HZ1500 PCMCIA WLAN Card with Compaq PP2130 Laptop PC (Laptop PC Serial: 470050-312)

Ambient Temp: 21.4 °C; Fluid Temp: 23.8 °C
Barometric Pressure: 101.8 kPa; Humidity: 55%

Communication System: DSSS
Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: M2450 ($\sigma = 1.99$ mho/m, $\epsilon_r = 50.8$, $\rho = 1000$ kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(4.6, 4.6, 4.6); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 19/05/2003
- Phantom: Planar back; Type: Barski Industries; Serial: 03-01
- Measurement SW: DAS4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 116

Bottom of Laptop 0 cm - Single Slot/Area Scan (22x26x1): Measurement grid: dx=15mm, dy=15mm
Bottom of Laptop 0 cm - Single Slot/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Peak SAR (extrapolated) = 0.314 W/kg
SAR(1 g) = 0.152 mW/g; SAR(10 g) = 0.0882 mW/g
Reference Value = 0.526 V/m
Power Drift = 0.2 dB



Test Date: 09/18/03


DUT: ParkerVision Inc. FCC ID: JFE-D2D00001; Type: HZ1500 PCMCIA WLAN Card with Compaq PP2130 Laptop PC (Laptop PC Serial: 470050-312)

Ambient Temp: 21.4 °C; Fluid Temp: 23.8 °C
Barometric Pressure: 101.8 kPa; Humidity: 55%

Communication System: DSSS
Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: M2450 ($\sigma = 1.99$ mho/m, $\epsilon_r = 50.8$, $\rho = 1000$ kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(4.6, 4.6, 4.6); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 19/05/2003
- Phantom: Planar back; Type: Barski Industries; Serial: 03-01
- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 116

Left Side of Laptop 0 cm - Single Slot/Area Scan (6x25x1): Measurement grid: dx=15mm, dy=15mm
Left Side of Laptop 0 cm - Single Slot/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Peak SAR (extrapolated) = 0.938 W/kg
SAR(1 g) = 0.419 mW/g; SAR(10 g) = 0.192 mW/g
Reference Value = 1.86 V/m
Power Drift = -0.1 dB



Test Date: 09/18/03


DUT: ParkerVision Inc. FCC ID: JFE-D2D00001; Type: HZ1500 PCMCIA WLAN Card with Compaq PP2150 Laptop PC (Laptop PC Serial: 470045-648)

Ambient Temp: 21.4 °C; Fluid Temp: 23.8 °C
Barometric Pressure: 101.8 kPa; Humidity: 55%

Communication System: DSSS
Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: M2450 ($\sigma = 1.99$ mho/m, $\epsilon_r = 50.8$, $\rho = 1000$ kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(4.6, 4.6, 4.6); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 19/05/2003
- Phantom: Planar back; Type: Barski Industries; Serial: 03-01
- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 116

Bottom of Laptop 0 cm - Single Slot/Area Scan (22x26x1): Measurement grid: dx=15mm, dy=15mm
Bottom of Laptop 0 cm - Single Slot/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Peak SAR (extrapolated) = 0.301 W/kg
SAR(1 g) = 0.145 mW/g; SAR(10 g) = 0.0804 mW/g
Reference Value = 0.378 V/m
Power Drift = 0.6 dB



Test Date: 09/18/03

DUT: ParkerVision Inc. FCC ID: JFE-D2D00001; Type: HZ1500 PCMCIA WLAN Card with Compaq PP2150 Laptop PC (Laptop PC Serial: 470045-648)

Ambient Temp: 21.4 °C; Fluid Temp: 23.8 °C
Barometric Pressure: 101.8 kPa; Humidity: 55%

Communication System: DSSS
Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: M2450 ($\sigma = 1.99 \text{ mho/m}$, $\epsilon_r = 50.8$, $\rho = 1000 \text{ kg/m}^3$)

- Probe: ET3DV6 - SN1387; ConvF(4.6, 4.6, 4.6); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 19/05/2003
- Phantom: Planar back; Type: Barski Industries; Serial: 03-01
- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 116

Side of Laptop 0 cm - Single Slot/Area Scan (6x25x1): Measurement grid: dx=15mm, dy=15mm


Side of Laptop 0 cm - Single Slot/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 0.965 W/kg

SAR(1 g) = 0.435 mW/g; SAR(10 g) = 0.198 mW/g

Reference Value = 12.2 V/m

Power Drift = 0.07 dB



APPENDIX B - SYSTEM PERFORMANCE CHECK DATA

Test Date: 09/18/03

DUT: Dipole 2450 MHz; Type: System Performance Check; Serial: 150

Ambient Temp: 21.2 °C; Fluid Temp: 23.9 °C
Barometric Pressure: 101.8 kPa; Humidity: 55%


Communication System: CW
Frequency: 2450 MHz; Duty Cycle: 1:1
Medium: HSL2450 ($\sigma = 1.88 \text{ mho/m}$, $\epsilon_r = 37.2$, $\rho = 1000 \text{ kg/m}^3$)


- Probe: ET3DV6 - SN1387; ConvF(5, 5, 5); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 19/05/2003
- Phantom: SAM front; Type: SAM 4.0; Serial: 1033
- Measurement SW: DAS4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 116

1387 Validation at 2450 MHz/Area Scan (6x10x1): Measurement grid: dx=10mm, dy=10mm

1387 Validation at 2450 MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 29.2 W/kg
SAR(1 g) = 14.1 mW/g; SAR(10 g) = 6.4 mW/g
Forward Conducted Power = 250 mW
Reference Value = 97.4 V/m
Power Drift = -0.05 dB





APPENDIX C - SYSTEM VALIDATION

2450MHz SYSTEM VALIDATION DIPOLE

Type:

2450MHz Validation Dipole

Serial Number:

150

Place of Calibration:

Celltech Labs Inc.

Date of Calibration:

September 17, 2003

Celltech Labs Inc. hereby certifies that this device has been calibrated on the date indicated above.

Calibrated by:

Spencer Watson


Approved by:

Russell W. Pipe

1. Dipole Construction & Electrical Characteristics

The validation dipole was constructed in accordance with the IEEE Std “Recommended Practice for Determining the Spatial-Peak Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques”. The electrical properties were measured using an HP 8753E Network Analyzer. The network analyzer was calibrated to the validation dipole N-type connector feed point using an HP85032E Type N calibration kit. The dipole was placed parallel to a planar phantom at a separation distance of 10.0mm from the simulating fluid using a loss-less dielectric spacer. The measured input impedance is:

Feed point impedance at 2450MHz	$\text{Re}\{Z\} = 44.488\Omega$ $\text{Im}\{Z\} = -2.4883\Omega$
Return Loss at 2450MHz	-25.322 dB



17 Sep 2003 11:17:40

CH1 S11 1 U FS

11 44.488 Ω -2.4883 Ω 26.107 pF


2 450.000 000 MHz

PRm

MARKER 1
2.45 GHz

Cor

↑




START 2 250.000 000 MHz

STOP 2 650.000 000 MHz

17 Sep 2003 11:16:48

CH1 S11 LOG 10 dB/REF 0 dB

1*-25.322 dB 2 450.000 000 MHz



START 2 250.000 000 MHz

STOP 2 650.000 000 MHz

Validation Dipole Dimensions

Frequency (MHz)	L (mm)	h (mm)	d (mm)
300	420.0	250.0	6.2
450	288.0	167.0	6.2
835	161.0	89.8	3.6
900	149.0	83.3	3.6
1450	89.1	51.7	3.6
1800	72.0	41.7	3.6
1900	68.0	39.5	3.6
2000	64.5	37.5	3.6
2450	51.8	30.6	3.6
3000	41.5	25.0	3.6

2. Validation Phantom

The validation phantom is the SAM (Specific Anthropomorphic Mannequin) phantom manufactured by Schmid & Partner Engineering AG. The SAM phantom is a Fiberglass shell integrated in a wooden table. The shape of the shell corresponds to the phantom defined by SCC34-SC2. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

Shell Thickness: 2.0 ± 0.1 mm
Filling Volume: Approx. 20 liters
Dimensions: 50 cm (W) x 100 cm (L)

2450MHz Dipole Calibration



2450MHz Dipole Calibration



3. Measurement Conditions

The planar phantom was filled with brain simulating tissue having the following electrical parameters at 2450MHz:


Relative Permittivity:	37.3
Conductivity:	1.88 mho/m
Ambient Temperature:	21.6°C
Fluid Temperature:	23.9°C
Fluid Depth:	≥ 15cm

The 2450MHz simulating tissue consists of the following ingredients:

Ingredient	Percentage by weight
Water	52.00%
Glycol Monobutyl	48.00%
Target Dielectric Parameters at 22°C	$\epsilon_r = 39.2 (+/-5\%)$ $\sigma = 1.80 \text{ S/m } (+/-5\%)$

4. SAR Measurement

The SAR measurement was performed with the E-field probe in mechanical detection mode only. The setup and determination of the forward power into the dipole was performed using the following procedures.



First, the power meter PM1 (including attenuator Att1) is connected to the cable to measure the forward power at the location of the dipole connector (X). The signal generator is adjusted for the desired forward power at the dipole connector (taking into account the attenuation of Att1) as read by power meter PM2. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter PM2. If the signal generator does not allow adjustment in 0.01dB steps, the remaining difference at PM2 must be taken into consideration. PM3 records the reflected power from the dipole to ensure that the value is not changed from the previous value. The reflected power should be 20dB below the forward power.

Ten SAR measurements were performed in order to achieve repeatability and to establish an average target value.

Validation Dipole SAR Test Results

Validation Measurement	SAR @ 0.25W Input averaged over 1g	SAR @ 1W Input averaged over 1g	SAR @ 0.25W Input averaged over 10g	SAR @ 1W Input averaged over 10g	Peak SAR @ 0.25W Input
Test 1	13.9	55.6	6.27	25.08	29.5
Test 2	13.9	55.6	6.25	25.00	29.1
Test 3	13.9	55.6	6.24	24.96	28.9
Test 4	14.0	56.0	6.31	25.24	29.1
Test 5	14.0	56.0	6.27	25.08	29.7
Test 6	13.8	55.2	6.25	25.00	29.3
Test 7	13.9	55.6	6.22	24.88	29.3
Test 8	13.9	55.6	6.24	24.96	29.4
Test 9	14.0	56.0	6.29	25.16	30.0
Test10	13.8	55.2	6.17	24.68	29.3
Average Value	13.91	55.64	6.251	25.00	29.36

The results have been normalized to 1W (forward power) into the dipole.

Averaged over 1cm (1g) of tissue: 55.64 mW/g

Averaged over 10cm (10g) of tissue: 25.00 mW/g

Test Date: 09/17/03

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:150


Ambient Temp: 22.2C; Fluid Temp: 23.8C
Barometric Pressure: 101.9 kPa; Humidity: 52%


Communication System: CW
Frequency: 2450 MHz; Duty Cycle: 1:1
Medium: HSL2450 ($\sigma = 1.88$ mho/m, $\epsilon_r = 37.3$, $\rho = 1000$ kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(5, 5, 5); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 19/05/2003
- Phantom: SAM front; Type: SAM 4.0; Serial: 1033
- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 116

Probe SN1387 Validation at 2450 MHz/Area Scan (6x10x1): Measurement grid: dx=10mm, dy=10mm

Probe SN1387 Validation at 2450 MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Peak SAR (extrapolated) = 29.5 W/kg
SAR(1 g) = 13.9 mW/g; SAR(10 g) = 6.27 mW/g
Reference Value = 96.7 V/m
Power Drift = -0.08 dB





2450MHz System Validation

Measured Fluid Dielectric Parameters (Brain)

September 17, 2003

Frequency	ϵ'	ϵ''
2.350000000 GHz	37.7457	13.5170
2.360000000 GHz	37.7101	13.5534
2.370000000 GHz	37.6951	13.5903
2.380000000 GHz	37.6613	13.6228
2.390000000 GHz	37.6411	13.6368
2.400000000 GHz	37.5853	13.6598
2.410000000 GHz	37.5236	13.6742
2.420000000 GHz	37.4573	13.7091
2.430000000 GHz	37.4063	13.7484
2.440000000 GHz	37.3419	13.7798
2.450000000 GHz	37.2875	13.8226
2.460000000 GHz	37.2447	13.8618
2.470000000 GHz	37.2198	13.8951
2.480000000 GHz	37.1940	13.9293
2.490000000 GHz	37.1679	13.9423
2.500000000 GHz	37.1333	13.9571
2.510000000 GHz	37.0990	13.9745
2.520000000 GHz	37.0410	14.0116
2.530000000 GHz	36.9938	14.0375
2.540000000 GHz	36.9185	14.0546
2.550000000 GHz	36.8657	14.0912

APPENDIX D - PROBE CALIBRATION

Client **Celltech Labs**

CALIBRATION CERTIFICATE

Object(s) **ET3DV6 - SN:1387**

Calibration procedure(s) **QA CAL-01.v2
Calibration procedure for dosimetric E-field probes**

Calibration date: **February 26, 2003**



Condition of the calibrated item **In Tolerance (according to the specific calibration document)**

This calibration statement documents traceability of M&TE used in the calibration procedures and conformity of the procedures with the ISO/IEC 17025 international standard.

All calibrations have been conducted in the closed laboratory facility: environment temperature 22 +/- 2 degrees Celsius and humidity < 75%.

Calibration Equipment used (M&TE critical for calibration)

Model Type	ID #	Cal Date	Scheduled Calibration
RF generator HP 8684C	US3642U01700	4-Aug-99 (in house check Aug-02)	In house check: Aug-05
Power sensor E4412A	MY41495277	8-Mar-02	Mar-03
Power sensor HP 8481A	MY41092180	18-Sep-02	Sep-03
Power meter EPM E4419B	GB41293874	13-Sep-02	Sep-03
Network Analyzer HP 8753E	US38432426	3-May-00	In house check: May 03
Fluke Process Calibrator Type 702	SN: 6295803	3-Sep-01	Sep-03

	Name	Function	Signature
Calibrated by:	Nico Vetterli	Technician	
Approved by:	Katja Pokovic	Laboratory Director	

Date issued: February 26, 2003

This calibration certificate is issued as an intermediate solution until the accreditation process (based on ISO/IEC 17025 International Standard) for Calibration Laboratory of Schmid & Partner Engineering AG is completed.

Probe ET3DV6

SN:1387

Manufactured:	September 21, 1999
Last calibration:	February 22, 2002
Recalibrated:	February 26, 2003

Calibrated for DASYS Systems

(Note: non-compatible with DASYS2 system!)

DASY - Parameters of Probe: ET3DV6 SN:1387

Sensitivity in Free Space

NormX	1.55 $\mu\text{V}/(\text{V}/\text{m})^2$
NormY	1.65 $\mu\text{V}/(\text{V}/\text{m})^2$
NormZ	1.64 $\mu\text{V}/(\text{V}/\text{m})^2$

Diode Compression

DCP X	92	mV
DCP Y	92	mV
DCP Z	92	mV

Sensitivity in Tissue Simulating Liquid

Head	900 MHz	$\epsilon_r = 41.5 \pm 5\%$	$\sigma = 0.97 \pm 5\%$ mho/m
Head	835 MHz	$\epsilon_r = 41.5 \pm 5\%$	$\sigma = 0.90 \pm 5\%$ mho/m
ConvF X	6.6 $\pm 9.5\%$ (k=2)		Boundary effect:
ConvF Y	6.6 $\pm 9.5\%$ (k=2)		Alpha 0.37
ConvF Z	6.6 $\pm 9.5\%$ (k=2)		Depth 2.61
Head	1800 MHz	$\epsilon_r = 40.0 \pm 5\%$	$\sigma = 1.40 \pm 5\%$ mho/m
Head	1900 MHz	$\epsilon_r = 40.0 \pm 5\%$	$\sigma = 1.40 \pm 5\%$ mho/m
ConvF X	5.2 $\pm 9.5\%$ (k=2)		Boundary effect:
ConvF Y	5.2 $\pm 9.5\%$ (k=2)		Alpha 0.50
ConvF Z	5.2 $\pm 9.5\%$ (k=2)		Depth 2.73





Boundary Effect


Head	900 MHz	Typical SAR gradient: 5 % per mm	
	Probe Tip to Boundary	1 mm	2 mm
	SAR _{be} [%] Without Correction Algorithm	10.2	5.9
	SAR _{be} [%] With Correction Algorithm	0.4	0.6
Head	1800 MHz	Typical SAR gradient: 10 % per mm	
	Probe Tip to Boundary	1 mm	2 mm
	SAR _{be} [%] Without Correction Algorithm	14.6	9.8
	SAR _{be} [%] With Correction Algorithm	0.2	0.0

Sensor Offset


Probe Tip to Sensor Center	2.7	mm
Optical Surface Detection	1.4 \pm 0.2	mm

Receiving Pattern (ϕ), $\theta = 0^\circ$






Isotropy Error (ϕ), $\theta = 0^\circ$





Frequency Response of E-Field


(TEM-Cell:ifi110, Waveguide R22)



Dynamic Range f(SAR_{brain}) (Waveguide R22)




Conversion Factor Assessment




Head	900 MHz	$\epsilon_r = 41.5 \pm 5\%$	$\sigma = 0.97 \pm 5\% \text{ mho/m}$
Head	835 MHz	$\epsilon_r = 41.5 \pm 5\%$	$\sigma = 0.90 \pm 5\% \text{ mho/m}$
	ConvF X	6.6 $\pm 9.5\%$ (k=2)	Boundary effect:
	ConvF Y	6.6 $\pm 9.5\%$ (k=2)	Alpha 0.37
	ConvF Z	6.6 $\pm 9.5\%$ (k=2)	Depth 2.61
Head	1800 MHz	$\epsilon_r = 40.0 \pm 5\%$	$\sigma = 1.40 \pm 5\% \text{ mho/m}$
Head	1900 MHz	$\epsilon_r = 40.0 \pm 5\%$	$\sigma = 1.40 \pm 5\% \text{ mho/m}$
	ConvF X	5.2 $\pm 9.5\%$ (k=2)	Boundary effect:
	ConvF Y	5.2 $\pm 9.5\%$ (k=2)	Alpha 0.50
	ConvF Z	5.2 $\pm 9.5\%$ (k=2)	Depth 2.73

Conversion Factor Assessment



Body	900 MHz	$\epsilon_r = 55.0 \pm 5\%$	$\sigma = 1.05 \pm 5\% \text{ mho/m}$
Body	835 MHz	$\epsilon_r = 55.2 \pm 5\%$	$\sigma = 0.97 \pm 5\% \text{ mho/m}$
	ConvF X	6.4 $\pm 9.5\%$ (k=2)	Boundary effect:
	ConvF Y	6.4 $\pm 9.5\%$ (k=2)	Alpha 0.45
	ConvF Z	6.4 $\pm 9.5\%$ (k=2)	Depth 2.35
Body	1800 MHz	$\epsilon_r = 53.3 \pm 5\%$	$\sigma = 1.52 \pm 5\% \text{ mho/m}$
Body	1900 MHz	$\epsilon_r = 53.3 \pm 5\%$	$\sigma = 1.52 \pm 5\% \text{ mho/m}$
	ConvF X	4.9 $\pm 9.5\%$ (k=2)	Boundary effect:
	ConvF Y	4.9 $\pm 9.5\%$ (k=2)	Alpha 0.60
	ConvF Z	4.9 $\pm 9.5\%$ (k=2)	Depth 2.59


Conversion Factor Assessment



Head	2450	MHz	$\epsilon_r = 39.2 \pm 5\%$	$\sigma = 1.80 \pm 5\%$ mho/m
	ConvF X		5.0 $\pm 8.9\%$ (k=2)	Boundary effect:
	ConvF Y		5.0 $\pm 8.9\%$ (k=2)	Alpha 1.04
	ConvF Z		5.0 $\pm 8.9\%$ (k=2)	Depth 1.85
Body	2450	MHz	$\epsilon_r = 52.7 \pm 5\%$	$\sigma = 1.95 \pm 5\%$ mho/m
	ConvF X		4.6 $\pm 8.9\%$ (k=2)	Boundary effect:
	ConvF Y		4.6 $\pm 8.9\%$ (k=2)	Alpha 1.20
	ConvF Z		4.6 $\pm 8.9\%$ (k=2)	Depth 1.60

Deviation from Isotropy in HSL

Error (θ, ϕ), $f = 900$ MHz




Additional Conversion Factors for Dosimetric E-Field Probe

Type:	ET3DV6
Serial Number:	1387
Place of Assessment:	Zurich
Date of Assessment:	February 28, 2003
Probe Calibration Date:	February 26, 2003

Schmid & Partner Engineering AG hereby certifies that conversion factor(s) of this probe have been evaluated on the date indicated above. The assessment was performed using the FDTD numerical code SEMCAD of Schmid & Partner Engineering AG. Since the evaluation is coupled with measured conversion factors, it has to be recalculated yearly, i.e., following the re-calibration schedule of the probe. The uncertainty of the numerical assessment is based on the extrapolation from measured value at 900 MHz or at 1800 MHz.

Assessed by:



Dosimetric E-Field Probe ET3DV6 SN:1387

Conversion factor (\pm standard deviation)

150 MHz	ConvF	$9.1 \pm 8\%$	$\epsilon_r = 52.3$ $\sigma = 0.76$ mho/m (head tissue)
300 MHz	ConvF	$7.9 \pm 8\%$	$\epsilon_r = 45.3$ $\sigma = 0.87$ mho/m (head tissue)
450 MHz	ConvF	$7.5 \pm 8\%$	$\epsilon_r = 43.5$ $\sigma = 0.87$ mho/m (head tissue)
150 MHz	ConvF	$8.8 \pm 8\%$	$\epsilon_r = 61.9$ $\sigma = 0.80$ mho/m (body tissue)
300 MHz	ConvF	$8.0 \pm 8\%$	$\epsilon_r = 58.2$ $\sigma = 0.92$ mho/m (body tissue)
450 MHz	ConvF	$7.7 \pm 8\%$	$\epsilon_r = 56.7$ $\sigma = 0.94$ mho/m (body tissue)

APPENDIX E - MEASURED FLUID DIELECTRIC PARAMETERS

2450MHz System Performance Check

Measured Fluid Dielectric Parameters (Brain)

September 18, 2003

Frequency	ϵ'	ϵ''
2.350000000 GHz	37.5790	13.4922
2.360000000 GHz	37.5641	13.5269
2.370000000 GHz	37.5499	13.5719
2.380000000 GHz	37.5315	13.5821
2.390000000 GHz	37.5018	13.6013
2.400000000 GHz	37.4511	13.6100
2.410000000 GHz	37.3963	13.6331
2.420000000 GHz	37.3324	13.6746
2.430000000 GHz	37.2713	13.7250
2.440000000 GHz	37.2323	13.7611
2.450000000 GHz	37.1814	13.8014
2.460000000 GHz	37.1385	13.8438
2.470000000 GHz	37.1223	13.8812
2.480000000 GHz	37.1003	13.9236
2.490000000 GHz	37.0889	13.9413
2.500000000 GHz	37.0638	13.9378
2.510000000 GHz	37.0215	13.9620
2.520000000 GHz	36.9607	13.9855
2.530000000 GHz	36.8851	14.0295
2.540000000 GHz	36.8355	14.0580
2.550000000 GHz	36.7828	14.0948

2450MHz DUT Evaluation (Body)

Measured Fluid Dielectric Parameters (Muscle)

September 18, 2003

Frequency	ϵ'	ϵ''
2.350000000 GHz	51.2155	14.2196
2.360000000 GHz	51.1780	14.2556
2.370000000 GHz	51.1558	14.3214
2.380000000 GHz	51.1148	14.3518
2.390000000 GHz	51.0824	14.3909
2.400000000 GHz	51.0221	14.4238
2.410000000 GHz	50.9752	14.4634
2.420000000 GHz	50.9030	14.5052
2.430000000 GHz	50.8648	14.5615
2.440000000 GHz	50.8057	14.5964
2.450000000 GHz	50.7597	14.6527
2.460000000 GHz	50.7178	14.6901
2.470000000 GHz	50.6917	14.7272
2.480000000 GHz	50.6698	14.7635
2.490000000 GHz	50.6358	14.7712
2.500000000 GHz	50.6045	14.8094
2.510000000 GHz	50.5606	14.8159
2.520000000 GHz	50.4927	14.8463
2.530000000 GHz	50.4466	14.9016
2.540000000 GHz	50.3920	14.9316
2.550000000 GHz	50.3600	14.9781

APPENDIX F - SAM PHANTOM CERTIFICATE OF CONFORMITY

Schmid & Partner Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fax +41 1 245 97 79

Certificate of conformity / First Article Inspection

Item	SAM Twin Phantom V4.0
Type No	QD 000 P40 BA
Series No	TP-1002 and higher
Manufacturer / Origin	Untersee Composites Hauptstr. 69 CH-8559 Fruthwilen Switzerland

Tests

The series production process used allows the limitation to test of first articles. Complete tests were made on the pre-series Type No. QD 000 P40 AA, Serial No. TP-1001 and on the series first article Type No. QD 000 P40 BA, Serial No. TP-1006. Certain parameters have been retested using further series units (called samples).

Test	Requirement	Details	Units tested
Shape	Compliance with the geometry according to the CAD model.	IT'IS CAD File (*)	First article, Samples
Material thickness	Compliant with the requirements according to the standards	2mm +/- 0.2mm in specific areas	First article, Samples
Material parameters	Dielectric parameters for required frequencies	200 MHz – 3 GHz Relative permittivity < 5 Loss tangent < 0.05.	Material sample TP 104-5
Material resistivity	The material has been tested to be compatible with the liquids defined in the standards	Liquid type HSL 1800 and others according to the standard.	Pre-series, First article

Standards

- [1] CENELEC EN 50361
 - [2] IEEE P1528-200x draft 6.5
 - [3] IEC PT 62209 draft 0.9
- (*) The IT'IS CAD file is derived from [2] and is also within the tolerance requirements of the shapes of [1] and [3].

Conformity

Based on the sample tests above, we certify that this item is in compliance with the uncertainty requirements of SAR measurements specified in standard [1] and draft standards [2] and [3].

Date 18.11.2001

Signature / Stamp

**Schmid & Partner
Engineering AG**

Zeughausstrasse 43, CH-8004 Zurich
Tel. +41 1 245 97 00, Fax +41 1 245 97 79

APPENDIX G - PLANAR PHANTOM CERTIFICATE OF CONFORMITY & DIMENSIONS

2378 Westlake Road
Kelowna, B.C. Canada
V1Z-2V2



Ph. # 250-769-6848
Fax # 250-769-6334
E-mail: barskiind@shaw.ca
Web: www.bcfiberglass.com

FIBERGLASS FABRICATORS

Certificate of Conformity

Item : Flat Planar Phantom Unit # 03-01
Date: June 16, 2003
Manufacturer: Barski Industries (1985 Ltd)

Test	Requirement	Details
Shape	Compliance to geometry according to drawing	Supplied CAD drawing
Material Thickness	Compliant with the requirements	2mm +/- 0.2mm in measurement area
Material Parameters	Dielectric parameters for required frequencies Based on Dow Chemical technical data	100 MHz-5 GHz Relative permittivity<5 Loss Tangent<0.05

Conformity

Based on the above information, we certify this product to be compliant to the requirements specified.

Signature: _____

A handwritten signature in black ink, appearing to read 'Daniel Chailier', is written over a horizontal line.

Daniel Chailier



Fiberglass Planar Phantom - Top View



Fiberglass Planar Phantom - Front View




Fiberglass Planar Phantom - Back View



Fiberglass Planar Phantom - Bottom View

Dimensions of Fiberglass Planar Phantom


(Manufactured by Barski Industries Ltd. - Unit# 03-01)




**Note: Measurements that aren't repeated for the opposite sides are the same as the side measured.
This drawing is not to scale.**

APPENDIX H - SAR TEST SETUP & DUT PHOTOGRAPHS

BODY SAR TEST SETUP PHOTOGRAPHS
HZ1500 PCMCIA WLAN Card with Toshiba Tecra Laptop PC
Bottom Side of Laptop PC - 0.0 cm Separation Distance to Planar Phantom




DUT in bottom PCMCIA card slot of host Laptop PC



DUT in top PCMCIA card slot of host Laptop PC



DUT in bottom PCMCIA card slot of host Laptop PC




DUT in top PCMCIA card slot of host Laptop PC


BODY SAR TEST SETUP PHOTOGRAPHS

HZ1500 PCMCIA WLAN Card with Toshiba Tecra Laptop PC


Right Side of Laptop PC - 0.0 cm Separation Distance to Planar Phantom (from DUT)




BODY SAR TEST SETUP PHOTOGRAPHS
HZ1500 PCMCIA WLAN Card with Compaq PP2130 Laptop PC
Bottom Side of Laptop PC - 0.0 cm Separation Distance to Planar Phantom



BODY SAR TEST SETUP PHOTOGRAPHS
HZ1500 PCMCIA WLAN Card with Compaq PP2130 Laptop PC
Left Side of Laptop PC - 0.0 cm Separation Distance to Planar Phantom (from DUT)



BODY SAR TEST SETUP PHOTOGRAPHS
HZ1500 PCMCIA WLAN Card with Compaq PP2150 Laptop PC
Bottom Side of Laptop PC - 0.0 cm Separation Distance to Planar Phantom



BODY SAR TEST SETUP PHOTOGRAPHS
HZ1500 PCMCIA WLAN Card with Compaq PP2150 Laptop PC
Left Side of Laptop PC - 0.0 cm Separation Distance to Planar Phantom (from DUT)



DUT PHOTOGRAPHS

HZ1500 PCMCIA WLAN CARD



DUT PHOTOGRAPHS

DUT with Toshiba Tecra Laptop PC - Top PCMCIA Card Slot



DUT PHOTOGRAPHS

DUT with Toshiba Tecra Laptop PC - Bottom PCMCIA Card Slot



DUT PHOTOGRAPHS

DUT with Compaq PP2130 Laptop PC (Single Slot)



DUT PHOTOGRAPHS

DUT with Compaq PP2150 Laptop PC (Single Slot)

