

RADIO TEST REPORT

Test Report No. 14983815H-A-R1

Customer	Audio-Technica Corporation
Description of EUT	Receiver Unit
Model Number of EUT	ATW-RU14
FCC ID	JFZRU14
Test Regulation	FCC Part 15 Subpart C
Test Result	Complied
Issue Date	February 26, 2024
Remarks	-

Representative Test Engineer



Nachi Konegawa
Engineer

Approved By



Satofumi Matsuyama
Engineer



CERTIFICATE 5107.02

- The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan, Inc.
 There is no testing item of "Non-accreditation".

Report Cover Page - Form-ULID-003532 (DCS:13-EM-F0429) Issue# 23.0

ANNOUNCEMENT

- This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- The results in this report apply only to the sample tested. (Laboratory was not involved in sampling.)
- This sample tested is in compliance with the limits of the above regulation.
- The test results in this test report are traceable to the national or international standards.
- This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
- This test report covers Radio technical requirements.
It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
- The all test items in this test report are conducted by UL Japan, Inc. Ise EMC Lab.
- The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan, Inc. has been accredited.
- The information provided by the customer for this report is identified in SECTION 1.
- The laboratory is not responsible for information provided by the customer which can impact the validity of the results.
- For test report(s) referred in this report, the latest version (including any revisions) is always referred.

REVISION HISTORY

Original Test Report No.: 14983815H-A

This report is a revised version of 14983815H-A. 14983815H-A is replaced with this report.

Revision	Test Report No.	Date	Page Revised Contents
- (Original)	14983815H-A	October 31, 2023	-
1	14983815H-A-R1	February 26, 2024	2.2: Product Description Radio Specification Correction of antenna gain. Antenna 1: 0 dBi Antenna 2: 0 dBi Antenna 3: 0 dBi (Rx only) Antenna 4: 0 dBi (Rx only) → Antenna 1: 2.14 dBi Antenna 2: 2.14 dBi Antenna 3: 2.14 dBi (Rx only) Antenna 4: 2.14 dBi (Rx only)
1	14983815H-A-R1	February 26, 2024	4.2: Configuration and Peripherals -Addition of explanatory note for test configuration.
1	14983815H-A-R1	February 26, 2024	APPENDIX 1: Test Data -Correction of antenna gain (and relevant value) for Maximum Peak Output Power and Conducted Spurious Emission data 0 dBi → 2.14 dBi -Deletion of below note. *2.0 dBi was applied to the test result based on ANSI C63.10 since antenna gain was less than 2.0 dBi.

Reference: Abbreviations (Including words undescribed in this report)

A2LA	The American Association for Laboratory Accreditation	ICES	Interference-Causing Equipment Standard
AC	Alternating Current	IEC	International Electrotechnical Commission
AFH	Adaptive Frequency Hopping	IEEE	Institute of Electrical and Electronics Engineers
AM	Amplitude Modulation	IF	Intermediate Frequency
Amp, AMP	Amplifier	ILAC	International Laboratory Accreditation Conference
ANSI	American National Standards Institute	ISED	Innovation, Science and Economic Development Canada
Ant, ANT	Antenna	ISO	International Organization for Standardization
AP	Access Point	JAB	Japan Accreditation Board
ASK	Amplitude Shift Keying	LAN	Local Area Network
Atten., ATT	Attenuator	LIMS	Laboratory Information Management System
AV	Average	MCS	Modulation and Coding Scheme
BPSK	Binary Phase-Shift Keying	MRA	Mutual Recognition Arrangement
BR	Bluetooth Basic Rate	N/A	Not Applicable
BT	Bluetooth	NIST	National Institute of Standards and Technology
BT LE	Bluetooth Low Energy	NS	No signal detect.
BW	BandWidth	NSA	Normalized Site Attenuation
Cal Int	Calibration Interval	NVLAP	National Voluntary Laboratory Accreditation Program
CCK	Complementary Code Keying	OBW	Occupied Band Width
Ch., CH	Channel	OFDM	Orthogonal Frequency Division Multiplexing
CISPR	Comite International Special des Perturbations Radioelectriques	P/M	Power meter
CW	Continuous Wave	PCB	Printed Circuit Board
DBPSK	Differential BPSK	PER	Packet Error Rate
DC	Direct Current	PHY	Physical Layer
D-factor	Distance factor	PK	Peak
DFS	Dynamic Frequency Selection	PN	Pseudo random Noise
DQPSK	Differential QPSK	PRBS	Pseudo-Random Bit Sequence
DSSS	Direct Sequence Spread Spectrum	PSD	Power Spectral Density
EDR	Enhanced Data Rate	QAM	Quadrature Amplitude Modulation
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power	QP	Quasi-Peak
EMC	ElectroMagnetic Compatibility	QPSK	Quadri-Phase Shift Keying
EMI	ElectroMagnetic Interference	RBW	Resolution Band Width
EN	European Norm	RDS	Radio Data System
ERP, e.r.p.	Effective Radiated Power	RE	Radio Equipment
EU	European Union	RF	Radio Frequency
EUT	Equipment Under Test	RMS	Root Mean Square
Fac.	Factor	RSS	Radio Standards Specifications
FCC	Federal Communications Commission	Rx	Receiving
FHSS	Frequency Hopping Spread Spectrum	SA, S/A	Spectrum Analyzer
FM	Frequency Modulation	SG	Signal Generator
Freq.	Frequency	SVSWR	Site-Voltage Standing Wave Ratio
FSK	Frequency Shift Keying	TR	Test Receiver
GFSK	Gaussian Frequency-Shift Keying	Tx	Transmitting
GNSS	Global Navigation Satellite System	VBW	Video BandWidth
GPS	Global Positioning System	Vert.	Vertical
Hori.	Horizontal	WLAN	Wireless LAN

CONTENTS	PAGE
SECTION 1: Customer Information	5
SECTION 2: Equipment Under Test (EUT).....	5
SECTION 3: Test Specification, Procedures & Results	6
SECTION 4: Operation of EUT during testing	9
SECTION 5: Conducted Emission.....	11
SECTION 6: Radiated Spurious Emission.....	12
SECTION 7: Antenna Terminal Conducted Tests	14
APPENDIX 1: Test Data	15
Conducted Emission	15
99 % Occupied Bandwidth and 6 dB Bandwidth.....	16
Maximum Peak Output Power	18
Average Output Power.....	19
Radiated Spurious Emission.....	21
Conducted Spurious Emission.....	27
Power Density	28
APPENDIX 2: Test Instruments	30
APPENDIX 3: Photographs of Test Setup	32
Conducted Emission	32
Radiated Spurious Emission.....	33
Worst Case Position	34
Antenna Terminal Conducted Tests	36

SECTION 1: Customer Information

Company Name	Audio-Technica Corporation
Address	2-46-1 Nishi-naruse, Machida, Tokyo 194-8666, Japan
Telephone Number	+81-42-739-9121
Contact Person	Hirohisa Yamamoto

The information provided from the customer is as follows;

- Customer, Description of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer Information
- SECTION 2: Equipment Under Test (EUT) other than the Receipt Date and Test Date
- SECTION 4: Operation of EUT during testing

SECTION 2: Equipment Under Test (EUT)

2.1 Identification of EUT

Description	Receiver Unit
Model Number	ATW-RU14
Serial Number	Refer to SECTION 4.2
Condition	Production prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification	No Modification by the test lab
Receipt Date	September 26, 2023 (Other than radiated spurious emission test (Below 1 GHz)) October 5, 2023 (Radiated spurious emission test (Below 1 GHz))
Test Date	September 26 to October 13, 2023

2.2 Product Description

General Specification

Rating	DC 12 V
Operating temperature	0 deg. C to 40 deg. C

Radio Specification

This report contains data provided by the customer which can impact the validity of results. UL Japan, Inc. is only responsible for the validity of results after the integration of the data provided by the customer. The data provided by the customer is marked "a)" in the table below.

Equipment Type	Transceiver
Frequency of Operation	2402 MHz to 2480 MHz
Type of Modulation	GFSK
Antenna Gain ^{a)}	Antenna 1: 2.14 dBi Antenna 2: 2.14 dBi Antenna 3: 2.14 dBi (Rx only) Antenna 4: 2.14 dBi (Rx only)

SECTION 3: Test Specification, Procedures & Results

3.1 Test Specification

Test Specification	FCC Part 15 Subpart C The latest version on the first day of the testing period
Title	FCC 47 CFR Part 15 Radio Frequency Device Subpart C Intentional Radiators Section 15.207 Conducted limits Section 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

* Also the EUT complies with FCC Part 15 Subpart B.

3.2 Procedures and Results

Item	Test Procedure	Specification	Worst Margin	Results	Remarks
Conducted Emission	FCC: ANSI C63.10-2013 6. Standard test methods ISED: RSS-Gen 8.8	FCC: Section 15.207 ISED: RSS-Gen 8.8	11.39 dB 0.32475 MHz, L	Complied	-
6dB Bandwidth	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section 15.247(a)(2) ISED: RSS-247 5.2(a)	See data.	Complied	Conducted
Maximum Peak Output Power	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.12	FCC: Section 15.247(b)(3) ISED: RSS-247 5.4(d)		Complied	Conducted
Power Density	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section 15.247(e) ISED: RSS-247 5.2(b)		Complied	Conducted
Spurious Emission Restricted Band Edges	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.13	FCC: Section 15.247(d) ISED: RSS-247 5.5 RSS-Gen 8.9 RSS-Gen 8.10	1.9 dB 2483.5 MHz AV, Horizontal	Complied	Conducted (below 30 MHz)/ Radiated (above 30 MHz) *1)
<p>Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593. * In case any questions arise about test procedure, ANSI C63.10: 2013 is also referred.</p> <p>*1) Radiated test was selected over 30 MHz based on section 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02 8.5 and 8.6.</p>					

FCC Part 15.31 (e)

This EUT provides the stable voltage constantly to RF Part regardless of input voltage. Therefore, this EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

The EUT has a unique coupling/antenna connector. Therefore the equipment complies with the requirement of 15.203.

3.3 Addition to Standard

Item	Test Procedure	Specification	Worst Margin	Results	Remarks
99% Occupied Bandwidth	ISED: RSS-Gen 6.7	ISED: -	N/A	-	Conducted

Other than above, no addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

Measurement uncertainty is not taken into account when stating conformity with a specified requirement. Note: When margins obtained from test results are less than the measurement uncertainty, the test results may exceed the limit.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor $k = 2$.

Conducted emission

Item	Frequency Range	Unit	Calculated Uncertainty (+/-)
AMN (LISN)	0.009 MHz to 0.15 MHz	dB	3.7
	0.15 MHz to 30 MHz	dB	3.3

Radiated emission

Measurement distance	Frequency Range	Unit	Calculated Uncertainty (+/-)
3 m	9 kHz to 30 MHz	dB	3.3
10 m		dB	3.1
3 m	30 MHz to 200 MHz	Horizontal	4.8
		Vertical	5.0
	200 MHz to 1000 MHz	Horizontal	5.1
		Vertical	6.2
10 m	30 MHz to 200 MHz	Horizontal	4.8
		Vertical	4.8
	200 MHz to 1000 MHz	Horizontal	4.9
		Vertical	5.0
3 m	1 GHz to 6 GHz	dB	4.9
	6 GHz to 18 GHz	dB	5.2
1 m	10 GHz to 26.5 GHz	dB	5.5
	26.5 GHz to 40 GHz	dB	5.4
10 m	1 GHz to 18 GHz	dB	5.3

Antenna Terminal Conducted Tests

Item	Unit	Calculated Uncertainty (+/-)
Antenna Terminated Conducted Emission / Power Density / Burst Power	dB	3.28
Adjacent Channel Power (ACP)	dB	2.27
Bandwidth (OBW)	%	0.96
Time Readout (Time span upto 100 msec)	%	0.11
Time Readout (Time span upto 1000 msec)	%	0.11
Time Readout (Time span upto 60 sec)	%	0.02
Power Measurement (Power meter)	dB	1.50
Frequency Readout (Frequency counter)	ppm	0.67
Frequency Readout (Spectrum analyzer frequency readout function)	ppm	1.61
Temperature (Constant temperature bath)	deg. C	0.78
Humidity (Constant temperature bath)	%RH	2.80
Modulation Characteristics	%	6.93
Frequency for Mobile	ppm	0.08

3.5 Test Location

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 Japan

Telephone: +81-596-24-8999

A2LA Certificate Number: 5107.02 / FCC Test Firm Registration Number: 884919

ISED Lab Company Number: 2973C / CAB identifier: JP0002

Test site	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms	Maximum measurement distance
No.1 semi-anechoic chamber	19.2 x 11.2 x 7.7	7.0 x 6.0	No.1 Power source room	10 m
No.2 semi-anechoic chamber	7.5 x 5.8 x 5.2	4.0 x 4.0	-	3 m
No.3 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.3 Preparation room	3 m
No.3 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.4 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.4 Preparation room	3 m
No.4 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.5 semi-anechoic chamber	6.0 x 6.0 x 3.9	6.0 x 6.0	-	-
No.5 measurement room	6.4 x 6.4 x 3.0	6.4 x 6.4	-	-
No.6 shielded room	4.0 x 4.5 x 2.7	4.0 x 4.5	-	-
No.6 measurement room	4.75 x 5.4 x 3.0	4.75 x 4.15	-	-
No.7 shielded room	4.7 x 7.5 x 2.7	4.7 x 7.5	-	-
No.8 measurement room	3.1 x 5.0 x 2.7	3.1 x 5.0	-	-
No.9 measurement room	8.8 x 4.6 x 2.8	2.4 x 2.4	-	-
No.10 shielded room	3.8 x 2.8 x 2.8	3.8 x 2.8	-	-
No.11 measurement room	4.0 x 3.4 x 2.5	N/A	-	-
No.12 measurement room	2.6 x 3.4 x 2.5	N/A	-	-
Large Chamber	16.9 x 22.1 x 10.17	16.9 x 22.1	-	10 m
Small Chamber	5.3 x 6.69 x 3.59	5.3 x 6.69	-	-

* Size of vertical conducting plane (for Conducted Emission test): 2.0 x 3.0 m for No.1, No.2, No.3, No.4, and No.5 semi-anechoic chambers and No.3 and No.4 shielded rooms.

3.6 Test Data, Test Instruments, and Test Set Up

Refer to APPENDIX.


SECTION 4: Operation of EUT during testing

4.1 Operating Mode(s)

*The Details of Operating Mode(s)

Test Item	Operating Mode	Tested Antenna	Tested Frequency
Conducted Spurious Emission, Radiated Spurious Emission (Below 1 GHz) Conducted Spurious Emission	Tx Transmitting	Antenna 2 *1)	2480 MHz *2)
Maximum Peak Output Power	Tx Transmitting	Antenna 1 Antenna 2	2402 MHz 2441 MHz 2480 MHz
Radiated Spurious Emission (Above 1 GHz), 6 dB Bandwidth, 99 % Occupied Bandwidth, Power Density	Tx Transmitting	Antenna 2 *1)	2402 MHz 2441 MHz 2480 MHz
*1) After the comparison between Antenna 1 and Antenna 2, test was performed with the antenna that had higher power as a representative.			
*2) The Frequency was tested as a representative, because it had the highest power at antenna terminal test.			
*Power of the EUT was set by the software as follows; Power Setting: 4 dBm Software: System20 Control (Date: September 26, 2023 Storage location: Driven by connected PC)			
*This setting of software is the worst case. Any conditions under the normal use do not exceed the condition of setting. In addition, end users cannot change the settings of the output power of the product.			

4.2 Configuration and Peripherals



- * Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.
- * The power supply for the EUT is provided by Item F.
- Conducted Emission test was performed using the AC adapter (Item G) with standard core that was included with Item F.
- * After the comparison between ATW-RU14 set in the ATW-RC14 slot, and with the ATW-RU14 connected with a LAN cable without being set in the slot, test was conducted with the ATW-RU14 connected with a LAN cable as worst condition.

Description of EUT and Support Equipment

No.	Item	Model number	Serial Number	Manufacturer	Remarks
A	Receiver Unit	ATW-RU14	23300063	Audio-Technica Corporation	EUT *1)
			23300071		EUT *2)
B	Antenna	ANTB18-198A0	-	SANSEI ELECTRIC CO.,LTD	EUT *2)
C	Antenna	ANTB18-198A0	-	SANSEI ELECTRIC CO.,LTD	EUT *2)
D	Antenna	ANTB18-198A0	-	SANSEI ELECTRIC CO.,LTD	EUT *2)
E	Antenna	ANTB18-198A0	-	SANSEI ELECTRIC CO.,LTD	EUT *2)
F	Receiver Chassis	ATW-RC14	23300063	Audio Technica Fukui Co., Ltd.	*1)
			23300071		*2)
G	AC Adapter	KSAS0051200050D5D	-	Kuantech (Ktec)	-
H	Laptop PC	X1 Carbon	R9-OH8TU 15/9	LENOVO	*1)
		CF-NX1GWGYS	2KKSA14614	Panasonic	*3)
I	AC Adapter	ADLX45NCC2A	8SSA10E75794 C1SG59R0GHF	LENOVO	*1)
		CF-AA6412C	6412CM112714770A	Panasonic	*3)

List of Cables Used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	LAN Cable	2.0	Unshielded	Unshielded	-
2	DC Cable	1.5	Unshielded	Unshielded	-
3	LAN Cable	3.0 *1), *3)	Shielded	Shielded	-
4	DC Cable	1.7 *1), 0.9 *3)	Unshielded	Unshielded	-
5	AC Cable	1.0 *1), 0.8 *3)	Unshielded	Unshielded	-

- *1) Used for Antenna Terminal conducted test,
- *2) Used for Conducted Emission test and Radiated Emission test
- *3) Used for Radiated Emission test

SECTION 5: Conducted Emission

Test Procedure and Conditions

EUT was placed on a urethane platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane.

The rear of tabletop was located 40 cm to the vertical conducting plane. The rear of EUT, including peripherals was aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. EUT was located 80 cm from a Line Impedance Stabilization Network (LISN) / Artificial mains Network (AMN) and excess AC cable was bundled in center.

For the tests on EUT with other peripherals (as a whole system)

I/O cables that were connected to the peripherals were bundled in center. They were folded back and forth forming a bundle 30 cm to 40 cm long and were hanged at a 40 cm height to the ground plane. All unused 50ohm connectors of the LISN (AMN) were resistivity terminated in 50 ohm when not connected to the measuring equipment.

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT in a Semi Anechoic Chamber.


The EUT was connected to a LISN. (Via Item F and Item G described in Section 4.1)

An overview sweep with peak detection has been performed.

Test results are rounded off and limit are rounded down, so some differences might be observed.

Detector	: QP and CISPR AV
Measurement Range	: 0.15 MHz to 30 MHz
Test Data	: APPENDIX
Test Result	: Pass

Figure 1: Test Setup



SECTION 6: Radiated Spurious Emission

Test Procedure

It was measured based on "8.5 and 8.6 of KDB 558074 D01 15.247 Meas Guidance v05r02".

[For below 1 GHz]

EUT was placed on a urethane platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[For above 1 GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 1.5 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with absorbent materials lined on a ground plane. Test antenna was aimed at the EUT for receiving the maximum signal and always kept within the illumination area of the 3 dB beamwidth of the antenna.

The height of the measuring antenna varied between 1 m and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer.

The measurements were made with the following detector function of the test receiver and the Spectrum analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

Test Antennas are used as below;

Frequency	30 MHz to 200 MHz	200 MHz to 1 GHz	Above 1 GHz
Antenna Type	Biconical	Logperiodic	Horn


In any 100 kHz bandwidth outside the restricted band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.

20 dBc was applied to the frequency over the limit of FCC 15.209 / Table 4 of RSS-Gen 8.9 (ISED) and outside the restricted band of FCC15.205 / Table 6 of RSS-Gen 8.10 (ISED).

Frequency	Below 1 GHz	Above 1 GHz		20 dBc
Instrument Used	Test Receiver	Spectrum Analyzer		Spectrum Analyzer
Detector	QP	PK	AV	PK
IF Bandwidth	BW 120 kHz	RBW: 1 MHz VBW: 3 MHz	11.12.2.5.1 RBW: 1 MHz VBW: 3 MHz Detector: Power Averaging (RMS) Trace: 100 traces 11.12.2.5.2 The duty cycle was less than 98% for detected noise, a duty factor was added to the 11.12.2.5.1 results.	RBW: 100 kHz VBW: 300 kHz

Figure 2: Test Setup


Below 1 GHz



* : Center of turn table

Test Distance: 3 m

1 GHz to 10 GHz




r : Radius of an outer periphery of EUT
 * : Center of turn table

Distance Factor: $20 \times \log(3.9 \text{ m} / 3.0 \text{ m}) = 2.28 \text{ dB}$
 * Test Distance: $(3 + \text{SVSWR Volume} / 2) - r = 3.9 \text{ m}$

SVSWR Volume : 2.0 m
 (SVSWR Volume has been calibrated based on CISPR 16-1-4.)
 $r = 0.1 \text{ m}$

10 GHz to 26.5 GHz



* : Center of turn table

Distance Factor: $20 \times \log(1.0 \text{ m} / 3.0 \text{ m}) = -9.5 \text{ dB}$
 *Test Distance: 1 m

The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT (including antennas) to see the position of maximum noise, and the test was made at the position that has the maximum noise.

Test results are rounded off and limit are rounded down, so some differences might be observed.

Measurement Range : 30 MHz to 26.5 GHz
Test Data : APPENDIX
Test Result : Pass

SECTION 7: Antenna Terminal Conducted Tests

Test Procedure

The tests were made with below setting connected to the antenna port.

Test	Span	RBW	VBW	Sweep time	Detector	Trace	Instrument Used
6dB Bandwidth	3 MHz	100 kHz	300 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99% Occupied Bandwidth *1)	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak	Max Hold	Spectrum Analyzer
Maximum Peak Output Power	-	-	-	Auto	Peak/Average *2)	-	Power Meter (Sensor: 50 MHz BW)
Peak Power Density	1.5 times the 6dB Bandwidth	3 kHz	10 kHz	Auto	Peak	Max Hold	Spectrum Analyzer *3)
Conducted Spurious Emission *4) *5)	9 kHz to 150 kHz	200 Hz	620 Hz	Auto	Peak	Max Hold	Spectrum Analyzer
	150 kHz to 30 MHz	10 kHz	30 kHz				

*1) Peak hold was applied as Worst-case measurement.

*2) Reference data

*3) Section 11.10.2 Method PKPSD (peak PSD) of "ANSI C63.10-2013".

*4) In the frequency range below 30MHz, RBW was narrowed to separate the noise contents.

Then, wide-band noise near the limit was checked separately, however the noise was not detected as shown in the chart.

(9 kHz - 150 kHz: RBW = 200 Hz, 150 kHz - 30 MHz: RBW = 10 kHz)

*5) The limits in CFR 47, Part 15, Subpart C, paragraph 15.209(a), are identical to those in RSS-Gen section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377 Ohms. For example, the measurement at frequency 9 kHz resulted in a level of 45.5 dBuV/m, which is equivalent to $45.5 - 51.5 = -6.0$ dBuA/m, which has the same margin, 3 dB, to the corresponding RSS-Gen Table 6 limit as it has to 15.209(a) limit.

Test results are rounded off and limit are rounded down, so some differences might be observed.
The equipment and cables were not used for factor 0 dB of the data sheets.


Test Data : APPENDIX
Test Result : Pass

APPENDIX 1: Test Data

Conducted Emission

Test place Ise EMC Lab. No.3 Semi Anechoic Chamber
 Date October 12, 2023
 Temperature / Humidity 22 deg. C / 47 % RH
 Engineer Yuichiro Yamazaki
 Mode Tx 2480 MHz Antenna 2

Limit : FCC_Part 15 Subpart C(15.207)



No.	Freq. [MHz]	Reading		USN [dB]	LOSS [dB]	Results		Limit		Margin		Phase	Comment
		<QP> [dBuV]	<AV> [dBuV]			<QP> [dBuV]	<AV> [dBuV]	<QP> [dBuV]	<AV> [dBuV]	<QP> [dB]	<AV> [dB]		
1	0.27975	26.30	21.20	0.13	13.14	39.57	34.47	60.82	50.82	21.25	16.35	N	
2	0.32470	28.50	23.10	0.13	13.14	41.77	36.37	59.59	49.59	17.82	13.22	N	
3	0.36254	18.10	11.30	0.13	13.15	31.38	24.58	58.67	48.67	27.29	24.09	N	
4	0.74433	19.60	7.70	0.15	13.18	32.93	21.03	56.00	46.00	23.07	24.97	N	
5	0.97432	25.00	9.90	0.16	13.21	38.37	23.27	56.00	46.00	17.63	22.73	N	
6	3.85351	22.20	8.60	0.33	13.37	35.90	22.30	56.00	46.00	20.10	23.70	N	
7	0.27920	27.50	23.40	0.15	13.14	40.79	36.69	60.84	50.84	20.05	14.15	L	
8	0.32475	29.90	24.90	0.15	13.14	43.19	38.19	59.58	49.58	16.39	11.39	L	
9	0.36253	20.80	13.00	0.16	13.15	34.11	26.31	58.67	48.67	24.56	22.36	L	
10	0.74225	20.90	10.10	0.18	13.18	34.26	23.46	56.00	46.00	21.74	22.54	L	
11	0.97471	25.80	13.90	0.20	13.21	39.21	27.31	56.00	46.00	16.79	18.69	L	
12	3.85163	22.70	10.40	0.35	13.37	36.42	24.12	56.00	46.00	19.58	21.88	L	


CHART: WITH FACTOR Peak hold data. CALCULATION : RESULT = READING + LISN + LOSS (CABLE + ATT)
 Except for the above table: adequate margin data below the limits.

99 % Occupied Bandwidth and 6 dB Bandwidth

Test place Ise EMC Lab. No.4 Preparation room
Date September 29, 2023
Temperature / Humidity 22 deg. C / 58 % RH
Engineer Tomoya Sone
Mode Tx Antenna 2

Frequency [MHz]	99% Occupied Bandwidth [kHz]	6dB Bandwidth [MHz]	Limit for 6dB Bandwidth [MHz]
2402	1016.9	0.667	> 0.5000
2441	1027.7	0.672	> 0.5000
2480	1022.8	0.668	> 0.5000

99 % Occupied Bandwidth and 6 dB Bandwidth



Maximum Peak Output Power

Test place Ise EMC Lab. No.4 Preparation room
Date September 29, 2023
Temperature / Humidity 22 deg. C / 58 % RH
Engineer Tomoya Sone
Mode Tx

Antenna 1				Conducted Power					e.i.r.p. for RSS-247					
Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result		Limit		Margin [dB]	Antenna Gain [dBi]	Result		Limit		Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]			[dBm]	[mW]	[dBm]	[mW]	
2402	-3.69	0.44	9.74	6.49	4.46	30.00	1000	23.51	2.14	8.63	7.29	36.02	4000	27.39
2441	-3.42	0.44	9.75	6.77	4.75	30.00	1000	23.23	2.14	8.91	7.78	36.02	4000	27.11
2480	-3.41	0.45	9.75	6.79	4.78	30.00	1000	23.21	2.14	8.93	7.82	36.02	4000	27.09

Antenna 2				Conducted Power					e.i.r.p. for RSS-247					
Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result		Limit		Margin [dB]	Antenna Gain [dBi]	Result		Limit		Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]			[dBm]	[mW]	[dBm]	[mW]	
2402	-3.22	0.44	9.74	6.96	4.97	30.00	1000	23.04	2.14	9.10	8.13	36.02	4000	26.92
2441	-2.97	0.44	9.75	7.22	5.27	30.00	1000	22.78	2.14	9.36	8.63	36.02	4000	26.66
2480	-2.96	0.45	9.75	7.24	5.30	30.00	1000	22.76	2.14	9.38	8.67	36.02	4000	26.64

Sample Calculation:

Result = Reading + Cable Loss + Attenuator Loss

e.i.r.p. Result = Conducted Power Result + Antenna Gain

*The equipment and cables were not used for factor 0 dB of the data sheets.

Average Output Power (Reference data for RF Exposure)

Test place	Ise EMC Lab. No.4 Preparation room
Date	September 29, 2023
Temperature / Humidity	22 deg. C / 58 % RH
Engineer	Tomoya Sone
Mode	Tx

Antenna 1

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result (Time average)		Duty factor [dB]	Result (Burst power average)	
				[dBm]	[mW]		[dBm]	[mW]
2402	-10.72	0.44	9.74	-0.54	0.88	6.82	6.28	4.25
2441	-10.44	0.44	9.75	-0.25	0.94	6.82	6.57	4.54
2480	-10.43	0.45	9.75	-0.23	0.95	6.82	6.59	4.56

Antenna 2

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result (Time average)		Duty factor [dB]	Result (Burst power average)	
				[dBm]	[mW]		[dBm]	[mW]
2402	-10.26	0.44	9.74	-0.08	0.98	6.82	6.74	4.72
2441	-9.99	0.44	9.75	0.20	1.05	6.82	7.02	5.04
2480	-9.95	0.45	9.75	0.25	1.06	6.82	7.07	5.09

Sample Calculation:


Result (Time average) = Reading + Cable Loss + Attenuator Loss

Result (Burst power average) = Time average + Duty factor

*The equipment and cables were not used for factor 0 dB of the data sheets.

Burst rate confirmation

Test place Ise EMC Lab. No.4 Semi Anechoic Chamber
 Date September 26, 2023
 Temperature / Humidity 20 deg. C / 45 % RH
 Engineer Nachi Konegawa
 Mode Tx



* Since the burst rate is not different between the channels, the data has been obtained on the representative channel.

Radiated Spurious Emission

Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.4	No.4	No.4
Date	September 26, 2023	September 28, 2023	September 29, 2023
Temperature / Humidity	20 deg. C / 45 % RH	20 deg. C / 44 % RH	22 deg. C / 55 % RH
Engineer	Nachi Konegawa (1 GHz to 10 GHz)	Nachi Konegawa (10 GHz to 18 GHz)	Yuta Moriya (18 GHz to 26.5 GHz)
Mode	Tx 2402 MHz Antenna 2		

Polarity	Frequency	Reading (QP / PK)	Reading (AV)	Ant. Factor	Loss	Gain	Duty Factor	Result (QP / PK)	Result (AV)	Limit (QP / PK)	Limit (AV)	Margin (QP / PK)	Margin (AV)	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dB]	[dB]	
Hori.	2390.0	52.9	38.1	27.8	5.3	32.0	6.8	53.9	46.0	73.9	53.9	20.0	7.9	*1)
Hori.	4804.0	42.9	34.2	31.3	7.3	31.2	6.8	50.4	48.5	73.9	53.9	23.5	5.4	
Hori.	7206.0	42.5	34.1	36.4	8.6	32.4	-	55.2	46.7	73.9	53.9	18.7	7.2	Floor noise
Hori.	9608.0	42.9	32.5	38.0	9.0	32.5	-	57.4	47.1	73.9	53.9	16.5	6.8	Floor noise
Hori.	12010.0	42.4	34.6	39.1	-3.6	32.8	-	45.2	37.3	73.9	53.9	28.7	16.6	Floor noise
Hori.	14412.0	44.0	35.7	40.7	-2.9	32.3	6.8	49.5	48.0	73.9	53.9	24.4	5.9	
Hori.	16814.0	42.2	34.9	40.1	-2.3	32.5	-	47.5	40.2	73.9	53.9	26.5	13.7	Floor noise
Vert.	2390.0	53.2	31.6	27.8	5.3	32.0	6.8	54.2	39.5	73.9	53.9	19.7	14.4	*1)
Vert.	4804.0	44.5	35.2	31.3	7.3	31.2	6.8	52.0	49.5	73.9	53.9	21.9	4.4	
Vert.	7206.0	42.5	34.1	36.4	8.6	32.4	-	55.2	46.7	73.9	53.9	18.7	7.2	Floor noise
Vert.	9608.0	42.9	32.5	38.0	9.0	32.5	-	57.4	47.1	73.9	53.9	16.5	6.8	Floor noise
Vert.	12010.0	45.2	35.6	39.1	-3.6	32.8	6.8	47.9	45.2	73.9	53.9	26.0	8.7	
Vert.	14412.0	47.4	37.1	40.7	-2.9	32.3	6.8	52.9	49.4	73.9	53.9	21.0	4.5	
Vert.	16814.0	42.2	34.9	40.1	-2.3	32.5	-	47.5	40.2	73.9	53.9	26.5	13.7	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

Result (AV)= Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

*QP detector was used up to 1GHz.

*1) Not Out of Band emission(Leakage Power)

20dBc Data Sheet

Polarity	Frequency	Reading (PK)	Ant Factor	Loss	Gain	Result	Limit	Margin	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dB/m]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
Hori.	2402.0	105.2	27.8	5.3	32.0	106.3	-	-	Carrier
Hori.	2400.0	57.0	27.8	5.3	32.0	58.1	86.3	28.2	
Vert.	2402.0	103.9	27.8	5.3	32.0	104.9	-	-	Carrier
Vert.	2400.0	56.1	27.8	5.3	32.0	57.2	84.9	27.8	



Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

Distance factor: 1 GHz - 10 GHz 20log (3.9 m / 3.0 m) = 2.28 dB

10 GHz - 26.5 GHz 20log (1.0 m / 3.0 m) = -9.5 dB

Radiated Spurious Emission (Reference Plot for band-edge)

Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.4
Date	September 26, 2023
Temperature / Humidity	20 deg. C / 45 % RH
Engineer	Nachi Konegawa
	(1 GHz to 10 GHz)
Mode	Tx 2402 MHz Antenna 2



* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.
Final result of restricted band edge and authorized band edge were shown in tabular data.

Radiated Spurious Emission

Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.4	No.4	No.4
Date	September 26, 2023	September 28, 2023	September 29, 2023
Temperature / Humidity	20 deg. C / 45 % RH	20 deg. C / 44 % RH	22 deg. C / 55 % RH
Engineer	Nachi Konegawa (1 GHz to 10 GHz)	Nachi Konegawa (10 GHz to 18 GHz)	Yuta Moriya (18 GHz to 26.5 GHz)
Mode	Tx 2441 MHz Antenna 2		

Polarity	Frequency	Reading (QP / PK)	Reading (AV)	Ant. Factor	Loss	Gain	Duty Factor	Result (QP / PK)	Result (AV)	Limit (QP / PK)	Limit (AV)	Margin (QP / PK)	Margin (AV)	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dB]	[dB]	
Hori.	4882.0	43.9	34.6	31.4	7.4	31.1	6.8	51.5	49.1	73.9	53.9	22.4	4.8	
Hori.	7323.0	42.8	33.8	36.6	8.6	32.4	-	55.5	46.6	73.9	53.9	18.4	7.4	Floor noise
Hori.	9764.0	42.4	31.4	38.4	9.1	32.6	-	57.3	46.3	73.9	53.9	16.6	7.6	Floor noise
Hori.	12205.0	42.2	34.8	39.0	-3.5	32.7	-	45.0	37.6	73.9	53.9	28.9	16.3	Floor noise
Hori.	14646.0	45.5	35.7	40.4	-2.9	32.3	6.8	50.7	47.7	73.9	53.9	23.3	6.2	
Hori.	17087.0	42.7	35.0	40.8	-2.3	32.5	-	48.8	41.0	73.9	53.9	25.1	12.9	Floor noise
Vert.	4882.0	44.2	35.1	31.4	7.4	31.1	6.8	51.8	49.5	73.9	53.9	22.1	4.4	
Vert.	7323.0	42.8	33.8	36.6	8.6	32.4	-	55.5	46.6	73.9	53.9	18.4	7.4	Floor noise
Vert.	9764.0	42.4	31.4	38.4	9.1	32.6	-	57.3	46.3	73.9	53.9	16.6	7.6	Floor noise
Vert.	12205.0	45.7	35.1	39.0	-3.5	32.7	6.8	48.5	44.8	73.9	53.9	25.4	9.1	
Vert.	14646.0	48.2	37.7	40.4	-2.9	32.3	6.8	53.4	49.7	73.9	53.9	20.5	4.2	
Vert.	17087.0	42.7	35.0	40.8	-2.3	32.5	-	48.8	41.0	73.9	53.9	25.1	12.9	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)
 Result (AV)= Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor
 *Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).
 *QP detector was used up to 1GHz.

Distance factor: 1 GHz - 10 GHz 20log (3.9 m / 3.0 m) = 2.28 dB
 10 GHz - 26.5 GHz 20log (1.0 m / 3.0 m) = -9.5 dB

Radiated Spurious Emission

Test place	Ise EMC Lab.			
Semi Anechoic Chamber	No.4	No.4	No.4	No.3
Date	September 26, 2023	September 28, 2023	September 29, 2023	October 13, 2023
Temperature / Humidity	20 deg. C / 45 % RH	20 deg. C / 44 % RH	22 deg. C / 55 % RH	24 deg. C / 34 % RH
Engineer	Nachi Konegawa (1 GHz to 10 GHz)	Nachi Konegawa (10 GHz to 18 GHz)	Yuta Moriya (18 GHz to 26.5 GHz)	Nachi Konegawa (Below 1 GHz)
Mode	Tx 2480 MHz Antenna 2			

Polarity	Frequency	Reading (QP / PK)	Reading (AV)	Ant. Factor	Loss	Gain	Duty Factor	Result (QP / PK)	Result (AV)	Limit (QP / PK)	Limit (AV)	Margin (QP / PK)	Margin (AV)	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dB]	[dB]	
Hori.	64.8	49.2	-	6.8	7.5	32.2	-	31.3	-	40.0	-	8.7	-	
Hori.	98.4	43.0	-	9.8	7.9	32.1	-	28.5	-	43.5	-	15.0	-	
Hori.	133.0	36.2	-	14.0	8.2	32.1	-	26.4	-	43.5	-	17.2	-	
Hori.	258.1	47.4	-	12.0	9.3	32.0	-	36.8	-	46.0	-	9.3	-	
Hori.	313.4	47.1	-	13.8	9.8	32.0	-	38.7	-	46.0	-	7.3	-	
Hori.	356.4	42.5	-	15.1	10.1	32.0	-	35.7	-	46.0	-	10.3	-	
Hori.	2483.5	66.0	44.1	27.7	5.3	32.0	6.8	67.0	52.0	73.9	53.9	6.9	1.9	*1)
Hori.	4960.0	43.1	34.2	31.6	7.4	31.1	6.8	51.0	48.9	73.9	53.9	22.9	5.0	
Hori.	7440.0	42.2	33.6	36.8	8.6	32.5	-	55.1	46.5	73.9	53.9	18.8	7.4	Floor noise
Hori.	9920.0	41.6	31.5	38.6	9.1	32.7	-	56.6	46.6	73.9	53.9	17.3	7.4	Floor noise
Hori.	12400.0	42.2	33.8	38.7	-3.5	32.6	-	44.8	36.5	73.9	53.9	29.1	17.4	Floor noise
Hori.	14880.0	47.1	36.4	39.6	-2.8	32.3	6.8	51.6	47.7	73.9	53.9	22.3	6.2	
Hori.	17360.0	43.0	34.8	42.8	-2.2	32.4	-	51.2	43.0	73.9	53.9	22.7	10.9	Floor noise
Vert.	66.3	52.0	-	6.6	7.5	32.2	-	34.0	-	40.0	-	6.0	-	
Vert.	88.8	45.1	-	8.4	7.8	32.1	-	29.2	-	43.5	-	14.3	-	
Vert.	159.8	40.3	-	15.4	8.5	32.1	-	32.2	-	43.5	-	11.3	-	
Vert.	313.4	40.2	-	13.8	9.8	32.0	-	31.8	-	46.0	-	14.2	-	
Vert.	356.4	39.9	-	15.1	10.1	32.0	-	33.1	-	46.0	-	12.9	-	
Vert.	762.3	33.0	-	20.5	12.3	31.6	-	34.2	-	46.0	-	11.8	-	
Vert.	2483.5	65.7	43.7	27.7	5.3	32.0	6.8	66.8	51.6	73.9	53.9	7.1	2.3	*1)
Vert.	4960.0	44.2	34.8	31.6	7.4	31.1	6.8	52.0	49.5	73.9	53.9	21.9	4.4	
Vert.	7440.0	42.2	33.6	36.8	8.6	32.5	-	55.1	46.5	73.9	53.9	18.8	7.4	Floor noise
Vert.	9920.0	41.6	31.5	38.6	9.1	32.7	-	56.6	46.6	73.9	53.9	17.3	7.4	Floor noise
Vert.	12400.0	45.1	34.7	38.7	-3.5	32.6	6.8	47.8	44.1	73.9	53.9	26.2	9.8	
Vert.	14880.0	49.1	38.2	39.6	-2.8	32.3	6.8	53.6	49.5	73.9	53.9	20.3	4.4	
Vert.	17360.0	43.0	34.8	42.8	-2.2	32.4	-	51.2	43.0	73.9	53.9	22.7	10.9	Floor noise



Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)
 Result (AV)= Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor
 *Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).
 *QP detector was used up to 1GHz.
 *1) Not Out of Band emission(Leakage Power)

Distance factor: 1 GHz - 10 GHz 20log (3.9 m / 3.0 m) = 2.28 dB
 10 GHz - 26.5 GHz 20log (1.0 m / 3.0 m) = -9.5 dB

**Radiated Spurious Emission
 (Reference Plot for band-edge)**

Test place
 Semi Anechoic Chamber
 Date
 Temperature / Humidity
 Engineer
 Mode



Ise EMC Lab.
 No.4
 September 26, 2023
 20 deg. C / 45 % RH
 Nachi Konegawa
 (1 GHz to 10 GHz)
 Tx 2480 MHz Antenna 2



* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.
 Final result of restricted band edge was shown in tabular data.

Radiated Spurious Emission
(Plot data, Worst case mode for Maximum Peak Output Power)


Test place	Ise EMC Lab.			
Semi Anechoic Chamber	No.4	No.4	No.4	No.3
Date	September 26, 2023	September 28, 2023	September 29, 2023	October 13, 2023
Temperature / Humidity	20 deg. C / 45 % RH	20 deg. C / 44 % RH	22 deg. C / 55 % RH	24 deg. C / 34 % RH
Engineer	Nachi Konegawa	Nachi Konegawa	Yuta Moriya	Nachi Konegawa
	(1 GHz to 10 GHz)	(10 GHz to 18 GHz)	(18 GHz to 26.5 GHz)	(Below 1 GHz)
Mode	Tx 2480 MHz Antenna 2			



*These plots data contain sufficient number to show the trend of characteristic features for EUT.

Conducted Spurious Emission

Test place Ise EMC Lab. No.4 Preparation room
 Date October 13, 2023
 Temperature / Humidity 24 deg. C / 47 % RH
 Engineer Tomoya Sone
 Mode Tx 2480 MHz Antenna 2



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator Loss [dB]	Antenna Gain [dBi]	N (Number of Output)	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
11.00	-99.2	0.00	9.8	2.1	1	-87.2	300	6.0	-26.0	46.7	72.7	
225.00	-88.6	0.00	9.8	2.1	1	-76.6	300	6.0	-15.3	20.5	35.8	

$E [dBuV/m] = EIRP [dBm] - 20 \log (Distance [m]) + Ground\ bounce [dB] + 104.8 [dBuV/m]$
 $EIRP [dBm] = Reading [dBm] + Cable\ loss [dB] + Attenuator\ Loss [dB] + Antenna\ gain [dBi] + 10 * \log (N)$
 N: Number of output

Power Density

Test place Ise EMC Lab. No.4 Preparation room
Date September 29, 2023
Temperature / Humidity 22 deg. C / 58 % RH
Engineer Tomoya Sone
Mode Tx Antenna 2


Freq. [MHz]	Reading [dBm / 3 kHz]	Cable Loss [dB]	Atten. Loss [dB]	Result [dBm / 3 kHz]	Limit [dBm / 3 kHz]	Margin [dB]
2402	-17.67	0.44	9.74	-7.49	8.00	15.49
2441	-17.45	0.44	9.75	-7.26	8.00	15.26
2480	-17.15	0.45	9.75	-6.95	8.00	14.95

Sample Calculation:

Result = Reading + Cable Loss + Attenuator Loss

*The equipment and cables were not used for factor 0 dB of the data sheets.

Power Density



APPENDIX 2: Test Instruments

Test Equipment (1/2)

Test Item	Local ID	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
AT	MAT-10	141156	Attenuator(10dB)	Weinschel Corp	2	BL1173	11/10/2022	12
AT	MAT-89	141419	Attenuator	Weinschel Associates	WA56-10	56100305	05/18/2023	12
AT	MCC-238	184491	Microwave Cable	Murata Manufacturing Company, Ltd.	MXHS83QE3000	-	09/12/2023	12
AT	MCC-239	184492	Microwave Cable	Murata Manufacturing Company, Ltd.	MXHS83QE3000	-	09/12/2023	12
AT	MCC-240	195231	Microwave Cable	Huber+Suhner	SF102D/11PC24/11PC24/1000mm	537062/126E	02/15/2023	12
AT	MMM-10	141545	DIGITAL HITESTER	HIOKI E.E. CORPORATION	3805	51201148	01/18/2023	12
AT	MOS-42	192303	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	0014	12/17/2022	12
AT	MPM-12	141809	Power Meter	Anritsu Corporation	ML2495A	825002	05/26/2023	12
AT	MPSE-17	141830	Power sensor	Anritsu Corporation	MA2411B	738285	05/26/2023	12
AT	MSA-16	141903	Spectrum Analyzer	Keysight Technologies Inc	E4440A	MY46186390	01/16/2023	12
CE	COTS-MEMI-02	178648	EMI measurement program	TSJ (Techno Science Japan)	TEPTO-DV	-	-	-
CE	MAEC-03	142008	AC3_Semi Anechoic Chamber (NSA)	TDK	Semi Anechoic Chamber 3m	DA-10005	05/23/2022	24
CE	MAT-67	141248	Attenuator	JFW Industries, Inc.	50FP-013H2 N	-	12/22/2022	12
CE	MCC-112	141216	Coaxial cable	Fujikura/Suhner/TSJ	5D-2W/SFM14/sucoform141-PE/421-010/RFM-E321(SW)	-/00640	07/25/2023	12
CE	MJM-16	142183	Measure	KOMELON	KMC-36	-	10/03/2022	12
CE	MLS-24	141358	LISN(AMN)	Schwarzbeck Mess-Elektronik OHG	NSLK8127	8127-730	07/13/2023	12
CE	MMM-08	141532	DIGITAL HITESTER	HIOKI E.E. CORPORATION	3805	51201197	01/17/2023	12
CE	MOS-13	141554	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	1301	01/13/2023	12
CE	MTR-08	141949	Test Receiver	Rohde & Schwarz	ESCI	100767	05/17/2023	12
RE	COTS-MEMI-02	178648	EMI measurement program	TSJ (Techno Science Japan)	TEPTO-DV	-	-	-
RE	KBA-05	141198	Biconical Antenna	Schwarzbeck Mess-Elektronik OHG	VHA9103+BBA9106	2513	06/06/2023	12
RE	MAEC-03	142008	AC3_Semi Anechoic Chamber (NSA)	TDK	Semi Anechoic Chamber 3m	DA-10005	05/23/2022	24
RE	MAEC-04	142011	AC4_Semi Anechoic Chamber (NSA)	TDK	Semi Anechoic Chamber 3m	DA-10005	05/22/2022	24
RE	MAEC-04-SVSWR	142017	AC4_Semi Anechoic Chamber (SVSWR)	TDK	Semi Anechoic Chamber 3m	DA-10005	04/14/2023	24
RE	MAT-95	142314	Attenuator	Pasternack Enterprises	PE7390-6	D/C 1504	06/23/2023	12
RE	MCC-265	234602	Microwave Cable	Huber+Suhner	SF126E/11PC35/11PC35/1000M,5000M	537063/126E / 537074/126E	03/16/2023	12
RE	MCC-51	141323	Coaxial cable	UL Japan	-	-	09/10/2023	12
RE	MHA-17	141506	Horn Antenna 15-40GHz	Schwarzbeck Mess-Elektronik OHG	BBHA9170	BBHA9170307	08/09/2023	12
RE	MHA-21	141508	Horn Antenna 1-18GHz	Schwarzbeck Mess-Elektronik OHG	BBHA9120D	557	05/17/2023	12

Test Equipment (2/2)

Test Item	Local ID	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
RE	MHF-25	141232	High Pass Filter 3.5-18.0GHz	UL Japan	HPF SELECTOR	001	09/04/2023	12
RE	MJM-16	142183	Measure	KOMELON	KMC-36	-	10/03/2022	12
RE	MJM-29	142230	Measure, Tape, Steel	KOMELON	KMC-36	-	-	-
RE	MLA-22	141266	Logperiodic Antenna (200-1000MHz)	Schwarzbeck Mess- Elektronik OHG	VUSLP9111B	9111B-191	08/10/2023	12
RE	MMM-08	141532	DIGITAL HiTESTER	HIOKI E.E. CORPORATION	3805	51201197	01/17/2023	12
RE	MMM-10	141545	DIGITAL HiTESTER	HIOKI E.E. CORPORATION	3805	51201148	01/18/2023	12
RE	MOS-13	141554	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	1301	01/13/2023	12
RE	MOS-15	141562	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	0010	01/13/2023	12
RE	MPA-12	141581	MicroWave System Amplifier	Keysight Technologies Inc	83017A	00650	10/05/2022	12
RE	MPA-13	141582	Pre Amplifier	SONOMA INSTRUMENT	310	260834	02/07/2023	12
RE	MSA-03	141884	Spectrum Analyzer	Keysight Technologies Inc	E4448A	MY44020357	03/13/2023	12
RE	MTR-08	141949	Test Receiver	Rohde & Schwarz	ESCI	100767	05/17/2023	12

*Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

Test item:

AT: Antenna Terminal Conducted test

CE: Conducted Emission

RE: Radiated Emission