

## TEST REPORT

Test report no.: 1-4465/17-02-27-B

BNetzA-CAB-02/21-102

### Testing laboratory

**CTC advanced GmbH**

Untertuerkheimer Strasse 6 – 10

66117 Saarbruecken / Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

Internet: <http://www.ctcadvanced.com>

e-mail: [mail@ctcadvanced.com](mailto:mail@ctcadvanced.com)

**Accredited Testing Laboratory:**

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2005) by the Deutsche Akkreditierungsstelle GmbH (DAkkS)

The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number: D-PL-12076-01-03

### Applicant

**Audio-Technica Corp.**

2-46-1 Nishi-naruse, Machida

194-8666 Tokyo / JAPAN

Phone: -/-

Fax: -/-

Contact: Alexander Leppes

e-mail: [aleppes@audio-technica.eu](mailto:aleppes@audio-technica.eu)

Phone: -/-

### Manufacturer

**Audio-Technica Corp.**

2-46-1 Nishi-naruse, Machida

194-8666 Tokyo / JAPAN

### Test standard/s

47 CFR Part 15

Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices

RSS - 210 Issue 9

Spectrum Management and Telecommunications Radio Standards Specification - Licence-Exempt Radio Apparatus: Category I Equipment

RSS - Gen Issue 5

General Requirements for Compliance of Radio

For further applied test standards please refer to section 3 of this test report.

### Test Item

**Kind of test item:** Body Pack Transmitter

**Model name:** ATW-T5201EF2

**FCC ID:** JFZT5201EF2

**IC:** 1752B-T5201EF2

EF2:


Frequency: 580.000 MHz – 607.875 MHz;  
657.100 MHz – 662.900 MHz

Technology tested: proprietary

Antenna: Whip antenna

Power supply: 2.4 V to 3.0 V DC by 2 x AA batteries

Temperature range: -10°C to +45°C



This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

### Test report authorized:

p.o.

Christoph Schneider  
Lab Manager  
Radio Communications & EMC

### Test performed:

p.o.

Yves Olsommer  
Testing Manager  
Radio Communications & EMC

## 1 Table of contents

1	Table of contents .....	2
2	General information .....	3
2.1	Notes and disclaimer .....	3
2.2	Application details.....	3
2.3	Test laboratories sub-contracted .....	3
3	Test standard/s and references .....	4
4	Test environment.....	5
5	Test item.....	5
5.1	General description.....	5
5.2	Additional information .....	5
6	Description of the test setup.....	6
6.1	Shielded fully anechoic chamber .....	7
6.2	Conducted measurements normal and extreme conditions.....	8
7	Sequence of testing .....	9
7.1	Sequence of testing radiated spurious 30 MHz to 1 GHz.....	9
7.2	Sequence of testing radiated spurious 1 GHz to 4 GHz .....	10
8	Measurement uncertainty .....	11
9	Summary of measurement results .....	12
10	Additional comments .....	13
11	Measurement results .....	14
11.1	Transmitter output power .....	14
11.2	Occupied bandwidth.....	16
11.3	Transmitter frequency stability .....	20
11.4	Transmitter unwanted emissions (radiated) .....	22
11.5	Necessary bandwidth (BN) for analogue systems .....	30
11.6	Frequency modulation .....	36
12	Observations .....	40
Annex A	Glossary.....	41
Annex B	Document history .....	42
Annex C	Accreditation Certificate .....	42

## 2 General information

### 2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. CTC advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CTC advanced GmbH.

The testing service provided by CTC advanced GmbH has been rendered under the current "General Terms and Conditions for CTC advanced GmbH".

CTC advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CTC advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CTC advanced GmbH test report include or imply any product or service warranties from CTC advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CTC advanced GmbH.

All rights and remedies regarding vendor's products and services for which CTC advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by CTC advanced GmbH. In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

**This test report replaces the test report with the number 1-4465/17-02-27-A and dated 2018-07-10.**

### 2.2 Application details

Date of receipt of order:	2017-11-07
Date of receipt of test item:	2018-02-05
Start of test:	2018-02-06
End of test:	2018-06-20
Person(s) present during the test:	-/-

### 2.3 Test laboratories sub-contracted

None

### 3 Test standard/s and references

Test standard	Date	Description
47 CFR Part 15	-/-	Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices
RSS - 210 Issue 9	August 2016	Spectrum Management and Telecommunications Radio Standards Specification - Licence-Exempt Radio Apparatus: Category I Equipment
RSS - Gen Issue 5	April 2018	General Requirements for Compliance of Radio
ETSI EN 300 422-1 V1.4.2	2011-08	Electromagnetic compatibility and Radio spectrum Matters (ERM); Wireless microphones in the 25 MHz to 3 GHz frequency range; Part 1: Technical characteristics and methods of measurement
ETSI EN 300 422-2 V1.3.1	2011-08	Electromagnetic compatibility and Radio spectrum Matters (ERM); Wireless microphones in the 25 MHz to 3 GHz frequency range; Part 2: Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive
Guidance	Version	Description
ANSI C63.4-2014	-/-	American national standard for methods of measurement of radio-noise emissions from low-voltage electrical and electronic equipment in the range of 9 kHz to 40 GHz

## 4 Test environment

Temperature	:	$T_{nom}$ $T_{max}$ $T_{min}$	+22 °C during room temperature tests +45 °C during high temperature tests -10 °C during low temperature tests
Relative humidity content	:		55 %
Barometric pressure	:		1021 hpa
Power supply	:	$V_{nom}$ $V_{max}$ $V_{min}$	3.0 V DC by 2 x AA batteries 3.0 V 2.4 V

## 5 Test item

### 5.1 General description

Kind of test item	:	Body Pack Transmitter
Type identification	:	ATW-T5201EF2
HMN	:	-/-
PMN	:	ATW-T5201
HVIN	:	ATW-T5201EF2
FVIN	:	-/-
S/N serial number	:	-/-
HW hardware status	:	-/-
SW software status	:	-/-
Frequency band	:	EF2: 580.000 MHz – 607.875 MHz; 657.100 MHz – 662.900 MHz
Type of radio transmission	:	Modulated carrier
Use of frequency spectrum	:	
Type of modulation	:	FM (F3M)
Channel spacing	:	EF2: 25 kHz
Antenna	:	Whip antenna (with SMA connector)
Power supply	:	2.4 V to 3.0 V DC by 2 x AA batteries
Temperature range	:	-10°C to +45°C

### 5.2 Additional information

The content of the following annexes is defined in the QA. It may be that not all of the listed annexes are necessary for this report, thus some values in between may be missing.

Test setup- and EUT-photos are included in test report:

- 1-4465/17-02-05\_AnnexA
- 1-4465/17-02-05\_AnnexB
- 1-4465/17-02-05\_AnnexC

## 6 Description of the test setup


Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, RF generating and signaling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).

In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).

**Agenda:** Kind of Calibration

k	calibration / calibrated	EK	limited calibration
ne	not required (k, ev, izw, zw not required)	zw	cyclical maintenance (external cyclical maintenance)
ev	periodic self verification	izw	internal cyclical maintenance
Ve	long-term stability recognized	g	blocked for accredited testing
vlk!	Attention: extended calibration interval		
NK!	Attention: not calibrated	*)	next calibration ordered / currently in progress

## 6.1 Shielded fully anechoic chamber



Measurement distance: tri-log antenna and horn antenna 3 meter

$$OP = AV + D - G + CA$$

(OP-radiated output power; AV-analyzer value; D-free field attenuation of measurement distance; G-antenna gain+amplifier gain; CA-loss signal path)


Example calculation:

$$OP \text{ [dBm]} = -65.0 \text{ [dBm]} + 50 \text{ [dB]} - 20 \text{ [dBi]} + 5 \text{ [dB]} = -30 \text{ [dBm]} \text{ (1 } \mu\text{W)}$$

**Equipment table:**

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A, B	Anechoic chamber	FAC 3/5m	MWB / TDK	87400/02	300000996	ev	-/-	-/-
2	B	Double-Ridged Waveguide Horn Antenna 1-18.0GHz	3115	EMCO	9107-3697	300001605	vKI!	14.02.2017	13.02.2019
3	A, B	Switch / Control Unit	3488A	HP	-/-	300000199	ne	-/-	-/-
4	B	Highpass Filter	WHK1.1/15G-10SS	Wainwright	3	300003255	ev	-/-	-/-
5	A	TRILOG Broadband Test-Antenna	VULB9163	Schwarzbeck Mess Elektronik	01029	300005379	k	07.04.2017	06.04.2020
6	B	Broadband Amplifier 0.5-18 GHz	CBLU5184540	CERNEX	22049	300004481	ev	-/-	-/-
7	A, B	4U RF Switch Platform	L4491A	Agilent Technologies	MY50000037	300004509	ne	-/-	-/-
8	A, B	NEXIO EMV-Software	BAT EMC V3.16.0.49	EMCO	-/-	300004682	ne	-/-	-/-
9	A, B	PC	ExOne	F+W	-/-	300004703	ne	-/-	-/-

## 6.2 Conducted measurements normal and extreme conditions



OP = AV + CA  
(OP-output power; AV-analyzer value; CA-loss signal path)

Example calculation:

OP [dBm] = 6.0 [dBm] + 11.7 [dB] = 17.7 [dBm] (58.88 mW)

### Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A	Power Supply 0-20V; 0-5A	6632B	HP	US37478366	400000117	vKI!	25.01.2017	24.01.2019
2	A, B	Signal- and Spectrum Analyzer	FSW26	R&S	101455	300004528	k	20.12.2017	19.12.2018
3	A	Climatic Box	VT 4011	Voetsch Industrietechnik	58566230600010	300005363	ev	01.06.2017	31.05.2019
4	B	Audio Analyzer 2Hz - 300 kHz	UPD	R&S	841074/009	300001236	k	02.02.2016	02.02.2018
5	B	Radiocom. Analyzer	CMTA 84	R&S	894199/012	300001176	vKI!	07.03.2016	07.03.2018



## 7 Sequence of testing

### 7.1 Sequence of testing radiated spurious 30 MHz to 1 GHz

#### Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

#### Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

#### Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position  $\pm 45^\circ$  and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

## 7.2 Sequence of testing radiated spurious 1 GHz to 4 GHz

### Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

### Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height is 1.5 m.
- At each turntable position and antenna polarization the analyzer sweeps with positive peak detector to find the maximum of all emissions.

### Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximizes the peaks by rotating the turntable from 0° to 360°. This measurement is repeated for different EUT-table positions (0° to 150° in 30°-steps) and for both antenna polarizations.
- The final measurement is done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

## 8 Measurement uncertainty

Measurement uncertainty	
Test case	Uncertainty
Transmitter output power	± 3 dB
Occupied bandwidth	± 3 kHz to 10 kHz (depends on the used RBW)
Transmitter frequency stability	± 1 Hz to 1 kHz (depends on the used RBW)
Transmitter unwanted emissions (radiated or conducted)	Radiated: ± 3 dB Conducted: ± 0.5 dB
Modulation characteristics	-/-
Necessary bandwidth (BN) for analogue systems	± 1 kHz (depends on the used RBW)
Frequency modulation	± 3 kHz (depends on the used RBW)
Spurious emissions conducted below 30 MHz (AC conducted)	± 2.6 dB

## 9 Summary of measurement results

<input checked="" type="checkbox"/>	No deviations from the technical specifications were ascertained
<input type="checkbox"/>	There were deviations from the technical specifications ascertained
<input type="checkbox"/>	This test report is only a partial test report. The content and verdict of the performed test cases are listed below.

TC Identifier	Description	Verdict	Date	Remark
RF-Testing	FCC Part 15 RSS - 210 Issue 9 RSS - Gen Issue 5	See table!	2018-07-16	-/-

Test specification clause	Test case	Temperature conditions	Voltage conditions	C	NC	NA	NP	Remark
FCC Part 15.236 (d)(1) FCC Part 15.236 (d)(2) RSS-210 – G.3.1 RSS-Gen	Transmitter output power	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
FCC Part 15.236 (f)(2) RSS-210 – G.3.2 RSS-Gen	Occupied bandwidth	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
FCC Part 15.236 (f)(3) RSS-210 – G.3.3 RSS-Gen	Transmitter frequency stability	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
		Extreme	Extreme	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
FCC Part 15.236 (g) RSS-210 – G.3.4	Transmitter unwanted emissions (radiated or conducted)	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
FCC Part 15.236 (g)	Necessary bandwidth (BN) for analogue systems	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
RSS-210 – G.3.5.2	Frequency modulation	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
FCC Part 15.236 (g) RSS-210 – G.3.4	Receiver spurious emissions	Nominal	Nominal	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	No receiver integrated!
FCC Part 15.107(a) FCC Part 15.207	Conducted emissions < 30 MHz	Nominal	Nominal	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	-/-

**Note:** C = Compliant; NC = Not compliant; NA = Not applicable; NP = Not performed

## 10 Additional comments

Reference documents: None

Special test descriptions: None

Configuration descriptions: None

Test mode:  No test mode available.  
Test signal is applied to the transmitter.

Special software is used.  
EUT is transmitting pseudo random data by itself

Antennas and transmit operating modes:  Operating mode 1 (single antenna)

- *Equipment with 1 antenna,*
- *Equipment with 2 diversity antennas operating in switched diversity mode by which at any moment in time only 1 antenna is used,*
- *Smart antenna system with 2 or more transmit/receive chains, but operating in a mode where only 1 transmit/receive chain is used)*

Operating mode 2 (multiple antennas, no beamforming)

- *Equipment operating in this mode contains a smart antenna system using two or more transmit/receive chains simultaneously but without beamforming.*

Operating mode 3 (multiple antennas, with beamforming)

- *Equipment operating in this mode contains a smart antenna system using two or more transmit/receive chains simultaneously with beamforming. In addition to the antenna assembly gain (G), the beamforming gain (Y) may have to be taken into account when performing the measurements.*

## 11 Measurement results

### 11.1 Transmitter output power

**Measurement:**

Measurement parameter	
Detector:	Peak (worst case) / Average (RMS)
Sweep time:	Auto / 20s
Resolution bandwidth:	> emission bandwidth
Video bandwidth:	> resolution bandwidth
Span:	> 2 times emissions bandwidth
Trace mode:	Max. hold
EUT configuration:	Peak: Unmodulated carrier  RMS: Modulate the transmitter with a 2.5 kHz tone at a level 16 dB higher than that required to produce a frequency deviation of $\pm 75$ kHz, or to produce 50% of the manufacturer's rated deviation, whichever is less.
Test setup:	See sub clause 6.2 – A
Measurement uncertainty:	See sub clause 8

**Limits:**

Frequency range	FCC	
470 MHz to 608 MHz	FCC Part 15.236(d)(1)	50 mW EIRP (17 dBm EIRP)
657 MHz to 663 MHz	FCC Part 15.236(d)(2)	20 mW EIRP (13 dBm EIRP)

Frequency range	IC	
470 MHz to 608 MHz	RSS-210 - G.3.1	250 mW EIRP (17 dBm EIRP)
614 MHz to 698 MHz		

**Result:**

Transmitter output power EIRP			
	Channels	Peak	Average
<b>EF2</b>	580.000 MHz	16.42 dBm	16.37 dBm
	594.000 MHz	15.98 dBm	15.93 dBm
	607.875 MHz	16.42 dBm	16.38 dBm
	657.125 MHz	8.31 dBm	8.25 dBm
	662.875 MHz	8.65 dBm	8.59 dBm

## 11.2 Occupied bandwidth

### Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	1 % to 5 % of the occupied bandwidth
Video bandwidth:	3 x resolution bandwidth
Span:	2 x emission bandwidth
Trace mode:	Max. hold
Analyzer function:	99% power occupied bandwidth function
EUT:	Modulated signal with max. frequency deviation
Test setup:	See sub clause 6.2 - A
Measurement uncertainty:	See sub clause 8

### Limits:

FCC & IC
470 MHz to 608 MHz 200 kHz 614 MHz to 698 MHz 200 kHz
Occupied bandwidth 99%. Other than single sideband or independent sideband transmitters - when modulated by a 2500 Hz tone at an input level 16 dB greater than that necessary to produce 50 percent modulation. The input level shall be established at the frequency of maximum response of the audio modulating circuit.


### Result:

Occupied bandwidth		
Channels		
EF2	580.000 MHz	106.04 kHz
	594.000 MHz	105.62 kHz
	607.875 MHz	106.68 kHz
	657.125 MHz	106.42 kHz
	662.875 MHz	106.12 kHz




**Plots:** EF2 (580 MHz to 608 MHz)


**Plot 1:** 580.000 MHz




**Plot 2:** 594.000 MHz




Plot 3: 607.875 MHz



Plot 4: 657.125 MHz



**Plot 5: 662.875 MHz**



### 11.3 Transmitter frequency stability

**Measurement:**

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	1 Hz / 10 Hz / 100 Hz
Video bandwidth:	3 x resolution bandwidth
Span:	wide enough to follow the frequency drift
Trace mode:	clear/write/view
EUT:	CW signal or MC with measurement method description
Test setup:	See sub clause 6.2 - B
Measurement uncertainty:	See sub clause 8

**Limits:**

FCC & IC	
470 MHz to 608 MHz	± 50 ppm
614 MHz to 698 MHz	± 50 ppm

**Results:**

Temperature / Voltage	580 MHz		594.000 MHz		607.875 MHz	
	Frequency (MHz)	Deviation (kHz / ppm)	Frequency (MHz)	Deviation (kHz / ppm)	Frequency (MHz)	Deviation (kHz / ppm)
-30 °C / V <sub>nom</sub>	580.00014	0.14 / 0.24	594.00012	0.12 / 0.20	607.87513	0.13 / 0.21
-20 °C / V <sub>nom</sub>	580.00016	0.16 / 0.27	594.00009	0.09 / 0.15	607.87516	0.16 / 0.26
-10 °C / V <sub>nom</sub>	580.00017	0.17 / 0.29	594.00011	0.11 / 0.19	607.87517	0.17 / 0.27
0 °C / V <sub>nom</sub>	580.00001	0.01 / 0.17	594.00004	0.04 / 0.07	607.87503	0.03 / 0.04
+10 °C / V <sub>nom</sub>	579.99997	-0.03 / -0.05	593.99996	-0.01 / -0.07	607.87498	-0.02 / -0.03
+20 °C / V <sub>nom</sub>	579.99992	-0.08 / -0.13	593.99995	-0.05 / -0.08	607.87492	-0.08 / -0.13
+30 °C / V <sub>nom</sub>	579.99994	-0.06 / -0.10	593.99993	-0.07 / -0.12	607.87494	-0.06 / -0.09
+40 °C / V <sub>nom</sub>	579.99993	-0.07 / -0.12	593.99990	-0.10 / -0.17	607.87493	-0.07 / -0.11
+50 °C / V <sub>nom</sub>	579.99989	-0.11 / -0.18	593.99988	-0.12 / -0.20	607.87488	-0.12 / -0.19
+20 °C / V <sub>nom</sub> - 15%	579.99991	-0.09 / -0.15	593.99995	-0.05 / -0.08	607.87493	-0.07 / -0.11
+20 °C / V <sub>nom</sub>	579.99992	-0.08 / -0.13	593.99995	-0.05 / -0.08	607.87492	-0.08 / -0.13
+20 °C / V <sub>nom</sub> + 15%	579.99993	-0.07 / -0.12	593.99994	-0.06 / -0.10	607.87492	-0.08 / -0.13

Temperature / Voltage	657.125 MHz		662.875 MHz	
	Frequency (MHz)	Deviation (kHz / ppm)	Frequency (MHz)	Deviation (kHz / ppm)
-30 °C / V <sub>nom</sub>	657.12515	0.15 / 0.22	662.87512	0.12 / 0.18
-20 °C / V <sub>nom</sub>	657.12517	0.17 / 0.25	662.87515	0.15 / 0.22
-10 °C / V <sub>nom</sub>	657.12501	0.01 / 0.01	662.87519	0.19 / 0.28
0 °C / V <sub>nom</sub>	657.12504	0.04 / 0.06	662.87506	0.06 / 0.09
+10 °C / V <sub>nom</sub>	657.12489	-0.11 / -0.16	662.87496	-0.04 / -0.06
+20 °C / V <sub>nom</sub>	657.12494	-0.06 / -0.09	662.87492	-0.08 / -0.12
+30 °C / V <sub>nom</sub>	657.12494	-0.06 / -0.09	662.87489	-0.11 / -0.16
+40 °C / V <sub>nom</sub>	657.12493	-0.07 / -0.10	662.87492	-0.08 / -0.12
+50 °C / V <sub>nom</sub>	657.12488	-0.12 / -0.18	662.87482	-0.18 / -0.27
+20 °C / V <sub>nom</sub> - 15%	657.12491	-0.09 / -0.13	662.87495	-0.05 / -0.07
+20 °C / V <sub>nom</sub>	657.12494	-0.06 / -0.09	662.87492	-0.08 / -0.12
+20 °C / V <sub>nom</sub> + 15%	657.12493	-0.07 / -0.10	662.87496	-0.04 / -0.06

## 11.4 Transmitter unwanted emissions (radiated)

### Measurement:

Measurement parameter	
Detector:	Peak (prescan) / RMS
Sweep time:	Auto
Resolution bandwidth:	See table below!
Video bandwidth:	See table below!
Span:	100 MHz steps!
Trace-Mode:	Max. hold
EUT:	MC with max frequency deviation
Used equipment:	See chapter 6.1- A / B
Measurement uncertainty:	See chapter 8

Frequency being measured	Measuring receiver bandwidth
25 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1 000 MHz	100 kHz
> 1 000 MHz	1 MHz

### Limits:

FCC & IC (see also ETSI EN 300 422-1 V1.4.2)			
State	Max. spurious level		
	47 MHz to 74 MHz 87.5 MHz to 118 MHz 174 MHz to 230 MHz 470 MHz to 862 MHz	Other frequencies ≤ 1000 MHz	All frequencies > 1000 MHz
Operating	4.0 nW	250 nW	1.00 µW
Standby	2.0 nW	2.0 nW	20.0 nW


FCC & IC	
The mean power of emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:	
On any frequency removed from the operating frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth: at least	25 dB
On any frequency removed from the operating frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth	35 dB
On any frequency removed from the operating frequency by more than 250 percent of the authorized bandwidth: at least	43 + 10log <sub>10</sub> (mean output power in watts) dB

**Results:**


carrier frequency (MHz)	unwanted emission frequency (MHz)	Limit	level (dB) / (dBm) or remark
580.000	1160	-30 dBm	-36.65 (RMS)
607.875	1823	-30 dBm	-36.39 (RMS)

**Plots:** radiated

**Plot 1:** 580.000 MHz, spurious emissions, 25 MHz – 4 GHz




**Plot 2:** 594.000 MHz, spurious emissions, 25 MHz – 4 GHz







Plot 3: 607.875 MHz, spurious emissions, 25 MHz – 4 GHz



Plot 4: 657.125 MHz, spurious emissions, 25 MHz – 4 GHz




**Plot 5:** 662.875 MHz, spurious emissions, 25 MHz – 4 GHz




**Plots:** conducted


**Plot 1:** 580.000 MHz, spectrum mask




**Plot 2:** 594.000 MHz, spectrum mask




Plot 3: 607.875 MHz, spectrum mask



Plot 4: 657.125 MHz, spectrum mask



Plot 5: 662.875 MHz, spectrum mask




### 11.5 Necessary bandwidth (BN) for analogue systems

**Measurement:**


Measurement parameter	
Detector:	Peak / Average (-90 dBc point only)
Sweep time:	Auto
Resolution bandwidth:	1 kHz
Video bandwidth:	1 kHz
Span:	$f_c - 1 \text{ MHz}$ to $f_c + 1 \text{ MHz}$ (2 MHz)
Trace mode:	Max hold/view
EUT:	CW and MC
Test setup:	See sub clause 6.2 - B
Measurement uncertainty:	See sub clause 8

**Limits:**




**Plots:** 580.000

**Plot 1:** Unmodulated carrier reference (with pilot-tone)




**Plot 2:** Modulated carrier with the weighted noise source




**Plots:** 594.000 MHz

**Plot 1:** Unmodulated carrier reference (with pilot-tone)




**Plot 2:** Modulated carrier with the weighted noise source






**Plots:** 607.875 MHz

**Plot 1:** Unmodulated carrier reference (with pilot-tone)




**Plot 2:** Modulated carrier with the weighted noise source




**Plots:** 657.125

**Plot 1:** Unmodulated carrier reference (with pilot-tone)




**Plot 2:** Modulated carrier with the weighted noise source




**Plots:** 662.875

**Plot 1:** Unmodulated carrier reference (with pilot-tone)



**Plot 2:** Modulated carrier with the weighted noise source



## 11.6 Frequency modulation

### Measurement:


Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	1 % to 5 % of the occupied bandwidth
Video bandwidth:	3 x resolution bandwidth
Span:	2 x emission bandwidth
Trace mode:	Max. hold
Analyzer function:	99% power occupied bandwidth function
EUT:	Modulated signal with frequency varied between 50 Hz and 15 kHz
Test setup:	See sub clause 6.2 - B
Measurement uncertainty:	See sub clause 8

### Limits:


IC
Frequency deviation up to a maximum of $\pm 75$ kHz

**Plots:** EF2 (580 MHz to 608 MHz)


**Plot 1:** 580.000 MHz, max hold with frequency variation from 50 Hz to 15 kHz




**Plot 2:** 594.000 MHz, max hold with frequency variation from 50 Hz to 15 kHz




**Plot 3:** 607.875 MHz, max hold with frequency variation from 50 Hz to 15 kHz



**Plot 4:** 657.125 MHz, max hold with frequency variation from 50 Hz to 15 kHz



**Plot 5:** 662.825 MHz, max hold with frequency variation from 50 Hz to 15 kHz



## 12 Observations

No observations except those reported with the single test cases have been made.



## Annex A Glossary

<b>EUT</b>	Equipment under test
<b>DUT</b>	Device under test
<b>UUT</b>	Unit under test
<b>GUE</b>	GNSS User Equipment
<b>ETSI</b>	European Telecommunications Standards Institute
<b>EN</b>	European Standard
<b>FCC</b>	Federal Communications Commission
<b>FCC ID</b>	Company Identifier at FCC
<b>IC</b>	Industry Canada
<b>PMN</b>	Product marketing name
<b>HMN</b>	Host marketing name
<b>HVIN</b>	Hardware version identification number
<b>FVIN</b>	Firmware version identification number
<b>EMC</b>	Electromagnetic Compatibility
<b>HW</b>	Hardware
<b>SW</b>	Software
<b>Inv. No.</b>	Inventory number
<b>S/N or SN</b>	Serial number
<b>C</b>	Compliant
<b>NC</b>	Not compliant
<b>NA</b>	Not applicable
<b>NP</b>	Not performed
<b>PP</b>	Positive peak
<b>QP</b>	Quasi peak
<b>AVG</b>	Average
<b>OC</b>	Operating channel
<b>OCW</b>	Operating channel bandwidth
<b>OBW</b>	Occupied bandwidth
<b>OOB</b>	Out of band
<b>DFS</b>	Dynamic frequency selection
<b>CAC</b>	Channel availability check
<b>OP</b>	Occupancy period
<b>NOP</b>	Non occupancy period
<b>DC</b>	Duty cycle
<b>PER</b>	Packet error rate
<b>CW</b>	Clean wave
<b>MC</b>	Modulated carrier
<b>WLAN</b>	Wireless local area network
<b>RLAN</b>	Radio local area network
<b>DSSS</b>	Dynamic sequence spread spectrum
<b>OFDM</b>	Orthogonal frequency division multiplexing
<b>FHSS</b>	Frequency hopping spread spectrum
<b>GNSS</b>	Global Navigation Satellite System
<b>C/N<sub>0</sub></b>	Carrier to noise-density ratio, expressed in dB-Hz

**Annex B Document history**

Version	Applied changes	Date of release
-/-	Initial release	2018-07-06
A	Corrected frequency range	2018-07-10
B	Editorial changes	2018-07-16

**Annex C Accreditation Certificate**

first page	last page
 <p>Deutsche Akkreditierungsstelle GmbH</p> <p>Entrusted according to Section 8 subsection 1 AkkStelleG in connection with Section 1 subsection 1 AkkStelleGBV Signatory to the Multilateral Agreements of EA, ILAC and IAF for Mutual Recognition</p> <p><b>Accreditation</b></p> <p>The Deutsche Akkreditierungsstelle GmbH attests that the testing laboratory <b>CTC advanced GmbH</b> Untertürkheimer Straße 6-10, 66117 Saarbrücken</p> <p>is competent under the terms of DIN EN ISO/IEC 17025:2005 to carry out tests in the following fields: <b>Telecommunication</b></p> <p>The accreditation certificate shall only apply in connection with the notice of accreditation of 02.06.2017 with the accreditation number D-PL-12076-01 and is valid until 21.04.2021. It comprises the cover sheet, the reverse side of the cover sheet and the following annex with a total of 43 pages.</p> <p>Registration number of the certificate: D-PL-12076-01-03</p> <p>Frankfurt, 02.06.2017</p> <p>Dipl.-Ing. (FH) Ralf Zierer Head of Division</p>	 <p>Deutsche Akkreditierungsstelle GmbH</p> <p>Office Berlin Spittelmarkt 10 10117 Berlin</p> <p>Office Frankfurt am Main Europa-Allee 52 60327 Frankfurt am Main</p> <p>Office Braunschweig Bundesallee 100 38116 Braunschweig</p> <p>The publication of extracts of the accreditation certificate is subject to the prior written approval by Deutsche Akkreditierungsstelle GmbH (DAkkS). Exempted is the unchanged form of separate disseminations of the cover sheet by the conformity assessment body mentioned overleaf.</p> <p>No impression shall be made that the accreditation also extends to fields beyond the scope of accreditation attested by DAkkS.</p> <p>The accreditation was granted pursuant to the Act on the Accreditation Body (AkkStelleG) of 31 July 2009 (Federal Law Gazette I p. 2625) and the Regulation (EC) No 765/2008 of the European Parliament and of the Council of 9 July 2008 setting out the requirements for accreditation and market surveillance relating to the marketing of products (Official Journal of the European Union L 218 of 9 July 2008, p. 30). DAkkS is a signatory to the Multilateral Agreements for Mutual Recognition of the European co-operation for Accreditation (EA), International Accreditation Forum (IAF) and International Laboratory Accreditation Cooperation (ILAC). The signatories to these agreements recognise each other's accreditations.</p> <p>The up-to-date state of membership can be retrieved from the following websites: EA: <a href="http://www.european-accreditation.org">www.european-accreditation.org</a> ILAC: <a href="http://www.ilac.org">www.ilac.org</a> IAF: <a href="http://www.laf.nu">www.laf.nu</a></p>

**Note: The current certificate annex is published on the website (link see below) of the Accreditation Body DAkkS or may be received by CTC advanced GmbH on request**

<https://www.dakks.de/as/ast/d/D-PL-12076-01-03e.pdf>