

## FCC RADIO TEST REPORT

Applicant's company	SMC Networks, Inc.
Applicant Address	20 Mason, Irvine, California 92618 United States
FCC ID	J15-RB6741
Manufacturer's company	Accton Technology Corporation
Manufacturer Address	#1, Creation Rd. III, Science-Based Industrial Park, Hsinchu, Taiwan, R.O.C

Product Name	Aegis 3G
Brand Name	SMC
Model Name	RB6741-Z
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2405~ 2475MHz
Received Date	Oct. 08, 2012
Final Test Date	Dec. 20, 2012
Submission Type	Original Equipment



### Statement

**Test result included is only for the IEEE 802.15.4 ZigBee part of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009, 47 CFR FCC Part 15 Subpart C** and **KDB 558074 D01 v02**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.

## Table of Contents

<b>1. CERTIFICATE OF COMPLIANCE .....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION .....</b>	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	3
3.3. Table for Filed Antenna.....	4
3.4. Table for Carrier Frequencies .....	4
3.5. Table for Test Modes .....	5
3.6. Table for Testing Locations.....	6
3.7. Table for Supporting Units .....	6
3.8. Table for Parameters of Test Software Setting .....	7
3.9. Test Configurations .....	8
<b>4. TEST RESULT .....</b>	<b>11</b>
4.1. AC Power Line Conducted Emissions Measurement.....	11
4.2. Maximum Conducted Output Power Measurement.....	15
4.3. Power Spectral Density Measurement .....	17
4.4. 6dB Spectrum Bandwidth Measurement .....	21
4.5. Radiated Emissions Measurement .....	24
4.6. Band Edge Emissions Measurement .....	33
4.7. Antenna Requirements .....	37
<b>5. LIST OF MEASURING EQUIPMENTS .....</b>	<b>38</b>
<b>6. TEST LOCATION.....</b>	<b>40</b>
<b>7. TAF CERTIFICATE OF ACCREDITATION .....</b>	<b>41</b>
<b>APPENDIX A. TEST PHOTOS .....</b>	<b>A1 ~ A5</b>
<b>APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>B1 ~ B3</b>
<b>APPENDIX C. CO-LOCATION REPORTT .....</b>	<b>C1 ~ C3</b>


## History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR2N2120	Rev. 01	Initial issue of report	Jan. 03, 2013

## 1. CERTIFICATE OF COMPLIANCE

Product Name : Aegis 3G  
Brand Name : SMC  
Model Name : RB6741-Z  
Applicant : SMC Networks, Inc.  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Oct. 08, 2012 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

  
\_\_\_\_\_  
Jordan Hsiao  
SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	11.03 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	8.06 dB
4.3	15.247(e)	Power Spectral Density	Complies	9.62 dB
4.5	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.6	15.247(d)	Radiated Emissions	Complies	1.18 dB
4.7	15.247(d)	Band Edge Emissions	Complies	0.21 dB
4.8	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 <sup>-8</sup>	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

### 3. GENERAL INFORMATION

#### 3.1. Product Details


Items	Description
Power Type	From Power Adapter and Battery
Modulation	DSSS (QPSK)
Data Rate (Mbps)	DSSS (250kbps)
Frequency Range	2405~ 2475MHz
Channel Number	15
Channel Band Width (99%)	2.42 MHz
Maximum Conducted Output Power	21.94 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3
3G Module	Got the Certificate, the FCC ID and IC ID as below: FCC ID: QISMU509C IC: 6369A-MU509C
WiFi Module	Got the Certificate, the FCC ID as below: FCC ID: HED7822GMN

#### 3.2. Accessories

Power	Brand	Model	Rating
Adapter 1	Sunny	SYS1428-1505-W2	INPUT: 100-240V~1.0A MAX, 50-60Hz OUTPUT: 5V, 3A, 15W MAX.
Adapter 2	ADAPTER TECH.	STD-05030U	INPUT: 100-240V~47-63Hz, 0.48A MAX OUTPUT: 5V, 3A 15W MAX
Battery 1	GETAC	541385120001	Output: 3.7Vdc, 5300mAh, 19.61Wh

### 3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	MAGIC	102700000010A	Chip Antenna	NA	3.2



### 3.4. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2405 ~ 2475MHz	11	2405 MHz	19	2445 MHz
	12	2410 MHz	20	2450 MHz
	13	2415 MHz	21	2455 MHz
	14	2420 MHz	22	2460 MHz
	15	2425 MHz	23	2465 MHz
	16	2430 MHz	24	2470 MHz
	17	2435 MHz	25	2475 MHz
	18	2440 MHz	-	-



### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	TX Mode	250 kbps	11/18/25	1
Power Spectral Density 6dB Spectrum Bandwidth	TX Mode	250 kbps	11/18/25	1
Radiated Emissions 9kHz~1GHz	Normal Link	-	-	-
Radiated Emissions 1GHz~10 <sup>th</sup> Harmonic	TX Mode	250 kbps	11/18/25	1
Band Edge Emissions	TX Mode	250 kbps	11/18/25	1

The following test modes were performed for all tests:

#### <For Conducted emission test>:

Due to Mode 3 generated the worst test result for Radiated emission below 1 GHz test, it was selected to do Conducted Emission test.

Mode 1: Upstanding EUT + USB + SD + ZigBee + Wifi + 3G + Adapter 1(SYS1428-1505-W2)

Mode 2: Upstanding EUT + USB + SD + ZigBee + Ethernet + 3G + Adapter 1(SYS1428-1505-W2)

Mode 1 generated the worst test result for Mode 1 ~ 2, thus measurement will follow this same test mode for Mode 3.

Mode 3: Upstanding EUT + USB + SD + ZigBee + Wifi + 3G + Adapter 2(STD-05030U)

Among Mode 1 ~ 3, Mode 3 was generated the worst test result, it was recorded in this report.

#### <For Radiated emission below 1 GHz test>:

Mode 1: Lying EUT + USB + SD + ZigBee + Wifi + 3G + Adapter 1(SYS1428-1505-W2)

Mode 2: Upstanding EUT + USB + SD + ZigBee + Wifi + 3G + Adapter 1(SYS1428-1505-W2)

Mode 2 generated the worst test result for Mode 1 ~ 2, thus measurement will follow this same test mode for Mode 3.

Mode 3: Upstanding EUT + USB + SD + ZigBee + Ethernet + 3G + Adapter 1(SYS1428-1505-W2)

Mode 3 generated the worst test result for Mode 1 ~ 3, thus measurement will follow this same test mode for Mode 4.

Mode 4: Upstanding EUT + USB + SD + ZigBee + Ethernet + 3G + Adapter 2(STD-05030U)

Among Mode 1 ~ 4, Mode 3 was generated the worst test result, it was recorded in this report.

#### < For Radiated emission above 1 GHz test>:

Mode 1: Lying EUT

Mode 2: Upstanding EUT

Due to Mode 2 generated the worst test result, it was recorded in this report.



#### <For MPE and Co-location Test>:

The EUT could be applied with WiFi + ZigBee + 3G function; therefore Maximum Permissible Exposure (Please refer to Appendix B) and Co-location (please refer to Appendix C) tests are added for simultaneously transmit between WiFi + ZigBee + 3G function.

### 3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	187376	IC 4086D
CO01-CB	Conduction	Hsin Chu	187376	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

### 3.7. Table for Supporting Units

#### For Conducted Emission test:

Support Unit	Brand	Model	FCC ID
Earphone	SHYARO CHI	MIC-04	N/A
Flash Disk	Silicon	D33B01	DoC
Wireless AP	BELKIN	WG7016G22-LF-AK	DoC
3G Base station	R&S	CMU 200	N/A
Notebook	DELL	P15F	E2K-P15F001(B)
SD Card	N/A	N/A	N/A
Zigbee	N/A	N/A	N/A

#### For Radiated Emission test:

Support Unit	Brand	Model	FCC ID
Flash Disk	Silicon	D33B01	DoC
Wireless AP	BELKIN	WG7016G22-LF-AK	DoC
3G Base station	R&S	CMU 200	N/A
SD Card	N/A	N/A	N/A
Earphone	E-Books	E-EPC040	N/A
Zigbee	N/A	N/A	N/A
Notebook	DELL	M1330	E2KWM3945ABG

### 3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### Power Parameters of IEEE 802.15.4 ZigBee

Test Software Version	Hyper Terminal		
Frequency	2405 MHz	2440 MHz	2475 MHz
IEEE 802.15.4 ZigBee	0	-4	-6


Executed "Hyper Terminal" was executed the test program to control the EUT continuously transmit RF signal.

### 3.9. Test Configurations

#### 3.9.1. Radiation Emissions Test Configuration


Test Configuration: 30MHz~1GHz

Test Mode: Mode 3



Item	Connection	Shield	Length
1	Power Cable	No	1.8m
2	Ant. Cable	No	10m
3	Audio Cable	No	1m
4	RJ-45 Cable	No	10m


Test Configuration: Above 1GHz



Item	Connection	Shield	Length
1	Power Cable	No	1.8m

### 3.9.2. AC Power Line Conduction Emissions Test Configuration

Test Mode: Mode 1



Item	Connection	Shield	Length
1	Power Cable	No	1.9m
2	RJ-45 Cable	No	1m
3	Audio Cable	No	1m
4	Ant. Cable	No	1m

## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For a Low-power Radio-frequency Device which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

#### 4.1.4. Test Setup Layout



#### LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50  $\Omega$ . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

#### 4.1.5. Test Deviation

There is no deviation with the original standard.


#### 4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.




#### 4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	25°C	Humidity	58%
Test Engineer	Sollo Luo	Phase	Line
Configuration	Normal Link / Mode 1		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.15080	50.44	-15.52	65.96	50.28	0.16	0.00	LINE	QP
2	0.15080	39.21	-16.75	55.96	39.05	0.16	0.00	LINE	AVERAGE
3	0.15900	52.97	-12.55	65.52	52.81	0.16	0.00	LINE	QP
4	0.15900	36.76	-18.76	55.52	36.60	0.16	0.00	LINE	AVERAGE
5	0.16589	30.20	-24.96	55.16	30.04	0.16	0.00	LINE	AVERAGE
6	0.16589	50.23	-14.93	65.16	50.07	0.16	0.00	LINE	QP
7	0.18056	31.00	-23.46	54.46	30.85	0.15	0.00	LINE	AVERAGE
8	0.18056	52.79	-11.67	64.46	52.64	0.15	0.00	LINE	QP
9	0.19447	50.39	-13.45	63.84	50.24	0.15	0.00	LINE	QP
10	0.19447	31.68	-22.16	53.84	31.53	0.15	0.00	LINE	AVERAGE
11	0.21620	48.71	-14.25	62.96	48.56	0.15	0.00	LINE	QP
12	0.21620	25.76	-27.20	52.96	25.61	0.15	0.00	LINE	AVERAGE

Temperature	25°C	Humidity	58%
Test Engineer	Sollo Luo	Phase	Neutral
Configuration	Normal Link / Mode 1		



	Freq	Level	Over	Limit	Read	LISN	Cable		
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Pol/Phase	Remark
			dB	dBuV	dBuV	dB	dB		
1	0.15900	53.91	-11.61	65.52	53.83	0.08	0.00	NEUTRAL	QP
2	0.15900	20.08	-35.44	55.52	20.00	0.08	0.00	NEUTRAL	AVERAGE
3	0.17584	53.65	-11.03	64.68	53.57	0.08	0.00	NEUTRAL	QP
4	0.17584	19.12	-35.56	54.68	19.04	0.08	0.00	NEUTRAL	AVERAGE
5	0.18938	48.46	-15.60	64.06	48.38	0.08	0.00	NEUTRAL	QP
6	0.18938	26.87	-27.19	54.06	26.79	0.08	0.00	NEUTRAL	AVERAGE
7	0.24037	46.85	-15.23	62.08	46.77	0.08	0.00	NEUTRAL	QP
8	0.24037	24.16	-27.92	52.08	24.08	0.08	0.00	NEUTRAL	AVERAGE
9	0.26583	39.52	-21.73	61.25	39.44	0.08	0.00	NEUTRAL	QP
10	0.26583	29.75	-21.50	51.25	29.67	0.08	0.00	NEUTRAL	AVERAGE
11	0.38724	38.54	-19.58	58.12	38.46	0.08	0.00	NEUTRAL	QP
12	0.38724	21.74	-26.38	48.12	21.66	0.08	0.00	NEUTRAL	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

## 4.2. Maximum Conducted Output Power Measurement

### 4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for Conducted Output Power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Detector	Average

### 4.2.3. Test Procedures

1. Test procedures refer KDB558074 v01 r02 section 8.2.3 option 3.
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of Maximum Conducted Output Power

Temperature	25°C	Humidity	56%
Test Engineer	Denis Su	Configurations	802.15.4 ZigBee
Test Date	Dec. 18, 2012		

#### Configuration IEEE 802.15.4 ZigBee

Channel	Frequency	Total Conducted Power (dBm)	Max. Limit (dBm)	Result
11	2405 MHz	21.94	30.00	Complies
18	2440 MHz	19.51	30.00	Complies
25	2475 MHz	16.98	30.00	Complies

### 4.3. Power Spectral Density Measurement

#### 4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RB	100 kHz
VB	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

#### 4.3.3. Test Procedures

1. Test procedures refer KDB558074 v01 r02 section 9.1 option 1
2. Spectrum analyzer must be capable of utilizing a number of measurement points in each sweep that is greater than or equal to twice the span/RBW in order to ensure bin-to-bin spacing of  $\leq RBW/2$  so that narrowband signals are not lost between frequency bins.
3. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
4. Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$  (use of a greater number of measurement points than this minimum requirement is recommended).
5. Use the peak marker function to determine the maximum level in any 100 kHz band segment within the fundamental EBW.
6. Scale the observed power level to an equivalent level in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where:  $BWCF = 10\log(3 \text{ kHz}/100 \text{ kHz} = -15.2 \text{ dB})$ .
7. The resulting PSD level must be  $\leq 8 \text{ dBm}$ .
8. When measuring power spectral density with multiple antenna systems, add every result of the values by mathematic formula.

#### 4.3.4. Test Setup Layout



#### 4.3.5. Test Deviation

There is no deviation with the original standard.

#### 4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.7. Test Result of Power Spectral Density

Temperature	25°C	Humidity	56%
Test Engineer	Denis Su	Configurations	802.15.4 ZigBee
Test Date	Dec. 18, 2012		

#### Configuration IEEE 802.15.4 ZigBee


Frequency	Power Density (dBm/100kHz)	BWCF factor (100kHz to 3kHz)	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
2405 MHz	18.54	-15.23	3.31	8.00	Complies
2440 MHz	16.13	-15.23	0.90	8.00	Complies
2475 MHz	13.61	-15.23	-1.62	8.00	Complies

Note: All the test values were listed in the report.

For plots, only the channel with maximum results was shown.



### Power Density Plot on Configuration 802.15.4 ZigBee / 2405 MHz



Date: 18.DEC.2012 11:39:26

#### 4.4. 6dB Spectrum Bandwidth Measurement

##### 4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

##### 4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	1-5 % or DTS BW, not exceed 100KHz
VB	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

##### 4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 5.1.1 EBW Measurement Procedure
3. Multiple antenna system was performed in accordance with KDB 662911 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

##### 4.4.4. Test Setup Layout



##### 4.4.5. Test Deviation

There is no deviation with the original standard.

##### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	25°C	Humidity	56%
Test Engineer	Denis Su	Configurations	802.15.4 ZigBee
Test Date	Dec. 18, 2012		


#### Configuration 802.15.4 ZigBee

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
11	2405 MHz	1.56	2.42	500.00	Complies
18	2440 MHz	1.54	2.40	500.00	Complies
25	2475 MHz	1.54	2.36	500.00	Complies

Note: All the test values were listed in the report.

For plots, only the channel with maximum results was shown.

### 6 dB Bandwidth Plot on Configuration 802.15.4 ZigBee / 2405 MHz



## 4.5. Radiated Emissions Measurement

### 4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 3MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

#### 4.5.3. Test Procedures


5. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
6. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
7. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
8. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
9. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
10. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
11. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
12. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
13. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
14. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.5.4. Test Setup Layout

For radiated emissions below 1GHz



For radiated emissions above 1GHz



#### 4.5.5. Test Deviation

There is no deviation with the original standard.

#### 4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



#### 4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	26°C	Humidity	60%
Test Engineer	Satoshi Yang	Test Date	Dec. 19, 2012

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

#### 4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	26°C	Humidity	60%
Test Engineer	Satoshi Yang	Configurations	Normal Link / Mode 3

*Horizontal*



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	94.02	32.71	43.50	-10.79	49.05	1.15	10.14	27.63	400	253	HORIZONTAL Peak
2	183.26	33.70	43.50	-9.80	49.39	1.62	9.87	27.18	300	206	HORIZONTAL Peak
3 !	450.01	41.24	46.00	-4.76	49.44	2.65	17.00	27.85	200	53	HORIZONTAL Peak
4 !	482.99	40.04	46.00	-5.96	47.80	2.73	17.53	28.02	200	33	HORIZONTAL Peak
5	747.80	38.42	46.00	-7.58	42.52	3.52	20.19	27.81	200	206	HORIZONTAL Peak
6 pp	831.22	42.33	46.00	-3.67	45.07	3.75	21.05	27.54	200	206	HORIZONTAL Peak

## Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1 pp	35.82	37.11	40.00	-2.89	47.84	0.70	16.37	27.80	100	158 VERTICAL	QP
2	94.02	37.32	43.50	-6.18	53.66	1.15	10.14	27.63	150	279 VERTICAL	Peak
3 !	183.26	39.08	43.50	-4.42	54.77	1.62	9.87	27.18	150	172 VERTICAL	Peak
4 !	450.01	41.75	46.00	-4.25	49.95	2.65	17.00	27.85	125	26 VERTICAL	Peak
5 pk	482.99	42.11	46.00	-3.89	49.87	2.73	17.53	28.02	150	125 VERTICAL	Peak
6	548.95	37.08	46.00	-8.92	43.48	2.92	18.78	28.10	150	133 VERTICAL	Peak

### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

#### 4.5.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

Temperature	26°C	Humidity	60%
Test Engineer	Satoshi Yang	Configurations	802.15.4 ZigBee CH 11
Test Date	Nov. 28, 2012		

##### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4810.91	49.55	74.00	-24.45	48.28	3.29	33.02	35.04	Peak	100	137	HORIZONTAL
2	4810.98	44.51	54.00	-9.49	43.24	3.29	33.02	35.04	Average	100	137	HORIZONTAL
3	12022.46	59.59	74.00	-14.41	50.63	5.25	38.97	35.26	Peak	160	195	HORIZONTAL
4	12027.76	48.99	54.00	-5.01	40.03	5.25	38.96	35.25	Average	160	195	HORIZONTAL

##### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4808.98	46.01	54.00	-7.99	44.74	3.29	33.02	35.04	Average	100	211	VERTICAL
2	4810.94	53.81	74.00	-20.19	52.54	3.29	33.02	35.04	Peak	100	211	VERTICAL
3	12022.42	62.80	74.00	-11.20	53.84	5.25	38.97	35.26	Peak	100	182	VERTICAL
4	12027.48	52.13	54.00	-1.87	43.16	5.25	38.97	35.25	Average	100	182	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Satoshi Yang	Configurations	802.15.4 ZigBee CH 18
Test Date	Nov. 29, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4880.95	49.17	54.00	-4.83	47.71	3.33	33.16	35.03	Average	180	155	HORIZONTAL
2	4880.95	58.63	74.00	-15.37	57.17	3.33	33.16	35.03	Peak	180	155	HORIZONTAL
3	7321.42	58.53	74.00	-15.47	53.91	4.06	35.96	35.40	Peak	137	186	HORIZONTAL
4	7321.58	48.11	54.00	-5.89	43.49	4.06	35.96	35.40	Average	137	186	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4880.96	44.00	54.00	-10.00	42.54	3.33	33.16	35.03	Average	130	82	VERTICAL
2	4881.05	53.54	74.00	-20.46	52.08	3.33	33.16	35.03	Peak	130	82	VERTICAL
3	7318.31	52.82	54.00	-1.18	48.20	4.06	35.96	35.40	Average	102	148	VERTICAL
4	7318.40	63.22	74.00	-10.78	58.60	4.06	35.96	35.40	Peak	102	148	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Satoshi Yang	Configurations	802.15.4 ZigBee CH 25
Test Date	Nov. 28, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4948.94	40.61	54.00	-13.39	38.95	3.37	33.30	35.01	Average	195	170	HORIZONTAL
2	4950.93	49.97	74.00	-24.03	48.31	3.37	33.30	35.01	Peak	195	170	HORIZONTAL
3	7423.55	52.56	74.00	-21.44	47.73	4.07	36.16	35.40	Peak	162	191	HORIZONTAL
4	7426.31	41.89	54.00	-12.11	37.06	4.07	36.16	35.40	Average	162	191	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4948.97	39.73	54.00	-14.27	38.07	3.37	33.30	35.01	Average	100	315	VERTICAL
2	4949.09	48.05	74.00	-25.95	46.39	3.37	33.30	35.01	Peak	100	315	VERTICAL
3	7426.31	43.06	54.00	-10.94	38.23	4.07	36.16	35.40	Average	161	142	VERTICAL
4	7426.33	53.71	74.00	-20.29	48.88	4.07	36.16	35.40	Peak	161	142	VERTICAL

### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 4.6. Band Edge Emissions Measurement

### 4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz / 300 KHz for Peak

### 4.6.3. Test Procedures

- The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.

### 4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

### 4.6.5. Test Deviation

There is no deviation with the original standard.

### 4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



#### 4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	26°C	Humidity	60%
Test Engineer	Satoshi Yang	Configurations	802.15.4 ZigBee CH 11, 18, 25
Test Date	Nov. 28, 2012		

##### Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2389.60	58.69	74.00	-15.31	28.31	2.21	28.17	0.00	Peak	105	15 VERTICAL
2	2390.00	48.73	54.00	-5.27	18.34	2.22	28.17	0.00	Average	105	15 VERTICAL
3	2404.60	117.17	74.00			2.22	28.21	0.00	Peak	105	15 VERTICAL
4	2405.00	112.57	54.00			2.22	28.21	0.00	Average	105	15 VERTICAL

Item 3, 4 are the fundamental frequency at 2405 MHz.

##### Channel 18

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2389.68	56.29	74.00	-17.71	25.91	2.21	28.17	0.00	Peak	100	282 HORIZONTAL
2	2390.00	45.07	54.00	-8.93	14.68	2.22	28.17	0.00	Average	100	282 HORIZONTAL
3	2439.68	108.44	74.00			2.23	28.29	0.00	Peak	100	282 HORIZONTAL
4	2440.00	103.70	54.00			2.23	28.29	0.00	Average	100	282 HORIZONTAL
5	2483.50	45.50	54.00	-8.50	14.86	2.26	28.38	0.00	Average	100	282 HORIZONTAL
6	2483.50	54.90	74.00	-19.10	24.26	2.26	28.38	0.00	Peak	100	282 HORIZONTAL

Item 3, 4 are the fundamental frequency at 2440 MHz.


##### Channel 25

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2474.60	110.97	74.00			2.26	28.37	0.00	Peak	100	8 VERTICAL
2	2475.00	106.53	54.00			2.26	28.37	0.00	Average	100	8 VERTICAL
3	2483.50	64.34	74.00	-9.66	33.71	2.26	28.37	0.00	Peak	100	8 VERTICAL
4	2483.90	53.79	54.00	-0.21	23.16	2.26	28.37	0.00	Average	100	8 VERTICAL

Item 1, 2 are the fundamental frequency at 2475 MHz.


For Emission not in Restricted Band

### Low Band Edge Plot on Configuration 802.15.4 ZigBee / Reference Level




Date: 18.DEC.2012 11:37:23

### High Band Edge Plot on Configuration 802.15.4 ZigBee / CH 11 (down 30dBc)




Date: 18.DEC.2012 11:45:27

### Low Band Edge Plot on Configuration 802.15.4 ZigBee / CH 18 (down 30dBc)



### High Band Edge Plot on Configuration 802.15.4 ZigBee / CH 25 (down 30dBc)



## **4.7. Antenna Requirements**

### **4.7.1. Limit**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### **4.7.2. Antenna Connector Construction**

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Oct. 23, 2012	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 26, 2012	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9kHz ~ 30MHz	Jun. 22, 2012	Conduction (CO01-CB)
Impulsbegrenzer Pulse Limiter	Rohde&Schwarz	ESH3-Z2	100430	9kHz~30MHz	Feb. 03, 2012	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	0.15MHz~30MHz	Dec. 04, 2012	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Jan. 11, 2012	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 31, 2012	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Nov. 16, 2012	Radiation (05CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 20, 2012	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz ~ 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz ~ 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9KHz~40GHz	Oct. 08, 2012	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 05, 2012	Conducted (TH01-CB)
Signal Generator	R&S	SMR40	100302	10MHz-40GHz	Nov. 27, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Signal generator	R&S	SMU200A	102782	10MHz-40GHz	Sep. 26, 2012	Conducted (TH01-CB)
Horn Antenna	COM-POWER	AH-118	071187	1GHz – 18GHz	May. 09, 2012	Conducted (TH01-CB)
Horn Antenna	COM-POWER	AH-118	071042	1GHz – 18GHz	Dec. 06, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 28, 2012	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 27, 2012	Conducted (TH01-CB)
Mixer	OML	M19HW/A	U91113-1	40 ~ 60 GHz	Mar. 23, 2011*	Radiation (TH01-CB)
Mixer	OML	M15HW/A	V91113-1	50 ~ 75 GHz	Mar. 23, 2011*	Radiation (TH01-CB)
Diplexer	OML	DPL313B	N/A	40~200GHz	N.C.R	Radiation (TH01-CB)
Mixer	OML	M12HW/A	E91113-1	60 ~ 90 GHz	Mar. 23, 2011*	Radiation (TH01-CB)
Mixer	OML	M08HW/A	F91113-1	90 ~ 140 GHz	Mar. 23, 2011*	Radiation (TH01-CB)
Mixer	OML	M05HW/A	G91113-1	140 ~ 220 GHz	N.C.R	Radiation (TH01-CB)
Standard Horn Antenna	Custom Microwave	HO19R	U91113-A	40 ~ 60 GHz	N.C.R	Radiation (TH01-CB)
Standard Horn Antenna	Custom Microwave	HO15R	V91113-A	50 ~ 75 GHz	N.C.R	Radiation (TH01-CB)
Standard Horn Antenna	Custom Microwave	HO12R	E91113-A	60 ~ 90 GHz	N.C.R	Radiation (TH01-CB)
Standard Horn Antenna	Custom Microwave	HO08R	F91113-A	90 ~ 140 GHz	N.C.R	Radiation (TH01-CB)
Standard Horn Antenna	Custom Microwave	HO05R	G91113-A	140 ~ 220 GHz	N.C.R	Radiation (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“ \* ” Calibration Interval of instruments listed above is two year.

N.C.R. means Non-Calibration required.

## 6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-091230

財團法人全國認證基金會  
Taiwan Accreditation Foundation

### Certificate of Accreditation

This is to certify that

**Sporton International Inc.**  
**EMC & Wireless Communications Laboratory**  
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,  
Taiwan, R.O.C.

**is accredited in respect of laboratory**

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2010 to January 09, 2013
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities



Jay-San Chen  
President, Taiwan Accreditation Foundation  
Date : December 30, 2009

P1, total 22 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix