



**FCC CFR47 PART 15 SUBPART C
CERTIFICATION
TEST REPORT**

FOR

IF / RF REMOTE CONTROL WITH LCD

MODEL NUMBER: AS02230-001

FCC ID: JJ4-DD1

REPORT NUMBER: 06U10212-1

ISSUE DATE: APRIL 13, 2006

Prepared for
GYRATION
12950 SARATOGA AVE.
SARATOGA, CA 95070, USA

Prepared by
COMPLIANCE CERTIFICATION SERVICES
561F MONTEREY ROAD
MORGAN HILL, CA 95037, USA
TEL: (408) 463-0885
FAX: (408) 463-0888

NVLAP[®]
LAB CODE:200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	04/13/06	Initial Issue	D. Garcia

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY.....	5
4.1. <i>MEASURING INSTRUMENT CALIBRATION.....</i>	5
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	5
5. EQUIPMENT UNDER TEST.....	6
5.1. <i>DESCRIPTION OF EUT</i>	6
5.2. <i>MAXIMUM OUTPUT POWER</i>	6
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS.....</i>	6
5.4. <i>SOFTWARE AND FIRMWARE</i>	6
5.5. <i>WORST-CASE CONFIGURATION AND MODE.....</i>	7
5.6. <i>DESCRIPTION OF TEST SETUP</i>	8
6. TEST AND MEASUREMENT EQUIPMENT	10
7. LIMITS AND RESULTS	11
7.1. <i>CHANNEL TESTS FOR THE 2400 TO 2483.5 MHz BAND</i>	11
7.1.1. 6 dB BANDWIDTH	11
7.1.2. 99% BANDWIDTH.....	15
7.1.3. PEAK OUTPUT POWER	19
7.1.4. AVERAGE POWER.....	24
7.1.5. PEAK POWER SPECTRAL DENSITY	25
7.1.6. CONDUCTED SPURIOUS EMISSIONS.....	29
7.2. <i>RADIATED EMISSIONS.....</i>	36
7.2.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS	36
7.2.2. TRANSMITTER ABOVE 1 GHz FOR 2400 TO 2483.5 MHz BAND	39
7.2.3. WORST-CASE RADIATED EMISSIONS BELOW 1 GHz	48
7.3. <i>POWERLINE CONDUCTED EMISSIONS</i>	52
8. SETUP PHOTO	53

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: GYRATION
12950 SARATOGA AVE.
SARATOGA, CA 95070, USA

EUT DESCRIPTION: IF /RF REMOTE CONTROL WITH LCD

MODEL: AS02230-001

SERIAL NUMBER: PROTOTYPE

DATE TESTED: JANUARY 6 to APRIL 11, 2006

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 15 SUBPART C	NO NON-COMPLIANCE NOTED

Compliance Certification Services, Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.


Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document. No part of this report may be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any government agency.

Approved & Released For CCS By:



DAVID GARCIA
EMC SUPERVISOR
COMPLIANCE CERTIFICATION SERVICES

Tested By:



VIEN TRAN
EMC ENGINEER
COMPLIANCE CERTIFICATION SERVICES

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2003, FCC CFR 47 Part 2 and FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 561F Monterey Road, Morgan Hill, California, USA. The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Radiated Emission, 30 to 200 MHz	+/- 3.3 dB
Radiated Emission, 200 to 1000 MHz	+4.5 / -2.9 dB
Radiated Emission, 1000 to 2000 MHz	+4.5 / -2.9 dB
Power Line Conducted Emission	+/- 2.9 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a wireless remote control which uses DSSS and operates in the 2.4 GHz band. It communicates with a USB Transceiver installed in a computer. The remote sends data to the computer via the radio. The transceiver receives data and sends out acknowledgements for the data received and awaits further data from the remote

The EUT is powered by 4 AAA batteries (6VDC).

The radio module is manufactured by CYPRESS.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

2400 to 2483.5 MHz Authorized Band

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402 - 2479	DSSS	-8.07	0.16

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an integral PCB antenna with a maximum gain of 0 dBi.

5.4. SOFTWARE AND FIRMWARE

Operating system: Computer Operation System; Standard Windows XP.

The firmware installed in the EUT during testing was SW02096-001, rev. 001.

5.5. WORST-CASE CONFIGURATION AND MODE

The worst-case channel is determined as the channel with the highest output power, based on the radio test reports for this product. The highest measured output power was at 2402 MHz. The EUT was tested in three orthogonal planes.

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

N/A.


I/O CABLES

N/A.

TEST SETUP

The EUT is a standalone unit powered by 4 AAA batteries (6VDC).

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	Cal Due
EMI Test Receiver	R & S	ESHS 20	827129/006	10/22/2006
Site A Line Stabilizer / Conditioner	Tripplite	LC-1800a	A0051681	CNR
LISN, 10 kHz ~ 30 MHz	FCC	LISN-50/250-25-2	2023	08/30/2006
LISN, 10 kHz ~ 30 MHz	Solar	8012-50-R-24-BNC	8379443	08/30/2006
Spectrum Analyzer	HP	E4446A	US42510266	03/28/2007
Antenna, Horn 1 ~ 18 GHz	EMCO	3115	6717	04/22/2006
Preamplifier, 1 ~ 26 GHz	Miteq	NSP2600-44	646456	08/17/2006
Temperature / Humidity Chamber	Thermotron	SE 600-10-10	29800	05/13/2006
Peak Power Meter	Agilent	E4416A	GB41291160	02/09/2007
Peak / Average Power Sensor	Agilent	E9327A	US40440755	02/10/2007
RF Filter Section	HP	85420E	3705A00256	03/29/2007
Spectrum Analyzer, 26.5 GHz	HP	8593EM	3710A00205	07/26/2006
Antenna, Bilog 30MHz---- 2GHz	Sunol Sciences	JB1	A121003	03/03/2007

7. LIMITS AND RESULTS

7.1. CHANNEL TESTS FOR THE 2400 TO 2483.5 MHz BAND

7.1.1. 6 dB BANDWIDTH

LIMIT

§15.247 (a) (2) For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.


RESULTS


No non-compliance noted:

Channel	Frequency (MHz)	6 dB Bandwidth (kHz)	Minimum Limit (kHz)	Margin (kHz)
Low	2402	600	500	100
Middle	2441	600	500	100
High	2480	600	500	100

6 DB BANDWIDTH







7.1.2. 99% BANDWIDTH

LIMIT

None; for reporting purposes only.

TEST PROCEDURE


The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.


RESULTS


No non-compliance noted:

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.4302
Middle	2441	1.5275
High	2479	1.3127

99% BANDWIDTH







7.1.3. PEAK OUTPUT POWER

PEAK POWER LIMIT

§15.247 (b) The maximum peak output power of the intentional radiator shall not exceed the following:

§15.247 (b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 watt.

§15.247 (b) (4) Except as shown in paragraphs (b)(4) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

§15.247 (b) (4) (i) Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer and the analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99% bandwidth.


RESULTS


The maximum antenna gain is 0 dBi for other than fixed, point-to-point operations, therefore the limit is 30 dBm.


No non-compliance noted:

Channel	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	-8.07	30	-38.07
Middle	2441	-8.37	30	-38.37
High	2479	-9.28	30	-39.28

OUTPUT POWER







7.1.4. AVERAGE POWER

AVERAGE POWER LIMIT

None, for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

No non-compliance noted:

The cable assembly insertion loss of 10.7 dB (including 10 dB pad and 0.7 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	Power (dBm)
Low	2402	-18.06
Middle	2441	-18.34
High	2479	-18.74

7.1.5. PEAK POWER SPECTRAL DENSITY

LIMIT

§15.247 (d) For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer, the maximum level in a 3 kHz bandwidth is measured with the spectrum analyzer using RBW = 3 kHz and VBW > 3 kHz, sweep time = span / 3 kHz, and video averaging is turned off. The PPSD is the highest level found across the emission in any 3 kHz band.


RESULTS


No non-compliance noted:

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	2402	-7.71	8	-15.71
Middle	2441	-8.23	8	-16.23
High	2479	-8.75	8	-16.75

PEAK POWER SPECTRAL DENSITY







7.1.6. CONDUCTED SPURIOUS EMISSIONS

LIMITS

§15.247 (c) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

RESULTS


No non-compliance noted:


SPURIOUS EMISSIONS, LOW CHANNEL







SPURIOUS EMISSIONS, MID CHANNEL





SPURIOUS EMISSIONS, HIGH CHANNEL





7.2. RADIATED EMISSIONS

7.2.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS

LIMITS

§15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

§15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.


For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.


7.2.2. TRANSMITTER ABOVE 1 GHz FOR 2400 TO 2483.5 MHz BAND


RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)







RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)







RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)





RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)






HARMONICS AND SPURIOUS EMISSIONS

04/10/06 High Frequency Measurement Compliance Certification Services, Morgan Hill Open Field Site																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
<p>Test Engineer: Vien Tran Project #: 06U10212 Company: Gyration EUT Description: IF/ RF Remote Control with LCD EUT M/N: AS02230-001 Test Target: FCC Class B Mode Of Operation: Tx Low, Mid & Hi channels</p> <p><u>Test Equipment:</u></p> <table border="1"> <tr> <td>Horn 1-18GHz</td> <td>Pre-amplifier 1-26GHz</td> <td>Pre-amplifier 26-40GHz</td> <td colspan="3">Horn > 18GHz</td> <td>Limit</td> </tr> <tr> <td>T60; S/N: 2238 @3m</td> <td>T145 Agilent 3008A0056</td> <td></td> <td colspan="3"></td> <td>FCC 15.209</td> </tr> <tr> <td colspan="15">Hi Frequency Cables</td> </tr> <tr> <td>2 foot cable</td> <td>3 foot cable</td> <td>12 foot cable</td> <td>HPF</td> <td>Reject Filter</td> <td colspan="10"> <u>Peak Measurements</u> RBW=VBW=1MHz <u>Average Measurements</u> RBW=1MHz ; VBW=10Hz </td> </tr> <tr> <td>Vien 187215002</td> <td>Vien 197209005</td> <td></td> <td>HPF_4.0GHz</td> <td></td> <td colspan="10"></td> </tr> </table> <p><u>Measurement Data:</u></p> <table border="1"> <thead> <tr> <th>f GHz</th> <th>Dist (m)</th> <th>Read Pk dBuV</th> <th>Read Avg. dBuV</th> <th>AF dB/m</th> <th>CL dB</th> <th>Amp dB</th> <th>D Corr dB</th> <th>Fltr dB</th> <th>Peak dBuV/m</th> <th>Avg dBuV/m</th> <th>Pk Lim dBuV/m</th> <th>Avg Lim dBuV/m</th> <th>Pk Mar dB</th> <th>Avg Mar dB</th> <th>Notes (V/H)</th> </tr> </thead> <tbody> <tr> <td colspan="15">LOW CHANNEL 0, 2402 MHz</td> </tr> <tr> <td>4.804</td> <td>3.0</td> <td>63.6</td> <td>35.1</td> <td>33.6</td> <td>2.9</td> <td>-34.8</td> <td>0.0</td> <td>0.6</td> <td>65.8</td> <td>37.3</td> <td>74</td> <td>54</td> <td>-8.2</td> <td>-16.7</td> <td>H</td> </tr> <tr> <td>7.206</td> <td>3.0</td> <td>51.7</td> <td>34.2</td> <td>36.1</td> <td>4.1</td> <td>-34.7</td> <td>0.0</td> <td>0.6</td> <td>57.9</td> <td>40.4</td> <td>74</td> <td>54</td> <td>-16.1</td> <td>-13.6</td> <td>H</td> </tr> <tr> <td>9.608</td> <td>3.0</td> <td>44.0</td> <td>33.1</td> <td>38.0</td> <td>4.7</td> <td>-35.0</td> <td>0.0</td> <td>0.8</td> <td>52.6</td> <td>41.7</td> <td>74</td> <td>54</td> <td>-21.4</td> <td>-12.3</td> <td>H, Noise Floor</td> </tr> <tr> <td>4.804</td> <td>3.0</td> <td>59.3</td> <td>34.5</td> <td>33.6</td> <td>2.9</td> <td>-34.8</td> <td>0.0</td> <td>0.6</td> <td>61.5</td> <td>36.7</td> <td>74</td> <td>54</td> <td>-12.5</td> <td>-17.3</td> <td>H</td> </tr> <tr> <td>7.206</td> <td>3.0</td> <td>54.0</td> <td>33.9</td> <td>36.1</td> <td>4.1</td> <td>-34.7</td> <td>0.0</td> <td>0.6</td> <td>60.2</td> <td>40.1</td> <td>74</td> <td>54</td> <td>-13.8</td> <td>-13.9</td> <td>V</td> </tr> <tr> <td>9.608</td> <td>3.0</td> <td>43.6</td> <td>32.8</td> <td>38.0</td> <td>4.7</td> <td>-35.0</td> <td>0.0</td> <td>0.8</td> <td>52.2</td> <td>41.4</td> <td>74</td> <td>54</td> <td>-21.8</td> <td>-12.6</td> <td>V, Noise Floor</td> </tr> <tr> <td colspan="15">MID CHANNEL 39, 2441 MHz</td> </tr> <tr> <td>4.882</td> <td>3.0</td> <td>64.0</td> <td>35.1</td> <td>33.7</td> <td>3.0</td> <td>-34.9</td> <td>0.0</td> <td>0.6</td> <td>66.4</td> <td>37.5</td> <td>74</td> <td>54</td> <td>-7.6</td> <td>-16.5</td> <td>H</td> </tr> <tr> <td>7.323</td> <td>3.0</td> <td>52.8</td> <td>33.7</td> <td>36.2</td> <td>4.2</td> <td>-34.7</td> <td>0.0</td> <td>0.6</td> <td>59.1</td> <td>40.0</td> <td>74</td> <td>54</td> <td>-14.9</td> <td>-14.0</td> <td>H</td> </tr> <tr> <td>9.764</td> <td>3.0</td> <td>42.0</td> <td>32.8</td> <td>38.2</td> <td>4.7</td> <td>-35.0</td> <td>0.0</td> <td>0.8</td> <td>50.7</td> <td>41.5</td> <td>74</td> <td>54</td> <td>-23.3</td> <td>-12.5</td> <td>H, Noise Floor</td> </tr> <tr> <td>4.882</td> <td>3.0</td> <td>60.8</td> <td>34.5</td> <td>33.7</td> <td>3.0</td> <td>-34.9</td> <td>0.0</td> <td>0.6</td> <td>63.2</td> <td>36.9</td> <td>74</td> <td>54</td> <td>-10.8</td> <td>-17.1</td> <td>H</td> </tr> <tr> <td>7.323</td> <td>3.0</td> <td>54.6</td> <td>33.8</td> <td>36.2</td> <td>4.2</td> <td>-34.7</td> <td>0.0</td> <td>0.6</td> <td>60.9</td> <td>40.1</td> <td>74</td> <td>54</td> <td>-13.1</td> <td>-13.9</td> <td>V</td> </tr> <tr> <td>9.764</td> <td>3.0</td> <td>42.2</td> <td>32.6</td> <td>38.2</td> <td>4.7</td> <td>-35.0</td> <td>0.0</td> <td>0.8</td> <td>50.9</td> <td>41.3</td> <td>74</td> <td>54</td> <td>-23.1</td> <td>-12.7</td> <td>V, Noise Floor</td> </tr> <tr> <td colspan="15">HI CHANNEL 77, 2479 MHz</td> </tr> <tr> <td>4.958</td> <td>3.0</td> <td>64.0</td> <td>34.9</td> <td>33.8</td> <td>3.1</td> <td>-34.9</td> <td>0.0</td> <td>0.6</td> <td>66.6</td> <td>37.5</td> <td>74</td> <td>54</td> <td>-7.4</td> <td>-16.5</td> <td>H</td> </tr> <tr> <td>7.437</td> <td>3.0</td> <td>53.0</td> <td>33.9</td> <td>36.3</td> <td>4.2</td> <td>-34.6</td> <td>0.0</td> <td>0.6</td> <td>59.5</td> <td>40.4</td> <td>74</td> <td>54</td> <td>-14.5</td> <td>-13.6</td> <td>H</td> </tr> <tr> <td>9.916</td> <td>3.0</td> <td>42.0</td> <td>32.8</td> <td>38.3</td> <td>4.7</td> <td>-35.1</td> <td>0.0</td> <td>0.8</td> <td>50.8</td> <td>41.6</td> <td>74</td> <td>54</td> <td>-23.2</td> <td>-12.4</td> <td>H, Noise Floor</td> </tr> <tr> <td>4.958</td> <td>3.0</td> <td>60.0</td> <td>34.2</td> <td>33.8</td> <td>3.1</td> <td>-34.9</td> <td>0.0</td> <td>0.6</td> <td>62.6</td> <td>36.8</td> <td>74</td> <td>54</td> <td>-11.4</td> <td>-17.2</td> <td>H</td> </tr> <tr> <td>7.437</td> <td>3.0</td> <td>55.5</td> <td>33.9</td> <td>36.3</td> <td>4.2</td> <td>-34.6</td> <td>0.0</td> <td>0.6</td> <td>62.0</td> <td>40.4</td> <td>74</td> <td>54</td> <td>-12.0</td> <td>-13.6</td> <td>V</td> </tr> <tr> <td>9.916</td> <td>3.0</td> <td>42.4</td> <td>32.8</td> <td>38.3</td> <td>4.7</td> <td>-35.1</td> <td>0.0</td> <td>0.8</td> <td>51.2</td> <td>41.6</td> <td>74</td> <td>54</td> <td>-22.8</td> <td>-12.4</td> <td>V, Noise Floor</td> </tr> <tr> <td colspan="15">No other emissions were detected above system noise floor</td> </tr> </tbody> </table> <p><u>Definitions:</u></p> <table border="1"> <tr> <td>f</td> <td>Measurement Frequency</td> <td>Amp</td> <td>Preamp Gain</td> <td>Avg Lim</td> <td>Average Field Strength Limit</td> </tr> <tr> <td>Dist</td> <td>Distance to Antenna</td> <td>D Corr</td> <td>Distance Correct to 3 meters</td> <td>Pk Lim</td> <td>Peak Field Strength Limit</td> </tr> <tr> <td>Read</td> <td>Analyzer Reading</td> <td>Avg</td> <td>Average Field Strength @ 3 m</td> <td>Avg Mar</td> <td>Margin vs. Average Limit</td> </tr> <tr> <td>AF</td> <td>Antenna Factor</td> <td>Peak</td> <td>Calculated Peak Field Strength</td> <td>Pk Mar</td> <td>Margin vs. Peak Limit</td> </tr> <tr> <td>CL</td> <td>Cable Loss</td> <td>HPF</td> <td>High Pass Filter</td> <td></td> <td></td> </tr> </table>															Horn 1-18GHz	Pre-amplifier 1-26GHz	Pre-amplifier 26-40GHz	Horn > 18GHz			Limit	T60; S/N: 2238 @3m	T145 Agilent 3008A0056					FCC 15.209	Hi Frequency Cables															2 foot cable	3 foot cable	12 foot cable	HPF	Reject Filter	<u>Peak Measurements</u> RBW=VBW=1MHz <u>Average Measurements</u> RBW=1MHz ; VBW=10Hz										Vien 187215002	Vien 197209005		HPF_4.0GHz												f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fltr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)	LOW CHANNEL 0, 2402 MHz															4.804	3.0	63.6	35.1	33.6	2.9	-34.8	0.0	0.6	65.8	37.3	74	54	-8.2	-16.7	H	7.206	3.0	51.7	34.2	36.1	4.1	-34.7	0.0	0.6	57.9	40.4	74	54	-16.1	-13.6	H	9.608	3.0	44.0	33.1	38.0	4.7	-35.0	0.0	0.8	52.6	41.7	74	54	-21.4	-12.3	H, Noise Floor	4.804	3.0	59.3	34.5	33.6	2.9	-34.8	0.0	0.6	61.5	36.7	74	54	-12.5	-17.3	H	7.206	3.0	54.0	33.9	36.1	4.1	-34.7	0.0	0.6	60.2	40.1	74	54	-13.8	-13.9	V	9.608	3.0	43.6	32.8	38.0	4.7	-35.0	0.0	0.8	52.2	41.4	74	54	-21.8	-12.6	V, Noise Floor	MID CHANNEL 39, 2441 MHz															4.882	3.0	64.0	35.1	33.7	3.0	-34.9	0.0	0.6	66.4	37.5	74	54	-7.6	-16.5	H	7.323	3.0	52.8	33.7	36.2	4.2	-34.7	0.0	0.6	59.1	40.0	74	54	-14.9	-14.0	H	9.764	3.0	42.0	32.8	38.2	4.7	-35.0	0.0	0.8	50.7	41.5	74	54	-23.3	-12.5	H, Noise Floor	4.882	3.0	60.8	34.5	33.7	3.0	-34.9	0.0	0.6	63.2	36.9	74	54	-10.8	-17.1	H	7.323	3.0	54.6	33.8	36.2	4.2	-34.7	0.0	0.6	60.9	40.1	74	54	-13.1	-13.9	V	9.764	3.0	42.2	32.6	38.2	4.7	-35.0	0.0	0.8	50.9	41.3	74	54	-23.1	-12.7	V, Noise Floor	HI CHANNEL 77, 2479 MHz															4.958	3.0	64.0	34.9	33.8	3.1	-34.9	0.0	0.6	66.6	37.5	74	54	-7.4	-16.5	H	7.437	3.0	53.0	33.9	36.3	4.2	-34.6	0.0	0.6	59.5	40.4	74	54	-14.5	-13.6	H	9.916	3.0	42.0	32.8	38.3	4.7	-35.1	0.0	0.8	50.8	41.6	74	54	-23.2	-12.4	H, Noise Floor	4.958	3.0	60.0	34.2	33.8	3.1	-34.9	0.0	0.6	62.6	36.8	74	54	-11.4	-17.2	H	7.437	3.0	55.5	33.9	36.3	4.2	-34.6	0.0	0.6	62.0	40.4	74	54	-12.0	-13.6	V	9.916	3.0	42.4	32.8	38.3	4.7	-35.1	0.0	0.8	51.2	41.6	74	54	-22.8	-12.4	V, Noise Floor	No other emissions were detected above system noise floor															f	Measurement Frequency	Amp	Preamp Gain	Avg Lim	Average Field Strength Limit	Dist	Distance to Antenna	D Corr	Distance Correct to 3 meters	Pk Lim	Peak Field Strength Limit	Read	Analyzer Reading	Avg	Average Field Strength @ 3 m	Avg Mar	Margin vs. Average Limit	AF	Antenna Factor	Peak	Calculated Peak Field Strength	Pk Mar	Margin vs. Peak Limit	CL	Cable Loss	HPF	High Pass Filter		
Horn 1-18GHz	Pre-amplifier 1-26GHz	Pre-amplifier 26-40GHz	Horn > 18GHz			Limit																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
T60; S/N: 2238 @3m	T145 Agilent 3008A0056					FCC 15.209																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
Hi Frequency Cables																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
2 foot cable	3 foot cable	12 foot cable	HPF	Reject Filter	<u>Peak Measurements</u> RBW=VBW=1MHz <u>Average Measurements</u> RBW=1MHz ; VBW=10Hz																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
Vien 187215002	Vien 197209005		HPF_4.0GHz																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fltr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
LOW CHANNEL 0, 2402 MHz																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
4.804	3.0	63.6	35.1	33.6	2.9	-34.8	0.0	0.6	65.8	37.3	74	54	-8.2	-16.7	H																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
7.206	3.0	51.7	34.2	36.1	4.1	-34.7	0.0	0.6	57.9	40.4	74	54	-16.1	-13.6	H																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
9.608	3.0	44.0	33.1	38.0	4.7	-35.0	0.0	0.8	52.6	41.7	74	54	-21.4	-12.3	H, Noise Floor																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
4.804	3.0	59.3	34.5	33.6	2.9	-34.8	0.0	0.6	61.5	36.7	74	54	-12.5	-17.3	H																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
7.206	3.0	54.0	33.9	36.1	4.1	-34.7	0.0	0.6	60.2	40.1	74	54	-13.8	-13.9	V																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
9.608	3.0	43.6	32.8	38.0	4.7	-35.0	0.0	0.8	52.2	41.4	74	54	-21.8	-12.6	V, Noise Floor																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
MID CHANNEL 39, 2441 MHz																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
4.882	3.0	64.0	35.1	33.7	3.0	-34.9	0.0	0.6	66.4	37.5	74	54	-7.6	-16.5	H																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
7.323	3.0	52.8	33.7	36.2	4.2	-34.7	0.0	0.6	59.1	40.0	74	54	-14.9	-14.0	H																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
9.764	3.0	42.0	32.8	38.2	4.7	-35.0	0.0	0.8	50.7	41.5	74	54	-23.3	-12.5	H, Noise Floor																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
4.882	3.0	60.8	34.5	33.7	3.0	-34.9	0.0	0.6	63.2	36.9	74	54	-10.8	-17.1	H																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
7.323	3.0	54.6	33.8	36.2	4.2	-34.7	0.0	0.6	60.9	40.1	74	54	-13.1	-13.9	V																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
9.764	3.0	42.2	32.6	38.2	4.7	-35.0	0.0	0.8	50.9	41.3	74	54	-23.1	-12.7	V, Noise Floor																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
HI CHANNEL 77, 2479 MHz																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
4.958	3.0	64.0	34.9	33.8	3.1	-34.9	0.0	0.6	66.6	37.5	74	54	-7.4	-16.5	H																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
7.437	3.0	53.0	33.9	36.3	4.2	-34.6	0.0	0.6	59.5	40.4	74	54	-14.5	-13.6	H																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
9.916	3.0	42.0	32.8	38.3	4.7	-35.1	0.0	0.8	50.8	41.6	74	54	-23.2	-12.4	H, Noise Floor																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
4.958	3.0	60.0	34.2	33.8	3.1	-34.9	0.0	0.6	62.6	36.8	74	54	-11.4	-17.2	H																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
7.437	3.0	55.5	33.9	36.3	4.2	-34.6	0.0	0.6	62.0	40.4	74	54	-12.0	-13.6	V																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
9.916	3.0	42.4	32.8	38.3	4.7	-35.1	0.0	0.8	51.2	41.6	74	54	-22.8	-12.4	V, Noise Floor																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
No other emissions were detected above system noise floor																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
f	Measurement Frequency	Amp	Preamp Gain	Avg Lim	Average Field Strength Limit																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
Dist	Distance to Antenna	D Corr	Distance Correct to 3 meters	Pk Lim	Peak Field Strength Limit																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
Read	Analyzer Reading	Avg	Average Field Strength @ 3 m	Avg Mar	Margin vs. Average Limit																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
AF	Antenna Factor	Peak	Calculated Peak Field Strength	Pk Mar	Margin vs. Peak Limit																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
CL	Cable Loss	HPF	High Pass Filter																																																																																																																																																																																																																																																																																																																																																																																																																																																																																

7.2.3. WORST-CASE RADIATED EMISSIONS BELOW 1 GHz


SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)



HORIZONTAL DATA

Freq	Read		Level	Line	Over	Limit	Remark
	Level	Factor					
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	30.970	30.84	-7.50	23.34	40.00	-16.66	Peak
2	128.940	31.81	-12.64	19.17	43.50	-24.33	Peak
3	373.380	32.43	-10.09	22.34	46.00	-23.66	Peak
4	496.570	32.40	-7.27	25.13	46.00	-20.87	Peak
5	623.640	32.09	-4.89	27.20	46.00	-18.80	Peak
6	832.190	32.32	-1.64	30.68	46.00	-15.32	Peak

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)



VERTICAL DATA


Freq	Read			Limit Line	Over Limit	Remark
	Level	Factor	Level			
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	30.000	31.12	-7.50	23.62	40.00	-16.38 Peak
2	121.180	31.76	-12.64	19.12	43.50	-24.38 Peak
3	494.630	32.61	-7.32	25.29	46.00	-20.71 Peak
4	649.830	32.25	-4.33	27.92	46.00	-18.08 Peak
5	698.330	32.59	-3.25	29.34	46.00	-16.66 Peak
6	924.340	31.99	-0.71	31.28	46.00	-14.72 Peak

7.3. POWERLINE CONDUCTED EMISSIONS


The EUT is battery operated; no power line conducted emissions were performed.

8. SETUP PHOTO


ANTENNA PORT CONDUCTED RF MEASUREMENT SETUP



RADIATED RF MEASUREMENT SETUP – EUT STAND ALONE



RADIATED BACK PHOTO



END OF REPORT