



Flom Test Labs
EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268
fax: (480) 926-3598
<http://www.flomlabs.com>
info@flomlabs.com

Date: August 22, 2007

Federal Communications Commission
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: International Electronics Inc.
Equipment: Wireless Keypad Interface
FCC ID: JLFKPD1
FCC Rules: 15.249

Gentlemen:

On behalf of the Applicant, enclosed please find Application Form 731, Engineering Test Report and all pertinent documentation, the whole for approval of the referenced equipment as shown.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

Hoosamuddin S. Bandukwala, Lab Director

enclosure(s)
cc: Applicant
HSB/mdw

List Of Exhibits
(FCC Certification (Transmitters) - Revised 9/28/98)

Applicant: International Electronics Inc.

FCC ID: JLFKPD1

By Applicant:

1. Letter Of Authorization
2. Identification Drawings
 - Id Label
 - Location Info
 - Attestation Statement(s)
 - Location of Compliance Statement
3. Documentation: 2.1033(B)
 - (3) User Manual(s)
 - (4) Operational Description
 - (5) Block Diagram
 - (5) Schematic Diagram
 - (7) External Photographs
 - Internal Photographs
 - Parts List
 - Active Devices

By F.T.L. Inc.

- A. Testimonial & Statement of Certification
- B. Statement of Qualifications



Flom Test Labs
EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268
fax: (480) 926-3598
<http://www.flomlabs.com>
info@flomlabs.com

Transmitter Certification

of

FCC ID: JLFKPD1
Model: Wireless Keypad Interface

to

Federal Communications Commission

Rule Part(s) 15.249

Date Of Report: August 22, 2007
Date of Revision: December 13, 2007

On the Behalf of the Applicant: International Electronics Inc.
5913-C NE 127th Ave, Suite 800
Vancouver, WA 98682

Attention of: Shary Nassimi, President
(360) 241-9090
email: iei@nwlink.com

Supervised By:

Hoosamuddin S. Bandukwala, Lab Director

The applicant has been cautioned as to the following:

15.21 Information to User.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) Special Accessories.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.


Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

Testimonial And Statement Of Certification

This is to certify that:

1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
2. **That** the technical data supplied with the application was taken under my direction and supervision.
3. **That** the data was obtained on representative units, randomly selected.
4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

Certifying Engineer:



Hoosamuddin S. Bandukwala, Lab Director

Table Of Contents

Rule	Description	Page
	Test Report	1
2.1033(c)	General Information Required	2
	Standard Test Conditions and Engineering Practices	4
	Test Results Summary	5
15.249	Field Strength of Fundamental	6
15.249(d)	Field Strength of Harmonics	7
15.249(c),	Radiated Spurious Emissions	10
	Test Equipment Utilized	11

Required information per ISO 17025-2005, paragraph 5.10:

a) **Test Report**

b) Laboratory: Flom Test Lab, Inc.
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85225

c) Report Number: d0780025

d) Client: International Electronics Inc.

e) Identification: Wireless Keypad Interface

Description: Transmitter

f) EUT Condition: Not required unless specified in individual tests.


g) Report Date: August 22, 2007
EUT Received:

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with FTL internal quality manual.

m) Supervised by:



Hoosamuddin S. Bandukwala, Lab Director

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

List Of General Information Required For Certification

In Accordance with FCC Rules and Regulations,
Volume II, Part 2 and to

15.249

Sub-Part 2.1033

(c)(1):

Name and Address of Applicant: International Electronics Inc.

(c)(2): **FCC ID:** JLFKPD1

Model Number: Wireless Keypad Interface

(c)(3): **Instruction Manual(s):**

Please See Attached Exhibits

(c)(4): **Type of Emission:** FSK

(c)(5): **FREQUENCY RANGE, MHz:** 902 to 928

(c)(6): **Power Rating, dBuV/m:** 88.2
 Switchable Variable N/A

(c)(7): **Maximum Power Rating, dBuV/m** 93.97

15.203: **Antenna Requirement:**

- The antenna is permanently attached to the EUT
- The antenna uses a unique coupling
- The EUT must be professionally installed
- The antenna requirement does not apply

The unit was tested with a quarter wave stub antenna with a gain of 3.0 dBi.

Subpart 2.1033 (continued)**(c)(8): Circuit Diagram/Circuit Description:**

Including description of circuitry & devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation and limiting power.

Please See Attached Exhibits

(c)(9): Label Information:

Please See Attached Exhibits

(c)(10): Photographs:

Please See Attached Exhibits

(c)(11): Digital Modulation Description:

Attached Exhibits

N/A

(c)(12): Test And Measurement Data :

Follows

Sub-part
2.1033(b):

Test And Measurement Data

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2 and the following individual Parts:

15.249 Operation within bands 902 - 928 MHz

Standard Test Conditions and Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-2004, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst-case measurements.

A2LA

"A2LA has accredited Flom Test Labs, Inc. Chandler, AZ for technical competence in the field of Electrical testing. The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO 17025:2005 'General Requirements for the Competence of Testing and Calibration Laboratories' and any additional program requirements in the identified field of testing."

Please refer to www.a2la.org for current scope of accreditation.

Certificate number: 2152.01



IC O.A.T.S. Number: 2044A-1

Test Results Summary

Specification	Test Name	Pass, Fail, N/A	Comments
15.249(a)	Field Strength of Fundamental	Pass	
15.249(a)	Field Strength of Harmonics	Pass	
15.249	Radiated Spurious Emissions	Pass	

Name of Test: Field Strength of Fundamental
Specification: 15.249(a)
Test Equipment Utilized i00228, i00317

Test Procedure


15.249(a) The field strength of emissions from intentional radiators operating in the 903 – 928 band shall comply with the following:

Fundamental frequency, MHz	Field strength of fundamental, mV / meter	Field strength of harmonics, μ V /meter
902 - 928	50	500

1mV = 1000uV 50000uV/mtr converts to **93.97 dBuV/mtr** (20 X log(E))

The UUT was tested on an Open Area Test Site (OATS) set 3 meters from the receiving antenna. A spectrum analyzer was used to verify the UUT met the requirements for Radiated Spurious Emissions. The UUT was tested with the appropriate antenna in both the vertical and horizontal orientation and raised from 1 to 4 meters while rotating the UUT 360° to ensure the TX signal levels were maximized.

Test Setup



Settings

RBW	VBW	Span	Detector
1 MHz	1 MHz	As necessary	Peak

Field Strength of Fundamental table


Tuned Frequency MHz	Emission Frequency MHz	Recorded Peak Measurement, dBuV/m	Correction factor, dB	Corrected Peak Measurement, dBuV/m	Quasi Peak Limit, dBuV/m	Result
903.000000	903.340000	59.1	29.1	88.2	93.97	Pass
915.000000	915.812500	57.2	29.5	86.7	93.97	Pass
926.000000	926.725000	57.7	30.0	87.7	93.97	Pass

Name of Test: Field Strength of Harmonics
Specification: 15.249
Test Equipment Utilized i00029, i00329

Test Procedure

The UUT was tested on an Open Area Test Site (OATS) at a distance of 3m from the receiving antenna. A spectrum analyzer was used to verify the UUT met the requirements for Radiated Spurious Emissions. The UUT was tested with the appropriate antenna in both the vertical and horizontal orientation and raised from 1 to 4 meters while rotating the UUT 360° to ensure the TX signal levels were maximized.

Test Setup



Settings

RBW	VBW	Span	Detector
1 MHz	1 MHz	As necessary	Peak

Field Strength of Harmonics Table

903MHz

Tuned Frequency MHz	Emission Frequency MHz	Recorded Peak Level (dBuV/m)	Correction factor (dB)	Corrected Peak Level (dBuV/m)	Average Limit (dBuV/m)	Result
903.000000	1806.350000	10.8	30.8	41.6	54.0	Pass
903.000000	2709.930000	1.7	34.4	36.1	54.0	Pass
903.000000	3613.015000	0.0	36.3	36.3	54.0	Pass
903.000000	4516.395000	-0.6	37.6	37.0	54.0	Pass
903.000000	5418.525000	0.1	40.3	40.4	54.0	Pass
903.000000	6321.900000	4.2	41.4	45.6	54.0	Pass

915MHz


Tuned Frequency MHz	Emission Frequency MHz	Recorded Peak Level (dBuV/m)	Correction factor (dB)	Corrected Peak Level (dBuV/m)	Average Limit (dBuV/m)	Result
915.000000	1831.240000	9.6	30.9	40.5	54.0	Pass
915.000000	2746.900000	-0.1	34.5	34.4	54.0	Pass
915.000000	3662.515000	-0.7	36.4	35.7	54.0	Pass
915.000000	4577.755000	0.8	37.8	38.6	54.0	Pass
915.000000	5493.090000	0.1	40.4	40.5	54.0	Pass
915.000000	6409.615000	4.3	41.6	45.9	54.0	Pass

927MHz


Tuned Frequency MHz	Emission Frequency MHz	Recorded Peak Level (dBuV/m)	Correction factor (dB)	Corrected Peak Level (dBuV/m)	Average Limit (dBuV/m)	Result
927.000000	1853.625000	10.4	31.0	41.4	54.0	Pass
927.000000	2780.075000	0.3	34.7	35.0	54.0	Pass
927.000000	3707.005000	-0.9	36.5	35.6	54.0	Pass
927.000000	4633.140000	-0.6	38.0	37.4	54.0	Pass
927.000000	5559.205000	0.5	40.5	41.0	54.0	Pass
927.000000	6486.140000	4.9	41.7	46.6	54.0	Pass

The UUT was tested for any out of band emissions to the 10th harmonic.

902 Band Edge Peak



928 Band Edge Peak



Settings

RBW	VBW	Span	Detector
100 KHz	100 KHz	100 Hz	Quasi- Peak

Sample Calculation

Corrected Level = Recorded Level + Correction factor


Tuned Frequency MHz	Emission Frequency MHz	Recorded QP Measurement, dBuV/m	Correction factor, dB	Corrected QP Measurement, dBuV/m	Quasi-Peak Limit, dBuV/m	Result
903.000	901.904	13.8	26.4	40.2	54.0	Pass
926.000	928.265	17.1	27.3	44.4	54.0	Pass

Name of Test: Radiated Spurious Emissions
Specification: 15.249(c), 15.209(a), 15.205
Spec. Limit
Test Equipment Utilized i00029, i00033, i00088, i00089, i00103

Test Procedure

The UUT was tested on an Open Area Test Site (OATS) set 3 meters from the receiving antenna. A spectrum analyzer was used to verify the UUT met the requirements for Radiated Spurious Emissions. The UUT was tested with the appropriate antenna in both the vertical and horizontal orientation and raised from 1 to 4 meters while rotating the UUT 360° to ensure the TX signal levels were maximized.

Test Setup



Settings

RBW = 100 KHz

VBW = 100KHz

Detector – Quasi Peak

Sample Calculations

Corrected Level = Recorded Level + Correction factor

Correction factor = ACF + Cable loss

Radiated Spurious Emissions

Tuned Freq (MHz)	Emission Freq (MHz)	Monitored Level (dBuV/m)	Correction Factor (dB)	Corrected Value (dBuV/m)	Limit (dBuV/m)	Result
915.000000	125.000000	13.3	14.3	27.6	40.0	Pass
915.000000	475.000000	15.3	19.9	35.2	40.0	Pass
915.000000	505.000000	17.6	20.5	38.1	46.0	Pass
915.000000	620.000000	12.2	23.5	35.7	46.0	Pass
915.000000	690.000000	13.9	23.3	37.2	46.0	Pass
915.000000	795.000000	17.6	24.6	42.2	46.0	Pass

Test Equipment Utilized

Description	MFG	Model Number	FTL Asset Number	Last Cal Date	Cal Due Date
Spectrum Analyzer	HP	8563E	i00029	1/26/06	1/26/07
Spectrum Analyzer	HP	85462A	i00033	11/03/06	11/03/07
Bi-conical Antenna	EMCO	3109B	i00088	10/14/05	10/14/07
Log Periodic Antenna	Apral	2001	i00089	10/20/05	10/20/07
Horn Antenna	EMCO	3115	i00103	9/5/06	9/5/07
Spectrum Analyzer	HP	8566B	i00290	6/16/06	6/16/07
Spectrum Analyzer	HP	8566B	i00329	4/16/07	4/16/08

In addition to the above listed equipment standard RF connectors and cables were utilized in the testing of the described equipment. Prior to testing these components were tested to verify proper operation.

END OF TEST REPORT