



Project No: Report No.: TM-2402000257P TMWK2402000546KS FCC ID: JNF-BTS-319XP

Page: 1/8 03 Rev.:

SAR TEST REPORT

FCC 47 CFR § 2.1093

for

Wireless Handheld Barcode Scanner

Model Name.: Z-3190BT Plus, Z-3192BT Plus

Prepared for:

ZEBEX INDUSTRIES INC. B1F.-1, No. 207, Sec. 3, Beixin Rd, Xindian Dist, New Taipei City 23143, Taiwan

Prepared by

Compliance Certification Services Inc. Wugu Lab. No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan. Issue Date: July 18, 2024

Note: This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, NIST or any government agencies. The test results in the report only apply to the tested sample.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan /新北市五股區五工六路 11 號 t:(886-2) 2299-9720 f:(886-2) 2299-9721 www.sgs.com.tw



Page: 2/8 Rev.: 03

Revision History

| Rev. | Issue Date | Revisions | Effect Page | Revised By |
|------|---------------|----------------------------------|-------------|------------|
| 00 | June 7, 2024 | Initial Issue | ALL | Peggy Tsai |
| 01 | July 3, 2024 | See the following Note Rev. (01) | P.6, 7 | Peggy Tsai |
| 02 | July 9, 2024 | See the following Note Rev. (02) | P.1, 4, 6 | Peggy Tsai |
| 03 | July 18, 2024 | See the following Note Rev. (03) | P.4 | Peggy Tsai |

Note:

Rev. (01)

1. Modify peak antenna gain to 2.13 dBi.

2. Modify Wireless Technologies in section 3.2.

3. Modify Standalone SAR Test Exclusion Considerations in section 4.1.

Rev. (02)

1. Modify model name to Z-3190BT Plus, Z-3192BT Plus.

2. Modify Hardware Version in section 3.1.

Rev. (03)

1. Modify Software Version in section 3.1.



| Report No.: | | TMWK2402000546KS | Rev.: | 03 |
|-------------|--------|---|-------|----|
| | | Table of Contents | | |
| 1 | ATTES | TATION OF TEST RESULTS | | 4 |
| 2 | TEST N | METHODOLOGY | | 5 |
| 3 | DEVIC | E UNDER TEST (DUT) INFORMATION | | 6 |
| | 3.1 DI | JT DESCRIPTION | | 6 |
| | 3.2 W | IRELESS TECHNOLOGIES | | 6 |
| 4 | RF EXI | POSURE CONDITIONS (TEST CONFIGURATIONS) | | 7 |
| | 4.1 ST | FANDALONE SAR TEST EXCLUSION CONSIDERATIONS | | 7 |
| 5 | FACILI | TIES | , | 8 |

Page: 3/8



1 Attestation of Test Results

| Applicant Name | ZEBEX INDUSTRIES INC. | | |
|----------------------|---|--|--|
| Model Name | Z-3190BT Plus, Z-3192BT Plus | | |
| Applicable Standards | FCC 47 CFR § 2.1093 | | |
| | KDB 447498 D04 Interim General RF Exposure Guidance v01 | | |
| Receive EUT Date: | February 22, 2024 | | |
| Test Results | Pass | | |

Compliance Certification Services Inc. , tested the above equipment in accordance with the requirements set forth in the above standards. Determination of compliance is based on the results of the compliance measurement,not taking into account measurement instrumentation uncertainy.All indications of Pass/Fail in this report are opinions expressed by Compliance Certification Services Inc, based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Approved & Released By: Multiple Sky Zhou Asst. Section Manager Compliance Certification Services Inc.



Page: 5/8 Rev.: 03

2 Test Methodology

All calculations were made in accordance with FCC KDB 447498 D04 Interim General RF Exposure Guidance v01



Device Under Test (DUT) Information 3

DUT Description 3.1

| Applicant Name | ZEBEX INDUSTRIES INC. | | | | | |
|---|---|--|--|--|--|--|
| Applicant Address | B1F1, No. 207, Sec. 3, Beixin Rd, Xindian Dist, New Taipei City 23143, Taiwan | | | | | |
| Manufacturer Name ZEBEX INDUSTRIES INC. | | | | | | |
| Manufacturer Address | B1F1, No. 207, Sec. 3, Beixin Rd, Xindian Dist, New Taipei City 23143, Taiwan | | | | | |
| Product | Wireless Handheld Barcode Scanner | | | | | |
| Trade Name | ZEBEX | | | | | |
| Model No. | Z-3190BT Plus, Z-3192BT Plus | | | | | |
| Model Discrepancy | Z-3190BT Plus: CCD Wireless Handheld Barcode Scanner | | | | | |
| | Z-3192BT Plus: 2D Image Wireless Handheld Barcode Scanner | | | | | |
| Hardware Version | 023-190BP1-034 & 023-190BP2-034 & 023-190BP3-034 | | | | | |
| | Z-3190BT Plus: Z-3190BT+(H02.x0) 09:27:50 Date:11/28/2023 | | | | | |
| Software Version | Z-3192BT Plus: Z-3192BT+(M01.03) Ver:01.00 Jul 11 2024 SN:20240319 BT Controller(H02.B2) BT0103 Jul 12 2024 | | | | | |
| Sample Stage | PVT | | | | | |

3.2 Wireless Technologies

| Wireless technologies | Frequency bands | Peak Antenna Gain (dBi) | Operating mode | | | |
|--------------------------|-----------------|----------------------------------|----------------|--|--|--|
| Bluetooth | 2.4 GHz | 2.13 | BR, EDR, BLE | | | |
| | Brand Name | PSA | | | | |
| Antenna | Туре | Chip Antenna | | | | |
| Specification | Parts Number | RFANT3216120A1T | | | | |

Notes:

The sample selected for test was prototype that representative to production product and was provided by manufacturer 1.

2. 3.

Disclaimer :Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received Disclaimer :Variant information between/among model numbers / trademarks are provided by the applicant, test results of this report are applicable to the sample EUT received of main test model name.)



Page: 7/8 Rev.: 03

4 **RF Exposure Conditions (Test Configurations)**

Refer to Section 5 for the specific details of the antenna-to-antenna and antenna-to-edge(s) distances.

4.1 Standalone SAR Test Exclusion Considerations

Since the Dedicated Host Approach is applied, the SAR-based exemption in Appendix B of KDB 447498 D04 is applied together with KDB 616217 § 4.3 to determine the minimum test separation distance:

- When the separation distance from the antenna to an adjacent edge is ≤ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.
- When the separation distance from the antenna to an adjacent edge is > 5 mm, the actual antenna-to-edge separation distance is applied to determine SAR test exclusion.
- The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold Pth (mW) described in the following formula.
 Pth is given by:

 $P_{\text{th}} (\text{mW}) = ERP_{20 \text{ cm}} (\text{mW}) = \begin{cases} 2040f & 0.3 \text{ GHz} \le f < 1.5 \text{ GHz} \\ \\ 3060 & 1.5 \text{ GHz} \le f \le 6 \text{ GHz} \end{cases}$

• The separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz . Pth is given by:

$$P_{\rm th} \,({\rm mW}) = \begin{cases} ERP_{20\,\,{\rm cm}} (d/20\,\,{\rm cm})^x & d \le 20\,\,{\rm cm} \\ \\ ERP_{20\,\,{\rm cm}} & 20\,\,{\rm cm} < d \le 40\,\,{\rm cm} \end{cases}$$

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20}\,\mathrm{cm}\sqrt{f}}\right)$$

and *f* is in GHz, *d* is the separation distances (cm).

SAR Test Exclusion Calculations for 1.5 GHz $\leq f \leq 6$ GHz

Maximum tune-up tolerance limit is 8 dBm.

The SAR test exemption is 2.5 times the SAR-based exemption threshold.

The device was assessed the 10g SAR limits.

| Тх | Frequency | Output | Power | Antenna Gain | ERP | ERP Threshold | Sonaration Distances (cm) | B (m)M) | Examption result |
|-----------|-----------|--------|-------|--------------|-------|---------------|---------------------------|---------|------------------|
| Interface | (GHz) | dBm | mW | (dBi) | (dBm) | (mW) | Separation Distances (cm) | | Exemption result |
| BT | 2.48 | 8.00 | 6 | 2.13 | 7.98 | 6.28 | 0.5 | 7 | -EXEMPT- |
| | | | | | | | • | | • |

Conclusion:

The Max. output power and ERP \leq Pth (mW); therefore, this qualifies for SAR test exclusion.



5 Facilities

All measurement facilities used to collect the measurement data are located at No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan.

END OF REPORT

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可,不可部份複製。

Page: 8/8 Rev.: 03