

## FCC Test Report

**Report No.:** RF191002E02 R1

**FCC ID:** JNZF00007

**Test Model:** F00007

**Received Date:** Oct. 02, 2019

**Test Date:** Oct. 05 to Dec. 18, 2019

**Issued Date:** Jan. 13, 2020

**Applicant:** LOGITECH FAR EAST LTD.

**Address:** #2 Creation Rd. 4, Science-Based Ind. Park Hsinchu Taiwan, R.O.C.

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan

**Test Location:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan.

**FCC Registration /  
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record</b> .....	<b>3</b>
<b>1 Certificate of Conformity</b> .....	<b>4</b>
<b>2 Summary of Test Results</b> .....	<b>5</b>
2.1 Measurement Uncertainty .....	5
2.2 Modification Record .....	5
<b>3 General Information</b> .....	<b>6</b>
3.1 General Description of EUT .....	6
3.2 Description of Test Modes .....	6
3.2.1 Test Mode Applicability and Tested Channel Detail .....	7
3.3 Description of Support Units .....	8
3.3.1 Configuration of System under Test .....	8
3.4 General Description of Applied Standards .....	9
<b>4 Test Types and Results</b> .....	<b>10</b>
4.1 Radiated Emission and Bandedge Measurement .....	10
4.1.1 Limits of Radiated Emission and Bandedge Measurement .....	10
4.1.2 Test Instruments .....	11
4.1.3 Test Procedures .....	12
4.1.4 Deviation from Test Standard .....	12
4.1.5 Test Set Up .....	13
4.1.6 EUT Operating Conditions .....	13
4.1.7 Test Results .....	14
4.2 Conducted Emission Measurement .....	30
4.2.1 Limits of Conducted Emission Measurement .....	30
4.2.2 Test Instruments .....	30
4.2.3 Test Procedures .....	32
4.2.4 Deviation from Test Standard .....	32
4.2.5 Test Setup .....	32
4.2.6 EUT Operating Conditions .....	32
4.2.7 Test Results .....	33
<b>5 Pictures of Test Arrangements</b> .....	<b>37</b>
<b>Appendix – Information of the Testing Laboratories</b> .....	<b>38</b>

### Release Control Record

Issue No.	Description	Date Issued
RF191002E02	Original release.	Dec. 03, 2019
RF191002E02 R1	Revised the radiated emission and page 13 note 3.	Jan. 13, 2020

## 1 Certificate of Conformity

**Product:** Powered 3-in-1 Dock

**Brand:** Logitech

**Test Model:** F00007

**Sample Status:** ENGINEERING SAMPLE

**Applicant:** LOGITECH FAR EAST LTD.

**Test Date:** Oct. 05 to Dec. 18, 2019

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.209)  
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :** Vivian Huang , **Date:** Jan. 13, 2020  
Vivian Huang / Specialist

**Approved by :** Clark Lin , **Date:** Jan. 13, 2020  
Clark Lin / Technical Manager

## 2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.209)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -6.59 dB at 0.15000MHz.
15.209	Radiated Emission Test	Pass	Meet the requirement of limit. Minimum passing margin is -3.0 dB at 44.50 MHz

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ( $\pm$ )
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.8 dB
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.0 dB
	30MHz ~ 1000MHz	4.9 dB

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

Product	Powered 3-in-1 Dock
Brand	Logitech
Test Model	F00007
Sample Status	ENGINEERING SAMPLE
Rating	DC 19V from power adapter
Operating Frequency	127.795 kHz / 326.5 kHz
Antenna Type	Coil Antenna
Field Strength	127.795 kHz: 9.86 dBuV/m 326.5 kHz: -17.41 dBuV/m
Dimensions	117.4*235.91*101 mm
Accessory Device	Adapter x1
Data Cable Supplied	NA
Maximum Power Output from the Charging Coil	Stand: 10W Pad: 10W Apple Watch Charger: 5W

Note:

- The EUT may have a lot of colors for marketing requirement.
- The EUT could be supplied with a power adapter as the following table:

Adapter No.	Brand	Model No.	Spec.	Color
1	logi	AD2105320	Input: 100-240V, 1.2A, 50/60Hz Output: 19V, 2.64A DC cable: 1.5 m	Black
2	logi	AD2105320	Input: 100-240V, 1.2A, 50/60Hz Output: 19V, 2.64A DC cable: 1.5 m	White

Note: From the above adapters, **Adapter 1** was selected as representative adapter for the test and its data was recorded in this report.

- The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

#### 3.2 Description of Test Modes

The following test frequency is provided to this EUT:

Operating Frequency (kHz)	Test Mode
127.795 / 326.5	Charging Mode
127.795 / 326.5	Standby Mode

### 3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable To		Description
	RE<1G	PLC	
1	√	√	Charging Mode
2	√	√	Standby Mode

Where **RE<1G**: Radiated Emission below 1GHz **PLC**: Power Line Conducted Emission

#### Radiated Emission Test (Below 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Operating Frequency (kHz)	Tested Frequency (kHz)
127.795 / 326.5	127.795 / 326.5

#### Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Operating Frequency (kHz)	Tested Frequency (kHz)
127.795 / 326.5	127.795 / 326.5

#### Test Condition:

Applicable To	Environmental Conditions	Input Power	Tested by
RE<1G	25 deg. C, 65% RH	120Vac, 60Hz	Nelson Teng
PLC	24 deg. C, 76% RH	120Vac, 60Hz	Andy Ho

### 3.3 Description of Support Units


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Loading 10W	NA	NA	NA	NA	Supplied by client(for RF Setup)
B.	Loading 5W	NA	NA	NA	NA	Supplied by client(for RF Setup)
C.	Apple watch Series4	NA	A1977	FHLYJ7QEKD3	NA	Supplied by client(for RF Setup)


ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	DC Cable	1	1.5	No	0	Supplied by client

#### 3.3.1 Configuration of System under Test

Charging Mode



Standby Mode:





### 3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

#### **47 CFR FCC Part 15, Subpart C (Section 15.209)**

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

##### For Frequency below 30MHz

Frequency (MHz)	Field Strength		Measurement Distance (meters)
	uV/m	dBuV/m	
0.009 – 0.490	2400 / F (kHz)	48.52-13.80	300
0.490 – 1.705	24000 / F (kHz)	33.80-22.97	30
1.705 – 30.0	30	29.54	30

##### For Frequency between 30-1000MHz

Frequency (MHz)	Field Strength		Measurement Distance (meters)
	uV/m	dBuV/m	
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

#### 4.1.2 Test Instruments

For 0.009 MHz ~ 30 MHz

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Keysight	N9038A	MY54450088	July 03, 2019	July 02, 2020
Pre-Amplifier EMCI	EMC001340	980142	May 30, 2019	May 29, 2020
Loop Antenna Electro-Metrics	EM-6879	264	Jan. 22, 2019	Jan. 21, 2020
RF Cable	NA	LOOPCAB-001	Jan. 14, 2019	Jan. 13, 2020
RF Cable	NA	LOOPCAB-002	Jan. 14, 2019	Jan. 13, 2020
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA

**Note:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 4.
3. Loop antenna was used for all emissions below 30 MHz.
4. Tested Date: Oct. 05 to Dec. 18, 2019

For 30 MHz ~ 1GHz

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Keysight	N9038A	MY54450088	July 03, 2019	July 02, 2020
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-01	Oct. 23, 2019	Oct. 22, 2020
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-406	Nov. 22, 2018	Nov. 21, 2019
RF Cable	8D	966-4-1	Mar. 19, 2019	Mar. 18, 2020
RF Cable	8D	966-4-2	Mar. 19, 2019	Mar. 18, 2020
RF Cable	8D	966-4-3	Mar. 19, 2019	Mar. 18, 2020
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-4-01	Sep. 26, 2019	Sep. 25, 2020
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA

**Note:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 4.
3. Loop antenna was used for all emissions below 30 MHz.
4. Tested Date: Nov. 19, 2019

### 4.1.3 Test Procedures

#### For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200Hz at frequency range 9kHz to 150kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency range 150kHz to 30MHz.
3. KDB 414788 OATS and Chamber Correlation Justification
  - Based on FCC 15.31(f)(2) : measurements may be performed at a distance closer than that specified in the regulations; however, an attempts should be made to avoid making measurements in the near field.
  - OATs and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

#### For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (AV) at frequency below 1GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Set Up

##### For Radiated emission below 30MHz



##### For Radiated emission 30MHz to 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

Test Mode 1:

- a. The EUT powered by adapter.
- b. The EUT is under the test mode when turn on the power.
- c. Put the Apple Watch on the EUT (under the worst-case 50% of the charging status) during the test.

Test Mode 2:

- a. The EUT powered by adapter.
- b. Set the EUT under standby condition.

### 4.1.7 Test Results

Below 30MHz Data:


Charging Mode

<b>TEST FREQUENCY</b>	127.795 kHz / 326.5 kHz	<b>DETECTOR FUNCTION</b>	Average (AV)
<b>FREQUENCY RANGE</b>	9kHz ~ 490kHz		

ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA PARALLEL AT 300 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	0.012	-12.02 AV	46.02	-58.04	1	254	32.02	35.96
2	0.027	-23.33 AV	38.98	-62.31	1	85	27.71	28.96
3	0.066	-21.62 AV	31.21	-52.83	1	284	37.54	20.84
4	0.069	-23.26 AV	30.83	-54.09	1	176	36.3	20.44
5	0.122	-27.5 AV	25.88	-53.38	1	51	37.04	15.46
6	0.128	9.86 AV	25.46	-15.6	1	147	74.64	15.22
7	0.15	-8.02 AV	24.08	-32.1	1	78	57.68	14.3
8	0.326	-52.39 AV	17.34	-69.73	1	51	19.96	7.65

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. Loop antenna was used for all radiated emission below 30MHz.
6. Data @3m=Data @300m-40log(300 / 3)=Data @300m-80




<b>TEST FREQUENCY</b>	127.795 kHz / 326.5 kHz	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	490kHz ~ 30MHz		

ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA PARALLEL AT 30 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4.738	-2.77 QP	29.54	-32.31	1	360	40.87	-3.64
2	12.198	-2.81 QP	29.54	-32.35	1	18	40.39	-3.2
3	18.243	4.03 QP	29.54	-25.51	1	142	48.28	-4.25
4	21.872	7.53 QP	29.54	-22.01	1	214	51.81	-4.28
5	23.128	11.05 QP	29.54	-18.49	1	258	55.14	-4.09

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. Loop antenna was used for all radiated emission below 30MHz.
6. Data @3m=Data @30m-40log(30 / 3)=Data @30m-40




<b>TEST FREQUENCY</b>	127.795 kHz / 326.5 kHz	<b>DETECTOR FUNCTION</b>	Average (AV)
<b>FREQUENCY RANGE</b>	9kHz ~ 490kHz		

**ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA PERPENDICULAR AT 300 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	0.021	-21.71 AV	41.16	-62.87	1	360	26.7	31.59
2	0.067	-26.88 AV	31.08	-57.96	1	65	32.42	20.7
3	0.078	-37.94 AV	29.76	-67.7	1	6	22.8	19.26
4	0.122	-33.95 AV	25.88	-59.83	1	157	30.59	15.46
5	0.128	3.33 AV	25.46	-22.13	1	1	68.11	15.22
6	0.13	-35.02 AV	25.33	-60.35	1	230	29.85	15.13
7	0.151	-7.87 AV	24.02	-31.89	1	217	57.86	14.27
8	0.326	-51.6 AV	17.34	-68.94	1	125	20.75	7.65

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. Loop antenna was used for all radiated emission below 30MHz.
6. Data @3m=Data @300m-40log(300 / 3)=Data @300m-80






<b>TEST FREQUENCY</b>	127.795 kHz / 326.5 kHz	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	490kHz ~ 30MHz		

**ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA PERPENDICULAR AT 30 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	7.922	-3.64 QP	29.54	-33.18	1	79	39.53	-3.17
2	12.749	-0.28 QP	29.54	-29.82	1	321	43.01	-3.29
3	18.245	6.49 QP	29.54	-23.05	1	184	50.74	-4.25
4	21.869	11.05 QP	29.54	-18.49	1	251	55.33	-4.28
5	23.128	12.65 QP	29.54	-16.89	1	25	56.74	-4.09

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. Loop antenna was used for all radiated emission below 30MHz.
6. Limit @3m=Limit@30m-40log(30 / 3)=Limit@30m-40




<b>TEST FREQUENCY</b>	127.795 kHz / 326.5 kHz	<b>DETECTOR FUNCTION</b>	Average (AV)
<b>FREQUENCY RANGE</b>	9kHz ~ 490kHz		

**ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA GROUND-PARALLEL AT 300 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	0.025	-17.58 AV	39.65	-57.23	1	256	32.59	29.83
2	0.048	-27.92 AV	33.98	-61.9	1	55	28.66	23.42
3	0.065	-28.88 AV	31.35	-60.23	1	360	30.15	20.97
4	0.07	-33.66 AV	30.7	-64.36	1	276	26.03	20.31
5	0.128	4.02 AV	25.46	-21.44	1	127	68.8	15.22
6	0.138	-37.84 AV	24.81	-62.65	1	13	27.36	14.8
7	0.15	-8.2 AV	24.08	-32.28	1	58	57.5	14.3
8	0.326	-50.9 AV	17.34	-68.24	1	91	21.45	7.65

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. Loop antenna was used for all radiated emission below 30MHz.
6. Data @3m=Data @300m-40log(300 / 3)=Data @300m-80




<b>TEST FREQUENCY</b>	127.795 kHz / 326.5 kHz	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	490kHz ~ 30MHz		

ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA GROUND-PARALLEL AT 30 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3.506	-1.45 QP	29.54	-30.99	1	6	42.1	-3.55
2	7.378	-3.36 QP	29.54	-32.9	1	236	39.9	-3.26
3	13.56	10.93 QP	29.54	-18.61	1	159	54.36	-3.43
4	17.693	5.92 QP	29.54	-23.62	1	145	50.08	-4.16
5	23.131	15.54 QP	29.54	-14	1	254	59.63	-4.09

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. Loop antenna was used for all radiated emission below 30MHz.
6. Limit @3m=Limit@30m-40log(30 / 3)=Limit@30m-40




Standby Mode

<b>TEST FREQUENCY</b>	127.795 kHz / 326.5 kHz	<b>DETECTOR FUNCTION</b>	Average (AV)
<b>FREQUENCY RANGE</b>	9kHz ~ 490kHz		

ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA PARALLEL AT 300 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	0.012	-11.9 AV	46.02	-57.92	1	119	32.2	35.9
2	0.027	-23.5 AV	38.98	-62.48	1	264	27.6	28.9
3	0.066	-21.7 AV	31.21	-52.91	1	291	37.4	20.9
4	0.069	-23.6 AV	30.83	-54.43	1	241	35.9	20.5
5	0.122	-27.7 AV	25.88	-53.58	1	263	36.8	15.5
6	0.128	9.6 AV	25.46	-15.86	1	272	74.4	15.2
7	0.15	-8.2 AV	24.08	-32.28	1	265	57.5	14.3
8	0.326	-17.41 AV	17.34	-34.75	1	241	54.94	7.65

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. Loop antenna was used for all radiated emission below 30MHz.
6. Data @3m=Data @300m-40log(300 / 3)=Data @300m-80




<b>TEST FREQUENCY</b>	127.795 kHz / 326.5 kHz	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	490kHz ~ 30MHz		

ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA PARALLEL AT 30 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4.738	-3.1 QP	29.54	-32.64	1	224	40.5	-3.6
2	12.198	-2.9 QP	29.54	-32.44	1	235	40.3	-3.2
3	18.243	3.7 QP	29.54	-25.84	1	223	47.9	-4.2
4	21.872	7.3 QP	29.54	-22.24	1	119	51.5	-4.2
5	23.128	10.7 QP	29.54	-18.84	1	142	54.8	-4.1

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. Loop antenna was used for all radiated emission below 30MHz.
6. Data @3m=Data @30m-40log(30 / 3)=Data @30m-40




<b>TEST FREQUENCY</b>	127.795 kHz / 326.5 kHz	<b>DETECTOR FUNCTION</b>	Average (AV)
<b>FREQUENCY RANGE</b>	9kHz ~ 490kHz		

ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA PERPENDICULAR AT 300 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	0.02	-22.2 AV	41.58	-63.78	1	264	25.8	32
2	0.07	-27.1 AV	30.7	-57.8	1	116	32.6	20.3
3	0.08	-38.1 AV	29.54	-67.64	1	132	22.9	19
4	0.12	-33.8 AV	26.02	-59.82	1	131	30.6	15.6
5	0.128	3.2 AV	25.46	-22.26	1	265	68	15.2
6	0.13	-34.9 AV	25.33	-60.23	1	114	30	15.1
7	0.151	-9.8 AV	24.02	-33.82	1	138	56	14.2
8	0.326	-31.28 AV	17.34	-48.62	1	149	41.07	7.65

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. Loop antenna was used for all radiated emission below 30MHz.
6. Data @3m=Data @300m-40log(300 / 3)=Data @300m-80




<b>TEST FREQUENCY</b>	127.795 kHz / 326.5 kHz	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	490kHz ~ 30MHz		

ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA PERPENDICULAR AT 30 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	7.922	-3.8 QP	29.54	-33.34	1	265	39.3	-3.1
2	12.749	-0.7 QP	29.54	-30.24	1	114	42.6	-3.3
3	18.245	6.3 QP	29.54	-23.24	1	149	50.5	-4.2
4	21.869	10.8 QP	29.54	-18.74	1	239	55	-4.2
5	23.128	12.3 QP	29.54	-17.24	1	265	56.4	-4.1

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. Loop antenna was used for all radiated emission below 30MHz.
6. Data @3m=Data @30m-40log(30 / 3)=Data @30m-40




<b>TEST FREQUENCY</b>	127.795 kHz / 326.5 kHz	<b>DETECTOR FUNCTION</b>	Average (AV)
<b>FREQUENCY RANGE</b>	9kHz ~ 490kHz		

ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA GROUND-PARALLEL AT 300 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	0.025	-17.8 AV	39.65	-57.45	1	179	32.3	29.9
2	0.048	-27.8 AV	33.98	-61.78	1	114	28.8	23.4
3	0.065	-29.2 AV	31.35	-60.55	1	172	29.8	21
4	0.07	-33.9 AV	30.7	-64.6	1	173	25.8	20.3
5	0.128	4.2 AV	25.46	-21.26	1	265	69	15.2
6	0.138	-37.9 AV	24.81	-62.71	1	149	27.3	14.8
7	0.15	-10.1 AV	24.08	-34.18	1	263	55.6	14.3
8	0.326	-21.34 AV	17.34	-38.68	1	241	51.01	7.65

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. Loop antenna was used for all radiated emission below 30MHz.
6. Data @3m=Data @300m-40log(300 / 3)=Data @300m-80






<b>TEST FREQUENCY</b>	127.795 kHz / 326.5 kHz	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	490kHz ~ 30MHz		

ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA GROUND-PARALLEL AT 30 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3.506	-1.8 QP	29.54	-31.34	1	114	41.8	-3.6
2	7.378	-3.7 QP	29.54	-33.24	1	114	39.6	-3.3
3	13.56	10.4 QP	29.54	-19.14	1	179	53.8	-3.4
4	17.693	5.5 QP	29.54	-24.04	1	334	49.6	-4.1
5	23.131	15.1 QP	29.54	-14.44	1	172	59.2	-4.1

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. Loop antenna was used for all radiated emission below 30MHz.
6. Data @3m=Data @30m-40log(30 / 3)=Data @30m-40



Above 30MHz Data:

Charging Mode


<b>TEST FREQUENCY</b>	127.795 kHz / 326.5 kHz	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	62.96	31.2 QP	40.0	-8.8	2.55 H	179	40.1	-8.9
2	111.06	34.4 QP	43.5	-9.1	3.00 H	143	45.0	-10.6
3	159.01	37.8 QP	43.5	-5.7	2.02 H	305	45.7	-7.9
4	229.35	40.3 QP	46.0	-5.7	1.10 H	295	50.1	-9.8
5	340.69	38.8 QP	46.0	-7.2	1.50 H	243	44.8	-6.0
6	536.00	38.4 QP	46.0	-7.6	1.50 H	269	39.5	-1.1

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.




<b>TEST FREQUENCY</b>	127.795 kHz / 326.5 kHz	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	44.50	36.8 QP	40.0	-3.2	1.00 V	254	45.0	-8.2
2	113.12	34.2 QP	43.5	-9.3	1.16 V	265	44.6	-10.4
3	167.19	33.4 QP	43.5	-10.1	1.10 V	264	41.7	-8.3
4	235.95	34.3 QP	46.0	-11.7	2.23 V	341	43.4	-9.1
5	341.63	33.8 QP	46.0	-12.2	1.59 V	271	39.8	-6.0
6	535.74	39.6 QP	46.0	-6.4	1.00 V	142	40.7	-1.1

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.




Standby Mode

<b>TEST FREQUENCY</b>	127.795 kHz / 326.5 kHz	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	62.96	30.2 QP	40.0	-9.8	2.50 H	114	39.1	-8.9
2	111.07	34.3 QP	43.5	-9.2	3.00 H	241	44.9	-10.6
3	159.01	37.7 QP	43.5	-5.8	1.50 H	145	45.6	-7.9
4	229.35	40.3 QP	46.0	-5.7	1.10 H	238	50.1	-9.8
5	340.68	38.3 QP	46.0	-7.7	1.00 H	243	44.3	-6.0
6	536.00	37.4 QP	46.0	-8.6	1.50 H	164	38.5	-1.1

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.




<b>TEST FREQUENCY</b>	127.795 kHz / 326.5 kHz	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	44.50	37.0 QP	40.0	-3.0	1.00 V	221	45.2	-8.2
2	113.13	33.5 QP	43.5	-10.0	1.05 V	249	43.9	-10.4
3	167.18	33.5 QP	43.5	-10.0	1.00 V	249	41.8	-8.3
4	235.96	34.3 QP	46.0	-11.7	2.00 V	269	43.4	-9.1
5	341.65	33.3 QP	46.0	-12.7	2.00 V	178	39.3	-6.0
6	535.76	39.5 QP	46.0	-6.5	1.00 V	264	40.6	-1.1

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.



## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

For Charging Mode:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 24, 2018	Oct. 23, 2019
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 22, 2018	Oct. 21, 2019
Line-Impedance Stabilization Network (for Peripheral) R&S	ESH3-Z5	835239/001	Mar. 17, 2019	Mar. 16, 2020
50 ohms Terminator	N/A	3	Oct. 22, 2018	Oct. 21, 2019
RF Cable	5D-FB	COCCAB-001	Sep. 27, 2019	Sep. 26, 2020
Fixed attenuator EMCI	STI02-2200-10	003	Mar. 14, 2019	Mar. 13, 2020
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

**Note:**

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
- 3 Tested Date: Oct. 07, 2019

For Standby Mode:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 23, 2019	Oct. 22, 2020
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 23, 2019	Oct. 22, 2020
Line-Impedance Stabilization Network (for Peripheral) R&S	ESH3-Z5	835239/001	Mar. 17, 2019	Mar. 16, 2020
50 ohms Terminator	N/A	3	Oct. 23, 2019	Oct. 22, 2020
RF Cable	5D-FB	COCCAB-001	Sep. 27, 2019	Sep. 26, 2020
Fixed attenuator EMCI	STI02-2200-10	003	Mar. 14, 2019	Mar. 13, 2020
Software BVADT	BVADT_Cond_V7.3.7.4	NA	NA	NA

**Note:**

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
- 3 Tested Date: Nov. 19, 2019

#### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (AV) and average detection (AV) at frequency 0.15MHz-30MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



Note: Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Conditions

Same as item 4.1.6.



#### 4.2.7 Test Results


##### Charging Mode

<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function</b>	Quasi-Peak (QP) / Average (AV)
------------------------	----------------	--------------------------	--------------------------------

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.99	49.42	32.65	59.41	42.64	66.00	56.00	-6.59	-13.36
2	0.15780	9.99	41.19	25.72	51.18	35.71	65.58	55.58	-14.40	-19.87
3	0.16952	9.99	37.03	21.64	47.02	31.63	64.98	54.98	-17.96	-23.35
4	0.19686	9.99	41.46	27.32	51.45	37.31	63.74	53.74	-12.29	-16.43
5	0.52110	10.01	31.14	26.79	41.15	36.80	56.00	46.00	-14.85	-9.20
6	3.45312	10.22	26.65	15.61	36.87	25.83	56.00	46.00	-19.13	-20.17
7	10.01171	10.65	26.76	18.73	37.41	29.38	60.00	50.00	-22.59	-20.62

##### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function</b>	Quasi-Peak (QP) / Average (AV)
------------------------	----------------	--------------------------	--------------------------------

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.99	48.16	32.65	58.15	42.64	66.00	56.00	-7.85	-13.36
2	0.16171	9.99	37.59	22.36	47.58	32.35	65.38	55.38	-17.80	-23.03
3	0.19296	9.99	39.26	26.26	49.25	36.25	63.91	53.91	-14.66	-17.66
4	0.22421	9.99	35.12	21.05	45.11	31.04	62.66	52.66	-17.55	-21.62
5	0.58748	10.02	28.85	23.19	38.87	33.21	56.00	46.00	-17.13	-12.79
6	3.52343	10.20	28.13	16.76	38.33	26.96	56.00	46.00	-17.67	-19.04
7	11.39452	10.66	29.02	21.35	39.68	32.01	60.00	50.00	-20.32	-17.99

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Standby Mode

<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function</b>	Quasi-Peak (QP) / Average (AV)
------------------------	----------------	--------------------------	--------------------------------

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15781	9.97	29.88	12.65	39.85	22.62	65.58	55.58	-25.73	-32.96
2	0.20078	9.97	25.68	12.61	35.65	22.58	63.58	53.58	-27.93	-31.00
3	0.56016	9.99	20.10	12.94	30.09	22.93	56.00	46.00	-25.91	-23.07
4	0.98203	10.03	8.05	0.47	18.08	10.50	56.00	46.00	-37.92	-35.50
5	3.21094	10.19	14.18	0.55	24.37	10.74	56.00	46.00	-31.63	-35.26
6	12.45313	10.89	14.12	1.89	25.01	12.78	60.00	50.00	-34.99	-37.22

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function</b>	Quasi-Peak (QP) / Average (AV)
------------------------	----------------	--------------------------	--------------------------------

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.98	29.13	10.72	39.11	20.70	66.00	56.00	-26.89	-35.30
2	0.16953	9.98	26.05	11.08	36.03	21.06	64.98	54.98	-28.95	-33.92
3	0.27109	9.99	18.87	4.76	28.86	14.75	61.08	51.08	-32.22	-36.33
4	0.56406	10.01	25.16	14.83	35.17	24.84	56.00	46.00	-20.83	-21.16
5	3.30859	10.20	11.48	-1.53	21.68	8.67	56.00	46.00	-34.32	-37.33
6	11.08203	10.70	12.25	3.08	22.95	13.78	60.00	50.00	-37.05	-36.22

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

### Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

### Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

### Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---