



# FCC TEST REPORT

**REPORT NO.:** RF130619E01

**MODEL NO.:** M-R0048

**FCC ID:** JNZMR0048

**RECEIVED:** June 19, 2013

**TESTED:** June 21, 2013

**ISSUED:** June 27, 2013

**APPLICANT:** LOGITECH FAR EAST LTD.

**ADDRESS:** #2 Creation Rd. 4, Science-Based Ind. Park Hsinchu  
Taiwan, R.O.C.

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.) Ltd.,  
Taoyuan Branch

**LAB ADDRESS :** No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

**TEST LOCATION (1):** No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

**TEST LOCATION (2):** No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung  
Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



## Table of Contents

RELEASE CONTROL RECORD.....	3
1 CERTIFICATION .....	4
2 SUMMARY OF TEST RESULTS .....	5
2.1 MEASUREMENT UNCERTAINTY.....	5
3 GENERAL INFORMATION.....	6
3.1 GENERAL DESCRIPTION OF EUT .....	6
3.2 DESCRIPTION OF TEST MODES .....	7
3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL .....	7
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	8
3.5 DESCRIPTION OF SUPPORT UNITS .....	9
3.6 CONFIGURATION OF SYSTEM UNDER TEST .....	9
4 TEST PROCEDURES AND RESULTS.....	10
4.1 RADIATED EMISSION AND BAND EDGE MEASUREMENT .....	10
4.1.1 LIMITS OF RADIATED EMISSION AND BAND EDGE MEASUREMENT.....	10
4.1.2 TEST INSTRUMENTS .....	11
4.1.3 TEST PROCEDURES .....	12
4.1.4 DEVIATION FROM TEST STANDARD .....	12
4.1.5 TEST SETUP .....	13
4.1.6 EUT OPERATING CONDITIONS .....	13
4.1.7 TEST RESULTS .....	14
5 PHOTOGRAPHS OF THE TEST CONFIGURATION.....	19
6 INFORMATION ON THE TESTING LABORATORIES .....	20
7 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....	21



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF130619E01	Original release	June 27, 2013



# 1 CERTIFICATION

**PRODUCT :** 2.4GHz Cordless Mouse  
**BRAND NAME :** Logitech  
**MODEL NO. :** M-R0048  
**TEST SAMPLE :** ENGINEERING SAMPLE  
**APPLICANT :** LOGITECH FAR EAST LTD.  
**TESTED :** June 21, 2013  
**STANDARDS :** **FCC Part 15, Subpart C (Section 15.249)**  
ANSI C63.10-2009

The above equipment (Model: M-R0048) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY :** , **DATE:** June 27, 2013  
(Lori Chung, Specialist)

**APPROVED BY :** , **DATE:** June 27, 2013  
(\*May Chen, Manager)

## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C (Section 15.249)			
STANDARD PARAGRAPH	TEST TYPE	RESULT	REMARK
15.207	Conducted Emission Test	NA	Power from battery.
15.209 15.249 15.249 (d)	Radiated Emission Test Band Edge Measurement Limit: 50dB less than the peak value of fundamental frequency or meet radiated emission limit in section 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -4.9dB at 57.50MHz

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Radiated emissions (30MHz-1GHz)	5.63 dB
Radiated emissions (1GHz -6GHz)	3.73 dB
Radiated emissions (6GHz -18GHz)	3.90 dB
Radiated emissions (18GHz -40GHz)	4.11 dB

### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	2.4GHz Cordless Mouse
<b>MODEL NO.</b>	M-R0048
<b>POWER SUPPLY</b>	DC 1.5V from battery
<b>MODULATION TYPE</b>	GFSK
<b>CARRIER FREQUENCY OF EACH CHANNEL</b>	2405MHz ~ 2474MHz
<b>NUMBER OF CHANNEL</b>	12
<b>ANTENNA TYPE</b>	PCB printed antenna with -3.43dBi antenna gain
<b>DATA CABLE</b>	NA
<b>I/O PORTS</b>	Refer to user's manual
<b>ASSOCIATED DEVICES</b>	2.4GHz Transceiver × 1 USB Stand × 1

**NOTE:**

1. The EUT operates in the 2.4GHz frequency spectrum and complies with GFSK techniques.
2. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 DESCRIPTION OF TEST MODES

Twelve channels are provided in this EUT.

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
1	2405	4	2417	7	2441	10	2465
2	2408	5	2432	8	2444	11	2471
3	2414	6	2435	9	2462	12	2474

### 3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO			DESCRIPTION
	RE <sup>3</sup> 1G	RE<1G	PLC	
-	√	√	-	-

Where **RE<1G**: Radiated Emission below 1GHz      **RE<sup>3</sup>1G**: Radiated Emission above 1GHz  
**PLC**: Power Line Conducted Emission

**NOTE**: No need to concern of Conducted Emission due to the EUT is powered by battery

#### RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
1 to 12	12	GFSK

#### RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
1 to 12	1, 8, 12	GFSK

#### TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
<b>RE<sup>3</sup>1G</b>	23deg. C, 64%RH	DC 1.5V	Tim Ho
<b>RE&lt;1G</b>	25deg. C, 68%RH	DC 1.5V	Tim Ho



### **3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (Section 15.249)**

ANSI C63.10-2009

All tests have been performed and recorded as per the above standards.






A D T

### 3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit.

### 3.6 CONFIGURATION OF SYSTEM UNDER TEST



## 4 TEST PROCEDURES AND RESULTS

### 4.1 RADIATED EMISSION AND BAND EDGE MEASUREMENT

#### 4.1.1 LIMITS OF RADIATED EMISSION AND BAND EDGE MEASUREMENT

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
902 ~ 928 MHz	50	500
2400 ~ 2483.5 MHz	50	500
5725 ~ 5875 MHz	50	500
24 ~ 24.25 GHz	250	2500

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits as below table, whichever is the lesser attenuation

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer Agilent	E4446A	MY48250253	Sep. 03, 2012	Sep. 02, 2013
MXE EMI Receiver Agilent	N9038A	MY51210105	Jan. 29, 2013	Jan. 28, 2014
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-03	Nov. 14, 2012	Nov. 13, 2013
Pre-Amplifier Agilent	8449B	3008A02578	June 26, 2012	June 25, 2013
Pre-Amplifier SPACEK LABS	SLKKa-48-6	9K16	Nov. 14, 2012	Nov. 13, 2013
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-360	Mar. 19, 2013	Mar. 18, 2014
Horn_Antenna AISi	AIH.8018	0000320091110	Nov. 19, 2012	Nov. 18, 2013
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 12, 2012	Oct. 11, 2013
RF Cable	NA	RF104-201 RF104-203 RF104-204	Dec. 25, 2012	Dec. 24, 2013
RF Cable	NA	CHGCAB_001	Oct. 06, 2012	Oct. 05, 2013
Software	ADT_Radiated _V8.7.07	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

**Note:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 3 The test was performed in 966 Chamber No. G.
4. The FCC Site Registration No. is 966073.
- 5 The VCCI Site Registration No. is G-137.
- 6 The CANADA Site Registration No. is IC 7450H-2.
- 7 Tested Date: June 21, 2013

#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.


**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.1.6 EUT OPERATING CONDITIONS

Set the EUT under transmission / receiver condition continuously at specific channel frequency.

#### 4.1.7 TEST RESULTS

##### BELOW 1GHz WORST-CASE DATA

<b>CHANNEL</b>	TX Channel 12	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	Below 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	57.50	35.1 QP	40.0	-4.9	1.50 H	10	49.30	-14.18
2	62.69	27.7 QP	40.0	-12.3	1.00 H	357	41.74	-14.07
3	142.18	32.1 QP	43.5	-11.4	2.00 H	240	45.68	-13.55
4	185.69	28.3 QP	43.5	-15.2	1.50 H	320	43.86	-15.55
5	274.20	23.3 QP	46.0	-22.7	2.00 H	343	36.95	-13.64
6	319.79	32.1 QP	46.0	-13.9	1.00 H	96	44.07	-11.94
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.58	31.8 QP	40.0	-8.3	1.00 V	199	46.32	-14.57
2	75.44	29.8 QP	40.0	-10.2	2.00 V	11	47.06	-17.28
3	93.92	35.9 QP	43.5	-7.6	1.50 V	106	54.82	-18.88
4	182.78	30.4 QP	43.5	-13.1	1.00 V	127	45.82	-15.45
5	236.32	31.6 QP	46.0	-14.5	1.00 V	101	46.91	-15.36
6	306.55	23.1 QP	46.0	-22.9	1.50 V	235	35.60	-12.52

##### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



A D T

**ABOVE 1GHz DATA**

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2400.00	46.5 PK	74.0	-27.5	1.14 H	174	75.36	-28.86
2	2400.00	9.6 AV	54.0	-44.4	1.14 H	174	38.46	-28.86
3	*2405.00	94.8 PK	114.0	-19.2	1.14 H	174	123.66	-28.86
4	*2405.00	57.9 AV	94.0	-36.1	1.14 H	174	86.76	-28.86
5	4810.00	55.9 PK	74.0	-18.1	1.51 H	61	81.57	-25.67
6	4810.00	19.0 AV	54.0	-35.0	1.51 H	61	44.67	-25.67
7	7215.00	59.4 PK	74.0	-14.6	1.52 H	209	83.49	-24.09
8	7215.00	22.5 AV	54.0	-31.5	1.52 H	209	46.59	-24.09

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2400.00	46.8 PK	74.0	-27.2	1.06 V	147	75.66	-28.86
2	2400.00	9.9 AV	54.0	-44.1	1.06 V	147	38.76	-28.86
3	*2405.00	83.4 PK	114.0	-30.6	1.06 V	147	112.26	-28.86
4	*2405.00	46.5 AV	94.0	-47.5	1.06 V	147	75.36	-28.86
5	4810.00	56.2 PK	74.0	-17.8	1.00 V	294	81.87	-25.67
6	4810.00	19.3 AV	54.0	-34.7	1.00 V	294	44.97	-25.67
7	7215.00	59.5 PK	74.0	-14.5	1.52 V	201	83.59	-24.09
8	7215.00	22.6 AV	54.0	-31.4	1.52 V	201	46.69	-24.09

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. The average value of fundamental frequency is: Average = Peak value + 20 log(Duty cycle)  
Where the duty factor is calculated from following formula: 20 log (Duty cycle) = 20 log (0.115 ms / 8.035 ms) = -36.9 dB Please see page 18 for plotted duty.



A D T

<b>CHANNEL</b>	TX Channel 8	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2444.00	96.0 PK	114.0	-18.0	1.13 H	209	124.80	-28.80
2	*2444.00	59.1 AV	94.0	-34.9	1.13 H	209	87.90	-28.80
3	4888.00	56.1 PK	74.0	-17.9	1.49 H	53	81.68	-25.58
4	4888.00	19.2 AV	54.0	-34.8	1.49 H	53	44.78	-25.58
5	7332.00	59.2 PK	74.0	-14.8	1.54 H	211	83.27	-24.07
6	7332.00	22.3 AV	54.0	-31.7	1.54 H	211	46.37	-24.07

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2444.00	83.9 PK	114.0	-30.1	1.06 V	303	112.70	-28.80
2	*2444.00	47.0 AV	94.0	-47.0	1.06 V	303	75.80	-28.80
3	4888.00	55.4 PK	74.0	-18.6	1.02 V	278	80.98	-25.58
4	4888.00	18.5 AV	54.0	-35.5	1.02 V	278	44.08	-25.58
5	7332.00	60.4 PK	74.0	-13.6	1.53 V	204	84.47	-24.07
6	7332.00	23.5 AV	54.0	-30.5	1.53 V	204	47.57	-24.07

**REMARKS:**

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " \* ": Fundamental frequency.
- The average value of fundamental frequency is: Average = Peak value + 20 log(Duty cycle)  
Where the duty factor is calculated from following formula: 20 log (Duty cycle) = 20 log (0.115 ms / 8.035 ms) = -36.9 dB Please see page 18 for plotted duty.





A D T

<b>CHANNEL</b>	TX Channel 12	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2474.00	96.1 PK	114.0	-17.9	1.11 H	210	124.87	-28.77
2	*2474.00	59.2 AV	94.0	-34.8	1.11 H	210	87.97	-28.77
3	2483.50	46.3 PK	74.0	-27.7	1.11 H	210	75.05	-28.75
4	2483.50	9.4 AV	54.0	-44.6	1.11 H	210	38.15	-28.75
5	4948.00	55.9 PK	74.0	-18.1	1.51 H	60	81.47	-25.57
6	4948.00	19.0 AV	54.0	-35.0	1.51 H	60	44.57	-25.57
7	7422.00	59.6 PK	74.0	-14.4	1.54 H	197	83.60	-24.00
8	7422.00	22.7 AV	54.0	-31.3	1.54 H	197	46.70	-24.00

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**


NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2474.00	88.2 PK	114.0	-25.8	1.05 V	301	116.97	-28.77
2	*2474.00	51.3 AV	94.0	-42.7	1.05 V	301	80.07	-28.77
3	2483.50	46.8 PK	74.0	-27.2	1.05 V	301	75.55	-28.75
4	2483.50	9.9 AV	54.0	-44.1	1.05 V	301	38.65	-28.75
5	4948.00	56.0 PK	74.0	-18.0	1.00 V	285	81.57	-25.57
6	4948.00	19.1 AV	54.0	-34.9	1.00 V	285	44.67	-25.57
7	7422.00	59.8 PK	74.0	-14.2	1.53 V	204	83.80	-24.00
8	7422.00	22.9 AV	54.0	-31.1	1.53 V	204	46.90	-24.00

**REMARKS:**

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " \* ": Fundamental frequency.
- The average value of fundamental frequency is: Average = Peak value + 20 log(Duty cycle)  
Where the duty factor is calculated from following formula: 20 log (Duty cycle) = 20 log (0.115 ms / 8.035 ms) = -36.9 dB Please see page 18 for plotted duty.



A D T



A D T

$$20 \log (\text{Duty cycle}) = 20 \log (0.115 \text{ ms} / 8.035 \text{ ms}) = -36.9 \text{ dB}$$



A D T

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



## 6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180

Fax: 886-2-26052943

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety/Telecom Lab:**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.



A D T

## **7 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No modifications were made to the EUT by the lab during the test.

--- END ---