

RF EXPOSURE REPORT

CERTIFICATE OF CONFORMITY

FCC Rule Part: FCC Part 2 (Section 2.1091 & 2.1093)

Report No.: MFBDKG-WTW-P22070918

FCC ID: JNZMR0096

Model No.: MR0096

Received Date: 2022/5/21

Test Date: 2022/8/12 **Issued Date**: 2022/9/6

Applicant: Logitech Far East Ltd.

Address: 7700 Gateway Boulevard Newark California United States

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan **Test Location:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan

FCC Registration / 723255 / TW2022

Designation Number:

Approved by:	\sim		, Date:	2022/9/6	
	May	Chen / Manager			

This test report consists of 9 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.





Prepared by : Vito Lung / Specialist



Table of Contents

Rele	ase Control Record	3
	Certificate	
	Applicable RF Exposure Limit	
	Applicable Evaluation Criteria	
	Test Results	
4.1	1 RF Exposure	7
5	Conclusion	8
6	Information of the Testing Laboratories	9



Release Control Record

Issue No.	Description	Date Issued
MFBDKG-WTW-P22070918	Original release.	2022/9/6

Report No.: MFBDKG-WTW-P22070918 Page No. 3 / 9 Report Format Version: 7.1.0



1 Certificate

Product: Wireless Mouse

Brand: Logitech

Test Model: MR0096

Sample Status: Engineering sample

Applicant: Logitech Far East Ltd.

Test Date: 2022/8/12

FCC Rule Part: FCC Part 2 (Section 2.1091 & 2.1093)

Standard: KDB 447498 D04 Interim General RF Exposure Guidance v01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.



2 Applicable RF Exposure Limit

- § 1.1310 Radiofrequency radiation exposure limits.
- (a) Specific absorption rate (SAR) shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in § 1.1307(b) of this part within the frequency range of 100 kHz to 6 GHz (inclusive).
- (b) The SAR limits for occupational/controlled exposure are 0.4 W/kg, as averaged over the whole body, and a peak spatialaverage SAR of 8 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit for occupational/controlled exposure is 20 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 6 minutes to determine compliance with occupational/controlled SAR limits.
- (c) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

(e) Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields

Limits for General Population/Uncontrolled Exposure

Littilis for General F optilation/officontrolled Exposure									
Frequency Range (MHz) Electric Field Strength (V/m)		Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)					
	Limits For General Population / Uncontrolled Exposure								
0.3-1.34	614	1.63	(100)*	30					
1.34-30	824/f	2.19/f	(180/f ²)*	30					
30-300	27.5	0.073	0.2	30					
300-1500			f/1500	30					
1500-100,000			1.0	30					

f = frequency in MHz. * = Plane-wave equivalent power density.

Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)				
Limits For General Population / Uncontrolled Exposure								
0.3-3.0	614	1.63	*(100)	⊴6				
3.0-30	1842/f	4.89/f	*(900/f²)	<6				
30-300	61.4	0.163	1.0	<6				
300-1,500			f/300	<6				
1,500-100,000			5	<6				

f = frequency in MHz. * = Plane-wave equivalent power density.

Report No.: MFBDKG-WTW-P22070918 Page No. 5 / 9 Report Format Version: 7.1.0



3 Applicable Evaluation Criteria

Exemption Evaluation

SAR-based Exemption - §1.1307(b)(3)(i)(B)

➤ The SAR-based exemption formula of §1.1307(b)(3)(i)(B), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW). This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz.

$$P_{\text{th}} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \le 20 \text{ cm} \\ \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \le 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20}\,\mathrm{cm}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm)

When 10-g extremity SAR applies, SAR test exemption may beconsidered by applying a factor of 2.5 to the SAR-based exemption thresholds.

Report No.: MFBDKG-WTW-P22070918 Page No. 6 / 9 Report Format Version: 7.1.0



4 Test Results

4.1 RF Exposure

Environmental Conditions:	25°C, 60% RH	Tested By:	John Peng
---------------------------	--------------	------------	-----------

SAR-based Exemption (10-g extremity SAR)							
Operation Mode	Frequency Band (MHz)	Average Power (mW)	Antenna Gain (dBi)	Maximum ERP (mW)	Distance (cm)	Limit Threshold (mW)	Test Result
Bluetooth	2402-2480	2.786	1.76	2.547	0.5	6.793	Pass

Report No.: MFBDKG-WTW-P22070918 Page No. 7 / 9 Report Format Version: 7.1.0



5 Conclusion

Source-base time average power is below Exemption Criteria and/or Routine Evaluation MPE thresholds, therefore the device is compliant FCC RF exposure requirement.

Report No.: MFBDKG-WTW-P22070918 Page No. 8 / 9 Report Format Version: 7.1.0



6 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180 Fax: 886-2-26051924

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@bureauveritas.com. web Site: http://ee.bureauveritas.com. two.decom.

The address and road map of all our labs can be found in our web site also.

--- END ---

Report No.: MFBDKG-WTW-P22070918 Page No. 9 / 9 Report Format Version: 7.1.0