



A D T

FCC TEST REPORT

REPORT NO.: RF131022E05

MODEL NO.: R-R0008

FCC ID: JNZRR0008

RECEIVED: Oct. 22, 2013

TESTED: Oct. 28 to 29, 2013

ISSUED: Nov. 05, 2013

APPLICANT: LOGITECH FAR EAST LTD.

ADDRESS: #2 Creation Rd. 4, Science-Based Ind. Park Hsinchu
Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd.,
Taoyuan Branch

LAB ADDRESS : No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

TEST LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

TEST LOCATION (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung
Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

This report should not be used by the client to claim
product certification, approval, or endorsement by
TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



A D T

Table of Contents

RELEASE CONTROL RECORD	3
1 CERTIFICATION	4
2 SUMMARY OF TEST RESULTS	5
2.1 MEASUREMENT UNCERTAINTY	5
3 GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF EUT	6
3.2 DESCRIPTION OF TEST MODES	6
3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	7
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS	8
3.5 DESCRIPTION OF SUPPORT UNITS	9
3.6 CONFIGURATION OF SYSTEM UNDER TEST	9
4 TEST PROCEDURES AND RESULTS	10
4.1 RADIATED EMISSION AND BAND EDGE MEASUREMENT	10
4.1.1 LIMITS OF RADIATED EMISSION AND BAND EDGE MEASUREMENT	10
4.1.2 TEST INSTRUMENTS	11
4.1.3 TEST PROCEDURES	12
4.1.4 DEVIATION FROM TEST STANDARD	12
4.1.5 TEST SETUP	13
4.1.6 EUT OPERATING CONDITIONS	14
4.1.7 TEST RESULTS	15
5 PHOTOGRAPHS OF THE TEST CONFIGURATION	20
6 INFORMATION ON THE TESTING LABORATORIES	21
7 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	22



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF131022E05	Original release	Nov. 05, 2013



A D T

1 CERTIFICATION

PRODUCT : Wireless Presenter

BRAND NAME : Logitech

MODEL NO. : R-R0008

TEST SAMPLE : ENGINEERING SAMPLE

APPLICANT : LOGITECH FAR EAST LTD.

TESTED : Oct. 28 to 29, 2013

STANDARDS : FCC Part 15, Subpart C (Section 15.249)

ANSI C63.10-2009

The above equipment (Model: R-R0008) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : , **DATE:** Nov. 05, 2013
(Claire Kuan, Specialist)

APPROVED BY : , **DATE:** Nov. 05, 2013
(May Chen, Manager)



A D T

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C (Section 15.249)			
STANDARD PARAGRAPH	TEST TYPE	RESULT	REMARK
15.207	Conducted Emission Test	NA	Power from battery.
15.209	Radiated Emission Test		
15.249	Band Edge Measurement		Meet the requirement of limit.
15.249 (d)	Limit: 50dB less than the peak value of fundamental frequency or meet radiated emission limit in section 15.209	PASS	Minimum passing margin is -9.5dB at 2400.00MHz

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Radiated emissions (30MHz-1GHz)	5.46 dB
Radiated emissions (1GHz -6GHz)	3.54 dB
Radiated emissions (6GHz -18GHz)	4.08 dB
Radiated emissions (18GHz -40GHz)	4.11 dB



A D T

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless Presenter
MODEL NO.	R-R0008
POWER SUPPLY	DC 3V from batteries
MODULATION TYPE	GFSK
CARRIER FREQUENCY OF EACH CHANNEL	2405MHz ~ 2474MHz
NUMBER OF CHANNEL	12
ANTENNA TYPE	PCB printed antenna (Gain: 0.22dBi)
DATA CABLE	NA
I/O PORTS	Refer to user's manual
ASSOCIATED DEVICES	2.4GHz Transceiver x 1 (Brand: Logitech / Model: C-U0014)

NOTE:

1. The EUT operates in the 2.4GHz frequency spectrum and complies with GFSK techniques.
2. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

12 channels are provided in this EUT.

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
1	2405	4	2417	7	2441	10	2465
2	2408	5	2432	8	2444	11	2471
3	2414	6	2435	9	2462	12	2474



A D T

3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO			DESCRIPTION
	RE \geq 1G	RE $<$ 1G	PLC	
-	✓	✓	-	-

Where

RE $<$ 1G: Radiated Emission below 1GHz

RE \geq 1G: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

NOTE:

1. No need to concern of Conducted Emission due to the EUT is powered by battery
2. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
1 to 12	1	GFSK

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
1 to 12	1, 8, 12	GFSK

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE \geq 1G	23deg. C, 65%RH	DC 3V	Robert Cheng
RE $<$ 1G	23deg. C, 65%RH	DC 3V	Robert Cheng



A D T

3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (Section 15.249)

ANSI C63.10-2009

All tests have been performed and recorded as per the above standards.




A D T

3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit.

3.6 CONFIGURATION OF SYSTEM UNDER TEST



TEST TABLE



A D T

4 TEST PROCEDURES AND RESULTS

4.1 RADIATED EMISSION AND BAND EDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BAND EDGE MEASUREMENT

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
902 ~ 928 MHz	50	500
2400 ~ 2483.5 MHz	50	500
5725 ~ 5875 MHz	50	500
24 ~ 24.25 GHz	250	2500

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits as below table, whichever is the lesser attenuation

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009 ~ 0.490	$2400/F(\text{kHz})$	300
0.490 ~ 1.705	$24000/F(\text{kHz})$	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_uV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
MXE EMI Receiver Agilent	N9038A	MY50010156	Jan. 16, 2013	Jan. 15, 2014
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-04	Nov. 14, 2012	Nov. 13, 2013
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Mar. 25, 2013	Mar. 24, 2014
RF Cable	NA	CHHCAB_001	Oct. 06, 2013	Oct. 05, 2014
Horn_Antenna AISI	AIH.8018	0000220091110	Nov. 27, 2012	Nov. 26, 2013
Pre-Amplifier Agilent	8449B	3008A01923	Oct. 30, 2012	Oct. 29, 2013
RF Cable	NA	RF104-205 RF104-207 RF104-202	Dec. 26, 2012	Dec. 25, 2013
Spectrum Analyzer Agilent	E4446A	MY48250253	Aug. 28, 2013	Aug. 27, 2014
Pre-Amplifier SPACEK LABS	SLKKa-48-6	9K16	Nov. 14, 2012	Nov. 13, 2013
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 08, 2013	Oct. 07, 2014
Software	ADT_Radiated_V8.7.07	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in 966 Chamber No. H.
4. The FCC Site Registration No. is 797305.
5. The CANADA Site Registration No. is IC 7450H-3.
6. Tested Date: Oct. 29, 2013



A D T

4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD


No deviation

4.1.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



A D T

4.1.6 EUT OPERATING CONDITIONS

Set the EUT under transmission / receiver condition continuously at specific channel frequency.



A D T

4.1.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	Below 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	50.12	13.2 QP	40.0	-26.8	1.47 H	76	26.30	-13.09
2	162.41	14.0 QP	43.5	-29.5	1.00 H	176	26.76	-12.80
3	246.20	18.5 QP	46.0	-27.5	1.56 H	183	32.41	-13.91
4	316.70	20.1 QP	46.0	-25.9	1.35 H	165	31.22	-11.12
5	486.82	19.2 QP	46.0	-26.8	1.00 H	339	26.67	-7.47
6	940.62	26.7 QP	46.0	-19.3	1.45 H	135	25.65	1.07

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	50.52	18.4 QP	40.0	-21.7	2.00 V	131	31.33	-12.98
2	76.75	19.7 QP	40.0	-20.3	1.00 V	115	36.71	-17.00
3	144.61	26.0 QP	43.5	-17.5	1.00 V	219	38.62	-12.64
4	245.92	27.9 QP	46.0	-18.1	1.00 V	121	41.84	-13.91
5	314.02	28.5 QP	46.0	-17.5	1.00 V	360	39.55	-11.03
6	376.53	22.4 QP	46.0	-23.6	1.00 V	253	32.23	-9.86

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
 - Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



A D T

ABOVE 1GHz DATA

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2400.00	64.5 PK	74.0	-9.5	1.10 H	36	67.92	-3.42
2	2400.00	23.7 AV	54.0	-30.3	1.10 H	36	27.12	-3.42
3	*2405.00	95.1 PK	114.0	-18.9	1.10 H	36	98.51	-3.41
4	*2405.00	54.3 AV	94.0	-39.7	1.10 H	36	57.71	-3.41
5	4810.00	54.9 PK	74.0	-19.1	1.47 H	354	48.43	6.47
6	4810.00	14.1 AV	54.0	-39.9	1.47 H	354	7.63	6.47
7	7215.00	64.2 PK	74.0	-9.8	1.59 H	153	53.32	10.88
8	7215.00	23.4 AV	54.0	-30.6	1.59 H	153	12.52	10.88

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2400.00	58.5 PK	74.0	-15.5	1.70 V	20	61.92	-3.42
2	2400.00	17.7 AV	54.0	-36.3	1.70 V	20	21.12	-3.42
3	*2405.00	88.0 PK	114.0	-26.0	1.70 V	20	91.41	-3.41
4	*2405.00	47.2 AV	94.0	-46.8	1.70 V	20	50.61	-3.41
5	4810.00	53.7 PK	74.0	-20.3	1.09 V	150	47.23	6.47
6	4810.00	12.9 AV	54.0	-41.1	1.09 V	150	6.43	6.47
7	7215.00	61.2 PK	74.0	-12.8	1.00 V	341	50.32	10.88
8	7215.00	20.4 AV	54.0	-33.6	1.00 V	341	9.52	10.88

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The average value of fundamental frequency is: Average = Peak value + 20 log(Duty cycle)
Where the duty factor is calculated from following formula:
20 log (Duty cycle) = 20 log (0.098 ms / 10.77 ms) = -40.8 dB
Please see page 18 for plotted duty.



A D T

CHANNEL	TX Channel 8	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2444.00	94.8 PK	114.0	-19.2	1.10 H	36	98.09	-3.29
2	*2444.00	54.0 AV	94.0	-40.0	1.10 H	36	57.29	-3.29
3	4888.00	53.8 PK	74.0	-20.2	1.55 H	360	47.26	6.54
4	4888.00	13.0 AV	54.0	-41.0	1.55 H	360	6.46	6.54
5	7332.00	62.7 PK	74.0	-11.3	1.46 H	174	51.52	11.18
6	7332.00	21.9 AV	54.0	-32.1	1.46 H	174	10.72	11.18
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2444.00	87.9 PK	114.0	-26.1	1.71 V	20	91.19	-3.29
2	*2444.00	47.1 AV	94.0	-46.9	1.71 V	20	50.39	-3.29
3	4888.00	52.9 PK	74.0	-21.1	1.08 V	142	46.36	6.54
4	4888.00	12.1 AV	54.0	-41.9	1.08 V	142	5.56	6.54
5	7332.00	57.6 PK	74.0	-16.4	1.05 V	359	46.42	11.18
6	7332.00	16.8 AV	54.0	-37.2	1.05 V	359	5.62	11.18

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The average value of fundamental frequency is: Average = Peak value + 20 log(Duty cycle)
Where the duty factor is calculated from following formula:
$$20 \log (\text{Duty cycle}) = 20 \log (0.098 \text{ ms} / 10.77 \text{ ms}) = -40.8 \text{ dB}$$

Please see page 18 for plotted duty.



A D T

CHANNEL	TX Channel 12	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		


ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2474.00	93.7 PK	114.0	-20.3	1.10 H	35	96.89	-3.19
2	*2474.00	52.9 AV	94.0	-41.1	1.10 H	35	56.09	-3.19
3	2483.50	57.9 PK	74.0	-16.1	1.10 H	36	61.06	-3.16
4	2483.50	17.1 AV	54.0	-36.9	1.10 H	36	20.26	-3.16
5	4948.00	54.5 PK	74.0	-19.5	1.49 H	354	47.96	6.54
6	4948.00	13.7 AV	54.0	-40.3	1.49 H	354	7.16	6.54
7	7422.00	63.5 PK	74.0	-10.5	1.52 H	135	52.01	11.49
8	7422.00	22.7 AV	54.0	-31.3	1.52 H	135	11.21	11.49
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2474.00	87.1 PK	114.0	-26.9	1.71 V	20	90.29	-3.19
2	*2474.00	46.3 AV	94.0	-47.7	1.71 V	20	49.49	-3.19
3	2483.50	54.3 PK	74.0	-19.7	1.71 V	20	57.46	-3.16
4	2483.50	13.5 AV	54.0	-40.5	1.71 V	20	16.66	-3.16
5	4948.00	53.2 PK	74.0	-20.8	1.05 V	144	46.66	6.54
6	4948.00	12.4 AV	54.0	-41.6	1.05 V	144	5.86	6.54
7	7422.00	61.7 PK	74.0	-12.3	1.00 V	339	50.21	11.49
8	7422.00	20.9 AV	54.0	-33.1	1.00 V	339	9.41	11.49

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The average value of fundamental frequency is: Average = Peak value + 20 log(Duty cycle)
Where the duty factor is calculated from following formula:
20 log (Duty cycle) = 20 log (0.098 ms / 10.77 ms) = -40.8 dB
Please see page 18 for plotted duty.



A D T





A D T

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



A D T

6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



A D T

7 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---