



A D T

FCC TEST REPORT

REPORT NO.: RF991220E05

MODEL NO.: Y-R0017

FCC ID: JNZYR0017

RECEIVED: Dec. 20, 2010

TESTED: Dec. 21 to 23, 2010

ISSUED: Dec. 28, 2010

APPLICANT: LOGITECH FAR EAST LTD.

ADDRESS: #2 Creation Rd. 4, Science-Based Ind. Park
Hsinchu Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

This test report consists of 25 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.





A D T

Table of Contents

RELEASE CONTROL RECORD	3
1 CERTIFICATION	4
2 SUMMARY OF TEST RESULTS	5
2.1 MEASUREMENT UNCERTAINTY	5
3 GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF EUT	6
3.2 DESCRIPTION OF TEST MODES	7
3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	7
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS	8
3.5 DESCRIPTION OF SUPPORT UNITS	9
3.6 CONFIGURATION OF SYSTEM UNDER TEST	9
4 TEST PROCEDURES AND RESULTS	10
4.1 RADIATED EMISSION MEASUREMENT	10
4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT	10
4.1.2 TEST INSTRUMENTS	11
4.1.3 TEST PROCEDURES	12
4.1.4 DEVIATION FROM TEST STANDARD	12
4.1.5 TEST SETUP	13
4.1.6 EUT OPERATING CONDITIONS	13
4.1.7 TEST RESULTS	14
4.2 CONDUCTED - OUT BAND MEASUREMENT	21
4.2.1 LIMITS OF CONDUCTED - OUT BAND MEASUREMENT	21
4.2.2 TEST INSTRUMENTS	21
4.2.3 TEST PROCEDURE	21
4.2.4 DEVIATION FROM TEST STANDARD	21
4.2.5 EUT OPERATING CONDITION	21
4.2.6 TEST RESULTS	22
5 INFORMATION ON THE TESTING LABORATORIES	24
6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	25



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
Original release	NA	Dec. 28, 2010



A D T

1 CERTIFICATION

PRODUCT : 2.4GHz Cordless Keyboard

BRAND NAME : Logitech

MODEL NO. : Y-R0017

TESTED : Dec. 21 to 23, 2010

TEST SAMPLE : ENGINEERING SAMPLE

APPLICANT : LOGITECH FAR EAST LTD.

STANDARDS : FCC Part 15, Subpart C (Section 15.249)

ANSI C63.4-2003

ANSI C63.10-2009

The above equipment (Model: Y-R0017) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Carol Liao , **DATE:** Dec. 28, 2010
(Carol Liao, Specialist)

APPROVED BY : May Chen , **DATE:** Dec. 28, 2010
(May Chen, Deputy Manager)



A D T

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Paragraph	Test Type	Result	Remark
15.207	Conducted Emission Test	NA	Not Applicable
15.249	Radiated Emission Test	PASS	Minimum passing margin is -6.9dB at 2400.00MHz
15.249	Conducted - Out Band Measurement	PASS	Meet the requirement of limit

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Radiated emissions (30MHz-1GHz)	3.94 dB
Radiated emissions (1GHz-18GHz)	2.49 dB
Radiated emissions (18GHz-40GHz)	2.70 dB



A D T

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	2.4GHz Cordless Keyboard
MODEL NO.	Y-R0017
FCC ID	JNZYR0017
POWER SUPPLY	DC 3V from batteries
MODULATION TYPE	GFSK
OPERATING FREQUENCY	2405MHz ~ 2474MHz
NUMBER OF CHANNEL	12
ANTENNA TYPE	PCB printed antenna with 2.48dBi antenna gain
DATA CABLE	NA
I/O PORTS	NA
ASSOCIATED DEVICES	NA

NOTE:

1. The above EUT information was declared by the manufacturer and for more detailed feature descriptions, please refer to the manufacturer's specifications or User's Manual.



A D T

3.2 DESCRIPTION OF TEST MODES

Twelve channels are provided to this EUT.

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
1	2405	4	2417	7	2441	10	2465
2	2408	5	2432	8	2444	11	2471
3	2414	6	2435	9	2462	12	2474

NOTE:

1. Below 1 GHz, the channel 1, 8, and 12 were pre-tested in chamber. The channel 1, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 8, and 12 were tested individually.

3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	PLC	RE < 1G	RE ≥ 1G	OB	
-	-	√	√	√	-

Where **PLC**: Power Line Conducted Emission

RE < 1G: Radiated Emission below 1GHz

RE ≥ 1G: Radiated Emission above 1GHz

OB: CONDUCTED OUT-BAND EMISSION MEASUREMENT

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
1 to 12	1	GFSK

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
1 to 12	1, 8, 12	GFSK



A D T

3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

47 CFR Part 15, Subpart C (Section 15.249)

ANSI C63.4: 2003

ANSI C63.10: 2009

All tests have been performed and recorded as per the above standards.



A D T

3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit.

3.6 CONFIGURATION OF SYSTEM UNDER TEST





A D T

4 TEST PROCEDURES AND RESULTS

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

According to 15.249 the field strength of emissions from intentional radiators operated under these frequencies bands shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (dBuV/m)	
	Peak	Average
2400 ~ 2483.5	114	94
Field Strength of Harmonics (dBuV/m)		
	74	54

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
ROHDE & SCHWARZ Spectrum Analyzer	FSP40	100036	Dec. 08, 2010	Dec. 07, 2011
Agilent PSA Spectrum Analyzer	E4446A	MY46180622	May 12 , 2010	May 11 , 2011
HP Pre_Amplifier	8449B	300801923	Nov. 01, 2010	Oct. 31, 2011
ROHDE & SCHWARZ Test Receiver	ESCS30	847124/029	Sep. 03, 2010	Sep. 02, 2011
SCHWARZBECK TRILOG Broadband Antenna	VULB 9168	138	Apr. 28, 2010	Apr. 27, 2011
Schwarzbeck Horn_Antenna	BBHA9120	D124	Dec. 17, 2010	Dec. 16, 2011
Schwarzbeck Horn_Antenna	BBHA 9170	BBHA9170153	Jan. 22, 2010	Jan. 21, 2011
RF Switches	EMH-011	1001	NA	NA
RF CABLE (Chaintek)	Sucoflex 104+ Sucoflex 106	RF104-101+R F106-101	Aug. 24, 2010	Aug. 23, 2011
RF Cable	8DFB	STCCAB-30M- 1GHz	NA	NA
Software	ADT_Radiated_V7.6.15.9.2	NA	NA	NA
CT Antenna Tower & Turn Table	NA	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) and Spectrum Analyzer (model: FSP40) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in Open Site No. C.
4. The FCC Site Registration No. is 656396.
5. The VCCI Site Registration No. is R-1626.
6. The CANADA Site Registration No. is IC 7450G-3.



A D T

4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meters open site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

Set the EUT under transmission / receiver condition continuously at specific channel frequency.



A D T

4.1.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Frequency Range		Below 1000MHz
INPUT POWER		Detector Function		Quasi-Peak
ENVIRONMENTAL CONDITIONS		Tested By		Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	58.06	24.5 QP	40.0	-15.5	1.00 H	19	10.70	13.80
2	120.00	20.0 QP	43.5	-23.5	1.21 H	22	7.50	12.50
3	160.00	29.8 QP	43.5	-13.7	1.00 H	252	14.00	15.80
4	248.17	25.4 QP	46.0	-20.6	1.00 H	316	11.60	13.80
5	368.00	25.9 QP	46.0	-20.1	1.00 H	20	8.10	17.80
6	675.24	31.1 QP	46.0	-14.9	1.00 H	20	5.20	25.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	60.00	28.0 QP	40.0	-12.0	1.00 V	7	14.20	13.80
2	120.00	25.5 QP	43.5	-18.0	1.00 V	257	13.00	12.50
3	137.67	29.5 QP	43.5	-14.0	1.00 V	155	14.60	14.90
4	160.00	26.3 QP	43.5	-17.2	1.00 V	11	10.50	15.80
5	200.00	29.4 QP	43.5	-14.1	1.00 V	322	18.20	11.20
6	276.83	30.4 QP	46.0	-15.6	1.00 V	8	15.40	15.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

ABOVE 1GHz DATA

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 1		FREQUENCY RANGE 1 ~ 25GHz
INPUT POWER		DC 3V from batteries		DETECTOR FUNCTION Peak (PK)
ENVIRONMENTAL CONDITIONS		20deg. C, 66%RH 1011 hPa		TESTED BY Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2400.00	56.3 PK	74.0	-17.7	1.00 H	109	24.99	31.31
2	2400.00	22.1 AV	54.0	-31.9	1.00 H	109	-9.21	31.31
3	*2405.00	80.1 PK	114.0	-33.9	1.00 H	108	48.77	31.33
4	*2405.00	45.9 AV	94.0	-48.1	1.00 H	108	14.57	31.33
5	4810.00	49.4 PK	74.0	-24.6	1.45 H	322	11.86	37.54
6	4810.00	15.2 AV	54.0	-38.8	1.45 H	322	-22.34	37.54
7	7215.00	54.7 PK	74.0	-19.3	1.41 H	0	11.06	43.64
8	7215.00	20.5 AV	54.0	-33.5	1.41 H	0	-23.14	43.64
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2400.00	67.1 PK	74.0	-6.9	1.37 V	0	35.79	31.31
2	2400.00	32.9 AV	54.0	-21.1	1.37 V	0	1.59	31.31
3	*2405.00	100.1 PK	114.0	-13.9	1.37 V	0	68.77	31.33
4	*2405.00	65.9 AV	94.0	-28.1	1.37 V	0	34.57	31.33
5	4810.00	47.3 PK	74.0	-26.7	1.00 V	273	9.76	37.54
6	4810.00	13.1 AV	54.0	-40.9	1.00 V	273	-24.44	37.54
7	7215.00	54.9 PK	74.0	-19.1	1.74 V	239	11.26	43.64
8	7215.00	20.7 AV	54.0	-33.3	1.74 V	239	-22.94	43.64

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency
6. The average value of fundamental frequency is: Average = Peak value + $20\log(\text{Duty cycle})$ Where the duty factor is calculated from following formula: $20 \log (\text{Duty cycle}) = 20 \log (0.4 \text{ ms} / 20.5 \text{ ms}) = -34.2 \text{ dB}$

Please see page 18 for plotted duty.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 8	FREQUENCY RANGE	
INPUT POWER	DC 3V from batteries	DETECTOR FUNCTION	
ENVIRONMENTAL CONDITIONS	20deg. C, 66%RH 1011 hPa	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2444.00	80.4 PK	114.0	-33.6	1.00 H	107	48.90	31.50
2	*2444.00	46.2 AV	94.0	-47.8	1.00 H	107	14.70	31.50
3	4888.00	47.4 PK	74.0	-26.6	1.34 H	64	9.66	37.74
4	4888.00	13.2 AV	54.0	-40.8	1.34 H	64	-24.54	37.74
5	7332.00	59.2 PK	74.0	-14.8	1.22 H	19	15.14	44.06
6	7332.00	25.0 AV	54.0	-29.0	1.22 H	19	-19.06	44.06

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2444.00	96.3 PK	114.0	-17.7	1.34 V	293	64.80	31.50
2	*2444.00	62.1 AV	94.0	-31.9	1.34 V	293	30.60	31.50
3	4888.00	46.3 PK	74.0	-27.7	1.00 V	154	8.56	37.74
4	4888.00	12.1 AV	54.0	-41.9	1.00 V	154	-25.64	37.74
5	7332.00	58.3 PK	74.0	-15.7	1.72 V	211	14.24	44.06
6	7332.00	24.1 AV	54.0	-29.9	1.72 V	211	-19.96	44.06

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency
6. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula: $20 \log (Duty\ cycle) = 20 \log (0.4\ ms / 20.5\ ms) = -34.2\ dB$

Please see page 18 for plotted duty.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 12	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	DC 3V from batteries	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	20deg. C, 66%RH 1011 hPa	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2474.00	81.8 PK	114.0	-32.2	1.00 H	104	50.17	31.63
2	*2474.00	47.6 AV	94.0	-46.4	1.00 H	104	15.97	31.63
3	2483.50	55.5 PK	74.0	-18.5	1.00 H	104	23.83	31.67
4	2483.50	21.3 AV	54.0	-32.7	1.00 H	104	-10.37	31.67
5	4948.00	45.8 PK	74.0	-28.2	1.56 H	304	7.91	37.89
6	4948.00	11.6 AV	54.0	-42.4	1.56 H	304	-26.29	37.89
7	7422.00	61.7 PK	74.0	-12.3	1.22 H	0	17.32	44.38
8	7422.00	27.5 AV	54.0	-26.5	1.22 H	0	-16.88	44.38
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2474.00	94.7 PK	114.0	-19.3	1.34 V	271	63.07	31.63
2	*2474.00	60.5 AV	94.0	-33.5	1.34 V	271	28.87	31.63
3	2483.50	65.3 PK	74.0	-8.7	1.34 V	271	33.63	31.67
4	2483.50	31.1 AV	54.0	-22.9	1.34 V	271	-0.57	31.67
5	4948.00	45.1 PK	74.0	-28.9	1.00 V	169	7.21	37.89
6	4948.00	10.9 AV	54.0	-43.1	1.00 V	169	-26.99	37.89
7	7422.00	61.0 PK	74.0	-13.0	1.01 V	122	16.62	44.38
8	7422.00	26.8 AV	54.0	-27.2	1.01 V	122	-17.58	44.38


REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency
6. The average value of fundamental frequency is: Average = Peak value + $20\log(\text{Duty cycle})$ Where the duty factor is calculated from following formula: $20 \log (\text{Duty cycle}) = 20 \log (0.4 \text{ ms} / 20.5 \text{ ms}) = -34.2 \text{ dB}$

Please see page 18 for plotted duty.




A D T






A D T

RESTRICTED BANDEDGE (CH1, HORIZONTAL)



RESTRICTED BANDEDGE (CH1, VERTICAL)




* The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle). And it meets the requirement of limit.




A D T

RESTRICTED BANDEDGE (CH12, HORIZONTAL)



RESTRICTED BANDEDGE (CH12, VERTICAL)



* The average value of fundamental frequency is: Average = Peak value + $20\log(\text{Duty cycle})$. And it meets the requirement of limit.



A D T

4.2 CONDUCTED - OUT BAND MEASUREMENT

4.2.1 LIMITS OF CONDUCTED - OUT BAND MEASUREMENT

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100036	Dec. 18, 2009	Dec. 17, 2010

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.2.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span from band edge. The band edges was measured and recorded.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation



4.2.5 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.2.6 TEST RESULTS

Emissions radiated outside of the specified frequency bands, please refer below pages for met the requirement of the general radiated emission limits in § 15.209.



CH1





A D T

CH12





A D T

5 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025:

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Email: service@adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



A D T

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

--- END ---