



# RF EXPOSURE REPORT

**REPORT NO.:** SA120417E01

**MODEL NO.:** Y-R0028

**FCC ID:** JNZYR0028

**RECEIVED:** Apr. 17, 2012

**TESTED:** May 05, 2012

**ISSUED:** May 11, 2012

**APPLICANT:** LOGITECH FAR EAST LTD.

**ADDRESS:** #2 Creation Rd. 4, Science-Based Ind. Park Hsinchu  
Taiwan, R.O.C.

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

**LAB ADDRESS:** No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,  
R.O.C.

This test report consists of 5 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval or endorsement by any government agency. The test results in the report only apply to the tested sample.



A D T

## TABLE OF CONTENTS

RELEASE CONTROL RECORD .....	3
1. CERTIFICATION .....	4
2. EVALUATION RESULT .....	5



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA120417E01	Original release	May 11, 2012



## 1. CERTIFICATION

**PRODUCT:** Bluetooth Keyboard

**BRAND:** Logitech

**MODEL:** Y-R0028

**TEST SAMPLE:** ENGINEERING SAMPLE

**APPLICANT:** LOGITECH FAR EAST LTD.

**TESTED:** May 05, 2012

**STANDARDS:** FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

IEEE C95.1

The above equipment (Model: Y-R0028) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Phoenix Huang , **DATE:** May 11, 2012  
( Phoenix Huang, Specialist )

**APPROVED BY** : May Chen , **DATE:** May 11, 2012  
(May Chen, Deputy Manager)

## 2. EVALUATION RESULT

No SAR Evaluation Required if power is below the following threshold:

Tunable Range		60/f SAR Limitation (mW)
F(GHz) Low	F(GHz) High	
2.402	2.480	24.19

Maximum measured transmitter power:

Pout Conducted (dBm)	Pout Conducted (mW)	Maximum Antenna Gain (dBi)	Pout EIRP (mW)
0.69	1.172	4.81	3.548

Threshold for no SAR evaluation is 24.19 mW

Maximum TX Power is 1.172 mW Conducted and 3.548 mW EIRP

Conclusion: No SAR evaluation required since maximum Transmitter Pout (both conducted and EIRP) is below FCC threshold

--- END ---