

## FCC Test Report

**Report No.:** RFBDKG-WTW-P21080001

**FCC ID:** JNZYR0081

**Test Model:** YR0081

**Received Date:** 2021/8/1

**Test Date:** 2021/8/8 ~ 2021/8/11

**Issued Date:** 2021/9/9

**Applicant:** LOGITECH FAR EAST LTD.

**Address:** 7700 Gateway Boulevard Newark California United States

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan

**Test Location:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan

**FCC Registration /  
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

## Table of Contents

<b>Release Control Record</b> .....	<b>4</b>
<b>1 Certificate of Conformity</b> .....	<b>5</b>
<b>2 Summary of Test Results</b> .....	<b>6</b>
2.1 Measurement Uncertainty.....	6
2.2 Modification Record.....	6
<b>3 General Information</b> .....	<b>7</b>
3.1 General Description of EUT.....	7
3.2 Description of Test Modes.....	9
3.2.1 Test Mode Applicability and Tested Channel Detail.....	10
3.3 Duty Cycle of Test Signal.....	12
3.4 Description of Support Units.....	13
3.4.1 Configuration of System under Test.....	13
3.5 General Description of Applied Standards and References.....	14
<b>4 Test Types and Results</b> .....	<b>15</b>
4.1 Radiated Emission and Bandedge Measurement.....	15
4.1.1 Limits of Radiated Emission and Bandedge Measurement.....	15
4.1.2 Test Instruments.....	16
4.1.3 Test Procedures.....	18
4.1.4 Deviation from Test Standard.....	18
4.1.5 Test Setup.....	19
4.1.6 EUT Operating Conditions.....	20
4.1.7 Test Results.....	21
4.2 Conducted Emission Measurement.....	37
4.2.1 Limits of Conducted Emission Measurement.....	37
4.2.2 Test Instruments.....	37
4.2.3 Test Procedures.....	38
4.2.4 Deviation from Test Standard.....	38
4.2.5 Test Setup.....	38
4.2.6 EUT Operating Conditions.....	38
4.2.7 Test Results.....	39
4.3 6dB Bandwidth Measurement.....	43
4.3.1 Limits of 6dB Bandwidth Measurement.....	43
4.3.2 Test Setup.....	43
4.3.3 Test Instruments.....	43
4.3.4 Test Procedure.....	43
4.3.5 Deviation from Test Standard.....	43
4.3.6 EUT Operating Conditions.....	43
4.3.7 Test Results.....	44
4.4 Conducted Output Power Measurement.....	46
4.4.1 Limits of Conducted Output Power Measurement.....	46
4.4.2 Test Setup.....	46
4.4.3 Test Instruments.....	46
4.4.4 Test Procedures.....	46
4.4.5 Deviation from Test Standard.....	46
4.4.6 EUT Operating Conditions.....	46
4.4.7 Test Results.....	47
4.5 Power Spectral Density Measurement.....	49
4.5.1 Limits of Power Spectral Density Measurement.....	49
4.5.2 Test Setup.....	49
4.5.3 Test Instruments.....	49
4.5.4 Test Procedure.....	49
4.5.5 Deviation from Test Standard.....	49
4.5.6 EUT Operating Condition.....	49

4.5.7 Test Results .....	50
4.6 Conducted Out of Band Emission Measurement.....	52
4.6.1 Limits of Conducted Out of Band Emission Measurement .....	52
4.6.2 Test Setup.....	52
4.6.3 Test Instruments .....	52
4.6.4 Test Procedure .....	52
4.6.5 Deviation from Test Standard .....	52
4.6.6 EUT Operating Condition .....	52
4.6.7 Test Results .....	53
<b>5 Pictures of Test Arrangements.....</b>	<b>58</b>
<b>Annex A - Band-Edge Measurement.....</b>	<b>59</b>
<b>Appendix – Information of the Testing Laboratories .....</b>	<b>63</b>

### Release Control Record

Issue No.	Description	Date Issued
RFBDKG-WTW-P21080001	Original release.	2021/9/9

## 1 Certificate of Conformity

**Product:** Wireless keyboard  
**Brand:** Logitech  
**Test Model:** YR0081  
**Sample Status:** Engineering sample  
**Applicant:** LOGITECH FAR EAST LTD.  
**Test Date:** 2021/8/8 ~ 2021/8/11  
**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Phoenix Huang , **Date:** 2021/9/9  
Phoenix Huang / Specialist

**Approved by :** Clark Lin , **Date:** 2021/9/9  
Clark Lin / Technical Manager

## 2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -9.49 dB at 0.56797 MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -4.4 dB at 38.10 MHz.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	Pass	Meet the requirement of limit.
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	No antenna connector is used.

### Note:

- For 2.4 GHz band compliance with rule 15.247(d) of the band-edge items, the test plots were recorded in Annex A.
- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ( $\pm$ )
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.9 dB
Conducted emissions	-	2.5 dB
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.1 dB
	30MHz ~ 1GHz	5.4 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	5.0 dB
	18GHz ~ 40GHz	5.3 dB

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

Product	Wireless keyboard
Brand	Logitech
Test Model	YR0081
Status of EUT	Engineering sample
Power Supply Rating	3.7Vdc from battery or 5Vdc from USB interface
Modulation Type	GFSK
Transfer Rate	Up to 2 Mbps (*Note 1)
Operating Frequency	2.402 ~ 2.480 GHz (*Note 1)
Number of Channel	40 (*Note 1)
Output Power	<b>BT-LE function:</b> BT-LE 1M: 2.265 mW BT-LE 2M: 2.265 mW <b>logi bolt function:</b> logi bolt 1M: 2.265 mW logi bolt 2M: 2.265 mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	NA
Cable Supplied	USB Cable Type A to Type C cable x 1 (shielded, 1 m), USB Cable Type C to Type C cable x 1 (shielded, 1 m)

Note:

1. BT-LE and logi bolt technique supports 1Mbps and 2Mbps data rates, both have been evaluated in this test report. Refer to "**section 3.2 Description of Test Modes**" for more detail specification.
2. This device have BT-LE and logi bolt functions. logi bolt is the same technology as BT-LE and is just a different marketing.
3. The EUT may have a lot of colors for marketing requirement.
4. Depending on device connected to the keyboard, EUT uses either BT-LE or logi bolt technology. BT-LE and logi bolt may not transmit simultaneously.
5. The antenna provided to the EUT, please refer to the following table:

Antenna Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type
1.97	2.4~2.4835	Printed Monopole Antenna	None

6. The EUT must be supplied with battery and following table:

Brand	Model No.	Spec.
Springpower technology(ShenZhen)Co., Ltd or Logitech	325085 or 533-000204	3.7 Vdc, 1500 mAh, 5.550 Wh

7. The EUT was pre-tested under the following modes:

<b>For Radiated Emission test</b>	
Pre-test Mode	Description
Mode A	Power from Battery
<b>Mode B</b>	<b>Power from USB adapter via USB-A to USB-C cable</b>
Mode C	Power from USB adapter via USB-C to USB-C cable
From the above modes, the worst case was found in <b>Mode B</b> . Therefore only the test data of the mode was recorded in this report.	
<b>For AC Power Conducted Emission test</b>	
Pre-test Mode	Description
Mode D	Power from Laptop via USB-A to USB-C cable
Mode E	Power from Laptop via USB-C to USB-C cable
<b>Mode F</b>	<b>Power from USB adapter via USB-A to USB-C cable</b>
From the above modes, the worst case was found in <b>Mode F</b> . Therefore only the test data of the mode was recorded in this report.	

8. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

9. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.



### 3.2 Description of Test Modes

#### BT-LE & logi bolt channels:

RF Channel	RF Center Frequency	Channel Index	Channels Type for BT 5.x		Channels Type for BT 4.x
			Maximum Data Rate 2Mbps	Maximum Data Rate 1Mbps	Maximum Data Rate 1Mbps
0	2402 MHz	37		●	●
1	2404 MHz	0	●		●
2	2406 MHz	1	●		●
3	2408 MHz	2	●		●
4	2410 MHz	3	●		●
5	2412 MHz	4	●		●
6	2414 MHz	5	●		●
7	2416 MHz	6	●		●
8	2418 MHz	7	●		●
9	2420 MHz	8	●		●
10	2422 MHz	9	●		●
11	2424 MHz	10	●		●
12	2426 MHz	38		●	●
13	2428 MHz	11	●		●
14	2430 MHz	12	●		●
15	2432 MHz	13	●		●
16	2434 MHz	14	●		●
17	2436 MHz	15	●		●
18	2438 MHz	16	●		●
19	2440 MHz	17	●		●
20	2442 MHz	18	●		●
21	2444 MHz	19	●		●
22	2446 MHz	20	●		●
23	2448 MHz	21	●		●
24	2450 MHz	22	●		●
25	2452 MHz	23	●		●
26	2454 MHz	24	●		●
27	2456 MHz	25	●		●
28	2458 MHz	26	●		●
29	2460 MHz	27	●		●
30	2462 MHz	28	●		●
31	2464 MHz	29	●		●
32	2466 MHz	30	●		●
33	2468 MHz	31	●		●
34	2470 MHz	32	●		●
35	2472 MHz	33	●		●
36	2474 MHz	34	●		●
37	2476 MHz	35	●		●
38	2478 MHz	36	●		●
39	2480 MHz	39		●	●

### 3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE $<$ 1G	PLC	APCM	
-	√	√	√	√	-

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz & Bandedge Measurement  
**RE $<$ 1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission  
**APCM**: Antenna Port Conducted Measurement

#### **Radiated Emission Test (Above 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	0, 19, 39	GFSK	1
0 to 39	1, 19, 38	GFSK	2

#### **Radiated Emission Test (Below 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	19	GFSK	1

#### **Power Line Conducted Emission Test:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	19	GFSK	1

#### **Antenna Port Conducted Measurement:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	0, 19, 39	GFSK	1
0 to 39	1, 19, 38	GFSK	2

**Test Condition:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (System)	TESTED BY
RE $\geq$ 1G	25deg. C, 66%RH	120Vac, 60Hz	Tom Yang
RE<1G	25deg. C, 66%RH	120Vac, 60Hz	Tom Yang
PLC	25deg. C, 66%RH	120Vac, 60Hz	Tom Yang
APCM	25deg. C, 60%RH	120Vac, 60Hz	Kevin Ko

### 3.3 Duty Cycle of Test Signal


Duty cycle of test signal is < 98 %, duty factor shall be considered.

**BT-LE 1M:** Duty cycle = 0.348 ms/7.061 ms = 0.049, Duty factor =  $10 \cdot \log(1/\text{Duty cycle}) = 13.07 \text{ dB}$

**BT-LE 2M:** Duty cycle = 0.175 ms/7.043 ms = 0.025, Duty factor =  $10 \cdot \log(1/\text{Duty cycle}) = 16.05 \text{ dB}$

**logi bolt 1M:** Duty cycle = 0.343 ms/7.046 ms = 0.049, Duty factor =  $10 \cdot \log(1/\text{Duty cycle}) = 13.13 \text{ dB}$

**logi bolt 2M:** Duty cycle = 0.177 ms/7.113 ms = 0.025, Duty factor =  $10 \cdot \log(1/\text{Duty cycle}) = 16.04 \text{ dB}$



Note: This is highest operational duty cycle.


### 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	USB Adapter	ASUS	EXA1205UA	NA	NA	Provided by Lab

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	USB Type A to Type C Cable	1	1	Yes	0	Supplied by client

#### 3.4.1 Configuration of System under Test



### **3.5 General Description of Applied Standards and References**

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

**Test Standard:**

**FCC Part 15, Subpart C (15.247)**

**ANSI C63.10-2013**

All test items have been performed and recorded as per the above standards.

**References Test Guidance:**

**KDB 558074 D01 15.247 Meas Guidance v05r02**

All test items have been performed as a reference to the above KDB test guidance.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**Note:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

## 4.1.2 Test Instruments

**For Radiated Emission test:**

Description & Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
MXE EMI Receiver(20 Hz to 44 GHz) Keysight	N9038A	MY54450088	2021/7/6	2022/7/5
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA
Pre_Amplifier EMCI	EMC001340	980142	2021/5/24	2022/5/23
LOOP ANTENNA Electro-Metrics	EM-6879	264	2021/3/5	2022/3/4
RF Coaxial Cable JYEBO	5D-FB	LOOPCAB-001	2021/1/7	2022/1/6
RF Coaxial Cable JYEBO	5D-FB	LOOPCAB-002	2021/1/7	2022/1/6
Pre_Amplifier Mini-Circuits	ZFL-1000VH2	QA0838008	2020/10/20	2021/10/19
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	2020/11/5	2021/11/4
RF Coaxial Cable COMMATE/PEWC	8D	966-3-1	2021/3/16	2022/3/15
RF Coaxial Cable COMMATE/PEWC	8D	966-3-2	2021/3/16	2022/3/15
RF Coaxial Cable COMMATE/PEWC	8D	966-3-3	2021/3/16	2022/3/15
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-3-01	2020/9/24	2021/9/23
Horn Antenna Schwarzbeck	BBHA9120-D	9120D-406	2020/11/22	2021/11/21
Pre_Amplifier EMCI	EMC12630SE	980384	2021/1/11	2022/1/10
RF Coaxial Cable EMCI	EMC104-SM-SM-1500	180504	2021/4/26	2022/4/25
RF Coaxial Cable EMCI	EMC104-SM-SM-2000	180601	2021/6/8	2022/6/7
RF Coaxial Cable EMCI	EMC104-SM-SM-6000	210201	2021/5/13	2022/5/12
Fix tool for Boresight antenna tower LIOW GUU	FBA-01	FBA_SIP01	NA	NA
Spectrum Analyzer Keysight	N9030A	MY54490679	2021/7/9	2022/7/8
Pre_Amplifier EMCI	EMC184045SE	980387	2021/1/11	2022/1/10
SHF-EHF Horn Schwarzbeck	BBHA 9170	BBHA9170519	2020/11/22	2021/11/21
RF Cable-Frequency range: 1-40GHz EMCI	EMC102-KM-KM-1200	160924	2021/1/11	2022/1/10
RF cable (40GHz) EMCI	EMC-KM-KM-4000	200214	2021/3/10	2022/3/9

- Note:
1. The test was performed in 966 Chamber No. 3.
  2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  3. Tested Date: 2021/8/8 ~ 2021/8/11



**For other test items**

Description & Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Spectrum Analyzer R&S	FSV40	101516	2021/3/8	2022/3/7
Power Meter Anritsu	ML2495A	1529002	2021/6/21	2022/6/20
Pulse Power Sensor Anritsu	MA2411B	1339443	2021/5/31	2022/5/30
Attenuator WOKEN	MDCS18N-10	MDCS18N-10-01	2021/4/13	2022/4/12
Software	ADT_RF Test Software V6.6.5.4	NA	NA	NA

- Note: 1. The test was performed in Oven room 2.  
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
 3. Tested Date: 2021/8/10

#### 4.1.3 Test Procedures

##### **For Radiated emission below 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

##### **Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

##### **For Radiated emission above 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

##### **Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup


##### For Radiated emission below 30MHz



##### For Radiated emission 30MHz to 1GHz



### For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

- a. Placed the EUT on the testing table.
- b. Controlling software (RF Sample with Receiver [Number Lock]) has been activated to set the EUT under transmission condition continuously at specific channel frequency.
  - ◆ BLE1M TX Modulated on channel 2402MHz
  - ◆ BLE1M TX Modulated on channel 2440MHz
  - ◆ BLE1M TX Modulated on channel 2480MHz
  - ◆ BLE2M TX Modulated on channel 2404MHz
  - ◆ BLE2M TX Modulated on channel 2440MHz
  - ◆ BLE2M TX Modulated on channel 2478MHz

#### 4.1.7 Test Results

##### Above 1GHz Data:

<b>RF Mode</b>	TX BT-LE 1M	<b>Channel</b>	CH 0 : 2402 MHz
<b>Frequency Range</b>	1GHz ~ 25GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

##### Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2363.50	56.2 PK	74.0	-17.8	1.07 H	239	57.3	-1.1
2	2363.50	45.7 AV	54.0	-8.3	1.07 H	239	46.8	-1.1
3	*2402.00	98.7 PK			1.07 H	239	99.9	-1.2
4	*2402.00	72.6 AV			1.07 H	239	73.8	-1.2
5	4804.00	44.5 PK	74.0	-29.5	3.54 H	132	40.7	3.8
6	4804.00	18.4 AV	54.0	-35.6	3.54 H	132	14.6	3.8

##### Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2320.60	56.6 PK	74.0	-17.4	2.85 V	288	57.7	-1.1
2	2320.60	45.3 AV	54.0	-8.7	2.85 V	288	46.4	-1.1
3	*2402.00	97.1 PK			2.85 V	288	98.3	-1.2
4	*2402.00	71.0 AV			2.85 V	288	72.2	-1.2
5	4804.00	45.2 PK	74.0	-28.8	1.21 V	337	41.4	3.8
6	4804.00	19.1 AV	54.0	-34.9	1.21 V	337	15.3	3.8

##### Remarks:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- Margin value = Emission Level – Limit value
- The other emission levels were very low against the limit.
- " \* ": Fundamental frequency.
- The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty factor is calculated from following formula:  
 $20 \log(\text{Duty cycle}) = 20 \log(0.348 \text{ ms} / 7.061 \text{ ms}) = -26.1 \text{ dB}$   
 Please see section 3.3 for plotted duty.

<b>RF Mode</b>	TX BT-LE 1M	<b>Channel</b>	CH 19 : 2440 MHz
<b>Frequency Range</b>	1GHz ~ 25GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	98.4 PK			1.02 H	235	99.6	-1.2
2	*2440.00	72.3 AV			1.02 H	235	73.5	-1.2
3	4880.00	43.8 PK	74.0	-30.2	3.47 H	121	40.0	3.8
4	4880.00	17.7 AV	54.0	-36.3	3.47 H	121	13.9	3.8
5	7320.00	52.6 PK	74.0	-21.4	1.16 H	152	42.9	9.7
6	7320.00	26.5 AV	54.0	-27.5	1.16 H	152	16.8	9.7

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	97.0 PK			2.89 V	294	98.2	-1.2
2	*2440.00	70.9 AV			2.89 V	294	72.1	-1.2
3	4880.00	45.0 PK	74.0	-29.0	1.19 V	336	41.2	3.8
4	4880.00	18.9 AV	54.0	-35.1	1.19 V	336	15.1	3.8
5	7320.00	50.8 PK	74.0	-23.2	1.23 V	29	41.1	9.7
6	7320.00	24.7 AV	54.0	-29.3	1.23 V	29	15.0	9.7

**Remarks:**

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- Margin value = Emission Level – Limit value
- The other emission levels were very low against the limit.
- " \* ": Fundamental frequency.
- The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty factor is calculated from following formula:  
 $20 \log(\text{Duty cycle}) = 20 \log(0.348 \text{ ms} / 7.061 \text{ ms}) = -26.1 \text{ dB}$   
 Please see section 3.3 for plotted duty.

<b>RF Mode</b>	TX BT-LE 1M	<b>Channel</b>	CH 39 : 2480 MHz
<b>Frequency Range</b>	1GHz ~ 25GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	98.2 PK			1.04 H	240	99.4	-1.2
2	*2480.00	72.1 AV			1.04 H	240	73.3	-1.2
3	2483.50	61.4 PK	74.0	-12.6	1.04 H	240	62.6	-1.2
4	2483.50	45.6 AV	54.0	-8.4	1.04 H	240	46.8	-1.2
5	4960.00	44.0 PK	74.0	-30.0	3.50 H	131	40.0	4.0
6	4960.00	17.9 AV	54.0	-36.1	3.50 H	131	13.9	4.0
7	7440.00	52.3 PK	74.0	-21.7	1.16 H	162	42.6	9.7
8	7440.00	26.2 AV	54.0	-27.8	1.16 H	162	16.5	9.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	96.3 PK			2.90 V	288	97.5	-1.2
2	*2480.00	70.2 AV			2.90 V	288	71.4	-1.2
3	2483.50	57.1 PK	74.0	-16.9	2.90 V	288	58.3	-1.2
4	2483.50	45.6 AV	54.0	-8.4	2.90 V	288	46.8	-1.2
5	4960.00	44.8 PK	74.0	-29.2	1.22 V	338	40.8	4.0
6	4960.00	18.7 AV	54.0	-35.3	1.22 V	338	14.7	4.0
7	7440.00	51.0 PK	74.0	-23.0	1.19 V	37	41.3	9.7
8	7440.00	24.9 AV	54.0	-29.1	1.19 V	37	15.2	9.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty factor is calculated from following formula:  
 $20 \log(\text{Duty cycle}) = 20 \log(0.348 \text{ ms} / 7.061 \text{ ms}) = -26.1 \text{ dB}$   
 Please see section 3.3 for plotted duty.

<b>RF Mode</b>	TX BT-LE 2M	<b>Channel</b>	CH 1 : 2404 MHz
<b>Frequency Range</b>	1GHz ~ 25GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2386.50	56.7 PK	74.0	-17.3	1.06 H	236	57.9	-1.2
2	2386.50	46.1 AV	54.0	-7.9	1.06 H	236	47.3	-1.2
3	*2404.00	98.5 PK			1.06 H	236	99.7	-1.2
4	*2404.00	66.4 AV			1.06 H	236	67.6	-1.2
5	4808.00	43.9 PK	74.0	-30.1	3.47 H	115	40.1	3.8
6	4808.00	11.8 AV	54.0	-42.2	3.47 H	115	8.0	3.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2350.20	56.6 PK	74.0	-17.4	3.07 V	295	57.7	-1.1
2	2350.20	46.0 AV	54.0	-8.0	3.07 V	295	47.1	-1.1
3	*2404.00	97.3 PK			3.07 V	295	98.5	-1.2
4	*2404.00	65.2 AV			3.07 V	295	66.4	-1.2
5	4808.00	45.4 PK	74.0	-28.6	1.26 V	324	41.6	3.8
6	4808.00	13.3 AV	54.0	-40.7	1.26 V	324	9.5	3.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty factor is calculated from following formula:  
 $20 \log(\text{Duty cycle}) = 20 \log(0.175 \text{ ms} / 7.043 \text{ ms}) = -32.1 \text{ dB}$   
 Please see section 3.3 for plotted duty.



<b>RF Mode</b>	TX BT-LE 2M	<b>Channel</b>	CH 19 : 2440 MHz
<b>Frequency Range</b>	1GHz ~ 25GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	98.1 PK			1.10 H	230	99.3	-1.2
2	*2440.00	66.0 AV			1.10 H	230	67.2	-1.2
3	4880.00	43.6 PK	74.0	-30.4	3.49 H	130	39.8	3.8
4	4880.00	11.5 AV	54.0	-42.5	3.49 H	130	7.7	3.8
5	7320.00	51.7 PK	74.0	-22.3	1.11 H	149	42.0	9.7
6	7320.00	19.6 AV	54.0	-34.4	1.11 H	149	9.9	9.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	96.7 PK			2.93 V	305	97.9	-1.2
2	*2440.00	64.6 AV			2.93 V	305	65.8	-1.2
3	4880.00	45.2 PK	74.0	-28.8	1.21 V	325	41.4	3.8
4	4880.00	13.1 AV	54.0	-40.9	1.21 V	325	9.3	3.8
5	7320.00	51.4 PK	74.0	-22.6	1.25 V	27	41.7	9.7
6	7320.00	19.3 AV	54.0	-34.7	1.25 V	27	9.6	9.7

**Remarks:**

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- Margin value = Emission Level – Limit value
- The other emission levels were very low against the limit.
- " \* ": Fundamental frequency.
- The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty factor is calculated from following formula:  
 $20 \log(\text{Duty cycle}) = 20 \log(0.175 \text{ ms} / 7.043 \text{ ms}) = -32.1 \text{ dB}$   
 Please see section 3.3 for plotted duty.

<b>RF Mode</b>	TX BT-LE 2M	<b>Channel</b>	CH 38 : 2478 MHz
<b>Frequency Range</b>	1GHz ~ 25GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2478.00	97.9 PK			1.05 H	243	99.1	-1.2
2	*2478.00	65.8 AV			1.05 H	243	67.0	-1.2
3	2483.50	56.1 PK	74.0	-17.9	1.05 H	243	57.3	-1.2
4	2483.50	45.6 AV	54.0	-8.4	1.05 H	243	46.8	-1.2
5	4956.00	43.9 PK	74.0	-30.1	3.50 H	143	39.9	4.0
6	4956.00	11.8 AV	54.0	-42.2	3.50 H	143	7.8	4.0
7	7434.00	52.0 PK	74.0	-22.0	1.11 H	151	42.3	9.7
8	7434.00	19.9 AV	54.0	-34.1	1.11 H	151	10.2	9.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2478.00	96.2 PK			2.96 V	291	97.4	-1.2
2	*2478.00	64.1 AV			2.96 V	291	65.3	-1.2
3	2483.50	56.0 PK	74.0	-18.0	2.96 V	291	57.2	-1.2
4	2483.50	45.5 AV	54.0	-8.5	2.96 V	291	46.7	-1.2
5	4956.00	44.4 PK	74.0	-29.6	1.27 V	337	40.4	4.0
6	4956.00	12.3 AV	54.0	-41.7	1.27 V	337	8.3	4.0
7	7434.00	51.3 PK	74.0	-22.7	1.19 V	43	41.6	9.7
8	7434.00	19.2 AV	54.0	-34.8	1.19 V	43	9.5	9.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty factor is calculated from following formula:  
 $20 \log(\text{Duty cycle}) = 20 \log(0.175 \text{ ms} / 7.043 \text{ ms}) = -32.1 \text{ dB}$   
 Please see section 3.3 for plotted duty.

<b>RF Mode</b>	TX logi bolt 1M	<b>Channel</b>	CH 0 : 2402 MHz
<b>Frequency Range</b>	1GHz ~ 25GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2346.90	56.8 PK	74.0	-17.2	1.02 H	243	57.9	-1.1
2	2346.90	46.1 AV	54.0	-7.9	1.02 H	243	47.2	-1.1
3	*2402.00	98.1 PK			1.02 H	243	99.3	-1.2
4	*2402.00	71.8 AV			1.02 H	243	73.0	-1.2
5	4804.00	44.8 PK	74.0	-29.2	3.52 H	138	41.0	3.8
6	4804.00	18.5 AV	54.0	-35.5	3.52 H	138	14.7	3.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2360.40	56.2 PK	74.0	-17.8	2.86 V	289	57.3	-1.1
2	2360.40	45.8 AV	54.0	-8.2	2.86 V	289	46.9	-1.1
3	*2402.00	96.5 PK			2.86 V	289	97.7	-1.2
4	*2402.00	70.2 AV			2.86 V	289	71.4	-1.2
5	4804.00	44.8 PK	74.0	-29.2	1.16 V	360	41.0	3.8
6	4804.00	18.5 AV	54.0	-35.5	1.16 V	360	14.7	3.8

**Remarks:**

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- Margin value = Emission Level – Limit value
- The other emission levels were very low against the limit.
- " \* ": Fundamental frequency.
- The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty factor is calculated from following formula:  
 $20 \log(\text{Duty cycle}) = 20 \log(0.343 \text{ ms} / 7.046 \text{ ms}) = -26.3 \text{ dB}$   
 Please see section 3.3 for plotted duty.

<b>RF Mode</b>	TX logi bolt 1M	<b>Channel</b>	CH 19 : 2440 MHz
<b>Frequency Range</b>	1GHz ~ 25GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	97.7 PK			1.08 H	252	98.9	-1.2
2	*2440.00	71.4 AV			1.08 H	252	72.6	-1.2
3	4880.00	44.2 PK	74.0	-29.8	3.59 H	151	40.4	3.8
4	4880.00	17.9 AV	54.0	-36.1	3.59 H	151	14.1	3.8
5	7320.00	52.1 PK	74.0	-21.9	1.10 H	149	42.4	9.7
6	7320.00	25.8 AV	54.0	-28.2	1.10 H	149	16.1	9.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	96.3 PK			2.79 V	290	97.5	-1.2
2	*2440.00	70.0 AV			2.79 V	290	71.2	-1.2
3	4880.00	45.2 PK	74.0	-28.8	1.15 V	339	41.4	3.8
4	4880.00	18.9 AV	54.0	-35.1	1.15 V	339	15.1	3.8
5	7320.00	50.6 PK	74.0	-23.4	1.17 V	15	40.9	9.7
6	7320.00	24.3 AV	54.0	-29.7	1.17 V	15	14.6	9.7

**Remarks:**

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- Margin value = Emission Level – Limit value
- The other emission levels were very low against the limit.
- " \* ": Fundamental frequency.
- The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty factor is calculated from following formula:  
 $20 \log(\text{Duty cycle}) = 20 \log(0.343 \text{ ms} / 7.046 \text{ ms}) = -26.3 \text{ dB}$   
 Please see section 3.3 for plotted duty.

<b>RF Mode</b>	TX logi bolt 1M	<b>Channel</b>	CH 39 : 2480 MHz
<b>Frequency Range</b>	1GHz ~ 25GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	97.4 PK			1.02 H	228	98.6	-1.2
2	*2480.00	71.1 AV			1.02 H	228	72.3	-1.2
3	2483.50	61.3 PK	74.0	-12.7	1.02 H	228	62.5	-1.2
4	2483.50	45.0 AV	54.0	-9.0	1.02 H	228	46.2	-1.2
5	4960.00	44.2 PK	74.0	-29.8	3.48 H	130	40.2	4.0
6	4960.00	17.9 AV	54.0	-36.1	3.48 H	130	13.9	4.0
7	7440.00	52.3 PK	74.0	-21.7	1.18 H	166	42.6	9.7
8	7440.00	26.0 AV	54.0	-28.0	1.18 H	166	16.3	9.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	95.6 PK			2.84 V	275	96.8	-1.2
2	*2480.00	69.3 AV			2.84 V	275	70.5	-1.2
3	2483.50	56.7 PK	74.0	-17.3	2.84 V	275	57.9	-1.2
4	2483.50	45.3 AV	54.0	-8.7	2.84 V	275	46.5	-1.2
5	4960.00	44.7 PK	74.0	-29.3	1.18 V	336	40.7	4.0
6	4960.00	18.4 AV	54.0	-35.6	1.18 V	336	14.4	4.0
7	7440.00	50.9 PK	74.0	-23.1	1.23 V	25	41.2	9.7
8	7440.00	24.6 AV	54.0	-29.4	1.23 V	25	14.9	9.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty factor is calculated from following formula:  
 $20 \log(\text{Duty cycle}) = 20 \log(0.343 \text{ ms} / 7.046 \text{ ms}) = -26.3 \text{ dB}$   
 Please see section 3.3 for plotted duty.

<b>RF Mode</b>	TX logi bolt 2M	<b>Channel</b>	CH 1 : 2404 MHz
<b>Frequency Range</b>	1GHz ~ 25GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2321.50	56.1 PK	74.0	-17.9	1.06 H	238	57.2	-1.1
2	2321.50	46.5 AV	54.0	-7.5	1.06 H	238	47.6	-1.1
3	*2404.00	98.1 PK			1.06 H	238	99.3	-1.2
4	*2404.00	66.0 AV			1.06 H	238	67.2	-1.2
5	4808.00	43.7 PK	74.0	-30.3	3.48 H	143	39.9	3.8
6	4808.00	11.6 AV	54.0	-42.4	3.48 H	143	7.8	3.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2361.70	57.0 PK	74.0	-17.0	2.91 V	287	58.1	-1.1
2	2361.70	46.0 AV	54.0	-8.0	2.91 V	287	47.1	-1.1
3	*2404.00	96.6 PK			2.91 V	287	97.8	-1.2
4	*2404.00	64.5 AV			2.91 V	287	65.7	-1.2
5	4808.00	44.5 PK	74.0	-29.5	1.12 V	342	40.7	3.8
6	4808.00	12.4 AV	54.0	-41.6	1.12 V	342	8.6	3.8

**Remarks:**

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- Margin value = Emission Level – Limit value
- The other emission levels were very low against the limit.
- " \* ": Fundamental frequency.
- The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty factor is calculated from following formula:  
 $20 \log(\text{Duty cycle}) = 20 \log(0.177 \text{ ms} / 7.113 \text{ ms}) = -32.1 \text{ dB}$   
 Please see section 3.3 for plotted duty.

<b>RF Mode</b>	TX logi bolt 2M	<b>Channel</b>	CH 19 : 2440 MHz
<b>Frequency Range</b>	1GHz ~ 25GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	97.5 PK			1.02 H	222	98.7	-1.2
2	*2440.00	65.4 AV			1.02 H	222	66.6	-1.2
3	4880.00	44.9 PK	74.0	-29.1	3.43 H	129	41.1	3.8
4	4880.00	12.8 AV	54.0	-41.2	3.43 H	129	9.0	3.8
5	7320.00	52.4 PK	74.0	-21.6	1.21 H	151	42.7	9.7
6	7320.00	20.3 AV	54.0	-33.7	1.21 H	151	10.6	9.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	96.4 PK			2.88 V	280	97.6	-1.2
2	*2440.00	64.3 AV			2.88 V	280	65.5	-1.2
3	4880.00	44.3 PK	74.0	-29.7	1.15 V	351	40.5	3.8
4	4880.00	12.2 AV	54.0	-41.8	1.15 V	351	8.4	3.8
5	7320.00	51.0 PK	74.0	-23.0	1.21 V	35	41.3	9.7
6	7320.00	18.9 AV	54.0	-35.1	1.21 V	35	9.2	9.7

**Remarks:**

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- Margin value = Emission Level – Limit value
- The other emission levels were very low against the limit.
- " \* ": Fundamental frequency.
- The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty factor is calculated from following formula:  
 $20 \log(\text{Duty cycle}) = 20 \log(0.177 \text{ ms} / 7.113 \text{ ms}) = -32.1 \text{ dB}$   
 Please see section 3.3 for plotted duty.

<b>RF Mode</b>	TX logi bolt 2M	<b>Channel</b>	CH 38 : 2478 MHz
<b>Frequency Range</b>	1GHz ~ 25GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2478.00	97.3 PK			1.07 H	234	98.5	-1.2
2	*2478.00	65.2 AV			1.07 H	234	66.4	-1.2
3	2483.50	57.2 PK	74.0	-16.8	1.07 H	234	58.4	-1.2
4	2483.50	45.1 AV	54.0	-8.9	1.07 H	234	46.3	-1.2
5	4956.00	44.4 PK	74.0	-29.6	3.54 H	141	40.4	4.0
6	4956.00	12.3 AV	54.0	-41.7	3.54 H	141	8.3	4.0
7	7434.00	52.1 PK	74.0	-21.9	1.12 H	137	42.4	9.7
8	7434.00	20.0 AV	54.0	-34.0	1.12 H	137	10.3	9.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2478.00	95.7 PK			2.85 V	274	96.9	-1.2
2	*2478.00	63.6 AV			2.85 V	274	64.8	-1.2
3	2483.50	56.0 PK	74.0	-18.0	2.85 V	274	57.2	-1.2
4	2483.50	45.4 AV	54.0	-8.6	2.85 V	274	46.6	-1.2
5	4956.00	44.1 PK	74.0	-29.9	1.29 V	352	40.1	4.0
6	4956.00	12.0 AV	54.0	-42.0	1.29 V	352	8.0	4.0
7	7434.00	51.5 PK	74.0	-22.5	1.18 V	31	41.8	9.7
8	7434.00	19.4 AV	54.0	-34.6	1.18 V	31	9.7	9.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty factor is calculated from following formula:  
 $20 \log(\text{Duty cycle}) = 20 \log(0.177 \text{ ms} / 7.113 \text{ ms}) = -32.1 \text{ dB}$   
 Please see section 3.3 for plotted duty.




### Below 1GHz Data:

<b>RF Mode</b>	TX BT-LE 1M	<b>Channel</b>	CH 19 : 2440 MHz
<b>Frequency Range</b>	9kHz ~ 1GHz	<b>Detector Function</b>	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	38.32	25.5 QP	40.0	-14.5	3.00 H	343	34.2	-8.7
2	74.67	21.6 QP	40.0	-18.4	3.00 H	331	33.2	-11.6
3	172.69	21.9 QP	43.5	-21.6	2.00 H	69	30.4	-8.5
4	302.59	22.9 QP	46.0	-23.1	1.00 H	179	29.3	-6.4
5	433.62	26.3 QP	46.0	-19.7	1.50 H	354	28.8	-2.5
6	587.87	28.7 QP	46.0	-17.3	2.00 H	109	27.8	0.9

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




<b>RF Mode</b>	TX BT-LE 1M	<b>Channel</b>	CH 19 : 2440 MHz
<b>Frequency Range</b>	9kHz ~ 1GHz	<b>Detector Function</b>	Quasi-Peak (QP)

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	38.10	35.6 QP	40.0	-4.4	1.00 V	277	44.4	-8.8
2	70.01	22.9 QP	40.0	-17.1	3.00 V	226	33.4	-10.5
3	152.92	20.2 QP	43.5	-23.3	1.50 V	54	27.9	-7.7
4	235.79	20.3 QP	46.0	-25.7	3.00 V	139	29.6	-9.3
5	331.84	22.5 QP	46.0	-23.5	3.00 V	310	27.9	-5.4
6	454.28	26.1 QP	46.0	-19.9	1.00 V	19	28.0	-1.9

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




<b>RF Mode</b>	TX logi bolt 1M	<b>Channel</b>	CH 19 : 2440 MHz
<b>Frequency Range</b>	9kHz ~ 1GHz	<b>Detector Function</b>	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	39.65	25.5 QP	40.0	-14.5	1.00 H	103	34.1	-8.6
2	73.82	20.7 QP	40.0	-19.3	3.00 H	1	32.1	-11.4
3	171.52	21.5 QP	43.5	-22.0	1.00 H	82	29.8	-8.3
4	334.73	22.1 QP	46.0	-23.9	3.00 H	86	27.4	-5.3
5	456.10	26.8 QP	46.0	-19.2	3.00 H	360	28.7	-1.9
6	557.32	28.5 QP	46.0	-17.5	1.00 H	6	28.5	0.0

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




<b>RF Mode</b>	TX logi bolt 1M	<b>Channel</b>	CH 19 : 2440 MHz
<b>Frequency Range</b>	9kHz ~ 1GHz	<b>Detector Function</b>	Quasi-Peak (QP)

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	38.42	33.1 QP	40.0	-6.9	1.00 V	360	41.8	-8.7
2	82.43	23.5 QP	40.0	-16.5	2.00 V	330	36.9	-13.4
3	150.86	21.3 QP	43.5	-22.2	3.00 V	4	28.9	-7.6
4	229.12	19.6 QP	46.0	-26.4	2.00 V	178	29.7	-10.1
5	462.35	26.9 QP	46.0	-19.1	1.00 V	18	28.7	-1.8
6	510.88	26.3 QP	46.0	-19.7	1.00 V	218	27.0	-0.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Test Receiver R&S	ESCS 30	847124/029	2020/10/20	2021/10/19
LISN R&S	ESH3-Z5	848773/004	2020/10/27	2021/10/26
LISN R & S	ESH3-Z5	835239/001	2021/3/26	2022/3/25
50 ohms Terminator	50	3	2020/10/26	2021/10/25
RF Coaxial Cable JYEBO	5D-FB	COCCAB-001	2020/9/26	2021/9/25
Fixed attenuator STI	STI02-2200-10	005	2020/8/29	2021/8/28
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

Note: 1. The test was performed in Conduction 1.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

3. Tested Date: 2021/8/8

#### 4.2.3 Test Procedures


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**Note:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note:** 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Conditions

- a. Placed the EUT on the testing table.
- b. Controlling software (RF Sample with Receiver [Number Lock]) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

◆ BLE1M TX Modulated on channel 2440MHz


#### 4.2.7 Test Results

<b>RF Mode</b>	TX BT-LE 1M	<b>Channel</b>	CH 19 : 2440 MHz
<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9kHz

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17734	9.99	37.00	29.59	46.99	39.58	64.61	54.61	-17.62	-15.03
2	0.22031	10.00	34.34	28.39	44.34	38.39	62.81	52.81	-18.47	-14.42
<b>3</b>	<b>0.56797</b>	<b>10.04</b>	<b>33.16</b>	<b>26.47</b>	<b>43.20</b>	<b>36.51</b>	<b>56.00</b>	<b>46.00</b>	<b>-12.80</b>	<b>-9.49</b>
4	0.91953	10.06	23.68	15.06	33.74	25.12	56.00	46.00	-22.26	-20.88
5	1.60156	10.10	22.83	14.45	32.93	24.55	56.00	46.00	-23.07	-21.45
6	14.55469	11.06	19.22	11.98	30.28	23.04	60.00	50.00	-29.72	-26.96

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




<b>RF Mode</b>	TX BT-LE 1M	<b>Channel</b>	CH 19 : 2440 MHz
<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9kHz

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17344	9.97	38.34	27.35	48.31	37.32	64.79	54.79	-16.48	-17.47
2	0.21641	10.00	34.50	25.17	44.50	35.17	62.96	52.96	-18.46	-17.79
3	0.56016	10.03	28.20	21.82	38.23	31.85	56.00	46.00	-17.77	-14.15
4	0.82969	10.05	30.31	5.12	40.36	15.17	56.00	46.00	-15.64	-30.83
5	1.67578	10.11	20.58	12.40	30.69	22.51	56.00	46.00	-25.31	-23.49
6	14.64063	10.87	16.09	10.18	26.96	21.05	60.00	50.00	-33.04	-28.95

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value






<b>RF Mode</b>	TX logi bolt 1M	<b>Channel</b>	CH 19 : 2440 MHz
<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9kHz

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17344	9.98	38.08	30.33	48.06	40.31	64.79	54.79	-16.73	-14.48
2	0.25938	10.01	31.97	25.32	41.98	35.33	61.45	51.45	-19.47	-16.12
3	0.56797	10.04	33.04	26.27	43.08	36.31	56.00	46.00	-12.92	-9.69
4	0.91953	10.06	23.84	15.76	33.90	25.82	56.00	46.00	-22.10	-20.18
5	1.62109	10.10	19.65	10.67	29.75	20.77	56.00	46.00	-26.25	-25.23
6	14.47656	11.05	19.91	12.55	30.96	23.60	60.00	50.00	-29.04	-26.40

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



<b>RF Mode</b>	TX logi bolt 1M	<b>Channel</b>	CH 19 : 2440 MHz
<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9kHz

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17344	9.97	36.82	25.83	46.79	35.80	64.79	54.79	-18.00	-18.99
2	0.22031	10.00	32.41	23.85	42.41	33.85	62.81	52.81	-20.40	-18.96
3	0.56016	10.03	27.16	18.99	37.19	29.02	56.00	46.00	-18.81	-16.98
4	0.90781	10.05	19.67	11.79	29.72	21.84	56.00	46.00	-26.28	-24.16
5	1.76172	10.11	20.74	10.50	30.85	20.61	56.00	46.00	-25.15	-25.39
6	14.86328	10.89	16.12	10.07	27.01	20.96	60.00	50.00	-32.99	-29.04

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




### 4.3 6dB Bandwidth Measurement

#### 4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

- ◆ BLE1M TX Modulated on channel 2402MHz
- ◆ BLE1M TX Modulated on channel 2440MHz
- ◆ BLE1M TX Modulated on channel 2480MHz
- ◆ BLE2M TX Modulated on channel 2404MHz
- ◆ BLE2M TX Modulated on channel 2440MHz
- ◆ BLE2M TX Modulated on channel 2478MHz

#### 4.3.7 Test Results

##### BT-LE 1M

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	0.68	0.5	Pass
19	2440	0.70	0.5	Pass
39	2480	0.71	0.5	Pass

##### BT-LE 2M

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2404	1.12	0.5	Pass
19	2440	1.14	0.5	Pass
38	2478	1.12	0.5	Pass

##### logi bolt 1M


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	0.70	0.5	Pass
19	2440	0.70	0.5	Pass
39	2480	0.70	0.5	Pass

##### logi bolt 2M


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2404	1.15	0.5	Pass
19	2440	1.16	0.5	Pass
38	2478	1.16	0.5	Pass

Spectrum Plot of Worst Value


**BT-LE 1M / CH 0**




**BT-LE 2M / CH 1**



**logi bolt 1M / CH 0**



**logi bolt 2M / CH 1**




## 4.4 Conducted Output Power Measurement

### 4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

### 4.4.2 Test Setup



### 4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.4.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

### 4.4.5 Deviation from Test Standard

No deviation.

### 4.4.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

- ◆ BLE1M TX Modulated on channel 2402MHz
- ◆ BLE1M TX Modulated on channel 2440MHz
- ◆ BLE1M TX Modulated on channel 2480MHz
- ◆ BLE2M TX Modulated on channel 2404MHz
- ◆ BLE2M TX Modulated on channel 2440MHz
- ◆ BLE2M TX Modulated on channel 2478MHz

#### 4.4.7 Test Results

#### FOR PEAK POWER

##### BT-LE 1M

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
0	2402	2.265	3.55	30	Pass
19	2440	2.265	3.55	30	Pass
39	2480	2.265	3.55	30	Pass

##### BT-LE 2M

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
1	2404	2.259	3.54	30	Pass
19	2440	2.259	3.54	30	Pass
38	2478	2.265	3.55	30	Pass

##### logi bolt 1M

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
0	2402	2.259	3.54	30	Pass
19	2440	2.265	3.55	30	Pass
39	2480	2.259	3.54	30	Pass

##### logi bolt 2M

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
1	2404	2.265	3.55	30	Pass
19	2440	2.259	3.54	30	Pass
38	2478	2.265	3.55	30	Pass

## FOR AVERAGE POWER

### BT-LE 1M

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	2.239	3.50
19	2440	2.244	3.51
39	2480	2.239	3.50

### BT-LE 2M

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
1	2404	2.244	3.51
19	2440	2.244	3.51
38	2478	2.244	3.51

### logi bolt 1M

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	2.239	3.50
19	2440	2.244	3.51
39	2480	2.239	3.50

### logi bolt 2M

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
1	2404	2.239	3.50
19	2440	2.244	3.51
38	2478	2.239	3.50




## 4.5 Power Spectral Density Measurement

### 4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedure

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d. Set the VBW  $\geq 3 \times \text{RBW}$ .
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.

### 4.5.5 Deviation from Test Standard

No deviation.

### 4.5.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

- ◆ BLE1M TX Modulated on channel 2402MHz
- ◆ BLE1M TX Modulated on channel 2440MHz
- ◆ BLE1M TX Modulated on channel 2480MHz
- ◆ BLE2M TX Modulated on channel 2404MHz
- ◆ BLE2M TX Modulated on channel 2440MHz
- ◆ BLE2M TX Modulated on channel 2478MHz

#### 4.5.7 Test Results

##### BT-LE 1M

Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	2402	-0.24	8	Pass
19	2440	-0.26	8	Pass
39	2480	-0.26	8	Pass

##### BT-LE 2M

Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
1	2404	-4.65	8	Pass
19	2440	-4.41	8	Pass
38	2478	-4.33	8	Pass

##### logi bolt 1M


Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	2402	-0.47	8	Pass
19	2440	-0.44	8	Pass
39	2480	-0.42	8	Pass

##### logi bolt 2M


Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
1	2404	-4.68	8	Pass
19	2440	-4.41	8	Pass
38	2478	-4.49	8	Pass

Spectrum Plot of Worst Value


**BT-LE 1M / CH 0**




**BT-LE 2M / CH 38**



**logi bolt 1M / CH 39**



**logi bolt 2M / CH 19**




## 4.6 Conducted Out of Band Emission Measurement

### 4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedure

#### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

### 4.6.5 Deviation from Test Standard

No deviation.

### 4.6.6 EUT Operating Condition


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

- ◆ BLE1M TX Modulated on channel 2402MHz
- ◆ BLE1M TX Modulated on channel 2440MHz
- ◆ BLE1M TX Modulated on channel 2480MHz
- ◆ BLE2M TX Modulated on channel 2404MHz
- ◆ BLE2M TX Modulated on channel 2440MHz
- ◆ BLE2M TX Modulated on channel 2478MHz

#### 4.6.7 Test Results



The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

BT-LE 1M





BT-LE 2M



CH 1




CH 19




CH 38




CH 1 Band edge



CH 38 Band edge




logi bolt 1M






logi bolt 2M





## 5 Pictures of Test Arrangements


Please refer to the attached file (Test Setup Photo).

### Annex A - Band-Edge Measurement









## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---