



Zacta

TEST REPORT

Report number : Z101C-15143

Issue date : December 29, 2015

The device, as described herewith, was tested pursuant to applicable test procedure and complies with the requirements of;

FCC Part15 Subpart C

The test results are traceable to the international or national standards.

Applicant	: KYOCERA Corporation
Equipment under test (EUT)	: Mobile Phone
Model number	: KA73
FCC ID	: JOYKA73

Date of test : November 13, 16, 19, 30, December 1, 2, 17, 2015
 Test place : TÜV SÜD Zacta Ltd. Yonezawa Testing Center
 4149-7 Hachimanpara 5-chome
 Yonezawa-shi Yamagata 992-1128 Japan
 Phone: +81-238-28-2880 Fax: +81-238-28-2888
 Test results : Complied

The results in this report are applicable only to the equipment tested.
 This report shall not be re-produced except in full without the written approval of TÜV SÜD Zacta Ltd.
 This test report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Tested by : Taiki Watanabe
 Taiki Watanabe

Tested by : Hikaru Shibata
 Hikaru Shibata

Authorized by : Hiroaki Suzuki
 Hiroaki Suzuki
 Manager of EMC Technical Department



Table of contents

	Page
1. Summary of Test	4
1.1 Purpose of test	4
1.2 Standards	4
1.3 List of applied test to the EUT	4
1.4 Modification to the EUT by laboratory	4
2. Equipment Under Test	5
2.1 General Description of equipment	5
2.2 EUT information	5
2.3 Variation of the family model(s)	6
2.4 Operating channels and frequencies	6
2.5 Operating mode	6
2.6 Operating flow	7
3. Configuration of equipment	8
3.1 Equipment(s) used	8
3.2 Cable(s) used	8
3.3 System configuration	8
4. 6dB Bandwidth	9
4.1 Measurement procedure	9
4.2 Limit	9
4.3 Measurement result	9
4.4 Trace data	10
5. Maximum conducted (average) output power	13
5.1 Measurement procedure	13
5.2 Limit	13
5.3 Measurement result	13
5.4 Trace data	15
6. Band Edge Compliance of RF Conducted Emissions	18
6.1 Measurement procedure	18
6.2 Limit	18
6.3 Measurement result	19
6.4 Trace data	20
7. Spurious emissions - Conducted -	23
7.1 Measurement procedure	23
7.2 Limit	23
7.3 Measurement result	23
7.4 Trace data	24
8. Spurious Emissions - Radiated -	33
8.1 Measurement procedure	33
8.2 Calculation method	34
8.3 Limit	34
8.4 Test data	35
9. Restricted Band of Operation	37
9.1 Measurement procedure	37



Zacta

9.2 Limit.....	37
9.3 Measurement Result.....	38
9.4 Test data.....	38
10. Transmitter Power Spectral Density.....	45
10.1 Measurement procedure.....	45
10.2 Limit.....	45
10.3 Measurement result.....	45
10.4 Trace data	47
11. AC Power Line Conducted Emissions.....	50
11.1 Measurement procedure	50
11.2 Calculation method.....	50
11.3 Limit.....	50
11.4 Test data.....	51
12. Antenna requirement	52
13. Uncertainty of measurement.....	53
14. Laboratory description	54
Appendix A. Test equipment.....	55
Appendix B. Duty Cycle.....	56

1. Summary of Test

1.1 Purpose of test

It is the original test in order to verify conformance to FCC Part 15 Subpart C.

1.2 Standards

CFR47 FCC Part 15 Subpart C

1.2.1 Test Methods

ANSI C63.10-2009, KDB 558074 D01 DTS Meas Guidance v03r03

1.2.2 Deviation from standards

None

1.3 List of applied test to the EUT

Test items Section	Test items	Condition	Result
15.247(a)(2)	6dB Bandwidth	Conducted	PASS
15.247(b)(3)	Maximum conducted (average) output power	Conducted	PASS
15.247(d)	Band Edge Compliance of RF Conducted Emissions	Conducted	PASS
15.247(d) 15.205 15.209	Spurious Emissions	Conducted Radiated	PASS
15.247(d) 15.205 15.209	Restricted Bands of Operation	Radiated	PASS
15.247(e)	Transmitter Power Spectral Density	Conducted	PASS
15.207	AC Power Line Conducted Emissions	Conducted	PASS

1.3.1 Test set up

Table-Top

1.4 Modification to the EUT by laboratory

None



Zacta

2. Equipment Under Test

2.1 General Description of equipment

EUT is the Mobile Phone.

2.2 EUT information

Applicant	:	KYOCERA Corporation Yokohama Office 2-1-1 Kagahara, Tsuzuki-ku Yokohama-shi, Kanagawa, Japan Phone: +81-45-943-6253 Fax: +81-45-943-6314
Equipment under test	:	Mobile Phone
Trade name	:	Kyocera
Model number	:	KA73
Serial number	:	N/A
EUT condition	:	Pre-Production
Power ratings	:	Battery: DC 3.8V
Size	:	(W) 51.3 × (D) 113.8 × (H) 18.2 mm
Environment	:	Indoor and Outdoor use
Terminal limitation	:	-20°C to 60°C
RF Specification Protocol	:	IEEE802.11b, IEEE802.11g, IEEE802.11n (HT20)
Frequency range	:	2412MHz-2462MHz
Number of RF Channels	:	11 Channels
Modulation type	:	IEEE802.11b: DSSS (DBPSK, DQPSK, CCK) IEEE802.11g / n (HT20): OFDM (BPSK, QPSK, 16QAM, 64QAM)
Data rate	:	IEEE802.11b: 1, 2, 5.5, 11Mbps IEEE802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps IEEE802.11n (HT20 LGI): 6.5, 13, 19.5, 26, 39, 52, 58.5, 65Mbps IEEE802.11n (HT20 SGI): 7.2, 14.4, 21.7, 28.9, 43.3, 57.8, 65, 72.2Mbps
Channel separation	:	5MHz
Output power	:	23.768mW (IEEE802.11b) 16.672mW (IEEE802.11g) 16.558mW (IEEE802.11n: HT20)
Antenna type	:	Internal antenna
Antenna gain	:	2.8dBi

2.3 Variation of the family model(s)

Not applicable

2.4 Operating channels and frequencies

Channel	Frequency [MHz]
1	2412
2	2417
3	2422
4	2427
5	2432
6	2437
7	2442
8	2447
9	2452
10	2457
11	2462

2.5 Operating mode

The EUT had been tested under operating condition.
There are three channels have been tested as following:

Tested Channel	Frequency [MHz]
Low	2412
Middle	2437
High	2462

The pre-test has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates.

Tested Channel	Modulation Type	Data Rate
Low, Middle, High	IEEE802.11b: DSSS	1Mbps
Low, Middle, High	IEEE802.11g: OFDM	6Mbps
Low, Middle, High	IEEE802.11n (HT20 LGI): OFDM	MCS0 (6.5Mbps)

The field strength of spurious emissions was measured at each position of all three axis X, Y and Z to compare the level, and the maximum noise.

The worst emission was found in Z axis and the worst case recorded.

2.6 Operating flow

[Tx mode]

- i) Test program setup to the DM tool
- ii) Select a Test mode
Operating frequency: Channel Low: 2412MHz, Channel Middle: 2437MHz, Channel High: 2462MHz
- iii) Start test mode

[Rx mode]

- i) Test program setup to the DM tool
- ii) Select a Test mode
Operating frequency: Channel Low: 2412MHz, Channel Middle: 2437MHz, Channel High: 2462MHz
- iii) Start test mode

3. Configuration of equipment

3.1 Equipment(s) used

No.	Equipment	Company	Model No.	Serial No.	FCC ID / DoC	Comment
1	Mobile Phone	KYOCERA	KA73	N/A	JOYKA73	EUT
2	AC Adapter	au	N/A	N/A	N/A	*

*: AC power line Conducted Emission Test.

3.2 Cable(s) used

No.	Cable	Length[m]	Shield	Connector	Comment
a	Micro USB cable(for AC Adapter)	1.0	Yes	Metal	*

*: AC power line Conducted Emission Test.

3.3 System configuration



: Un-detachable cable

Note1: Numbers assigned to equipment or cables on this diagram correspond to the list in "3.1 Equipment(s) used" and "3.2 Cable(s) used".

4. 6dB Bandwidth

4.1 Measurement procedure


[FCC 15.247(a)(2), KDB 558074 D01 v0303, Section 8.2]

The bandwidth at 6dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;

- a) RBW = 100kHz.
- b) VBW \geq 3 x RBW.
- c) Sweep time = auto-couple.
- d) Detector = peak.
- e) Trace mode = max hold.

- Test configuration



4.2 Limit

The minimum permissible 6dB bandwidth is 500kHz.

4.3 Measurement result

Date : November 13, 2015
 Temperature : 23.6 [°C]
 Humidity : 47.4 [%]
 Test place : Shielded room No.4

Test engineer : Hikaru Shibata


Channel	Frequency [MHz]	6dB bandwidth [MHz]		
		IEEE802.11b	IEEE802.11g	IEEE802.11n (HT20)
Low	2412	7.156	16.279	16.812
Middle	2437	7.152	16.082	16.346
High	2462	7.169	16.331	16.959




Zacta

4.4 Trace data [IEEE802.11b]


Channel Low



Channel Middle



Channel High







Zacta

[IEEE802.11g]


Channel Low



Channel Middle



Channel High







Zacta

[IEEE802.11n (HT20)]


Channel Low



Channel Middle



Channel High



5. Maximum conducted (average) output power

5.1 Measurement procedure


[FCC 15.247(b)(3), KDB 558074 D01 v03r03, Section 9.2.2.1]

The peak power is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;

- a) RBW = 1-5% of the DTS bandwidth not to exceed 1MHz.
- b) VBW $\geq 3 \times$ RBW.
- c) Span ≥ 1.5 times the DTS bandwidth.
- d) Sweep time = auto-couple.
- e) Detector = RMS.
- f) Trace mode = Clear/Write, Single, 100 count
- g) Points $\geq 2 \times$ Span / RBW

- Test configuration



5.2 Limit

1W (1000mW) or less

5.3 Measurement result

Date : November 13, 2015
 Temperature : 23.6 [°C]
 Humidity : 47.4 [%]
 Test place : Shielded room No.4

Test engineer : Hikaru Shibata

**[IEEE802.11b]
Battery Full**

Channel	Center Frequency (MHz)	Reading (dBm)	Factor (dB)	Level (dBm)	Peak Output Power (mW)	Limit (mW)	Result
Low	2412.00	3.07	10.53	13.60	22.909	≤1000	PASS
Middle	2437.00	3.23	10.53	13.76	23.768	≤1000	PASS
High	2462.00	3.17	10.53	13.70	23.442	≤1000	PASS

**[IEEE802.11g]
Battery Full**

Channel	Center Frequency (MHz)	Reading (dBm)	Factor (dB)	Level (dBm)	Peak Output Power (mW)	Limit (mW)	Result
Low	2412.00	1.54	10.53	12.07	16.106	≤1000	PASS
Middle	2437.00	1.69	10.53	12.22	16.672	≤1000	PASS
High	2462.00	1.19	10.53	11.72	14.859	≤1000	PASS

**[IEEE802.11n (HT20)]
Battery Full**

Channel	Center Frequency (MHz)	Reading (dBm)	Factor (dB)	Level (dBm)	Peak Output Power (mW)	Limit (mW)	Result
Low	2412.00	1.17	10.53	11.70	14.791	≤1000	PASS
Middle	2437.00	1.66	10.53	12.19	16.558	≤1000	PASS
High	2462.00	1.08	10.53	11.61	14.488	≤1000	PASS

Calculation;

$$\text{Reading (dBm)} + \text{Factor (dB)} = \text{Level (dBm)}$$


$$10\log P = \text{Level (dBm)}$$

$$P = 10^{(\text{Maximum Peak Output Power} / 10)} \text{ (mW)}$$




Zacta

5.4 Trace data
[IEEE802.11b]
[Battery Full]
Channel Low



Channel Middle




Channel High





Zacta


[IEEE802.11g]
[Battery Full]
Channel Low



Channel Middle




Channel High






Zacta


[IEEE802.11n(HT20)]
[Battery Full]
Channel Low



Channel Middle



Channel High



6. Band Edge Compliance of RF Conducted Emissions

6.1 Measurement procedure


[FCC 15.247(d), KDB 558074 D01 v03r03, Section 11.0]

The Band Edge is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;

- a) Span = Arbitrary setting. (Setting suitable for measurement.)
- b) RBW \geq 1% of the span
- c) VBW \geq RBW
- d) Sweep time = auto-couple.
- e) Detector = peak.
- f) Trace mode = max hold.

- Test configuration



6.2 Limit

In any 100kHz bandwidth outside the frequency band the radio frequency power that is produced by the intentional radiator shall be at least 30dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.



Zacta

6.3 Measurement result

Date : November 13, 2015
 Temperature : 23.6 [°C]
 Humidity : 47.4 [%]
 Test place : Shielded room No.4

Test engineer :

Hikaru Shibata

[IEEE802.11b]

Channel	Frequency (MHz)	RF Power Level (dBm)	Band-edge Frequency (MHz)	Band-edge Level (dBm)	Difference Level (dBm)	Limit (dBm)	Result
Low	2412.00	-4.51	2400.00	-57.65	53.14	At least 30dB below from peak of RF	PASS
High	2462.00	-4.39	2483.50	-67.94	63.55	At least 30dB below from peak of RF	PASS

[IEEE802.11g]

Channel	Frequency (MHz)	RF Power Level (dBm)	Band-edge Frequency (MHz)	Band-edge Level (dBm)	Difference Level (dBm)	Limit (dBm)	Result
Low	2412.00	-9.96	2399.44	-47.47	37.51	At least 30dB below from peak of RF	PASS
High	2462.00	-10.24	2483.58	-57.43	47.19	At least 30dB below from peak of RF	PASS

[IEEE802.11n (HT20)]


Channel	Frequency (MHz)	RF Power Level (dBm)	Band-edge Frequency (MHz)	Band-edge Level (dBm)	Difference Level (dBm)	Limit (dBm)	Result
Low	2412.00	-10.06	2399.84	-47.08	37.02	At least 30dB below from peak of RF	PASS
High	2462.00	-10.22	2484.14	-57.37	47.15	At least 30dB below from peak of RF	PASS




Zacta

6.4 Trace data [IEEE802.11b]

Channel Low



Channel High







Zacta

[IEEE802.11g]

Channel Low




Channel High




[IEEE802.11n (HT20)]

Channel Low



Channel High



7. Spurious emissions - Conducted -

7.1 Measurement procedure


[FCC 15.247(d), KDB 558074 D01 v03r03, Section 11.0]

The spurious emissions (Conducted) are measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;

- a) Span = wide enough to fully capture the emission being measured.
- b) RBW = 100 kHz.
- c) VBW \geq RBW.
- d) Sweep time = auto-couple.
- e) Detector = peak.
- f) Trace mode = max hold.

- Test configuration



7.2 Limit

In any 100kHz bandwidth outside the frequency band the radio frequency power that is produced by the intentional radiator shall be at least 30dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

7.3 Measurement result

Date : November 16, 2015
 Temperature : 23.8 [°C]
 Humidity : 45.1 [%]
 Test place : Shielded room No.4


Tested by : Hikaru Shibata

Channel	Frequency [MHz]	Limit [dB]	Results Chart	Result
Low	2412	At least 30dB below from peak of RF	See the trace Data	PASS
Middle	2437	At least 30dB below from peak of RF	See the trace Data	PASS
High	2462	At least 30dB below from peak of RF	See the trace Data	PASS




Zacta


7.4 Trace data
[IEEE802.11b]
Channel Low
30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz



15GHz-20GHz




20GHz-25GHz






Zacta


Channel Middle 30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz



15GHz-20GHz




20GHz-25GHz






Zacta


Channel High 30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz



15GHz-20GHz




20GHz-25GHz






Zacta


**[IEEE802.11g]
Channel Low
30MHz-1GHz**




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz



15GHz-20GHz




20GHz-25GHz






Zacta


Channel Middle 30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz



15GHz-20GHz




20GHz-25GHz






Zacta


Channel High 30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz



15GHz-20GHz




20GHz-25GHz






Zacta


[IEEE802.11n (HT20)]
Channel Low
30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz



15GHz-20GHz




20GHz-25GHz






Zacta


Channel Middle 30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz



15GHz-20GHz




20GHz-25GHz






Zacta


Channel High 30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz



15GHz-20GHz



20GHz-25GHz



8. Spurious Emissions - Radiated -

8.1 Measurement procedure

[FCC 247(d), 15.205, 15.209, KDB 558074 D01 v03r03, Section 12.0]

Test was applied by following conditions.

Test method	:	ANSI C63.10
Frequency range	:	9kHz to 25GHz
Test place	:	3m Semi-anechoic chamber
EUT was placed on	:	FRP table / (W)2.0m × (D)1.0m × (H)0.8m
Antenna distance	:	3m
Test receiver setting	:	Below 1GHz
- Detector	:	Average (9kHz-90kHz, 110kHz-490kHz), Quasi-peak
- Bandwidth	:	200Hz, 120kHz
Spectrum analyzer setting	:	Above 1GHz
- Peak	:	RBW=1MHz, VBW=3MHz, Span=0Hz, Sweep=auto
- Average	:	RBW=1MHz, VBW=10Hz, Span=0Hz, Sweep=auto
	:	Display mode=Linear


Average Measurement Setting [VBW]

Mode	Duty Cycle (%)	T _{on} (us)	T _{off} (us)	Determined VBW Setting
IEEE802.11b	99.03	1022	10	10Hz (Duty Cycle \geq 98%)
IEEE802.11g	99.42	1362	8	10Hz (Duty Cycle \geq 98%)
IEEE802.11n(HT20)	99.38	1276	8	10Hz (Duty Cycle \geq 98%)

Radiated emission measurements are performed at 3m distance with the broadband antenna (Loop antenna, TRILOG antenna and Double ridged guide antenna). The antenna is positioned both the horizontal and vertical planes of polarization and height is varied 1m to 4m and stopped at height producing the maximum emission. As for the Loop antenna, it is positioned with its plane vertical, and the center of the Loop antenna is 1m above the ground plane.

The EUT is Placed on a turntable, which is 0.8m above ground plane. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. The test results represent the worst case emission for each emission with manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation. Sufficient time for the EUT, support equipment, and test equipment are allowed in order for them to warm up to their normal operating condition.

- Test configuration



8.2 Calculation method

[9kHz to 150kHz]

Emission level = Reading + (Ant. factor + Cable system loss)

Margin = Limit – Emission level

[150kHz to 25GHz]

Emission level = Reading + (Ant. factor + Cable system loss – Amp. Gain)

Margin = Limit – Emission level

Example:

Limit @ 4804.0MHz : 74.0dBuV/m (Peak Limit)

S.A Reading = 39.9dBuV Cable system loss = 8.3dB

Result = 39.9 + 8.3 = 48.2dBuV/m

Margin = 74.0 - 48.2 = 25.8dB

8.3 Limit

Frequency [MHz]	Field strength		Distance [m]
	[uV/m]	[dBuV/m]	
0.009-0.490	2400 / F [kHz]	20logE [uV/m]	300
0.490-1.705	24000 / F [kHz]	20logE [uV/m]	30
1.705-30	30	29.5	30
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level [dBuV/m] = 20log Emission [uV/m]
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition modulation.



Zacta

8.4 Test data

Date : November 30, 2015
 Temperature : 20.1 [°C]
 Humidity : 22.4 [%]
 Test place : 3m Semi-anechoic chamber

Test engineer : Hikaru Shibata

[IEEE802.11b]

Channel Low

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c. f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]
1	4824.000	H	49.5	36.0	8.4	57.9	44.4	74.0	54.0	16.1	9.6	100.0	0.0
2	4824.000	V	49.1	35.9	8.4	57.5	44.3	74.0	54.0	16.5	9.7	100.0	0.0

Channel Middle

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c. f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]
1	4874.000	H	48.6	36.0	8.7	57.3	44.7	74.0	54.0	16.7	9.3	100.0	0.0
2	4874.000	V	49.9	36.0	8.7	58.6	44.7	74.0	54.0	15.4	9.3	100.0	0.0

Channel High

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c. f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]
1	4924.000	H	49.7	36.0	8.9	58.6	44.9	74.0	54.0	15.4	9.1	100.0	0.0
2	4924.000	V	50.3	36.6	8.9	59.2	45.5	74.0	54.0	14.8	8.5	129.0	264.0

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.
3. No emission was detected in the receive mode.

[IEEE802.11g] Channel Low

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]
1	4824.000	H	48.8	35.8	8.4	57.2	44.2	74.0	54.0	16.8	9.8	100.0	0.0
2	4824.000	V	49.7	35.8	8.4	58.1	44.2	74.0	54.0	15.9	9.8	100.0	0.0

Channel Middle

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]
1	4874.000	H	49.4	35.8	8.7	58.1	44.5	74.0	54.0	15.9	9.5	100.0	0.0
2	4874.000	V	49.6	35.8	8.7	58.3	44.5	74.0	54.0	15.7	9.5	100.0	0.0

Channel High

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]
1	4924.000	H	49.8	35.9	8.9	58.7	44.8	74.0	54.0	15.3	9.2	100.0	0.0
2	4924.000	V	48.4	36.0	8.9	57.3	44.9	74.0	54.0	16.7	9.1	100.0	0.0

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.
3. No emission was detected in the receive mode.

[IEEE802.11n (HT20)]

Channel Low

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]
1	4824.000	H	48.7	35.5	8.4	57.1	43.9	74.0	54.0	16.9	10.1	100.0	0.0
2	4824.000	V	49.6	35.8	8.4	58.0	44.2	74.0	54.0	16.0	9.8	100.0	0.0

Channel Middle

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]
1	4874.000	H	48.8	35.5	8.7	57.5	44.2	74.0	54.0	16.5	9.8	100.0	0.0
2	4874.000	V	49.5	35.3	8.7	58.2	44.0	74.0	54.0	15.8	10.0	100.0	0.0

Channel High

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]
1	4924.000	H	48.6	35.6	8.9	57.5	44.5	74.0	54.0	16.5	9.5	100.0	0.0
2	4924.000	V	48.8	35.6	8.9	57.7	44.5	74.0	54.0	16.3	9.5	100.0	0.0

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.
3. No emission was detected in the receive mode.

9. Restricted Band of Operation

9.1 Measurement procedure

[FCC 247(d), 15.205, 15.209, KDB 558074 D01 v03r03, Section 12.0]

Test was applied by following conditions.

Test method : ANSI C63.10
 Test place : 3m Semi-anechoic chamber
 EUT was placed on : FRP table / (W)2.0m × (D)1.0m × (H)0.8m
 Antenna distance : 3m

Spectrum analyzer setting
 - Peak : RBW=1MHz, VBW=3MHz, Span=Arbitrary setting, Sweep=auto
 - Average : RBW=1MHz, VBW=10Hz, Span=Arbitrary setting, Sweep=auto
 Display mode=Linear


Average Measurement Setting [VBW]

Mode	Duty Cycle (%)	T _{on} (us)	T _{off} (us)	Determined VBW Setting
IEEE802.11b	99.03	1022	10	10Hz (Duty Cycle \geq 98%)
IEEE802.11g	99.42	1362	8	10Hz (Duty Cycle \geq 98%)
IEEE802.11n(HT20)	99.38	1276	8	10Hz (Duty Cycle \geq 98%)

Radiated emission measurements are performed at 3m distance with the broadband antenna (Double ridged guide antenna). The antenna is positioned both the horizontal and vertical planes of polarization and height is varied 1m to 4m and stopped at height producing the maximum emission.

The EUT is Placed on a turntable, which is 0.8m above ground plane. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. The test results represent the worst case emission for each emission with manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation. Sufficient time for the EUT, support equipment, and test equipment are allowed in order for them to warm up to their normal operating condition.

- Test configuration



9.2 Limit

Emission at the boundary of the restricted band provided by 15.205 shall be lower than 15.209 limit.



Zacta

9.3 Measurement Result

Channel	Frequency [MHz]	Results Chart	Result
Low	2412	See the Trace Data	Pass
High	2462	See the Trace Data	Pass

9.4 Test data


Date	: December 1, 2015		
Temperature	: 22.1[°C]		
Humidity	: 24.9 [%]	Test engineer	:
Test place	: 3m Semi-anechoic chamber		<u>Taiki Watanabe</u>
Date	: December 2, 2015		
Temperature	: 23.1[°C]		
Humidity	: 23.2 [%]	Test engineer	:
Test place	: 3m Semi-anechoic chamber		<u>Taiki Watanabe</u>
Date	: December 17, 2015		
Temperature	: 23.0[°C]		
Humidity	: 22.4 [%]	Test engineer	:
Test place	: 3m Semi-anechoic chamber		<u>Taiki Watanabe</u>



Zacta


[IEEE802.11b]

Channel Low Horizontal Peak




Date: 1.DEC.2015 13:12:47

Average




Date: 1.DEC.2015 13:08:08

Vertical Peak



Date: 1.DEC.2015 13:21:00

Average




Date: 1.DEC.2015 13:23:37




Zacta

Channel High Horizontal Peak




Date: 1.DEC.2015 13:38:27

Average




Date: 1.DEC.2015 13:38:07

Vertical Peak



Date: 1.DEC.2015 13:36:23

Average




Date: 1.DEC.2015 13:53:57



Zacta


[IEEE802.11g]

Channel Low Horizontal Peak




Date: 17.DEC.2015 22:14:11

Average




Date: 17.DEC.2015 22:15:43

Vertical Peak



Date: 2.DEC.2015 06:33:53

Average




Date: 2.DEC.2015 06:32:04




Zacta

Channel High Horizontal Peak




Date: 2.DEC.2015 06:46:32

Average




Date: 2.DEC.2015 06:45:47

Vertical Peak



Date: 2.DEC.2015 06:51:32

Average




Date: 2.DEC.2015 06:50:11



Zacta


[IEEE802.11n (HT20)]

Channel Low Horizontal Peak




Date: 2.DEC.2015 07:19:41

Average




Date: 2.DEC.2015 07:19:13

Vertical Peak



Date: 2.DEC.2015 07:37:25

Average




Date: 2.DEC.2015 07:36:54




Zacta

Channel High Horizontal Peak




Date: 17.DEC.2015 22:40:43

Average




Date: 17.DEC.2015 22:39:16

Vertical Peak



Date: 2.DEC.2015 07:00:55

Average



Date: 2.DEC.2015 07:03:09

10. Transmitter Power Spectral Density

10.1 Measurement procedure


[FCC 15.247(e), KDB 558074 D01 v03r03, Section 10.2]

The peak power is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;

- a) Span = 1.5 times the 6 dB bandwidth.
- b) RBW = 3kHz - 100kHz.
- c) VBW \geq 3 x RBW.
- d) Sweep time = auto-couple.
- e) Detector = peak.
- f) Trace mode = max hold.

- Test configuration



10.2 Limit

The peak power spectral density shall not be greater than 8dBm in any 3kHz band.

10.3 Measurement result

Date : November 16, 2015
 Temperature : 23.8 [°C]
 Humidity : 45.1 [%]
 Test place : Shielded room No.4

Test engineer :

Hikaru Shibata

[IEEE802.11b]

Channel	Center Frequency (MHz)	Reading (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dBm)	Result
Low	2412.00	-17.91	10.53	-7.38	8.00	15.38	PASS
Middle	2437.00	-16.47	10.53	-5.94	8.00	13.94	PASS
High	2462.00	-17.58	10.53	-7.05	8.00	15.05	PASS

Calculation;

Transmitter Power Spectral Density Level (Margin) = Limit – (Reading + Factor)

[IEEE802.11g]

Channel	Center Frequency (MHz)	Reading (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dBm)	Result
Low	2412.00	-22.85	10.53	-12.32	8.00	20.32	PASS
Middle	2437.00	-22.81	10.53	-12.28	8.00	20.28	PASS
High	2462.00	-22.60	10.53	-12.07	8.00	20.07	PASS

Calculation;

Transmitter Power Spectral Density Level (Margin) = Limit – (Reading + Factor)

[IEEE802.11n (HT20)]

Channel	Center Frequency (MHz)	Reading (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dBm)	Result
Low	2412.00	-23.31	10.53	-12.78	8.00	20.78	PASS
Middle	2437.00	-22.91	10.53	-12.38	8.00	20.38	PASS
High	2462.00	-23.34	10.53	-12.81	8.00	20.81	PASS

Calculation;


Transmitter Power Spectral Density Level (Margin) = Limit – (Reading + Factor)




Zacta

10.4 Trace data
[IEEE802.11b]


Channel Low



Channel Middle



Channel High







Zacta

[IEEE802.11g]


Channel Low



Channel Middle



Channel High







Zacta

[IEEE802.11n (HT20)]


Channel Low



Channel Middle



Channel High



11. AC Power Line Conducted Emissions

11.1 Measurement procedure [FCC 15.207]

Test was applied by following conditions.


Test method	: ANSI C63.10
Frequency range	: 0.15MHz to 30MHz
Test place	: 10m Semi-anechoic chamber
EUT was placed on	: FRP table / (W)2.0m × (D)1.0m × (H)0.8m
Vertical Metal Reference Plane	: (W)2.0m × (H)2.0m 0.4m away from EUT
Test receiver setting	
- Detector	: Quasi-peak, Average
- Bandwidth	: 9kHz

EUT and peripherals are connected to 50Ω/50μH Line Impedance Stabilization Network (LISN) which are connected to reference ground plane, and are placed 80cm away from EUT. Excess of AC power cable is bundled in center.

LISN for peripheral is terminated in 50Ω.

EUT operating mode is selected to emit the maximum noise. Overall frequency range is investigated with spectrum analyzer using peak detector. Maximum emission configuration is determined by manipulating the EUT, peripherals, interconnecting cables. Then, emission measurements are performed with test receiver in above setting to each current-carrying conductor of the mains port. Sufficient time for EUT, peripherals and test equipment is provided in order for them to warm up to their normal operating condition. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits.

- Test configuration



11.2 Calculation method

Emission level = Reading + (LISN. factor + Cable system loss)

Margin = Limit – Emission level

11.3 Limit

Frequency [MHz]	Limit	
	QP [dBuV]	AV [dBuV]
0.15-0.5	66-56*	56-46*
0.5-5	56	46
5-30	60	50


*: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.



Zacta

11.4 Test data

***** CONDUCTED EMISSION at MAINS PORT *****
 [10m semi-anechoic chamber #1]



Final Result

— L1 Phase —

No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading AV [dB(μV)]	c. f [dB]	Result QP [dB(μV)]	Result AV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin AV [dB]
1	0.798	21.9	10.8	10.6	32.5	21.4	56.0	46.0	23.5	24.6
2	1.238	23.6	10.6	10.6	34.2	21.2	56.0	46.0	21.8	24.8
3	1.588	26.1	11.5	10.7	36.8	22.2	56.0	46.0	19.2	23.8
4	1.883	27.3	10.6	10.7	38.0	21.3	56.0	46.0	18.0	24.7
5	2.001	25.5	10.6	10.7	36.2	21.3	56.0	46.0	19.8	24.7
6	2.523	26.5	18.2	10.8	37.3	29.0	56.0	46.0	18.7	17.0

— L2 Phase —

No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading AV [dB(μV)]	c. f [dB]	Result QP [dB(μV)]	Result AV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin AV [dB]
1	0.359	32.1	21.6	10.7	42.8	32.3	58.8	48.8	16.0	16.5
2	0.527	24.0	13.9	10.7	34.7	24.6	56.0	46.0	21.3	21.4
3	0.763	24.8	12.6	10.7	35.5	23.3	56.0	46.0	20.5	22.7
4	1.001	25.3	13.2	10.7	36.0	23.9	56.0	46.0	20.0	22.1
5	1.608	25.6	12.0	10.8	36.4	22.8	56.0	46.0	19.6	23.2
6	1.912	25.9	9.8	10.8	36.7	20.6	56.0	46.0	19.3	25.4



Zacta

12. Antenna requirement

According to FCC section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The antenna is a special antenna mounted inside of the EUT. Therefore, the EUT complies with the antenna requirement of FCC section 15.203.



Zacta

13. Uncertainty of measurement

Expanded uncertainties stated are calculated with a coverage Factor $k=2$.

Please note that these results are not taken into account when determining compliance or non-compliance with test result.

Test item	Measurement uncertainty
Conducted emission at mains port	$\pm 3.0\text{dB}$
Radiated emission (9kHz – 30MHz)	$\pm 4.4\text{dB}$
Radiated emission (30MHz – 1000MHz)	$\pm 4.5\text{dB}$
Radiated emission (1000MHz – 26GHz)	$\pm 3.9\text{dB}$



Zacta

14. Laboratory description

1. Location:

TÜV SÜD Zacta Ltd. Yonezawa Testing Center
 4149-7 Hachimanpara 5-chome Yonezawa-shi Yamagata 992-1128 Japan
 Phone: +81-238-28-2880 Fax: +81-238-28-2888

2. Facility filing information:

1) NVLAP accreditation: NVLAP Lab. code: 200306-0

2) VLAC accreditation: Lab. code: VLAC-013

Site name	Radiated emission	Conducted emission for mains port	Conducted emission for telecom port	Radiated emission (CMAD)	Expiry Date
3m Semi-anechoic chamber	VLAC-013	VLAC-013	VLAC-013	-	Jul. 3, 2017
10m Semi-anechoic chamber No.1				VLAC-013	
10m Semi-anechoic chamber No.2				VLAC-013	
Shielded room No.1	-	VLAC-013	-	-	

3) FCC filing:

Site name	Registration Number	Expiry Date
Site 3	91065	Oct. 1, 2017
3m Semi-anechoic chamber	540072	Feb. 20, 2017
10m Semi-anechoic chamber No.1		
10m Semi-anechoic chamber No.2		
Shielded room No.1		

4) Industry Canada Oats site filing:

Site name	Sites on file: Oats 3m/10m	Expiry Date
Site 3	4224A-3	Dec. 3, 2017
3m Semi-anechoic chamber	4224A-4	
10m Semi-anechoic chamber No.1	4224A-5	
10m Semi-anechoic chamber No.2	4224A-6	Jan. 15, 2017

5) VCCI site filing:

Site name	Radiated emission	Conducted emission for mains port	Conducted emission for telecom port	Expiry Date
Site 3	R-138	C-134	T-1222	Nov. 16, 2017
3m Semi-anechoic chamber	A-0166	A-0166	A-0166	Jul. 3, 2017
10m Semi-anechoic chamber No.1				
10m Semi-anechoic chamber No.2				
Shielded room No.1	-	A-0166	A-0166	

6) TÜV SÜD PS authorization:

Authorized as an EMC test laboratory

7) TÜV Rheinland authorization:

Authorized as an EMC test laboratory

Appendix A. Test equipment

Antenna port conducted test

Equipment	Company	Model No.	Serial No.	Cal. due	Cal. date
Spectrum analyzer	Agilent Technologies	E4440A	US44302655	Jun. 30, 2016	Jun. 11, 2015
Microwave cable	RS	YH-13S5	N/A (S403)	May 31, 2016	May 10, 2015
Coaxial cable	RS	YH20_S1	N/A (S389)	Aug. 31, 2016	Aug. 6, 2015
Attenuator	Weinschel	56-10	J4993	Nov. 30, 2016	Nov. 12, 2015
Power meter	ROHDE&SCHWARZ	NRP2	103269	Jun. 30, 2016	Jun. 25, 2015
Power sensor	ROHDE&SCHWARZ	NRP-Z81	102467	Jun. 30, 2016	Jun. 25, 2015

Radiated emission

Equipment	Company	Model No.	Serial No.	Cal. Due	Cal. Date
EMI Receiver	ROHDE&SCHWARZ	ESCI	100764	Aug. 31, 2016	Aug. 21, 2015
Preamplifier	ANRITSU	MH648A	M96057	Jun. 30, 2016	Jun. 30, 2015
Loop antenna	ROHDE&SCHWARZ	HFH2-Z2	892246/010	Apr. 30, 2016	Apr. 2, 2015
Attenuator	TDC	TAT-43B-06	N/A (S209)	Apr. 30, 2016	Apr. 16, 2015
Biconical antenna	Schwarzbeck	VHA9103/BBA9106	2155	Jun. 30, 2016	Jun. 4, 2015
Log periodic antenna	Schwarzbeck	UHALP9108A	0560	Jun. 30, 2016	Jun. 4, 2015
Attenuator	TME	CFA-01NPJ-6	N/A (S275)	Jun. 30, 2016	Jun. 23, 2015
Attenuator	TME	CFA-01NPJ-3	N/A (S272)	Jun. 30, 2016	Jun. 23, 2015
Spectrum analyzer	Agilent Technologies	E4440A	US40420937	Jul. 31, 2016	Jul. 23, 2015
Preamplifier	Agilent Technologies	8449B	3008A1008	Dec. 31, 2015	Dec. 5, 2014
Double ridged guide antenna	EMCO	3115	5205	Feb. 29, 2016	Feb. 16, 2015
Attenuator	Agilent Technologies	8491B	MY39268633	Feb. 29, 2016	Feb. 1, 2015
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	BBHA9170189	Jun. 30, 2016	Jun. 16, 2015
Preamplifier	TJSJ	MLA-100M18-B02-40	1929118	May 31, 2016	May 1, 2015
Notch filter	Micro-Tronics	BRM50702	045	Nov. 30, 2016	Nov. 12, 2015
Microwave cable	SUHNER	SUCOFLEX104/9m	346316/4	Oct. 31, 2016	Oct. 23, 2015
		SUCOFLEX104/1m	322084/4	Oct. 31, 2016	Oct. 23, 2015
		SUCOFLEX104/1.5m	317226/4	Oct. 31, 2016	Oct. 23, 2015
		SUCOFLEX104/7m	41625/6	Oct. 31, 2016	Oct. 23, 2015
PC	DELL	DIMENSION E521	75465BX	N/A	N/A
Software	TOYO Corporation	EP5/RE-AJ	0611193/V5.4.011	N/A	N/A
3m Semi-anechoic chamber	TOKIN	N/A	N/A (9002-NSA)	Apr. 30, 2016	Apr. 27, 2015
3m Semi-anechoic chamber	TOKIN	N/A	N/A (9002-SVSWR)	Apr. 30, 2016	Apr. 27, 2015

Conducted emission at mains port


Equipment	Company	Model No.	Serial No.	Cal. due	Cal. date
EMI Receiver	ROHDE&SCHWARZ	ESCI	100765	Sep. 30, 2016	Sep. 2, 2015
Attenuator	TYC	BA-PJ-10	N/A (S344)	Apr. 30, 2016	Apr. 6, 2015
Line impedance stabilization network for EUT	Kyoritsu Electrical Works, Ltd.	KNW-407F	8-2003-1	Mar. 31, 2016	Mar. 5, 2015
Coaxial cable	FUJIKURA	5D-2W/4m	N/A (S349)	Feb. 29, 2016	Feb. 27, 2015
Coaxial cable	SUHNER	SUCOFLEX104/2m	317672/4	May 31, 2016	May 29, 2015
Coaxial cable	SUHNER	RG214/U/25m	N/A (S191)	Feb. 29, 2016	Feb. 27, 2015
PC	HP	Dc7800small	JPA7450FPJ	N/A	N/A
Software	TOYO Corporation	EP5/CE-AJ	0611193/V5.6.000	N/A	N/A

*: The calibrations of the above equipment are traceable to NIST or equivalent standards of the reference organizations.

Appendix B. Duty Cycle


[Plot & Calculation]

11b




$$\text{Duty Cycle} = T_{\text{on}} / (T_{\text{on}} + T_{\text{off}}) = 1022[\mu\text{s}] / (1022[\mu\text{s}] + 10[\mu\text{s}]) = 99.03\%$$

11g



$$\text{Duty Cycle} = T_{\text{on}} / (T_{\text{on}} + T_{\text{off}}) = 1362[\mu\text{s}] / (1362[\mu\text{s}] + 8[\mu\text{s}]) = 99.42\%$$

11n(HT:20)



$$\text{Duty Cycle} = T_{\text{on}} / (T_{\text{on}} + T_{\text{off}}) = 1276[\mu\text{s}] / (1276[\mu\text{s}] + 8[\mu\text{s}]) = 99.38\%$$