

RF Exposure Report

Report No.: SABHAA-WTW-P20070391

FCC ID: JOYDA39

Test Model: AL-T51A2-1

Series Model: AL-T52V1

Received Date: Jul. 20, 2020

Test Date: Jul. 31 ~ Aug. 15, 2020

Issued Date: Sep. 01, 2020

Applicant: Kyocera Corporation

Address: 2-1-1 Kagahara, Tsuzuki-ku Yokohama-city Kanagawa 224-8502 Japan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan
Branch Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

FCC Registration / 788550 / TW0003

Designation Number:



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SABHAA-WTW-P20070391	Original release.	Sep. 01, 2020

1 Certificate of Conformity

Product: Telematics Module

Brand: Kyocera

Test Model: AL-T51A2-1

Series Model: AL-T52V1

Sample Status: Engineering Sample

Applicant: Kyocera Corporation


Test Date: Jul. 31 ~ Aug. 15, 2020

Standards: FCC Part 2 (Section 2.1091)

References Test Guidance : KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : , **Date:** Sep. 01, 2020
Gina Liu / Specialist

Approved by : , **Date:** Sep. 01, 2020
Dylan Chiou / Senior Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

3 Calculation Result of Maximum Power

Function	Frequency Band (MHz)	ERP (dBm)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA Band 5	826.4~846.6	17.30	19.45	20	0.018	0.551
LTE Band 12 (Channel Bandwidth 1.4MHz)	699.7~715.3	24.10	26.25	20	0.084	0.466
FCC Part 22: LTE Band 26 (Channel Bandwidth 1.4MHz)	824.7~848.3	22.00	24.15	20	0.052	0.550
FCC Part 90: LTE Band 26 (Channel Bandwidth 1.4MHz)	814.7~823.3	23.30	25.45	20	0.070	0.543

Note: ERP=EIRP-2.15

Function	Frequency Band (MHz)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA Band 2	1852.4~1907.6	22.60	20	0.036	1
WCDMA Band 4	1712.4~1752.6	18.30	20	0.013	1
LTE Band 2 (Channel Bandwidth 1.4MHz)	1850.7~1909.3	27.80	20	0.120	1
LTE Band 4 (Channel Bandwidth 10MHz)	1715.0~1750.0	24.80	20	0.060	1

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

Max.: WWAN 3G + WWAN 4G = $0.036/1 + 0.120/1 = 0.036 + 0.120 = 0.156 < 1$

---END---