

# TEST REPORT



**DT&C Co., Ltd.**

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042  
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRRFCC2110-0104

2. Customer

• Name : Kyocera Corporation

• Address : Yokohama Office 2-1-1 Kagahara, Tsuzuki-ku Yokohama-shi, Kanagawa, Japan

3. Use of Report : FCC Original Grant

4. Product Name / Model Name : Mobile Phone / EB1084

FCC ID : JOYEB1084

5. FCC Regulation(s) : CFR 47 Part 2 subpart 2.1093

Test Method Used : IEEE 1528-2013, IEC/IEEE 62209-1528

FCC SAR KDB Publications (Details in test report)

6. Date of Test : 2021.10.18 ~ 2021.10.22



7. Location of Test :  Permanent Testing Lab  On Site Testing

8. Testing Environment : Refer to appended test report.

9. Test Result : Refer to attached test report.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test report is not related to KOLAS accreditation.

Affirmation	Tested by Name : WonJu Ji 	Reviewed by Name : HakMin Kim 
-------------	--	--

2021 . 10 . 28 .

**DT&C Co., Ltd.**

If this report is required to confirmation of authenticity, please contact to [report@dtnc.net](mailto:report@dtnc.net)

## Test Report Version

Test Report No.	Date	Description	Tested by	Reviewed by
DRRFCC2110-0104	Oct. 28, 2021	Initial issue	WonJu Ji	HakMin Kim

**Table of Contents**

<b>1. DESCRIPTION OF DEVICE .....</b>	<b>5</b>
1.1 General Information.....	5
1.2 Power Reduction for SAR.....	6
1.3 Nominal and Maximum Output Power Specifications.....	6
1.4 DUT Antenna Locations.....	6
1.5 Simultaneous Transmission Capabilities.....	6
1.6 Miscellaneous SAR Test Considerations.....	6
1.7 Guidance Applied.....	7
1.8 Device Serial Numbers.....	7
1.9 FCC & ISED MRA test lab designation no. : KR0034.....	7
<b>2. LTE INFORMATION.....</b>	<b>8</b>
<b>3. INTROCUCTION.....</b>	<b>9</b>
<b>4. DOSIMETRIC ASSESSMENT .....</b>	<b>10</b>
4.1 Measurement Procedure.....	10
<b>5. DEFINITION OF REFERENCE POINTS .....</b>	<b>12</b>
5.1 Ear Reference Point.....	12
5.2 Handset Reference Points.....	12
<b>6. TEST CONFIGURATION POSITIONS FOR HANDSETS.....</b>	<b>13</b>
6.1 Device Holder.....	13
6.2 Positioning for Cheek/Touch.....	13
6.3 Positioning for Ear / 15 ° Tilt.....	13
6.4 Body-Worn Accessory Configurations.....	14
6.5 Extremity Exposure Configurations.....	14
6.6 Wireless Router Configurations.....	15
6.7 Phablet Configurations.....	15
<b>7. RF EXPOSURE LIMITS.....</b>	<b>16</b>
<b>8. FCC MEASUREMENT PROCEDURES .....</b>	<b>17</b>
8.1 Measured and Reported SAR.....	17
8.2 Procedures Used to Establish RF Signal for SAR.....	17
8.3 SAR Measurement Conditions for WCDMA (UMTS).....	17
8.3.1 Output Power Verification.....	17
8.3.2 Head SAR Measurements for Handsets.....	17
8.3.3 Body SAR Measurements.....	18
8.3.4 Release 5 HSDPA Data Devices.....	18
8.3.5 Release 6 HSUPA Data Devices.....	18
8.4 SAR Measurement Conditions for LTE.....	19
8.4.1 Spectrum Plots for RB Configurations.....	19
8.4.2 MPR.....	19
8.4.3 A-MPR.....	19
8.4.4 Required RB Size and RB Offsets for SAR Testing.....	19
8.4.5 64QAM uplink.....	20
8.5 SAR Testing with 802.11 Transmitters.....	20
8.5.1 General Device Setup.....	20
8.5.2 U-NII and U-NII-2A.....	20
8.5.3 U-NII-2C and U-NII-3.....	20
8.5.4 Initial Test Position Procedure.....	21
8.5.5 2.4 GHz SAR Test Requirements.....	21
8.5.6 OFDM Transmission Mode and SAR Test Channel Selection.....	21
8.5.7 Initial Test Configuration Procedure.....	21
8.5.8 Subsequent Test Configuration Procedures.....	21
<b>9. RF CONDUCTED POWERS.....</b>	<b>22</b>
9.1 GSM Nominal and Maximum Output Power Spec and Conducted Powers.....	22
9.2 WCDMA Nominal and Maximum Output Power Spec and Conducted Powers.....	23
9.3 LTE Nominal and Maximum Output Power Spec and Conducted Powers.....	24
9.4 WLAN Nominal and Maximum Output Power Spec and Conducted Powers.....	28
9.5 Bluetooth Conducted Powers.....	30

<b>10. SYSTEM VERIFICATION</b>	<b>32</b>
10.1 Tissue Verification	32
10.2 Test System Verification	33
<b>11. SAR TEST RESULTS</b>	<b>34</b>
11.1 Head SAR Results	34
11.2 Standalone Body-Worn SAR Worn SAR Results	36
11.3 Standalone Hotspot SAR Results	38
11.4 Standalone Phablet SAR Results	39
11.5 SAR Test Notes	40
<b>12. FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS</b>	<b>43</b>
12.1 Introduction	43
12.2 Simultaneous Transmission Procedures	43
12.3 Simultaneous Transmission Capabilities	43
12.4 Head SAR Simultaneous Transmission Analysis	45
12.5 Body-Worn Simultaneous Transmission Analysis	47
12.6 Hotspot SAR Simultaneous Transmission Analysis	49
12.7 Phablet SAR Simultaneous Transmission Analysis	50
12.8 Simultaneous Transmission Conclusion	50
<b>13. SAR MEASUREMENT VARIABILITY</b>	<b>51</b>
13.1 Measurement Variability	51
13.2 Measurement Uncertainty	51
<b>14. EQUIPMENT LIST</b>	<b>52</b>
<b>15. MEASUREMENT UNCERTAINTIES</b>	<b>53</b>
<b>16. CONCLUSION</b>	<b>60</b>
<b>17. REFERENCES</b>	<b>61</b>
<b>APPENDIX A. – Probe Calibration Data</b>	<b>63</b>
<b>APPENDIX B. – Dipole Calibration Data</b>	<b>121</b>
<b>APPENDIX C. – SAR Tissue Specifications</b>	<b>162</b>
<b>APPENDIX D. – SAR SYSTEM VALIDATION</b>	<b>164</b>
<b>APPENDIX E. – Description of Test Equipment</b>	<b>166</b>

# 1. DESCRIPTION OF DEVICE

## 1.1 General Information

EUT type	Mobile Phone					
FCC ID	JOYEB1084					
Equipment model name	EB1084					
Equipment add model name	N/A					
Equipment serial no.	Identical prototype					
FCC & ISED MRA Designation No.	KR0034					
ISED#	5740A					
Mode(s) of Operation	GSM 1900, WCDMA 1700, WCDMA 1900, LTE Band 4, 2, 2.4 G W-LAN (802.11b/g/n-HT20), 5 G W-LAN (802.11a/n-HT20/n-HT40/ac-VHT20/ac-VHT40/ac-VHT80), Bluetooth					
TX Frequency Range	<b>Band</b>	<b>Mode</b>	<b>Operating Modes</b>	<b>Bandwidth</b>	<b>Frequency</b>	
	GSM 1900	GSM/GPRS	Voice/Data	-	1 850.2 ~ 1 909.8 MHz	
	WCDMA 1700	WCDMA	Voice/Data	-	1 712.4 ~ 1 752.6 MHz	
	WCDMA 1900	WCDMA	Voice/Data	-	1 852.4 ~ 1 907.6 MHz	
	LTE Band 4	LTE	Voice/Data	1.4/3/5/10/15/20MHz	1 710.7 ~ 1 754.3 MHz	
	LTE Band 2	LTE	Voice/Data	1.4/3/5/10/15/20MHz	1 850.7 ~ 1 909.3 MHz	
	2.4 GHz W-LAN	802.11b/g/n	Voice/Data	HT20	2 412 ~ 2 462 MHz	
	5.2 GHz W-LAN	802.11a/n/ac	Voice/Data	HT20/VHT20	5 180 ~ 5 240 MHz	
		802.11n/ac	Voice/Data	HT40/VHT40	5 190 ~ 5 230 MHz	
		802.11ac	Voice/Data	VHT80	5 210 MHz	
	5.3 GHz W-LAN	802.11a/n/ac	Voice/Data	HT20/VHT20	5 260 ~ 5 320 MHz	
		802.11n/ac	Voice/Data	HT40/VHT40	5 270 ~ 5 310 MHz	
		802.11ac	Voice/Data	VHT80	5 290 MHz	
	5.6 GHz W-LAN	802.11a/n/ac	Voice/Data	HT20/VHT20	5 500 ~ 5 700 MHz	
		802.11n/ac	Voice/Data	HT40/VHT40	5 510 ~ 5 670 MHz	
		802.11ac	Voice/Data	VHT80	5 530 MHz	
	5.8 GHz W-LAN	802.11a/n/ac	Voice/Data	HT20/VHT20	5 745 ~ 5 825 MHz	
		802.11n/ac	Voice/Data	HT40/VHT40	5 755 ~ 5 795 MHz	
		802.11ac	Voice/Data	VHT80	5 775 MHz	
	Bluetooth	-	Data	-	2 402 ~ 2 480 MHz	
	RX Frequency Range	GSM 1900	GSM/GPRS	Voice/Data	-	1 930.2 ~ 1 989.8 MHz
		WCDMA 1700	WCDMA	Voice/Data	-	2 112.4 ~ 2 152.6 MHz
		WCDMA 1900	WCDMA	Voice/Data	-	1 932.4 ~ 1 987.6 MHz
		LTE Band 4	LTE	Voice/Data	1.4/3/5/10/15/20MHz	2 110.7 ~ 2 154.3 MHz
LTE Band 2		LTE	Voice/Data	1.4/3/5/10/15/20MHz	1 930.7 ~ 1 989.3 MHz	
2.4 GHz W-LAN		802.11b/g/n	Voice/Data	HT20	2 412 ~ 2 462 MHz	
5.2 GHz W-LAN		802.11a/n/ac	Voice/Data	HT20/VHT20	5 180 ~ 5 240 MHz	
		802.11n/ac	Voice/Data	HT40/VHT40	5 190 ~ 5 230 MHz	
		802.11ac	Voice/Data	VHT80	5 210 MHz	
5.3 GHz W-LAN		802.11a/n/ac	Voice/Data	HT20/VHT20	5 260 ~ 5 320 MHz	
		802.11n/ac	Voice/Data	HT40/VHT40	5 270 ~ 5 310 MHz	
		802.11ac	Voice/Data	VHT80	5 290 MHz	
5.6 GHz W-LAN		802.11a/n/ac	Voice/Data	HT20/VHT20	5 500 ~ 5 700 MHz	
		802.11n/ac	Voice/Data	HT40/VHT40	5 510 ~ 5 670 MHz	
		802.11ac	Voice/Data	VHT80	5 530 MHz	
5.8 GHz W-LAN		802.11a/n/ac	Voice/Data	HT20/VHT20	5 745 ~ 5 825 MHz	
		802.11n/ac	Voice/Data	HT40/VHT40	5 755 ~ 5 795 MHz	
		802.11ac	Voice/Data	VHT80	5 775 MHz	
Bluetooth		-	Data	-	2 402 ~ 2 480 MHz	
Equipment Class		Band	Reported SAR			
			1g SAR (W/kg)			10g SAR (W/kg)
			Head	Body-Worn	Hotspot	Phablet
PCE		GSM 1900	0.13	0.35	-	-
PCE		GPRS 1900	0.13	0.35	0.79	-
PCE	WCDMA 1700	0.36	0.45	0.74	-	
PCE	WCDMA 1900	0.23	0.55	1.18	-	
PCE	LTE Band 4	0.32	0.36	0.59	-	
PCE	LTE Band 2	0.21	0.60	1.12	-	
DTS	2.4 GHz W-LAN	0.17	< 0.1	0.24	-	
U-NII-1	5.2 GHz W-LAN	-	-	-	-	
U-NII-2A	5.3 GHz W-LAN	0.13	0.32	-	0.90	
U-NII-2C	5.6 GHz W-LAN	0.19	0.36	-	0.96	
U-NII-3	5.8 GHz W-LAN	0.23	0.34	-	1.40	
DSS	Bluetooth	0.30	0.18	0.41	-	
Simultaneous SAR per KDB 690783 D01v01r03		<b>0.71</b>	<b>1.14</b>	<b>1.59</b>	-	
FCC Equipment Class	Licensed Portable Transmitter Held to Ear (PCE) Part 15 Spread Spectrum Transmitter(DSS) Digital Transmission System(DTS) Unlicensed National Information Infrastructure (UNII)					
Date(s) of Tests	2021.10.18 ~ 2021.10.22					
Antenna Type	Internal Antenna					
Functions	<ul style="list-style-type: none"> <li>GSM/GPRS (GPRS Class: 12) supported.</li> <li>* DTM not supported.</li> <li>No simultaneous transmission between BT &amp; 2.4GHz WLAN</li> <li>Simultaneous transmission between [GSM, WCDMA voice &amp; WLAN], [GPRS, WCDMA &amp; WLAN], [LTE &amp; WLAN].</li> <li>VoIP is supported.</li> <li>W-LAN 2.4GHz is supported Hotspot.</li> <li>W-LAN 5 GHz is not supported Hotspot.</li> </ul>					

## 1.2 Power Reduction for SAR

There is no power reduction used for any band/mode implemented in this device for SAR purposes.

## 1.3 Nominal and Maximum Output Power Specifications

The Nominal and Maximum Output Power Specifications are in section 9 of this test report.

## 1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. A diagram showing the location of the device of the device antenna can be found in JOYEB1083\_Antenna Location. Since the diagonal dimension of this device is > 160 mm and < 200 mm, it is considered a "phablet".

Mode	Device Sides for SAR Testing					
	Top	Bottom	Front	Rear	Right	Left
GSM/GPRS 1900	X	O	O	O	O	O
WCDMA 1700	X	O	O	O	O	O
WCDMA 1900	X	O	O	O	O	O
LTE Band 4	X	O	O	O	O	O
LTE Band 2	X	O	O	O	O	O
2.4G W-LAN	O	X	O	O	X	O
5G W-LAN	X	X	O	O	X	X
Bluetooth	O	X	O	O	X	O

Note 1: Particular DUT edges were not required to be evaluated for Hotspot SAR or Phablet SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 648474 D04v01r03. The antenna document shows the distances between the transmit antennas and the edges of the device.

Note 2: O - Test / X - Not test.

## 1.5 Simultaneous Transmission Capabilities

The Simultaneous Transmission Capabilities are in section 12 of this test report.

## 1.6 Miscellaneous SAR Test Considerations

### (A) WIFI

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB publication 248227 D01v02r02.

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160 mm and less than 200 mm. Phablet SAR tests were not required when wireless router 1g SAR < 1.2 W/kg.

### (B) Licensed Transmitter(s)

GSM/GPRS DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS Data.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

Per FCC KDB Publication 648474 D04 v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160 mm and less than 200 mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg.

## 1.7 Guidance Applied

- IEEE 1528-2013
- IEC/IEEE 62209-1528
- FCC KDB Publication 941225 D01v03r01 (3G SAR Procedures)
- FCC KDB Publication 941225 D05v02r05 (SAR for LTE Devices)
- FCC KDB Publication 941225 D05Av01r02 (LTE Rel.10 KDB Inquiry Sheet)
- FCC KDB Publication 941225 D06v02r01(Hotspot Mode)
- FCC KDB Publication 248227 D01v02r02 (802.11 Wi-Fi SAR)
- FCC KDB Publication 447498 D01v06 (General RF Exposure Guidance)
- FCC KDB Publication 648474 D04v01r03 (Handset SAR)
- FCC KDB Publication 690783 D01v01r03 (SAR Listings on Grants)
- FCC KDB Publication 865664 D01v01r04 (SAR Measurement 100 MHz to 6 GHz)
- FCC KDB Publication 865664 D02v01r02 (RF Exposure Reporting)
- October 2013 TCB Workshop Notes (GPRS testing criteria)
- April 2015 TCB Workshop Notes (Simultaneous transmission summation clarified)
- October 2016 TCB Workshop Notes (Bluetooth Duty Factor)
- April 2019 TCB Workshop Notes (Tissue Simulating Liquids)

## 1.8 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 11.

## 1.9 FCC & ISED MRA test lab designation no. : KR0034



## 2. LTE INFORMATION

LTE Information					
FCC ID	JOYEB1084				
Form Factor	Mobile Phone				
Frequency Range of each LTE transmission Band	LTE Band 4 (AWS) (1 710.7 ~ 1 754.3 MHz) LTE Band 2 (PCS) (1 850.7 ~ 1 909.3 MHz)				
Channel Bandwidths	LTE Band 4 : 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz LTE Band 2 : 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
Channel Number and Frequencies(MHz)	Low	Low-Mid	Mid	Mid-High	High
LTE Band 4 (AWS): 1.4 MHz	1 710.7 (19957)	N/A	1 732.5 (20175)	N/A	1 754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1 711.5 (19965)	N/A	1 732.5 (20175)	N/A	1 753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1 712.5 (19975)	N/A	1 732.5 (20175)	N/A	1 752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1 715.0 (20000)	N/A	1 732.5 (20175)	N/A	1 750.0 (20350)
LTE Band 4 (AWS): 15 MHz	1 717.5 (20025)	N/A	1 732.5 (20175)	N/A	1 747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1 720.0 (20050)	N/A	1 732.5 (20175) <sup>Note1</sup>	N/A	1 745.0 (20300)
LTE Band 2 (PCS): 1.4 MHz	1 850.7 (18607)	N/A	1 880.0 (18900)	N/A	1 909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1 851.5 (18615)	N/A	1 880.0 (18900)	N/A	1 908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1 852.5 (18625)	N/A	1 880.0 (18900)	N/A	1 907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1 855.0 (18650)	N/A	1 880.0 (18900)	N/A	1 905.0 (19150)
LTE Band 2 (PCS): 15 MHz	1 857.5 (18675)	N/A	1 880.0 (18900)	N/A	1 902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1 860.0 (18700)	N/A	1 880.0 (18900)	N/A	1 900.0 (19100)
UE Category	UE Cat 4				
Modulations Supported in UL	QPSK, 16QAM, 64QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3~6.2.5? (manufacturer attestation to be provided)	Yes				
A-MPR (Additional MPR) disabled for SAR Testing?	Yes				
LTE Carrier Aggregation	This device does not support both UL and DL carrier aggregation.				

Note(s)

1. LTE B4 (AWS) can not contain three non-overlapping channels of 20 MHz bandwidth.

Per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.



### 3. INTROCUCTION

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices.

The FCC has adopted the guidelines for evaluating the environmental effects of radio frequency radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave is used for guidance in measuring SAR due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields," NCRP Report No. 86 NCRP, 1986, Bethesda, MD 20814. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

#### SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density ( $\rho$ ) It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Fig. 3.1)

$$SAR = \frac{d}{dt} \left( \frac{dU}{dm} \right) = \frac{d}{dt} \left( \frac{dU}{\rho dv} \right)$$

Fig. 3.1 SAR Mathematical Equation

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- $\sigma$  = conductivity of the tissue-simulating material (S/m)
- $\rho$  = mass density of the tissue-simulating material (kg/m<sup>3</sup>)
- E = Total RMS electric field strength (V/m)


NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relations to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.

## 4. DOSIMETRIC ASSESSMENT

### 4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4.1) and IEEE1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4.1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
  - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4.1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
  - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
  - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.



**Figure 4.1**  
**Sample SAR Area Scan**

		$\leq 3$ GHz	$> 3$ GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface		$5 \text{ mm} \pm 1 \text{ mm}$	$\frac{1}{2} \cdot \delta \cdot \ln(2) \text{ mm} \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location		$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{Area}$ , $\Delta y_{Area}$		$\leq 2$ GHz: $\leq 15 \text{ mm}$ 2 – 3 GHz: $\leq 12 \text{ mm}$	3 – 4 GHz: $\leq 12 \text{ mm}$ 4 – 6 GHz: $\leq 10 \text{ mm}$
		When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}$ , $\Delta y_{Zoom}$		$\leq 2$ GHz: $\leq 8 \text{ mm}$ 2 – 3 GHz: $\leq 5 \text{ mm}^*$	3 – 4 GHz: $\leq 5 \text{ mm}^*$ 4 – 6 GHz: $\leq 4 \text{ mm}^*$
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	$\leq 5 \text{ mm}$	3 – 4 GHz: $\leq 4 \text{ mm}$ 4 – 5 GHz: $\leq 3 \text{ mm}$ 5 – 6 GHz: $\leq 2 \text{ mm}$
	graded grid	$\Delta z_{Zoom}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface	$\leq 4 \text{ mm}$
		$\Delta z_{Zoom}(n>1)$ : between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1) \text{ mm}$
Minimum zoom scan volume	x, y, z	$\geq 30 \text{ mm}$	3 – 4 GHz: $\geq 28 \text{ mm}$ 4 – 5 GHz: $\geq 25 \text{ mm}$ 5 – 6 GHz: $\geq 22 \text{ mm}$
Note: $\delta$ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details. * When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB Publication 447498 is $\leq 1.4 \text{ W/kg}$ , $\leq 8 \text{ mm}$ , $\leq 7 \text{ mm}$ and $\leq 5 \text{ mm}$ zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.			

Table 4.1 Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04\*

## 5. DEFINITION OF REFERENCE POINTS

### 5.1 Ear Reference Point

Figure 5.1 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point(ERP), and “RE” is the right ERP. The ERPs are 15 mm posterior to the entrance to the Ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5.1. The plane Passing, through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck- Front) is perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 5.1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning.




Figure 5.1  
Close-up side view of ERP

### 5.2 Handset Reference Points

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the “test device reference point” located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Fig. 5.3). The “test device reference point” was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5.2 Front, back and side view SAM Twin Phantom




Figure 5.3 Handset Vertical Center & Horizontal Line Reference Points

## 6. TEST CONFIGURATION POSITIONS FOR HANDSETS

### 6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon = 3$  and loss tangent  $\delta = 0.02$ .

### 6.2 Positioning for Cheek/Touch

1. The test device was positioned with the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6.1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.



Figure 6.1 Front, Side and Top View of Cheek/Touch Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the ear.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the plane normal to MB-NF including the line MB (reference plane).
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the phone contact with the ear, the handset was rotated about the line NF until any point on the handset made contact with a phantom point below the ear (cheek). (See Figure 6.2)

### 6.3 Positioning for Ear / 15 ° Tilt

With the test device aligned in the “Cheek/Touch Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degree.
2. The phone was then rotated around the horizontal line by 15 degree.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the phone touches the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. The tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6.3).




Figure 6.2 Side view w/relevant markings



Figure 6.3 Front, Side and Top View of Ear/15° Position



## 6.4 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6.4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is  $> 1.2 \text{ W/kg}$ , the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




Figure 6.4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

## 6.5 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

## 6.6 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ( $L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$ ) are based on a composite test separation distance of 10 mm from the front, rear and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative test separation distance configuration may be used to support both SAR conditions.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitter often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was not activated during SAR assessment, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

## 6.7 Phablet Configurations

For smart phones with a display diagonal  $> 150 \text{ mm}$  or an overall diagonal dimension  $> 160 \text{ mm}$  that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the phablets procedures outlined in KDB Publication 648474 D04v01r03 should be applied to evaluate SAR compliance. A device marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance. In addition to the normally required head and body-worn accessory SAR test procedures required for handsets, the UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna  $\leq 25 \text{ mm}$  from that surface or edge, in direct contact with the phantom, for 10g SAR. The UMPC mini-tablet 1g SAR at 5 mm is not required. When hotspot mode applies, 10g SAR is required only for the surfaces and edges with hotspot mode 1g SAR  $> 1.2 \text{ W/kg}$ .



## 7. RF EXPOSURE LIMITS

### Uncontrolled Environment:

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

### Controlled Environment:

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 7.1.SAR Human Exposure Specified in ANSI/IEEE C95.1-1992**

	HUMAN EXPOSURE LIMITS	
	General Public Exposure (W/kg) or (mW/g)	Occupational Exposure (W/kg) or (mW/g)
SPATIAL PEAK SAR * (Brain)	1.60	8.00
SPATIAL AVERAGE SAR ** (Whole Body)	0.08	0.40
SPATIAL PEAK SAR *** (Hands / Feet / Ankle / Wrist)	4.00	20.0

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e.as a result of employment or occupation).

## 8. FCC MEASUREMENT PROCEDURES

---

Power measurements were performed using a base station simulator under digital average power.

### 8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, When SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as reported SAR. The highest reported SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

### 8.2 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01.

The device was placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test were evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device was tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviated by more than 5%, the SAR test and drift measurements were repeated.

### 8.3 SAR Measurement Conditions for WCDMA (UMTS)

#### 8.3.1 Output Power Verification

Maximum output power is measured on the High, Middle and Low channels for each applicable transmission band according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all “1s”.

Maximum output power is verified on the High, Middle and Low channels according to the general, descriptions in section 5.2 of 3GPP TS 34.121 (release 5), using the appropriate RMC with TPC,(transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

#### 8.3.2 Head SAR Measurements for Handsets

SAR for head exposure configurations is measured using the 12.2 kbps RMC with TPC bits configured to all “1s”. SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than 0.25 dB higher than that measured in 12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2 AMR with a 3.4 kbps SRB (signaling radio bearer) using the exposure configuration that resulted in the highest SAR for that RF channel in the 12.2 kbps RMC mode.

### 8.3.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all "1s".

### 8.3.4 Release 5 HSDPA Data Devices

The following procedures are applicable to HSDPA data devices operating under 3GPP Release 5. SAR is required for devices in body-worn accessory and other body exposure conditions, including handsets and data modems operating in various electronic devices. HSDPA operates in conjunction with WCDMA and requires an active DPCCH. The default test configuration is to measure SAR in WCDMA with HSDPA remain inactive, to establish a radio link between the test device and a communication test set using a 12.2 kbps RMC configured in Test Loop Mode 1. SAR for HSDPA is selectively measured using the highest reported SAR configuration in WCDMA, with an FRC in H-set 1 and a 12.2 kbps RMC. SAR is selectively confirmed for other physical channel configurations (DPCCH & DPDCHn) according to exposure conditions, device operating capabilities and maximum output power specified for production units, including tune-up tolerance by applying the 3G SAR test reduction procedures. Maximum output power is verified according to the applicable versions of 3GPP TS 34.121. SAR must be measured based on these maximum output conditions and requirements in KDB Publication 447498, with respect to the UE Categories, and explained in the SAR report. When Maximum Power Reduction (MPR) applies, the implementations must be clearly identified in the SAR report to support test results according to Cubic Metric (CM) and, as appropriate, Enhanced MPR (E-MPR) requirements.

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{hs}^{(1)}$	CM (dB) <sup>(2)</sup>
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15 <sup>(3)</sup>	15/15 <sup>(3)</sup>	64	12/15 <sup>(3)</sup>	24/15	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

Note 1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$   
 Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ .  
 Note 3: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$ .

Figure 8.1 Table 1

### 8.3.5 Release 6 HSUPA Data Devices

The following procedures are applicable to HSPA (HSUPA/HSDPA) data devices operating under 3GPP Release 6. SAR is required for devices in body-worn accessory and other body exposure conditions, including handsets and data modems operating in various electronic devices. HSUPA operates in conjunction with WCDMA and HSDPA. SAR is initially measured in WCDMA test configurations with HSPA remain inactive. The default test configuration is to establish a radio link between the test device and a communication test set to configure a 12.2 kbps RMC in Test Loop Mode 1. SAR for HSPA is selectively measured with HS-DPCCH, E-DPCCH and E-DPDCH, all enabled, along with a 12.2 kbps RMC using the highest reported SAR configuration in WCDMA with 12.2 kbps RMC only.

An FRC is configured according to HS-DPCCH Sub-test 1 using H-set 1 and QPSK. HSPA is configured according to E-DCH Sub-test 5 requirements. SAR for other HSPA sub-test configurations is confirmed selectively according to exposure conditions, E-DCH UE Category and maximum output power of production units, including tune-up tolerance by applying the 3G SAR test reduction procedure. Maximum output power is verified according to procedures in applicable versions of 3GPP TS 34.121. SAR must be measured based on these maximum output conditions and requirements in KDB Publication 447498, with respect to the UE Categories for HS-DPCCH and HSPA, and explained in the SAR report. When Maximum Power Reduction (MPR) applies, the implementations must be clearly identified in the SAR report to support test results according to Cubic Metric (CM) and, as appropriate, Enhanced MPR (E-MPR) requirements.

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{hs}^{(1)}$	$\beta_{ec}$	$\beta_{ed}$	$\beta_{ed}$ (SF)	$\beta_{ed}$ (codes)	CM <sup>(2)</sup> (dB)	MPR (dB)	AG <sup>(4)</sup> Index	E-TFCI
1	11/15 <sup>(3)</sup>	15/15 <sup>(3)</sup>	64	11/15 <sup>(3)</sup>	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed}: 47/15$ $\beta_{ed}: 47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 <sup>(4)</sup>	15/15 <sup>(4)</sup>	64	15/15 <sup>(4)</sup>	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$ .  
 Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.  
 Note 3: For subtest 1 the  $\beta_c/\beta_d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 10/15$  and  $\beta_d = 15/15$ .  
 Note 4: For subtest 5 the  $\beta_c/\beta_d$  ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 14/15$  and  $\beta_d = 15/15$ .  
 Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.  
 Note 6:  $\beta_{ed}$  cannot be set directly; it is set by Absolute Grant Value.

Figure 8.2 Table 2

## 8.4 SAR Measurement Conditions for LTE

LTE modes were tested according to FCC KDB 941225 D05v02r05 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR. The call simulator was used for LTE output power measurement and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

### 8.4.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

### 8.4.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36. 101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

### 8.4.3 A-MPR

A-MPR (Addition MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

### 8.4.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r05:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
  - i. The required channel and offset combination with the highest maximum output power is required for SAR.
  - ii. When the reported SAR is  $\leq 0.8$  W/kg, testing of the remaining RB offset configurations and required test channel is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
  - iii. When the reported SAR for a required test channel is  $> 1.45$  W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is  $< 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to 0.5 dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is  $< 1.45$  W/kg.

### 8.4.5 64QAM uplink

- (1) Per KDB 941225 D05 V02r05, we'll measure conducted powers per Section 5.1 for all uplink modulations (QPSK, 16QAM, 64QAM) and include in the test report.
- (2) From these power measurements, we will apply the procedures in Section 5.2.4 ("Higher Order Modulations") to determine SAR test reduction for 16QAM and 64QAM test cases.

## 8.5 SAR Testing with 802.11 Transmitters

The normal network operating configurations are not suitable for measuring the SAR of 802.11 b/g/n transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227D01v02r02 for more details.

### 8.5.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92-96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

### 8.5.2 U-NII and U-NII-2A

For devices that operate in only one of the U-NII-1 and U-NII-2A bands, the normally required SAR procedures for OFDM configurations are applied. For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following, with respect to the highest reported SAR and maximum output power specified for production units. The procedures are applied independently to each exposure configuration; for example, head, body, hotspot mode etc.

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is  $\leq 1.2$  W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, each band is tested independently for SAR.

### 8.5.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements.

When Terminal Doppler Weather Rader (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification.

Unless band gap channels are permanently disabled, SAR must be considered for these channels. When band gap channels are disabled, each band is tested independently according to the normally required OFDM SAR measurements and probe calibration frequency points requirements.



#### 8.5.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all position in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is  $\leq 0.4$  W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR position until the reported SAR result is  $\leq 0.8$  W/kg or all test position are measured.

#### 8.5.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is  $\leq 0.8$  W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is  $> 0.8$  W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is  $> 1.2$  W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power is  $> 1.2$  W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

#### 8.5.6 OFDM Transmission Mode and SAR Test Channel Selection

For the 2.4 GHz and 5 GHz bands, when the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a and 802.11n or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n or 802.11g then 802.11n is used for SAR measurement. When the maximum output power were the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

#### 8.5.7 Initial Test Configuration Procedure

For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, and lowest data rate. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is  $\leq 0.8$  W/kg, no additional measurements on other test channels are required.

Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is  $\leq 1.2$  W/kg or all channels are measured.

#### 8.5.8 Subsequent Test Configuration Procedures

For OFDM configurations, in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure, when applicable. When the highest reported SAR for the initial test configuration, adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power is  $\leq 1.2$  W/kg, no additional SAR testing for the subsequent test configurations is required.

## 9. RF CONDUCTED POWERS

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06

### 9.1 GSM Nominal and Maximum Output Power Spec and Conducted Powers

Band & Mode		Voice[dBm]	Burst Average GMSK [dBm]			
		1 TX Slot	1 TX Slot	2 TX Slot	3 TX Slot	4 TX Slot
GSM/GPRS 1900	Maximum	30.4	30.4	27.4	25.6	24.4
	Nominal	29.0	29.0	26.0	24.2	23.0

Table 9.1.1 GSM Nominal and Maximum Output Power Spec

Band	Channel	Maximum Burst-Averaged Output Power(dBm)				
		Voice	GPRS Data (GMSK)			
		GSM CS 1 Slot	GPRS 1 TX Slot	GPRS 2 TX Slot	GPRS 3 TX Slot	GPRS 4 TX Slot
PCS 1900	512	29.00	28.78	25.89	23.98	22.89
	661	29.02	28.74	26.07	24.12	23.25
	810	28.94	29.37	26.35	24.59	23.36
Band	Channel	Calculated Maximum Frame-Averaged Output Power(dBm)				
		Voice	GPRS Data (GMSK)			
		GSM CS 1 Slot	GPRS 1 TX Slot	GPRS 2 TX Slot	GPRS 3 TX Slot	GPRS 4 TX Slot
PCS 1900	512	19.97	19.75	19.87	19.72	19.88
	661	19.99	19.71	20.05	19.86	20.24
	810	19.91	20.34	20.33	20.33	20.35
<b>PCS 1900</b>	<b>Frame Avg. Targets:</b>	<b>19.97</b>	19.97	19.98	19.94	<b>19.99</b>

Table 9.1.2 GSM Conducted Power

Note:

- Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- GPRS (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.

GPRS Multislot class: 12 (max 4 TX Uplink slots)  
DTM Multislot Class: N/A



Figure 9.1 Power Measurement Setup



## 9.2 WCDMA Nominal and Maximum Output Power Spec and Conducted Powers

3GPP Release Version	Mode		AWS Band (dBm)		PCS Band (dBm)		3GPP MPR (dB)
			Maximum	Nominal	Maximum	Nominal	
99	WCDMA	Voice	Maximum	24.5	Maximum	24.5	-
			Nominal	24.0	Nominal	24.0	
5	HSDPA	Subtest 1	Maximum	23.5	Maximum	23.5	0
			Nominal	23.0	Nominal	23.0	
5		Subtest 2	Maximum	23.5	Maximum	23.5	0
			Nominal	23.0	Nominal	23.0	
5		Subtest 3	Maximum	23.0	Maximum	23.0	0.5
			Nominal	22.5	Nominal	22.5	
5		Subtest 4	Maximum	23.0	Maximum	23.0	0.5
			Nominal	22.5	Nominal	22.5	
6	HSUPA	Subtest 1	Maximum	23.5	Maximum	23.5	0
			Nominal	23.0	Nominal	23.0	
6		Subtest 2	Maximum	21.5	Maximum	21.5	2
			Nominal	21.0	Nominal	21.0	
6		Subtest 3	Maximum	22.5	Maximum	22.5	1
			Nominal	22.0	Nominal	22.0	
6		Subtest 4	Maximum	21.5	Maximum	21.5	2
			Nominal	21.0	Nominal	21.0	
6		Subtest 5	Maximum	23.5	Maximum	23.5	0
			Nominal	23.0	Nominal	23.0	


**Table 9.2.1 WCDMA Nominal and Maximum Output Power Spec**

3GPP Release Version	Mode	3GPP 34.121 Subtest	AWS Band (dBm)			PCS Band (dBm)			3GPP MPR (dB)
			1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	23.47	23.48	23.47	23.48	23.49	23.50	-
99		12.2 kbps AMR	23.47	23.47	23.46	23.44	23.45	23.41	-
5	HSDPA	Subtest 1	22.47	22.44	22.43	22.50	22.46	22.49	0
5		Subtest 2	22.45	22.48	22.47	22.49	22.48	22.45	0
5		Subtest 3	21.99	21.97	21.93	21.99	21.96	21.93	0.5
5		Subtest 4	21.96	21.93	21.88	21.97	21.93	21.89	0.5
6	HSUPA	Subtest 1	22.44	22.46	22.45	22.43	22.45	22.42	0
6		Subtest 2	20.39	20.44	20.41	20.40	20.42	20.35	2
6		Subtest 3	21.42	21.48	21.46	21.49	21.49	21.48	1
6		Subtest 4	20.44	20.43	20.38	20.33	20.40	20.38	2
6		Subtest 5	22.36	22.43	22.42	22.32	22.40	22.39	0

**Table 9.2.2 WCDMA Conducted Power**

WCDMA SAR was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.

The manufacturer declares that the HSDPA and HSUPA transmitter's power will not exceed the R99 maximum transmit power in devices based on Qualcomm's HSPA chipset solutions.



**Figure 9.2 Power Measurement Setup**

### 9.3 LTE Nominal and Maximum Output Power Spec and Conducted Powers

Band & Mode	Modulated Average[dBm]	
	LTE Band 4	Maximum
	Nominal	23.0

Table 9.3.2.1 Nominal and Maximum Output Power Spec

#### 1) LTE Band 4

Modulation	RB Size	RB Offset	LTE Band 4 (AWS) Conducted Power– 20 MHz Bandwidth		MPR Allowed Per 3GPP(dB)	MPR (dB)
			Mid Channel			
			20175 (1 732.5 MHz)			
			Conducted Power (dBm)			
QPSK	1	0	23.60		≤ 1	0
	1	50	23.59			
	1	99	23.57			
	50	0	22.61			1
	50	25	22.58			
	50	50	22.57			
16QAM	100	0	22.60		≤ 2	1
	1	0	22.59			
	1	50	22.57			
	1	99	22.56			2
	50	0	21.60			
	50	25	21.56			
64QAM	50	50	21.55		≤ 3	2
	100	0	21.59			
	1	0	21.58			
	1	50	21.57			3
	1	99	21.55			
	50	0	20.60			
	50	25	20.59			
	50	50	20.56			
	100	0	20.59			3

Table 9.3.1.2 LTE Conducted Power

Note: LTE B4 (AWS) can not contain three non-overlapping channels of 20 MHz bandwidth.  
 Per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Modulation	RB Size	RB Offset	LTE Band 4 (AWS) Conducted Power– 15 MHz Bandwidth			MPR Allowed Per 3GPP(dB)	MPR (dB)
			Low Channel	Mid Channel	High Channel		
			20025 (1 717.5 MHz)	20175 (1 732.5 MHz)	20325 (1 747.5 MHz)		
			Conducted Power (dBm)				
QPSK	1	0	23.54	23.55	23.51	≤ 1	0
	1	36	23.50	23.53	23.49		
	1	74	23.44	23.46	23.41		
	36	0	22.52	22.58	22.50		1
	36	18	22.50	22.53	22.48		
	36	37	22.44	22.46	22.40		
16QAM	75	0	22.49	22.52	22.47	≤ 2	1
	1	0	22.50	22.53	22.48		
	1	36	22.45	22.48	22.43		
	1	74	22.41	22.45	22.39		2
	36	0	21.55	21.59	21.51		
	36	18	21.52	21.55	21.46		
64QAM	36	37	21.49	21.54	21.38	≤ 3	2
	75	0	21.51	21.52	21.44		
	1	0	21.51	21.56	21.46		
	1	36	21.49	21.52	21.45		3
	1	74	21.43	21.48	21.38		
	36	0	20.53	20.55	20.52		
	36	18	20.50	20.52	20.49		
	36	37	20.43	20.50	20.41		
	75	0	20.48	20.50	20.45		3

Table 9.3.1.3 LTE Conducted Power

Modulation	RB Size	RB Offset	LTE Band 4 (AWS) Conducted Power– 10 MHz Bandwidth			MPR Allowed Per 3GPP(dB)	MPR (dB)
			Low Channel	Mid Channel	High Channel		
			20000 (1 715.0 MHz)	20175 (1 732.5 MHz)	20350 (1 750.0 MHz)		
			Conducted Power (dBm)				
QPSK	1	0	23.51	23.55	23.49	≤ 1	0
	1	25	23.48	23.53	23.47		
	1	49	23.44	23.50	23.42		
	25	0	22.45	22.49	22.44		1
	25	12	22.43	22.45	22.41		
	25	25	22.40	22.43	22.38		
16QAM	50	0	22.41	22.44	22.39	≤ 2	1
	1	0	22.48	22.56	22.48		
	1	25	22.45	22.51	22.44		
	1	49	22.42	22.50	22.40		2
	25	0	21.43	21.45	21.41		
	25	12	21.40	21.44	21.38		
64QAM	25	25	21.38	21.42	21.37	≤ 3	2
	50	0	21.39	21.43	21.37		
	1	0	21.53	21.54	21.43		
	1	25	21.50	21.52	21.41		3
	1	49	21.48	21.49	21.40		
	25	0	20.50	20.53	20.48		
	25	12	20.48	20.50	20.46		
	25	25	20.44	20.49	20.41		
	50	0	20.47	20.49	20.40		3

Table 9.3.1.4 LTE Conducted Power

LTE Band 4 (AWS) Conducted Power– 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed Per 3GPP(dB)	MPR (dB)
			19975 (1 712.5 MHz)	20175 (1 732.5 MHz)	20375 (1 752.5 MHz)		
Conducted Power (dBm)							
QPSK	1	0	23.52	23.56	23.50	≤ 1	0
	1	12	23.50	23.53	23.48		
	1	24	23.45	23.49	23.43		
	12	0	22.50	22.53	22.48		1
	12	6	22.48	22.50	22.47		
	12	13	22.47	22.48	22.45		
	25	0	22.49	22.51	22.47		
16QAM	1	0	22.53	22.54	22.51	≤ 1	1
	1	12	22.52	22.52	22.50		
	1	24	22.49	22.51	22.45		
	12	0	21.51	21.55	21.50		≤ 2
	12	6	21.50	21.53	21.46		
	12	13	21.46	21.47	21.44		
	25	0	21.50	21.53	21.49		
64QAM	1	0	21.50	21.53	21.48	≤ 2	2
	1	12	21.48	21.51	21.45		
	1	24	21.43	21.50	21.42		
	12	0	20.49	20.54	20.47		≤ 3
	12	6	20.48	20.53	20.45		
	12	13	20.45	20.49	20.43		
	25	0	20.46	20.49	20.44		

Table 9.3.1.5 LTE Conducted Power

LTE Band 4 (AWS) Conducted Power– 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed Per 3GPP(dB)	MPR (dB)
			19965 (1 711.5 MHz)	20175 (1 732.5 MHz)	20385 (1 753.5 MHz)		
Conducted Power (dBm)							
QPSK	1	0	23.53	23.56	23.50	≤ 1	0
	1	7	23.50	23.53	23.48		
	1	14	23.46	23.51	23.42		
	8	0	22.51	22.57	22.50		1
	8	4	22.48	22.53	22.46		
	8	7	22.45	22.52	22.43		
	15	0	22.43	22.55	22.49		
16QAM	1	0	22.54	22.58	22.51	≤ 1	1
	1	7	22.51	22.57	22.47		
	1	14	22.47	22.53	22.45		
	8	0	21.53	21.56	21.48		≤ 2
	8	4	21.52	21.53	21.43		
	8	7	21.49	21.50	21.41		
	15	0	21.50	21.55	21.43		
64QAM	1	0	21.51	21.53	21.50	≤ 2	2
	1	7	21.49	21.50	21.46		
	1	14	21.47	21.48	21.44		
	8	0	20.49	20.53	20.47		≤ 3
	8	4	20.46	20.50	20.45		
	8	7	20.43	20.48	20.42		
	15	0	20.48	20.50	20.46		

Table 9.3.1.6 LTE Conducted Power

TE Band 4 (AWS) Conducted Power– 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed Per 3GPP(dB)	MPR (dB)
			19957 (1 710.7 MHz)	20175 (1 732.5 MHz)	20393 (1 754.3 MHz)		
Conducted Power (dBm)							
QPSK	1	0	23.51	23.53	23.46	≤ 1	0
	1	2	23.43	23.48	23.41		
	1	5	23.40	23.44	23.37		
	3	0	23.43	23.46	23.40		0
	3	2	23.40	23.43	23.35		
	3	3	23.39	23.42	23.32		
	6	0	22.41	22.44	22.39		
16QAM	1	0	22.48	22.50	22.43	≤ 1	1
	1	2	22.41	22.44	22.38		
	1	5	22.39	22.42	22.35		
	3	0	22.38	22.40	22.36		1
	3	2	22.36	22.38	22.33		
	3	3	22.32	22.35	22.31		
	6	0	21.36	21.38	21.35		
64QAM	1	0	21.52	21.56	21.50	≤ 2	2
	1	2	21.38	21.40	21.35		
	1	5	21.35	21.39	21.33		
	3	0	21.42	21.43	21.39		2
	3	2	21.40	21.41	21.36		
	3	3	21.36	21.39	21.33		
	6	0	20.39	20.42	20.37		

Table 9.3.1.7 LTE Conducted Power

Band & Mode	Modulated Average(dBm)	
	LTE Band 2(PCS)	Maximum
	Nominal	23.0

Table 9.3.2.1 Nominal and Maximum Output Power Spec

## 2) LTE Band 2 (PCS)

Modulation	RB Size	RB Offset	LTE Band 2 (PCS) Conducted Power– 20 MHz Bandwidth			MPR Allowed Per 3GPP(dB)	MPR (dB)
			Low Channel	Mid Channel	High Channel		
			18700 (1 860.0 MHz)	18900 (1 880.0 MHz)	19100 (1 900.0 MHz)		
Conducted Power (dBm)							
QPSK	1	0	23.39	23.48	23.45	≤ 1	0
	1	50	23.47	23.49	23.48		
	1	99	23.35	23.46	23.41		
	50	0	22.33	22.45	22.44		1
	50	25	22.39	22.47	22.45		
	50	50	22.30	22.44	22.42		
100	0	22.38	22.46	22.42	1		
16QAM	1	0	22.40	22.46	22.44	≤ 1	1
	1	50	22.45	22.48	22.47		
	1	99	22.38	22.44	22.41		
	50	0	21.38	21.46	21.43		≤ 2
	50	25	21.40	21.48	21.45		
	50	50	21.35	21.40	21.40		
100	0	21.39	21.43	21.40	2		
64QAM	1	0	21.40	21.45	21.39	≤ 2	2
	1	50	21.42	21.47	21.43		
	1	99	21.36	21.43	21.36		
	50	0	20.41	20.48	20.45		≤ 3
	50	25	20.44	20.49	20.46		
	50	50	20.40	20.47	20.44		
100	0	20.43	20.48	20.45	3		

Table 9.3.2.2 LTE Conducted Power

Modulation	RB Size	RB Offset	LTE Band 2 (PCS) Conducted Power– 15 MHz Bandwidth			MPR Allowed Per 3GPP(dB)	MPR (dB)
			Low Channel	Mid Channel	High Channel		
			18675 (1 857.5 MHz)	18900 (1 880.0 MHz)	19125 (1 902.5 MHz)		
Conducted Power (dBm)							
QPSK	1	0	23.31	23.36	23.34	≤ 1	0
	1	36	23.33	23.38	23.36		
	1	74	23.29	23.35	23.33		
	36	0	22.30	22.36	22.34		1
	36	18	22.34	22.40	22.38		
	36	37	22.29	22.35	22.31		
75	0	22.30	22.36	22.34	1		
16QAM	1	0	22.35	22.37	22.36	≤ 1	1
	1	36	22.36	22.39	22.37		
	1	74	22.30	22.36	22.34		
	36	0	21.31	21.40	21.35		≤ 2
	36	18	21.33	21.41	21.40		
	36	37	21.28	21.38	21.33		
75	0	21.29	21.35	21.35	2		
64QAM	1	0	21.33	21.36	21.35	≤ 2	2
	1	36	21.35	21.40	21.39		
	1	74	21.31	21.33	21.32		
	36	0	20.33	20.43	20.38		≤ 3
	36	18	20.36	20.45	20.43		
	36	37	20.29	20.36	20.34		
75	0	20.29	20.38	20.30	3		

Table 9.3.2.3 LTE Conducted Power

Modulation	RB Size	RB Offset	LTE Band 2 (PCS) Conducted Power– 10 MHz Bandwidth			MPR Allowed Per 3GPP(dB)	MPR (dB)
			Low Channel	Mid Channel	High Channel		
			18650 (1 855.0 MHz)	18900 (1 880.0 MHz)	19150 (1 905.0 MHz)		
Conducted Power (dBm)							
QPSK	1	0	23.36	23.44	23.41	≤ 1	0
	1	25	23.40	23.45	23.44		
	1	49	23.33	23.40	23.37		
	25	0	22.31	22.40	22.35		1
	25	12	22.35	22.45	22.39		
	25	25	22.30	22.35	22.34		
50	0	22.33	22.44	22.37	1		
16QAM	1	0	22.39	22.41	22.39	≤ 1	1
	1	25	22.43	22.45	22.44		
	1	49	22.35	22.38	22.36		
	25	0	21.35	21.39	21.36		≤ 2
	25	12	21.39	21.43	21.40		
	25	25	21.32	21.36	21.34		
50	0	21.36	21.39	21.38	2		
64QAM	1	0	21.33	21.40	21.36	≤ 2	2
	1	25	21.38	21.41	21.40		
	1	49	21.30	21.36	21.33		
	25	0	20.36	20.38	20.37		≤ 3
	25	12	20.40	20.44	20.41		
	25	25	20.33	20.37	20.36		
50	0	20.35	20.40	20.36	3		

Table 9.3.2.4 LTE Conducted Power

LTE Band 2 (PCS) Conducted Power- 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed Per 3GPP(dB)	MPR (dB)
			18625 (1 852.5 MHz)	18900 (1 880.0 MHz)	19175 (1 907.5 MHz)		
			Conducted Power (dBm)				
QPSK	1	0	23.33	23.36	23.34	≤ 1	0
	1	12	23.35	23.40	23.38		
	1	24	23.30	23.34	23.32		
	12	0	22.25	22.33	22.30		1
	12	6	22.30	22.36	22.35		
	12	13	22.24	22.30	22.29		
	25	0	22.24	22.30	22.28		
16QAM	1	0	22.31	22.35	22.33	≤ 1	1
	1	12	22.33	22.36	22.35		
	1	24	22.29	22.33	22.30		
	12	0	21.26	21.29	21.27	≤ 2	2
	12	6	21.31	21.35	21.33		
	12	13	21.22	21.28	21.25		
	25	0	21.21	21.26	21.25		
64QAM	1	0	21.30	21.33	21.31	≤ 2	2
	1	12	21.32	21.36	21.37		
	1	24	21.25	21.28	21.27		
	12	0	20.29	20.35	20.33	≤ 3	3
	12	6	20.33	20.37	20.36		
	12	13	20.25	20.33	20.30		
	25	0	20.23	20.28	20.25		

Table 9.3.2.5 LTE Conducted Power

LTE Band 2 (PCS) Conducted Power- 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed Per 3GPP(dB)	MPR (dB)
			18615 (1 851.5 MHz)	18900 (1 880.0 MHz)	19185 (1 908.5 MHz)		
			Conducted Power (dBm)				
QPSK	1	0	23.28	23.36	23.35	≤ 1	0
	1	7	23.30	23.40	23.38		
	1	14	23.25	23.33	23.31		
	8	0	22.30	22.36	22.33		1
	8	4	22.33	22.38	22.36		
	8	7	22.25	22.33	22.28		
	15	0	22.22	22.31	22.28		
16QAM	1	0	22.33	22.41	22.35	≤ 1	1
	1	7	22.35	22.42	22.36		
	1	14	22.30	22.40	22.32		
	8	0	21.26	21.34	21.30	≤ 2	2
	8	4	21.30	21.39	21.35		
	8	7	21.24	21.32	21.25		
	15	0	21.24	21.33	21.25		
64QAM	1	0	21.35	21.38	21.37	≤ 2	2
	1	7	21.38	21.40	21.39		
	1	14	21.33	21.36	21.35		
	8	0	20.25	20.33	20.28	≤ 3	3
	8	4	20.29	20.35	20.33		
	8	7	20.22	20.30	20.26		
	15	0	20.20	20.29	20.23		

Table 9.3.2.6 LTE Conducted Power

LTE Band 2 (PCS) Conducted Power- 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed Per 3GPP(dB)	MPR (dB)
			18607 (1 850.7 MHz)	18900 (1 880.0 MHz)	19193 (1 909.3 MHz)		
			Conducted Power (dBm)				
QPSK	1	0	23.33	23.36	23.35	≤ 1	0
	1	2	23.36	23.40	23.38		
	1	5	23.30	23.33	23.32		
	3	0	23.28	23.33	23.25		0
	3	2	23.33	23.36	23.35		
	3	3	23.24	23.29	23.24		
	6	0	22.30	22.33	22.32		
16QAM	1	0	22.31	22.34	22.32	≤ 1	1
	1	2	22.33	22.35	22.34		
	1	5	22.29	22.33	22.31		
	3	0	22.25	22.30	22.28		1
	3	2	22.27	22.33	22.30		
	3	3	22.21	22.25	22.23		
	6	0	21.25	21.35	21.28		
64QAM	1	0	21.28	21.37	21.33	≤ 2	2
	1	2	21.30	21.39	21.36		
	1	5	21.26	21.36	21.32		
	3	0	21.24	21.31	21.25		2
	3	2	21.28	21.35	21.31		
	3	3	21.20	21.28	21.22		
	6	0	20.23	20.33	20.25		

Table 9.3.2.7 LTE Conducted Power

### 9.4 WLAN Nominal and Maximum Output Power Spec and Conducted Powers

Band (GHz)	Mode	Modulated Average[dBm]	
		Maximum	Nominal
2.4	802.11b	15.0	12.0
	802.11g	15.0	12.0
	802.11n	15.0	12.0

Table 9.4.1 Nominal and Maximum Output Power Spec

Mode	Freq. (MHz)	Channel	IEEE 802.11 (2.4 GHz) Conducted Power
			[dBm]
802.11b	2 412	1	12.77
	2 437	6	12.90
	2 462	11	12.20
802.11g	2 412	1	12.44
	2 437	6	12.36
	2 462	11	11.73
802.11n (HT-20)	2 412	1	12.46
	2 437	6	12.33
	2 462	11	11.63

Table 9.4.2 IEEE 802.11 Average RF Power

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, duo to an even number of channels, both channels were measured.
- Output Power and SAR is not required for 802.11 g/n HT20/ac VHT20 channels when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjust SAR is  $\leq 1.2$  W/kg.
- The underlined data rate and channel above were tested for SAR.

The average output powers of this device were tested by below configuration.




Figure 9.4.1 Power Measurement Setup

Band (GHz)	Mode	Modulated Average[dBm]	
		Maximum	Nominal
5 (UNII)	802.11a	14.5	11.5
	802.11n/ac (20MHz)	14.5	11.5
	802.11n/ac (40MHz)	14.5	11.5
	802.11ac (80MHz)	14.5	11.5

Table 9.4.3 Nominal and Maximum Output Power Spec

Mode	Freq. (MHz)	Channel	IEEE 802.11a (5 GHz) Conducted Power
			[dBm]
802.11a	5 180	36	11.42
	5 200	40	11.40
	5 220	44	11.35
	5 240	48	11.39
	5 260	52	11.52
	5 280	56	11.22
	5 300	60	11.18
	5 320	64	11.28
	5 500	100	11.15
	5 600	120	11.30
	5 660	132	11.21
	5 700	140	10.76
	5 745	149	10.01
	5 785	157	9.88
	5 825	165	9.93

Table 9.4.4 IEEE 802.11a Average RF Power

Mode	Freq. (MHz)	Channel	IEEE 802.11n HT20 (5 GHz) Conducted Power
			[dBm]
802.11n (HT-20)	5 180	36	11.15
	5 200	40	11.23
	5 220	44	11.30
	5 240	48	11.14
	5 260	52	11.12
	5 280	56	11.03
	5 300	60	11.00
	5 320	64	11.01
	5 500	100	10.99
	5 600	120	10.86
	5 660	132	10.85
	5 700	140	10.68
	5 745	149	9.79
	5 785	157	9.66
	5 825	165	9.89

Table 9.4.5 IEEE 802.11n HT20 Average RF Power

Mode	Freq. (MHz)	Channel	IEEE 802.11ac VHT20 (5 GHz) Conducted Power	
				[dBm]
802.11ac (VHT-20)	5 180	36		11.02
	5 200	40		11.10
	5 220	44		11.09
	5 240	48		11.12
	5 260	52		11.03
	5 280	56		11.15
	5 300	60		11.12
	5 320	64		11.13
	5 500	100		11.00
	5 600	120		10.93
	5 660	132		10.99
	5 700	140		10.83
	5 745	149		9.83
	5 785	157		9.99
	5 825	165		9.86

Table 9.4.6 IEEE 802.11ac VHT20 Average RF Power

Mode	Freq. (MHz)	Channel	IEEE 802.11n HT40 (5 GHz) Conducted Power	
				[dBm]
802.11n (HT-40)	5 190	38		11.71
	5 230	46		11.83
	5 270	54		11.69
	5 310	62		11.80
	5 510	102		11.33
	5 590	118		11.39
	5 670	134		11.35
	5 755	151		11.44
	5 795	159		10.43

Table 9.4.7 IEEE 802.11n HT40 Average RF Power

Mode	Freq. (MHz)	Channel	IEEE 802.11ac VHT40 (5 GHz) Conducted Power	
				[dBm]
802.11ac (VHT-40)	5 190	38		11.77
	5 230	46		11.71
	5 270	54		11.69
	5 310	62		11.82
	5 510	102		11.39
	5 590	118		11.44
	5 670	134		11.36
	5 755	151		10.49
	5 795	159		10.38

Table 9.4.8 IEEE 802.11ac VHT40 Average RF Power

Mode	Freq. (MHz)	Channel	IEEE 802.11ac VHT80 (5 GHz) Conducted Power	
				[dBm]
802.11ac (VHT-80)	5 210	42		11.55
	5 290	58		11.58
	5 530	106		11.23
	5 610	122		11.72
	5 690	138		11.55
	5 775	155		10.66

Table 9.4.9 IEEE 802.11ac VHT80 Average RF Power

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, duo to an even number of channels, both channels were measured.
- Output Power and SAR is not required for 802.11 g/n HT20/ac VHT20 channels when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjust SAR is ≤ 1.2 W/kg.
- The underlined data rate and channel above were tested for SAR.

The average output powers of this device were tested by below configuration.




Figure 9.4.2 Power Measurement Setup



## 9.5 Bluetooth Conducted Powers

Frame Modulated Average[dBm]		
Bluetooth 1 Mbps	Maximum	16.0
	Nominal	12.3
Bluetooth 2 Mbps	Maximum	13.0
	Nominal	9.3
Bluetooth 3 Mbps	Maximum	13.0
	Nominal	9.3
Bluetooth (LE)	Maximum	9.8
	Nominal	6.1

Table 9.5.1 Nominal and Maximum Output Power Spec (Frame)

Channel	Frequency	Frame AVG Output Power (1Mbps)	Frame AVG Output Power (2Mbps)	Frame AVG Output Power (3Mbps)
	(MHz)	(dBm)	(dBm)	(dBm)
Low	2 402	12.60	9.96	9.93
Mid	2 441	12.75	10.11	10.05
High	2 480	12.52	9.89	9.83

Table 9.5.2 Bluetooth Frame Average RF Power

Channel	Frequency	Frame AVG Output Power(LE / 1Mbps)	Frame AVG Output Power(LE / 2Mbps)
	(MHz)	(dBm)	(dBm)
Low	2 402	7.01	6.99
Mid	2 440	6.66	6.63
High	2 480	5.98	5.91

Table 9.5.3 Bluetooth LE Frame Average RF Power

- Bluetooth Conducted Powers procedures

- Bluetooth (BDR, EDR)

- 1) Enter DUT mode in EUT and operate it.

When it operating, The EUT is transmitting at maximum power level and duty cycle fixed.

- 2) Instruments and EUT were connected like Figure 9.5.1.

- 3) The maximum output powers of BDR(1 Mbps), EDR(2, 3 Mbps) and each frequency were set by a Bluetooth Tester.

- 4) Power levels were measured by a Power Meter.

2. Bluetooth (LE)

- 1) Enter LE mode in EUT and operate it.

When it operating, The EUT is transmitting at maximum power level and duty cycle fixed.

- 2) Instruments and EUT were connected like Figure 9.5.1.

- 3) The average conducted output powers of LE and each frequency can measurement according to setting program in EUT.

- 4) Power levels were measured by a Power Meter.



Figure 9.5.1 Average Power Measurement Setup

- Bluetooth Transmission Plot




Figure 9.5.2 Bluetooth Transmission Plot

- Bluetooth Duty Cycle Calculation

$$\text{Duty Cycle} = \text{Pulse/Period} * 100\% = (2.880/3.750) * 100 = 76.8\%$$

# 10. SYSTEM VERIFICATION

## 10.1 Tissue Verification

MEASURED TISSUE PARAMETERS										
Date(s)	Tissue Type	Ambient Temp.[°C]	Liquid Temp.[°C]	Measured Frequency [MHz]	Target Dielectric Constant, $\epsilon_r$	Target Conductivity, $\sigma$ (S/m)	Measured Dielectric Constant, $\epsilon_r$	Measured Conductivity, $\sigma$ (S/m)	Er Deviation [%]	$\sigma$ Deviation [%]
Oct. 22. 2021	1800 Head	22.2	22.1	1 712.4	40.126	1.350	39.761	1.317	-0.91	-2.44
				1 720.0	40.114	1.354	39.720	1.323	-0.98	-2.29
				1 732.4	40.097	1.361	39.646	1.332	-1.12	-2.13
				1 732.5	40.097	1.361	39.646	1.332	-1.12	-2.13
				1 745.0	40.079	1.369	39.587	1.343	-1.23	-1.90
				1 752.6	40.069	1.373	39.554	1.349	-1.29	-1.75
				1 770.0	40.043	1.383	39.488	1.366	-1.39	-1.23
Oct. 21. 2021	1900 Head	21.6	21.5	1 850.2	40.000	1.400	40.464	1.373	1.16	-1.93
				1 852.4	40.000	1.400	40.457	1.373	1.14	-1.93
				1 860.0	40.000	1.400	40.399	1.385	1.00	-1.07
				1 880.0	40.000	1.400	40.308	1.406	0.77	0.43
				1 900.0	40.000	1.400	40.199	1.426	0.50	1.86
				1 907.6	40.000	1.400	40.162	1.433	0.40	2.36
				1 909.8	40.000	1.400	40.152	1.435	0.38	2.50
Oct. 20. 2021	1900 Head	21.7	21.6	1 850.2	40.000	1.400	40.665	1.385	1.66	-1.07
				1 852.4	40.000	1.400	40.658	1.387	1.65	-0.93
				1 860.0	40.000	1.400	40.632	1.393	1.58	-0.50
				1 880.0	40.000	1.400	40.577	1.411	1.44	0.79
				1 900.0	40.000	1.400	40.539	1.428	1.35	2.00
				1 907.6	40.000	1.400	40.528	1.433	1.32	2.36
				1 909.8	40.000	1.400	40.527	1.434	1.32	2.43
Oct. 18. 2021	2450 Head	20.9	20.8	2 402.0	39.282	1.757	40.442	1.712	2.95	-2.56
				2 412.0	39.265	1.766	40.417	1.730	2.93	-2.04
				2 437.0	39.222	1.788	40.364	1.759	2.91	-1.62
				2 441.0	39.215	1.792	40.352	1.763	2.90	-1.62
				2 450.0	39.200	1.800	40.334	1.773	2.89	-1.50
				2 462.0	39.184	1.813	40.311	1.786	2.88	-1.49
				2 480.0	39.160	1.832	40.263	1.806	2.82	-1.42
Oct. 19. 2021	5300 Head	20.3	20.2	5 260.0	35.940	4.720	35.810	4.844	-0.36	2.63
				5 270.0	35.930	4.730	35.797	4.857	-0.37	2.68
				5 280.0	35.920	4.740	35.787	4.867	-0.37	2.68
				5 290.0	35.910	4.750	35.768	4.876	-0.40	2.65
				5 300.0	35.900	4.760	35.744	4.887	-0.43	2.67
				5 310.0	35.890	4.770	35.722	4.901	-0.47	2.75
				5 320.0	35.880	4.780	35.708	4.913	-0.48	2.78
Oct. 20. 2021	5600 Head	20.3	20.2	5 500.0	35.650	4.965	35.193	5.035	-1.28	1.41
				5 510.0	35.635	4.976	35.170	5.043	-1.30	1.35
				5 530.0	35.605	4.997	35.125	5.068	-1.35	1.42
				5 550.0	35.575	5.018	35.096	5.089	-1.35	1.41
				5 580.0	35.530	5.049	35.036	5.127	-1.39	1.54
				5 600.0	35.500	5.070	35.017	5.150	-1.36	1.58
				5 610.0	35.490	5.080	35.005	5.158	-1.37	1.54
				5 660.0	35.440	5.130	34.906	5.213	-1.51	1.62
				5 670.0	35.430	5.140	34.882	5.223	-1.55	1.61
				5 690.0	35.410	5.160	34.843	5.252	-1.60	1.78
				5 710.0	35.390	5.180	34.827	5.275	-1.59	1.83
Oct. 21. 2021	5800 Head	20.8	20.7	5 720.0	35.380	5.190	34.815	5.282	-1.60	1.77
				5 800.0	35.300	5.270	34.656	5.376	-1.82	2.01
				5 745.0	35.355	5.215	34.767	5.312	-1.66	1.86
				5 755.0	35.345	5.225	34.754	5.323	-1.67	1.88
				5 775.0	35.325	5.245	34.715	5.342	-1.73	1.85
				5 785.0	35.315	5.255	34.691	5.355	-1.77	1.90
				5 795.0	35.305	5.265	34.670	5.370	-1.80	1.99
5 800.0	35.300	5.270	34.662	5.377	-1.81	2.03				
5 825.0	35.275	5.296	34.639	5.403	-1.80	2.02				

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB 865664 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

### Measurement Procedure for Tissue verification:

- 1) The network analyzer and probe system was configured and calibrated.
- 2) The probe was immersed in the sample which was placed in a nonmetallic container. Trapped air bubbles beneath the flange were minimized by placing the probe at a slight angle.
- 3) The complex admittance with respect to the probe aperture was measured.
- 4) The complex relative permittivity  $\epsilon_r$ , for example from the below equation (Poumaropoulos and Mera):

$$Y = \frac{j2\omega\epsilon_0\epsilon_r}{\ln(b/a)} \int_0^b \int_0^a \cos\phi' \exp\left[-\frac{j\omega r(\mu_0\epsilon_0\epsilon_r)^{1/2}}{r}\right] d\phi' d\rho' d\rho$$

where Y is the admittance of the probe in contact with the sample, the primed and unprimed coordinates refer to source and observation points, respectively,  $r^2 = \rho'^2 + \rho^2 - 2\rho'\rho\cos\phi'$ ,  $\omega$  is the angular frequency, and  $j = \sqrt{-1}$ .

## 10.2 Test System Verification

Prior to assessment, the system is verified to the  $\pm 10\%$  of the specifications at using the SAR Dipole kit(s). (Graphic Plots Attached)

**Table 10.2.1 System Verification Results (1g)**


SYSTEM DIPOLE VERIFICATION TARGET & MEASURED												
SAR System #	Freq. [MHz]	SAR Dipole kits	Date(s)	Tissue Type	Ambient Temp. [°C]	Liquid Temp. [°C]	Probe S/N	Input Power (mW)	1 W Target SAR <sub>1g</sub> (W/kg)	Measured SAR <sub>1g</sub> (W/kg)	1 W Normalized SAR <sub>1g</sub> (W/kg)	Deviation [%]
D	1 800	D1800V2, SN:2d047	Oct. 22. 2021	Head	22.2	22.1	3327	100	39.3	3.71	37.10	-5.60
D	1 900	D1900V2, SN:5d029	Oct. 21. 2021	Head	21.6	21.5	3327	100	40.5	4.08	40.80	0.74
E	1 900	D1900V2, SN:5d029	Oct. 20. 2021	Head	21.7	21.6	7337	100	40.5	4.03	40.30	-0.49
C	2 450	D2450V2, SN: 726	Oct. 18. 2021	Head	20.9	20.8	7368	100	51.8	5.43	54.30	4.83
C	5 300	D5GHZV2, SN:1103	Oct. 19. 2021	Head	20.3	20.2	7368	100	84.7	8.59	85.90	1.42
C	5 600	D5GHZV2, SN:1103	Oct. 20. 2021	Head	20.3	20.2	7368	100	86.4	8.58	85.80	-0.69
C	5 800	D5GHZV2, SN:1103	Oct. 21. 2021	Head	20.8	20.7	7368	100	83.5	8.30	83.00	-0.60

**Table 10.2.2 System Verification Results (10g)**

SYSTEM DIPOLE VERIFICATION TARGET & MEASURED												
SAR System #	Freq. [MHz]	SAR Dipole kits	Date(s)	Tissue Type	Ambient Temp. [°C]	Liquid Temp. [°C]	Probe S/N	Input Power (mW)	1 W Target SAR <sub>10g</sub> (W/kg)	Measured SAR <sub>10g</sub> (W/kg)	1 W Normalized SAR <sub>10g</sub> (W/kg)	Deviation [%]
C	5 300	D5GHZV2, SN:1103	Oct. 19. 2021	Head	20.3	20.2	7368	100	24.1	2.47	24.70	2.49
C	5 600	D5GHZV2, SN:1103	Oct. 20. 2021	Head	20.3	20.2	7368	100	24.5	2.42	24.20	-1.22
C	5 800	D5GHZV2, SN:1103	Oct. 21. 2021	Head	20.8	20.7	7368	100	23.5	2.35	23.50	0.00

Note(s) :

1. System Verification was measured with input 100 mW and normalized to 1W.
2. Full system validation status and results can be found in Attachment D.



**Figure 10.1 Dipole Verification Test Setup Diagram & Photo**

# 11. SAR TEST RESULTS

## 11.1 Head SAR Results

**Table 11.1.1 PCS/GPRS 1900 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/ Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	# of Time Slots	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
MHz	Ch													
1880.0	661	PCS1900	PCS	30.40	29.02	0.030	Left Touch	FCC #1	1	1:8.3	0.096	1.374	0.132	A1
1880.0	661	PCS1900	PCS	30.40	29.02	0.000	Right Touch	FCC #1	1	1:8.3	0.053	1.374	0.073	
1880.0	661	PCS1900	PCS	30.40	29.02	0.000	Left Tilt	FCC #1	1	1:8.3	0.037	1.374	0.051	
1880.0	661	PCS1900	PCS	30.40	29.02	0.050	Right Tilt	FCC #1	1	1:8.3	0.043	1.374	0.059	
1880.0	661	PCS1900	GPRS	24.40	23.25	0.010	Left Touch	FCC #1	4	1:2.075	0.097	1.303	0.126	A2
1880.0	661	PCS1900	GPRS	24.40	23.25	0.170	Right Touch	FCC #1	4	1:2.075	0.059	1.303	0.077	
1880.0	661	PCS1900	GPRS	24.40	23.25	0.000	Left Tilt	FCC #1	4	1:2.075	0.039	1.303	0.051	
1880.0	661	PCS1900	GPRS	24.40	23.25	0.040	Right Tilt	FCC #1	4	1:2.075	0.046	1.303	0.060	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Head 1.6 W/kg (mW/g) averaged over 1 gram			

**Table 11.1.2 WCDMA 1700 Head SAR**

MEASUREMENT RESULTS													
FREQUENCY		Mode/ Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
MHz	Ch												
1732.4	1412	WCDMA 1700	RMC	24.50	23.48	0.130	Left Touch	FCC #1	1:1	0.283	1.265	0.358	A3
1732.4	1412	WCDMA 1700	RMC	24.50	23.48	0.170	Right Touch	FCC #1	1:1	0.142	1.265	0.180	
1732.4	1412	WCDMA 1700	RMC	24.50	23.48	0.110	Left Tilt	FCC #1	1:1	0.118	1.265	0.149	
1732.4	1412	WCDMA 1700	RMC	24.50	23.48	0.040	Right Tilt	FCC #1	1:1	0.090	1.265	0.114	
ANSI / IEEE C95.1-2005- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Head 1.6 W/kg (mW/g) averaged over 1 gram		

**Table 11.1.3 WCDMA 1900 Head SAR**

MEASUREMENT RESULTS													
FREQUENCY		Mode/ Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
MHz	Ch												
1880.0	9400	WCDMA 1900	RMC	24.50	23.49	-0.180	Left Touch	FCC #1	1:1	0.182	1.262	0.230	A4
1880.0	9400	WCDMA 1900	RMC	24.50	23.49	-0.150	Right Touch	FCC #1	1:1	0.073	1.262	0.092	
1880.0	9400	WCDMA 1900	RMC	24.50	23.49	-0.140	Left Tilt	FCC #1	1:1	0.104	1.262	0.131	
1880.0	9400	WCDMA 1900	RMC	24.50	23.49	-0.170	Right Tilt	FCC #1	1:1	0.070	1.262	0.088	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Head 1.6 W/kg (mW/g) averaged over 1 gram		

**Table 11.1.4 LTE Band 4 (AWS) Head SAR**

MEASUREMENT RESULTS																	
FREQUENCY		Mode/ Band	BW [MHz]	Max Allowed Power [dBm]	Cond. PWR [dBm]	Drift Power [dB]	MPR	Position	Device Serial Number	Mod.	RB Size	RB Offs.	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
MHz	Ch																
1732.5	20175	LTE B4	20	24.50	23.60	0.020	0	Left Touch	FCC #1	QPSK	1	0	1:1	0.256	1.230	0.315	A5
1732.5	20175	LTE B4	20	23.50	22.61	0.180	1	Left Touch	FCC #1	QPSK	50	0	1:1	0.207	1.227	0.254	
1732.5	20175	LTE B4	20	24.50	23.60	0.060	0	Right Touch	FCC #1	QPSK	1	0	1:1	0.116	1.230	0.143	
1732.5	20175	LTE B4	20	23.50	22.61	0.020	1	Right Touch	FCC #1	QPSK	50	0	1:1	0.091	1.227	0.112	
1732.5	20175	LTE B4	20	24.50	23.60	0.070	0	Left Tilt	FCC #1	QPSK	1	0	1:1	0.116	1.230	0.143	
1732.5	20175	LTE B4	20	23.50	22.61	0.030	1	Left Tilt	FCC #1	QPSK	50	0	1:1	0.093	1.227	0.114	
1732.5	20175	LTE B4	20	24.50	23.60	0.070	0	Right Tilt	FCC #1	QPSK	1	0	1:1	0.084	1.230	0.103	
1732.5	20175	LTE B4	20	23.50	22.61	0.060	1	Right Tilt	FCC #1	QPSK	50	0	1:1	0.065	1.227	0.080	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure													Head 1.6 W/kg (mW/g) averaged over 1 gram				

**Table 11.1.5 LTE Band 2 (PCS) Head SAR**

MEASUREMENT RESULTS																	
FREQUENCY		Mode/ Band	BW [MHz]	Max Allowed Power [dBm]	Cond. PWR [dBm]	Drift Power [dB]	MPR	Position	Device Serial Number	Mod.	RB Size	RB Offs.	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
MHz	Ch																
1880.0	18900	LTE B2	20	24.50	23.49	0.100	0	Left Touch	FCC #1	QPSK	1	50	1:1	0.163	1.262	0.206	A6
1880.0	18900	LTE B2	20	23.50	22.47	0.050	1	Left Touch	FCC #1	QPSK	50	25	1:1	0.137	1.268	0.174	
1880.0	18900	LTE B2	20	24.50	23.49	0.150	0	Right Touch	FCC #1	QPSK	1	50	1:1	0.100	1.262	0.126	
1880.0	18900	LTE B2	20	23.50	22.47	0.080	1	Right Touch	FCC #1	QPSK	50	25	1:1	0.085	1.268	0.108	
1880.0	18900	LTE B2	20	24.50	23.49	-0.190	0	Left Tilt	FCC #1	QPSK	1	50	1:1	0.063	1.262	0.080	
1880.0	18900	LTE B2	20	23.50	22.47	0.040	1	Left Tilt	FCC #1	QPSK	50	25	1:1	0.048	1.268	0.061	
1880.0	18900	LTE B2	20	24.50	23.49	-0.000	0	Right Tilt	FCC #1	QPSK	1	50	1:1	0.046	1.262	0.058	
1880.0	18900	LTE B2	20	23.50	22.47	0.180	1	Right Tilt	FCC #1	QPSK	50	25	1:1	0.033	1.268	0.042	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure													Head 1.6 W/kg (mW/g) averaged over 1 gram				

**Table 11.1.6 DTS Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode (Antenna)	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch														
2 437.0	6	802.11b	15.00	12.90	-0.060	Left Touch	FCC #2	0.033	1	91.5	0.028	1.622	1.093	0.050	
2 437.0	6	802.11b	15.00	12.90	0.140	Right Touch	FCC #2	0.097	1	91.5	0.094	1.622	1.093	0.167	A7
2 437.0	6	802.11b	15.00	12.90	-0.150	Left Tilt	FCC #2	0.018	1	91.5	0.015	1.622	1.093	0.027	
2 437.0	6	802.11b	15.00	12.90	0.090	Right Tilt	FCC #2	0.033	1	91.5	0.033	1.622	1.093	0.058	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Head 1.6 W/kg (mW/g) averaged over 1 gram				

Adjusted SAR results for OFDM SAR												
FREQUENCY		Mode/ Antenna	Service	Maximum Allowed Power [dBm]	1g Scaled SAR (W/kg)	FREQUENCY [MHz]	Mode	Service	Maximum Allowed Power [dBm]	Ratio of OFDM to DSSS	1g Adjusted SAR (W/kg)	Determine OFDM SAR
MHz	Ch											
2 437.0	6	802.11b	DSSS	15.0	0.167	2 437.0	802.11g	OFDM	15.0	1.000	0.167	X
2 437.0	6	802.11b	DSSS	15.0	0.167	2 437.0	802.11n	OFDM	15.0	1.000	0.167	X
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Head 1.6 W/kg (mW/g) averaged over 1 gram	

Note: SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

**Table 11.1.7 UNII Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode (Antenna)	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch														
5 290.0	58	802.11ac	14.50	11.58	0.000	Left Touch	FCC #2	0.010	MCS0	89.6	0.015	1.959	1.116	0.033	
5 290.0	58	802.11ac	14.50	11.58	0.000	Right Touch	FCC #2	0.097	MCS0	89.6	0.061	1.959	1.116	0.133	A8
5 290.0	58	802.11ac	14.50	11.58	0.000	Left Tilt	FCC #2	0.014	MCS0	89.6	0.008	1.959	1.116	0.017	
5 290.0	58	802.11ac	14.50	11.58	0.000	Right Tilt	FCC #2	0.027	MCS0	89.6	0.015	1.959	1.116	0.033	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Head 1.6 W/kg (mW/g) averaged over 1 gram				

Adjusted SAR results for UNII-1 and UNII-2A SAR												
FREQUENCY		Mode/ Antenna	Service	Maximum Allowed Power [dBm]	1g Scaled SAR (W/kg)	FREQUENCY [MHz]	Mode	Service	Maximum Allowed Power [dBm]	Adjusted Factor	1g Adjusted SAR (W/kg)	SAR for the band with lower maximum output power
MHz	Ch											
5 290.0	58	802.11ac	OFDM	14.5	0.133	5 210.0	802.11ac	OFDM	14.5	1.000	0.133	X
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Head 1.6 W/kg (mW/g) averaged over 1 gram	

Note: U-NII-1 and U-NII-2A Bands: When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration.

**Table 11.1.8 UNII Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode (Antenna)	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch														
5 610.0	122	802.11ac	14.50	11.72	0.000	Left Touch	FCC #2	0.012	MCS0	89.6	0.018	1.897	1.116	0.038	
5 610.0	122	802.11ac	14.50	11.72	0.000	Right Touch	FCC #2	0.128	MCS0	89.6	0.088	1.897	1.116	0.186	A9
5 610.0	122	802.11ac	14.50	11.72	0.000	Left Tilt	FCC #2	0.016	MCS0	89.6	0.010	1.897	1.116	0.021	
5 610.0	122	802.11ac	14.50	11.72	0.000	Right Tilt	FCC #2	0.031	MCS0	89.6	0.018	1.897	1.116	0.038	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Head 1.6 W/kg (mW/g) averaged over 1 gram				

**Table 11.1.9 UNII Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode (Antenna)	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch														
5 775.0	155	802.11ac	14.50	10.66	0.000	Left Touch	FCC #2	0.011	MCS0	89.6	0.020	2.421	1.116	0.054	
5 775.0	155	802.11ac	14.50	10.66	0.000	Right Touch	FCC #2	0.101	MCS0	89.6	0.084	2.421	1.116	0.227	A10
5 775.0	155	802.11ac	14.50	10.66	0.000	Left Tilt	FCC #2	0.015	MCS0	89.6	0.009	2.421	1.116	0.024	
5 775.0	155	802.11ac	14.50	10.66	0.000	Right Tilt	FCC #2	0.030	MCS0	89.6	0.017	2.421	1.116	0.046	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Head 1.6 W/kg (mW/g) averaged over 1 gram				

**Table 11.1.10 Bluetooth Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Rate [Mbps]	Duty Cycle (%)	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #	
MHz	Ch														
2 441.0	39	Bluetooth	16.00	12.75	-0.140	Left Touch	FCC #2	1	76.8	0.044	2.113	1.302	0.121		
2 441.0	39	Bluetooth	16.00	12.75	0.030	Right Touch	FCC #2	1	76.8	0.109	2.113	1.302	0.300	A11	
2 441.0	39	Bluetooth	16.00	12.75	0.040	Left Tilt	FCC #2	1	76.8	0.020	2.113	1.302	0.055		
2 441.0	39	Bluetooth	16.00	12.75	0.000	Right Tilt	FCC #2	1	76.8	0.035	2.113	1.302	0.096		
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Head 1.6 W/kg (mW/g) averaged over 1 gram				



## 11.2 Standalone Body-Worn SAR Worn SAR Results

**Table 11.2.1 PCS/GPRS/WCDMA Body-Worn SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/ Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Spacing [Side]	Device Serial Number	# of Time Slots	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
MHz	Ch													
1880.0	661	PCS1900	PCS	30.40	29.02	0.100	15 mm [Front]	FCC #1	1	1:8.3	0.065	1.374	0.089	
1880.0	661	PCS1900	PCS	30.40	29.02	0.070	15 mm [Rear]	FCC #1	1	1:8.3	0.254	1.374	0.349	A12
1880.0	661	PCS1900	GPRS	24.40	23.25	0.030	15 mm [Front]	FCC #1	4	1:2.075	0.075	1.303	0.098	
1880.0	661	PCS1900	GPRS	24.40	23.25	-0.090	15 mm [Rear]	FCC #1	4	1:2.075	0.269	1.303	0.351	A13
1732.4	1412	WCDMA 1700	RMC	24.50	23.48	0.050	15 mm [Front]	FCC #1	N/A	1:1	0.255	1.265	0.323	
1732.4	1412	WCDMA 1700	RMC	24.50	23.48	0.050	15 mm [Rear]	FCC #1	N/A	1:1	0.353	1.265	0.447	A14
1880.0	9400	WCDMA 1900	RMC	24.50	23.49	0.060	15 mm [Front]	FCC #1	N/A	1:1	0.100	1.262	0.126	
1880.0	9400	WCDMA 1900	RMC	24.50	23.49	-0.010	15 mm [Rear]	FCC #1	N/A	1:1	0.439	1.262	0.554	A15
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak										Body 1.6 W/kg (mW/g) averaged over 1 gram				
Uncontrolled Exposure/General Population Exposure														

Note: Yellow entries represent variability measurements

**Table 11.2.2 LTE B4, B2 Body-Worn SAR**

MEASUREMENT RESULTS																	
FREQUENCY		Mode/ Band	BW [MHz]	Max Allowed Power [dBm]	Cond. PWR [dBm]	Drift Power [dB]	MPR	Position	Device Serial Number	Mod.	RB Size	RB Offs.	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
MHz	Ch																
1732.5	20175	LTE B4	20	24.50	23.60	0.000	0	15 mm [Front]	FCC #1	QPSK	1	0	1:1	0.247	1.230	0.304	
1732.5	20175	LTE B4	20	23.50	22.61	0.050	1	15 mm [Front]	FCC #1	QPSK	50	0	1:1	0.192	1.227	0.236	
1732.5	20175	LTE B4	20	24.50	23.60	0.100	0	15 mm [Rear]	FCC #1	QPSK	1	0	1:1	0.294	1.230	0.362	A16
1732.5	20175	LTE B4	20	23.50	22.61	0.070	1	15 mm [Rear]	FCC #1	QPSK	50	0	1:1	0.231	1.227	0.283	
1880.0	18900	LTE B2	20	24.50	23.49	0.050	0	15 mm [Front]	FCC #1	QPSK	1	50	1:1	0.116	1.262	0.146	
1880.0	18900	LTE B2	20	23.50	22.47	0.020	1	15 mm [Front]	FCC #1	QPSK	50	25	1:1	0.094	1.268	0.119	
1880.0	18900	LTE B2	20	24.50	23.49	-0.030	0	15 mm [Rear]	FCC #1	QPSK	1	50	1:1	0.473	1.262	0.597	A17
1880.0	18900	LTE B2	20	23.50	22.47	-0.020	1	15 mm [Rear]	FCC #1	QPSK	50	25	1:1	0.391	1.268	0.496	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak										Body 1.6 W/kg (mW/g) averaged over 1 gram							
Uncontrolled Exposure/General Population Exposure																	

**Table 11.2.3 DTS Body-Worn SAR**

MEASUREMENT RESULTS																
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	SAR (W/kg)	Plots #	
MHz	Ch															
2437.0	6	802.11b	15.00	12.90	0.170	15 mm [Front]	FCC #2	0.018	1	91.5	0.012	1.622	1.093	0.021		
2437.0	6	802.11b	15.00	12.90	-0.100	15 mm [Rear]	FCC #2	0.054	1	91.5	0.049	1.622	1.093	0.087	A18	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak										Body 1.6 W/kg (mW/g) averaged over 1 gram						
Uncontrolled Exposure/General Population Exposure																

**Adjusted SAR results for OFDM SAR**

Adjusted SAR results for OFDM SAR												
FREQUENCY		Mode/ Antenna	Service	Maximum Allowed Power [dBm]	1g Scaled SAR (W/kg)	FREQUENCY [MHz]	Mode	Service	Maximum Allowed Power [dBm]	Ratio of OFDM to DSSS	1g Adjusted SAR (W/kg)	Determine OFDM SAR
MHz	Ch											
2437.0	6	802.11b	DSSS	15.0	0.087	2437.0	802.11g	OFDM	15.0	1.000	0.087	X
2437.0	6	802.11b	DSSS	15.0	0.087	2437.0	802.11n	OFDM	15.0	1.000	0.087	X
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak										Body 1.6 W/kg (mW/g) averaged over 1 gram		
Uncontrolled Exposure/General Population Exposure												

 Note: SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.

**Table 11.2.4 UNII Body-Worn SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch														
5290.0	58	802.11ac	14.50	11.58	0.060	15 mm [Front]	FCC #2	0.015	MCS0	89.6	0.007	1.959	1.116	0.015	
5290.0	58	802.11ac	14.50	11.58	-0.020	15 mm [Rear]	FCC #2	0.149	MCS0	89.6	0.145	1.959	1.116	0.317	A19
ANSI / IEEE C95.1-2005- SAFETY LIMIT Spatial Peak										Body 1.6 W/kg (mW/g) averaged over 1 gram					
Uncontrolled Exposure/General Population Exposure															

**Adjusted SAR results for UNII-1 and UNII-2A SAR**

Adjusted SAR results for UNII-1 and UNII-2A SAR												
FREQUENCY		Mode/ Antenna	Service	Maximum Allowed Power [dBm]	1g Scaled SAR (W/kg)	FREQUENCY [MHz]	Mode	Service	Maximum Allowed Power [dBm]	Adjusted Factor	1g Adjusted SAR (W/kg)	SAR for the band with lower maximum output power
MHz	Ch											
5290.0	58	802.11ac	OFDM	14.5	0.317	5210.0	802.11ac	OFDM	14.5	1.000	0.317	X
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak										Head 1.6 W/kg (mW/g) averaged over 1 gram		
Uncontrolled Exposure/General Population Exposure												

 Note: U-NII-1 and U-NII-2A Bands: When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for the band with lower maximum output power in that test configuration.



**Table 11.2.5 UNII Body-Worn SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch														
5 610.0	122	802.11ac	14.50	11.72	0.030	15 mm [Front]	FCC #2	0.018	MCS0	89.6	0.009	1.897	1.116	0.019	
5 610.0	122	802.11ac	14.50	11.72	-0.070	15 mm [Rear]	FCC #2	0.170	MCS0	89.6	0.172	1.897	1.116	0.364	A20
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure										Body 1.6 W/kg (mW/g) averaged over 1 gram					

**Table 11.2.6 UNII Body-Worn SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch														
5 775.0	155	802.11ac	14.50	10.66	0.010	15 mm [Front]	FCC #2	0.017	MCS0	89.6	0.008	2.421	1.116	0.022	
5 775.0	155	802.11ac	14.50	10.66	-0.000	15 mm [Rear]	FCC #2	0.120	MCS0	89.6	0.125	2.421	1.116	0.338	A21
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure										Body 1.6 W/kg (mW/g) averaged over 1 gram					

**Table 11.2.7 Bluetooth Body-Worn SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Rate [Mbps]	Duty Cycle (%)	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch													
2 441.0	39	Bluetooth	16.00	12.75	0.120	15 mm [Front]	FCC #2	1	76.8	0.009	2.113	1.302	0.025	
2 441.0	39	Bluetooth	16.00	12.75	0.160	15 mm [Rear]	FCC #2	1	76.8	0.064	2.113	1.302	0.176	A22
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure										Body 1.6 W/kg (mW/g) averaged over 1 gram				

### 11.3 Standalone Hotspot SAR Results

Table 11.3.1 GPRS/WCDMA Hotspot SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/ Band	Service	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift Power (dB)	Spacing (Site)	Device Serial Number	# of Time Slots	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
Mhz	Ch													
1 880.0	661	PCS1900	GPRS	24.40	23.25	0.050	10 mm [Bottom]	FCC #1	4	1:2.075	0.344	1.303	0.448	
1 880.0	661	PCS1900	GPRS	24.40	23.25	0.010	10 mm [Front]	FCC #1	4	1:2.075	0.142	1.303	0.185	
1 880.0	661	PCS1900	GPRS	24.40	23.25	0.050	10 mm [Rear]	FCC #1	4	1:2.075	0.605	1.303	0.788	A23
1 880.0	661	PCS1900	GPRS	24.40	23.25	0.010	10 mm [Right]	FCC #1	4	1:2.075	0.004	1.303	0.005	
1 880.0	661	PCS1900	GPRS	24.40	23.25	0.070	10 mm [Left]	FCC #1	4	1:2.075	0.140	1.303	0.182	
1 732.4	1412	WCDMA 1700	RMC	24.50	23.48	0.150	10 mm [Bottom]	FCC #1	N/A	1:1	0.266	1.265	0.336	
1 732.4	1412	WCDMA 1700	RMC	24.50	23.48	0.140	10 mm [Front]	FCC #1	N/A	1:1	0.537	1.265	0.679	
1 732.4	1412	WCDMA 1700	RMC	24.50	23.48	0.010	10 mm [Rear]	FCC #1	N/A	1:1	0.581	1.265	0.735	A24
1 732.4	1412	WCDMA 1700	RMC	24.50	23.48	0.190	10 mm [Right]	FCC #1	N/A	1:1	0.054	1.265	0.068	
1 732.4	1412	WCDMA 1700	RMC	24.50	23.48	0.030	10 mm [Left]	FCC #1	N/A	1:1	0.347	1.265	0.439	
1 852.4	9262	WCDMA 1900	RMC	24.50	23.48	-0.030	10 mm [Bottom]	FCC #1	N/A	1:1	0.703	1.265	0.889	
1 880.0	9400	WCDMA 1900	RMC	24.50	23.49	-0.020	10 mm [Bottom]	FCC #1	N/A	1:1	0.683	1.262	0.862	
1 907.6	9538	WCDMA 1900	RMC	24.50	23.50	-0.030	10 mm [Bottom]	FCC #1	N/A	1:1	0.617	1.259	0.777	
1 880.0	9400	WCDMA 1900	RMC	24.50	23.49	0.030	10 mm [Front]	FCC #1	N/A	1:1	0.212	1.262	0.268	
1 852.4	9262	WCDMA 1900	RMC	24.50	23.48	0.020	10 mm [Rear]	FCC #1	N/A	1:1	0.935	1.265	1.183	A25
1 880.0	9400	WCDMA 1900	RMC	24.50	23.49	-0.000	10 mm [Rear]	FCC #1	N/A	1:1	0.907	1.262	1.145	
1 907.6	9538	WCDMA 1900	RMC	24.50	23.50	0.030	10 mm [Rear]	FCC #1	N/A	1:1	0.849	1.259	1.069	
1 880.0	9400	WCDMA 1900	RMC	24.50	23.49	0.090	10 mm [Right]	FCC #1	N/A	1:1	0.009	1.262	0.011	
1 880.0	9400	WCDMA 1900	RMC	24.50	23.49	0.010	10 mm [Left]	FCC #1	N/A	1:1	0.241	1.262	0.304	
1 852.4	9262	WCDMA 1900	RMC	24.50	23.48	-0.010	10 mm [Rear]	FCC #1	N/A	1:1	0.932	1.265	1.179	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Body 1.6 W/kg (mW/g) averaged over 1 gram			

Note: Yellow entries represent variability measurements

Table 11.3.2 LTE B4 Hotspot SAR

MEASUREMENT RESULTS																	
FREQUENCY		Mode/ Band	BW (MHz)	Max Allowed Power (dBm)	Cond. PWR (dBm)	Drift Power (dB)	MPR	Position	Device Serial Number	Mod.	RB Size	RB Offs.	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
Mhz	Ch																
1 732.5	20175	LTE B4	20	24.50	23.60	0.120	0	10 mm [Bottom]	FCC #1	QPSK	1	0	1:1	0.206	1.230	0.253	
1 732.5	20175	LTE B4	20	23.50	22.61	0.150	1	10 mm [Bottom]	FCC #1	QPSK	50	0	1:1	0.188	1.227	0.231	
1 732.5	20175	LTE B4	20	24.50	23.60	0.140	0	10 mm [Front]	FCC #1	QPSK	1	0	1:1	0.371	1.230	0.456	
1 732.5	20175	LTE B4	20	23.50	22.61	0.040	1	10 mm [Front]	FCC #1	QPSK	50	0	1:1	0.291	1.227	0.357	
1 732.5	20175	LTE B4	20	24.50	23.60	0.050	0	10 mm [Rear]	FCC #1	QPSK	1	0	1:1	0.480	1.230	0.590	A26
1 732.5	20175	LTE B4	20	23.50	22.61	0.030	1	10 mm [Rear]	FCC #1	QPSK	50	0	1:1	0.387	1.227	0.475	
1 732.5	20175	LTE B4	20	24.50	23.60	0.150	0	10 mm [Right]	FCC #1	QPSK	1	0	1:1	0.026	1.230	0.032	
1 732.5	20175	LTE B4	20	23.50	22.61	0.150	1	10 mm [Right]	FCC #1	QPSK	50	0	1:1	0.025	1.227	0.031	
1 732.5	20175	LTE B4	20	24.50	23.60	0.130	0	10 mm [Left]	FCC #1	QPSK	1	0	1:1	0.257	1.230	0.316	
1 732.5	20175	LTE B4	20	23.50	22.61	0.120	1	10 mm [Left]	FCC #1	QPSK	50	0	1:1	0.202	1.227	0.248	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Body 1.6 W/kg (mW/g) averaged over 1 gram						

Table 11.3.3 LTE B2 Hotspot SAR

MEASUREMENT RESULTS																	
FREQUENCY		Mode/ Band	BW (MHz)	Max Allowed Power (dBm)	Cond. PWR (dBm)	Drift Power (dB)	MPR	Position	Device Serial Number	Mod.	RB Size	RB Offs.	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
Mhz	Ch																
1 880.0	18900	LTE B2	20	24.50	23.49	-0.190	0	10 mm [Bottom]	FCC #1	QPSK	1	50	1:1	0.664	1.262	0.838	
1 880.0	18900	LTE B2	20	23.50	22.47	-0.020	1	10 mm [Bottom]	FCC #1	QPSK	50	25	1:1	0.524	1.268	0.664	
1 880.0	18900	LTE B2	20	24.50	23.49	0.030	0	10 mm [Front]	FCC #1	QPSK	1	50	1:1	0.255	1.262	0.322	
1 880.0	18900	LTE B2	20	23.50	22.47	0.010	1	10 mm [Front]	FCC #1	QPSK	50	25	1:1	0.207	1.268	0.262	
1 860.0	18700	LTE B2	20	24.50	23.47	-0.020	0	10 mm [Rear]	FCC #1	QPSK	1	50	1:1	0.851	1.268	1.079	
1 860.0	18700	LTE B2	20	23.50	22.39	-0.040	1	10 mm [Rear]	FCC #1	QPSK	50	25	1:1	0.702	1.291	0.906	
1 880.0	18900	LTE B2	20	24.50	23.49	-0.010	0	10 mm [Rear]	FCC #1	QPSK	1	50	1:1	0.877	1.262	1.107	
1 880.0	18900	LTE B2	20	23.50	22.47	-0.020	1	10 mm [Rear]	FCC #1	QPSK	50	25	1:1	0.723	1.268	0.917	
1 880.0	18900	LTE B2	20	24.00	22.46	-0.000	1	10 mm [Rear]	FCC #1	QPSK	100	0	1:1	0.720	1.426	1.027	
1 900.0	19100	LTE B2	20	24.50	23.48	-0.030	0	10 mm [Rear]	FCC #1	QPSK	1	50	1:1	0.882	1.265	1.116	A27
1 900.0	19100	LTE B2	20	23.50	22.45	0.010	1	10 mm [Rear]	FCC #1	QPSK	50	25	1:1	0.728	1.274	0.927	
1 880.0	18900	LTE B2	20	24.50	23.49	0.030	0	10 mm [Right]	FCC #1	QPSK	1	50	1:1	0.009	1.262	0.011	
1 880.0	18900	LTE B2	20	23.50	22.47	0.130	1	10 mm [Right]	FCC #1	QPSK	50	25	1:1	0.005	1.268	0.006	
1 880.0	18900	LTE B2	20	24.50	23.49	-0.030	0	10 mm [Left]	FCC #1	QPSK	1	50	1:1	0.219	1.262	0.276	
1 880.0	18900	LTE B2	20	23.50	22.47	0.020	1	10 mm [Left]	FCC #1	QPSK	50	25	1:1	0.175	1.268	0.222	
1 900.0	19100	LTE B2	20	24.50	23.48	0.190	0	10 mm [Rear]	FCC #1	QPSK	1	50	1:1	0.880	1.265	1.113	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Body 1.6 W/kg (mW/g) averaged over 1 gram						

Note: Yellow entries represent variability measurements

Table 11.3.4 DTS Hotspot SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift Power (dB)	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate (Mbps)	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	SAR (W/kg)	Plots #
Mhz	Ch														
2 437.0	6	802.11b	15.00	12.90	0.090	10 mm [Top]	FCC #2	0.010	1	91.5	0.006	1.622	1.093	0.011	
2 437.0	6	802.11b	15.00	12.90	0.080	10 mm [Front]	FCC #2	0.029	1	91.5	0.026	1.622	1.093	0.046	
2 437.0	6	802.11b	15.00	12.90	0.040	10 mm [Rear]	FCC #2	0.141	1	91.5	0.137	1.622	1.093	0.243	A28
2 437.0	6	802.11b	15.00	12.90	-0.030	10 mm [Left]	FCC #2	0.109	1	91.5	0.102	1.622	1.093	0.181	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Body 1.6 W/kg (mW/g) averaged over 1 gram				

Note: SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

Adjusted SAR results for OFDM SAR

Adjusted SAR results for OFDM SAR														
FREQUENCY		Mode/ Antenna	Service	Maximum Allowed SAR (W/kg)	1g Scaled SAR (W/kg)	FREQUENCY (MHz)	Mode	Service	Maximum Allowed Power (dBm)	Ratio of OFDM to DSSS	1g Adjusted SAR (W/kg)	Determine OFDM SAR		
Mhz	Ch													
2 437.0	6	802.11b	DSSS	15.0	0.243	2 437.0	802.11g	OFDM	15.0	1.000	0.243	X		
2 437.0	6	802.11b	DSSS	15.0	0.243	2 437.0	802.11n	OFDM	15.0	1.000	0.243	X		
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Body 1.6 W/kg (mW/g) averaged over 1 gram			

Note: SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

Table 11.3.5 Bluetooth Hotspot SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift Power (dB)	Phantom Position	Device Serial Number	Rate (Mbps)	Duty Cycle (%)	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
Mhz	Ch													
2 441.0	39	Bluetooth	16.00	12.75	0.050	10 mm [Top]	FCC #2	1	76.8	0.009	2.113	1.302	0.026	
2 441.0	39	Bluetooth	16.00	12.75	0.100	10 mm [Front]	FCC #2	1	76.8	0.020	2.113	1.302	0.055	
2 441.0	39	Bluetooth	16.00	12.75	0.160	10 mm [Rear]	FCC #2	1	76.8	0.148	2.113	1.302	0.407	A29
2 441.0	39	Bluetooth	16.00	12.75	0.020	10 mm [Left]	FCC #2	1	76.8	0.113	2.113	1.302	0.311	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Body 1.6			

### 11.4 Standalone Phablet SAR Results

Per FCC KDB Publication 648474 D04 Handset SAR, Phablet SAR tests were not required when Hotspot 1g SAR (scaled to maximum output power including tolerance) < 1.2 W/kg.

**Table 11.4.1 UNII Phablet SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift Power (dB)	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate (Mbps)	Duty Cycle	10g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	10g Scaled SAR (W/kg)	Plots #
MHz	Ch														
5 290.0	58	802.11ac	14.50	11.58	0.000	0 mm [Top]	FCC #2	0.006	MCS0	89.6	0.006	1.959	1.116	0.013	
5 290.0	58	802.11ac	14.50	11.58	0.030	0 mm [Front]	FCC #2	0.030	MCS0	89.6	0.018	1.959	1.116	0.039	
5 290.0	58	802.11ac	14.50	11.58	0.060	0 mm [Rear]	FCC #2	0.317	MCS0	89.6	0.410	1.959	1.116	0.896	A30
5 290.0	58	802.11ac	14.50	11.58	0.050	0 mm [Left]	FCC #2	0.220	MCS0	89.6	0.276	1.959	1.116	0.603	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Phablet 4.0 W/kg (mW/g) averaged over 10 gram				

**Table 11.4.2 UNII Phablet SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift Power (dB)	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate (Mbps)	Duty Cycle	10g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	10g Scaled SAR (W/kg)	Plots #
MHz	Ch														
5 610.0	122	802.11ac	14.50	11.72	-0.000	0 mm [Top]	FCC #2	0.006	MCS0	89.6	0.007	1.897	1.019	0.014	
5 610.0	122	802.11ac	14.50	11.72	0.170	0 mm [Front]	FCC #2	0.036	MCS0	89.6	0.022	1.897	1.019	0.043	
5 610.0	122	802.11ac	14.50	11.72	0.020	0 mm [Rear]	FCC #2	0.356	MCS0	89.6	0.494	1.897	1.019	0.955	A31
5 610.0	122	802.11ac	14.50	11.72	0.130	0 mm [Left]	FCC #2	0.247	MCS0	89.6	0.328	1.897	1.019	0.634	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Phablet 4.0 W/kg (mW/g) averaged over 10 gram				

**Table 11.4.3 UNII Phablet SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Drift Power (dB)	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate (Mbps)	Duty Cycle	10g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	10g Scaled SAR (W/kg)	Plots #
MHz	Ch														
5 775.0	155	802.11ac	14.50	10.66	0.020	0 mm [Top]	FCC #2	0.006	MCS0	89.6	0.006	2.421	1.116	0.016	
5 775.0	155	802.11ac	14.50	10.66	0.080	0 mm [Front]	FCC #2	0.034	MCS0	89.6	0.022	2.421	1.116	0.059	
5 775.0	155	802.11ac	14.50	10.66	0.150	0 mm [Rear]	FCC #2	0.385	MCS0	89.6	0.519	2.421	1.116	1.402	A32
5 775.0	155	802.11ac	14.50	10.66	0.180	0 mm [Left]	FCC #2	0.237	MCS0	89.6	0.323	2.421	1.116	0.873	
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure											Phablet 4.0 W/kg (mW/g) averaged over 10 gram				

## 11.5 SAR Test Notes

### General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements. A standard battery was used for all SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 15 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was not > 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were performed.
8. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated.
9. SAR measurements were performed using the DASY5 automated system. The procedure for spatial peak SAR evaluation has been implemented according to the IEEE 1528 standard. During a maximum search, global and local maxima searches are automatically performed in 2-D after each area scan measurement. The algorithm will find the global maximum and all local maxima within 2 dB of the global maxima for all SAR distributions. All local maxima within 2 dB of the global maximum were searched and passed for the Zoom Scan measurement.

### GSM Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. This device supports GSM VOIP in the head and body-worn configurations; therefore GPRS was additionally evaluated for head and body-worn compliance.
3. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR.
4. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s). Since the maximum output power variation across the required test channels is not > 1/2 dB, the middle channel was used for testing.

**WCDMA (UMTS) Notes:**

1. WCDMA (UMTS) mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel was used.

**LTE Notes:**

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r05. The general test procedures used for testing can be found in Section 8.4.4.
2. According to FCC KDB 941225 D05v02r05, when the reported SAR is  $\leq 0.8$  W/kg, testing of the 100% RB allocation and required test channels is not required.  
Otherwise, SAR is required for the remaining required test channels using the 1 RB, 50% RB and 100% RB allocation with highest output power for that channel.  
Only one channel, and as reported SAR values for 1 RB allocation and 50% RB allocation were less than 1.45 W/kg only the highest power RB offset for each allocation was required.
3. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36. 101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
4. A-MPR was disabled for all SAR tests by setting NS=1 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
5. SAR test reduction is applied using the following criteria:  
Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB, and 50% RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is  $> 0.8$  W/kg, testing for other channels is performed at the highest output power level for 1 RB, and 50% RB configuration for that channel. Testing for 100% RB configuration is performed at the highest output power level for 100% RB configuration across the Low, Mid and High channel when the highest reported SAR for 1 RB and 50% RB are  $> 0.8$  W/kg, Testing for the remaining required channels is not needed because the reported SAR for 100% RB Allocation  $< 1.45$  W/kg. Testing for 16QAM modulation is not required because the reported SAR for QPSK is  $< 1.45$  W/kg and its output power is not more than 0.5 dB higher than that a QPSK. Testing for the other channel bandwidths is not required because the reported SAR for the highest channel bandwidth is  $< 1.45$  W/kg and its output power is not more than 0.5 dB higher than that of the highest channel bandwidth.

## WLAN Notes:

1. The initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is  $\leq 0.4$  W/kg, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is  $\leq 0.8$  W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output and the adjust SAR is  $\leq 1.2$  W/kg.
3. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg.
4. When the maximum reported 1g averaged SAR  $\leq 0.8$  W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was  $\leq 1.20$  W/kg or all test channels were measured.
5. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor to determine compliance.

## **12. FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS**

---

### **12.1 Introduction**

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to handsets with built-in unlicensed transmitters such as 802.11b/g/n and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

### **12.2 Simultaneous Transmission Procedures**

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the sum 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is  $\leq 1.6$  W/kg. The different test position in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1-g or 10-g SAR.

### **12.3 Simultaneous Transmission Capabilities**

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds.

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06.

**Table 12.3.1 Simultaneous SAR Cases**

No.	Capable Transmit Configuration	Head SAR	Body-Worn SAR	Hotspot SAR	Phablet SAR	Note
1	GSM Voice + Wi-Fi 2.4 GHz	Yes	Yes	N/A	Yes	
2	GSM Voice + Wi-Fi 5 GHz	Yes	Yes	N/A	Yes	
3	GSM Voice + Bluetooth 2.4 GHz	Yes	Yes	N/A	Yes	
4	GSM Voice + Bluetooth 2.4 GHz + Wi-Fi 5GHz	Yes	Yes	N/A	Yes	
5	WCDMA + Wi-Fi 2.4 GHz	Yes	Yes	Yes	Yes	
6	WCDMA + Wi-Fi 5 GHz	Yes	Yes	N/A	Yes	
7	WCDMA + Bluetooth 2.4 GHz	Yes	Yes	Yes	Yes	
8	WCDMA + Bluetooth 2.4 GHz + Wi-Fi 5GHz	Yes	Yes	N/A	Yes	
9	LTE + Wi-Fi 2.4 GHz	Yes	Yes	Yes	Yes	
10	LTE + Wi-Fi 5 GHz	Yes	Yes	N/A	Yes	
11	LTE + Bluetooth 2.4 GHz	Yes	Yes	Yes	Yes	
12	LTE + Bluetooth 2.4 GHz + Wi-Fi 5GHz	Yes	Yes	N/A	Yes	
13	GPRS + Wi-Fi 2.4 GHz	Yes	Yes	Yes	Yes	
14	GPRS + Wi-Fi 5 GHz	Yes	Yes	N/A	Yes	
15	GPRS + Bluetooth 2.4 GHz	Yes	Yes	Yes	Yes	
16	GPRS + Bluetooth 2.4 GHz + Wi-Fi 5GHz	Yes	Yes	N/A	Yes	

**Notes:**

1. WiFi 2.4GHz is supported Hotspot.
2. WiFi 5GHz is not supported Hotspot.
3. LTE, WCDMA, GPRS is supported Hotspot.
4. VoIP is supported in LTE, WCDMA, GSM
5. GSM, WCDMA and LTE can not transmit simultaneously since they share the same chip.



## 12.4 Head SAR Simultaneous Transmission Analysis

**Table 12.4.1 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth + 5.3 GHz W-LAN (Held to Ear)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)		Bluetooth SAR (W/kg)		5.3G W-LAN SAR (W/kg)		ΣSAR (W/kg)		
			1	2	3	1+2	1+3	1+2+3			
Head SAR	GSM 1900	Left Touch	0.132	0.121	0.033	0.253	0.165	0.286			
		Right Touch	0.073	0.300	0.133	0.373	0.206	0.506			
		Left Tilt	0.051	0.055	0.017	0.106	0.068	0.123			
	GPRS 1900	Right Tilt	0.059	0.096	0.033	0.155	0.092	0.188			
		Left Touch	0.126	0.121	0.033	0.247	0.159	0.280			
		Right Touch	0.077	0.300	0.133	0.377	0.210	0.510			
	WCDMA 1700	Left Touch	0.051	0.055	0.017	0.106	0.068	0.123			
		Right Touch	0.060	0.096	0.033	0.156	0.093	0.189			
		Left Tilt	0.358	0.121	0.033	0.479	0.391	0.512			
	WCDMA 1900	Right Touch	0.180	0.300	0.133	0.480	0.313	0.613			
		Left Tilt	0.149	0.055	0.017	0.204	0.166	0.221			
		Right Tilt	0.114	0.096	0.033	0.210	0.147	0.243			
	LTE Band 4	Left Touch	0.230	0.121	0.033	0.351	0.263	0.384			
		Right Touch	0.092	0.300	0.133	0.392	0.225	0.525			
		Left Tilt	0.131	0.055	0.017	0.186	0.148	0.203			
	LTE Band 2	Right Tilt	0.088	0.096	0.033	0.184	0.121	0.217			
		Left Touch	0.315	0.121	0.033	0.436	0.348	0.469			
		Right Touch	0.143	0.300	0.133	0.443	0.276	0.576			
		Left Tilt	0.143	0.055	0.017	0.198	0.160	0.215			
		Right Tilt	0.103	0.096	0.033	0.199	0.136	0.232			
		Left Touch	0.206	0.121	0.033	0.327	0.239	0.360			
		Right Touch	0.126	0.300	0.133	0.426	0.259	0.559			
		Left Tilt	0.080	0.055	0.017	0.135	0.107	0.152			
		Right Tilt	0.058	0.096	0.033	0.154	0.091	0.187			

**Table 12.4.2 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth + 5.6 GHz W-LAN (Held to Ear)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)		Bluetooth SAR (W/kg)		5.6G W-LAN SAR (W/kg)		ΣSAR (W/kg)		
			1	2	3	1+2	1+3	1+2+3			
Head SAR	GSM 1900	Left Touch	0.132	0.121	0.038	0.253	0.170	0.291			
		Right Touch	0.073	0.300	0.186	0.373	0.259	0.599			
		Left Tilt	0.051	0.055	0.021	0.106	0.072	0.127			
	GPRS 1900	Right Tilt	0.059	0.096	0.038	0.155	0.097	0.193			
		Left Touch	0.126	0.121	0.038	0.247	0.164	0.286			
		Right Touch	0.077	0.300	0.186	0.377	0.263	0.563			
	WCDMA 1700	Left Touch	0.051	0.055	0.021	0.106	0.072	0.127			
		Right Touch	0.060	0.096	0.038	0.156	0.098	0.194			
		Left Tilt	0.358	0.121	0.038	0.479	0.396	0.517			
	WCDMA 1900	Right Touch	0.180	0.300	0.186	0.480	0.366	0.666			
		Left Tilt	0.149	0.055	0.021	0.204	0.170	0.225			
		Right Tilt	0.114	0.096	0.038	0.210	0.152	0.248			
	LTE Band 4	Left Touch	0.230	0.121	0.038	0.351	0.268	0.389			
		Right Touch	0.092	0.300	0.186	0.392	0.278	0.578			
		Left Tilt	0.131	0.055	0.021	0.186	0.152	0.207			
	LTE Band 2	Right Tilt	0.088	0.096	0.038	0.184	0.126	0.222			
		Left Touch	0.315	0.121	0.038	0.436	0.353	0.474			
		Right Touch	0.143	0.300	0.186	0.443	0.329	0.629			
		Left Tilt	0.143	0.055	0.021	0.198	0.164	0.219			
		Right Tilt	0.103	0.096	0.038	0.199	0.141	0.237			
		Left Touch	0.206	0.121	0.038	0.327	0.244	0.365			
		Right Touch	0.126	0.300	0.186	0.426	0.312	0.612			
		Left Tilt	0.080	0.055	0.021	0.135	0.101	0.156			
		Right Tilt	0.058	0.096	0.038	0.154	0.096	0.192			

**Table 12.4.3 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth + 5.8 GHz W-LAN (Held to Ear)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)		Bluetooth SAR (W/kg)		5.8G W-LAN SAR (W/kg)		ΣSAR (W/kg)		
			1	2	3	1+2	1+3	1+2+3			
Head SAR	GSM 1900	Left Touch	0.132	0.121	0.054	0.253	0.186	0.307			
		Right Touch	0.073	0.300	0.227	0.373	0.300	0.600			
		Left Tilt	0.051	0.055	0.024	0.106	0.075	0.130			
	GPRS 1900	Right Tilt	0.059	0.096	0.046	0.155	0.105	0.201			
		Left Touch	0.126	0.121	0.054	0.247	0.180	0.301			
		Right Touch	0.077	0.300	0.227	0.377	0.304	0.604			
	WCDMA 1700	Left Touch	0.051	0.055	0.024	0.106	0.075	0.130			
		Right Touch	0.060	0.096	0.046	0.156	0.106	0.202			
		Left Tilt	0.358	0.121	0.054	0.479	0.412	0.533			
	WCDMA 1900	Right Touch	0.180	0.300	0.227	0.480	0.407	0.707			
		Left Tilt	0.149	0.055	0.024	0.204	0.173	0.228			
		Right Tilt	0.114	0.096	0.046	0.210	0.160	0.256			
	LTE Band 4	Left Touch	0.230	0.121	0.054	0.351	0.284	0.405			
		Right Touch	0.092	0.300	0.227	0.392	0.319	0.519			
		Left Tilt	0.131	0.055	0.024	0.186	0.155	0.210			
	LTE Band 2	Right Tilt	0.088	0.096	0.046	0.184	0.134	0.230			
		Left Touch	0.315	0.121	0.054	0.436	0.369	0.490			
		Right Touch	0.143	0.300	0.227	0.443	0.370	0.670			
		Left Tilt	0.143	0.055	0.024	0.198	0.167	0.222			
		Right Tilt	0.103	0.096	0.046	0.199	0.149	0.245			
		Left Touch	0.206	0.121	0.054	0.327	0.260	0.381			
		Right Touch	0.126	0.300	0.227	0.426	0.353	0.653			
		Left Tilt	0.080	0.055	0.024	0.135	0.104	0.159			
		Right Tilt	0.058	0.096	0.046	0.154	0.104	0.200			

**Table 12.4.4 Simultaneous Transmission Scenario : 2G/3G/4G + 2.4 GHz W-LAN (Held to Ear)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)		2.4G W-LAN SAR (W/kg)		ΣSAR (W/kg)
			1	2	1+2		
Head SAR	GSM 1900	Left Touch	0.132	0.050	0.182		
		Right Touch	0.073	0.167	0.240		
		Left Tilt	0.051	0.027	0.078		
	GPRS 1900	Right Tilt	0.059	0.058	0.117		
		Left Touch	0.126	0.050	0.176		
		Right Touch	0.077	0.167	0.244		
	WCDMA 1700	Left Touch	0.051	0.027	0.078		
		Right Touch	0.060	0.058	0.118		
		Left Tilt	0.358	0.050	0.408		
	WCDMA 1900	Right Touch	0.180	0.167	0.347		
		Left Tilt	0.149	0.027	0.176		
		Right Tilt	0.114	0.058	0.172		
	LTE Band 4	Left Touch	0.230	0.050	0.280		
		Right Touch	0.092	0.167	0.259		
		Left Tilt	0.131	0.027	0.158		
	LTE Band 2	Right Tilt	0.088	0.058	0.146		
		Left Touch	0.315	0.050	0.365		
		Right Touch	0.143	0.167	0.310		
		Left Tilt	0.143	0.027	0.170		
		Right Tilt	0.103	0.058	0.161		
		Left Touch	0.206	0.050	0.256		
		Right Touch	0.126	0.167	0.293		
		Left Tilt	0.080	0.027	0.107		
		Right Tilt	0.058	0.058	0.116		

**Table 12.4.5 Simultaneous Transmission Scenario : 2G/3G/4G + 5.3 GHz W-LAN (Held to Ear)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	5.3G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Head SAR	GSM 1900	Left Touch	0.132	0.033	0.165
		Right Touch	0.073	0.133	0.206
		Left Tilt	0.051	0.017	0.068
		Right Tilt	0.059	0.033	0.092
	GPRS 1900	Left Touch	0.126	0.033	0.159
		Right Touch	0.077	0.133	0.210
		Left Tilt	0.051	0.017	0.068
		Right Tilt	0.060	0.033	0.093
	WCDMA 1700	Left Touch	0.358	0.033	0.391
		Right Touch	0.180	0.133	0.313
		Left Tilt	0.149	0.017	0.166
		Right Tilt	0.114	0.033	0.147
	WCDMA 1900	Left Touch	0.230	0.033	0.263
		Right Touch	0.092	0.133	0.225
		Left Tilt	0.131	0.017	0.148
		Right Tilt	0.088	0.033	0.121
	LTE Band 4	Left Touch	0.315	0.033	0.348
		Right Touch	0.143	0.133	0.276
		Left Tilt	0.143	0.017	0.160
		Right Tilt	0.103	0.033	0.136
	LTE Band 2	Left Touch	0.206	0.033	0.239
		Right Touch	0.126	0.133	0.259
		Left Tilt	0.080	0.017	0.097
		Right Tilt	0.058	0.033	0.091

**Table 12.4.6 Simultaneous Transmission Scenario : 2G/3G/4G + 5.6 GHz W-LAN (Held to Ear)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	5.6G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Head SAR	GSM 1900	Left Touch	0.132	0.038	0.170
		Right Touch	0.073	0.186	0.259
		Left Tilt	0.051	0.021	0.072
		Right Tilt	0.059	0.038	0.097
	GPRS 1900	Left Touch	0.126	0.038	0.164
		Right Touch	0.077	0.186	0.263
		Left Tilt	0.051	0.021	0.072
		Right Tilt	0.060	0.038	0.098
	WCDMA 1700	Left Touch	0.358	0.038	0.396
		Right Touch	0.180	0.186	0.366
		Left Tilt	0.149	0.021	0.170
		Right Tilt	0.114	0.038	0.152
	WCDMA 1900	Left Touch	0.230	0.038	0.268
		Right Touch	0.092	0.186	0.278
		Left Tilt	0.131	0.021	0.152
		Right Tilt	0.088	0.038	0.126
	LTE Band 4	Left Touch	0.315	0.038	0.353
		Right Touch	0.143	0.186	0.329
		Left Tilt	0.143	0.021	0.164
		Right Tilt	0.103	0.038	0.141
	LTE Band 2	Left Touch	0.206	0.038	0.244
		Right Touch	0.126	0.186	0.312
		Left Tilt	0.080	0.021	0.101
		Right Tilt	0.058	0.038	0.096

**Table 12.4.7 Simultaneous Transmission Scenario : 2G/3G/4G + 5.8 GHz W-LAN (Held to Ear)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	5.8G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Head SAR	GSM 1900	Left Touch	0.132	0.054	0.186
		Right Touch	0.073	0.227	0.300
		Left Tilt	0.051	0.024	0.075
		Right Tilt	0.059	0.046	0.105
	GPRS 1900	Left Touch	0.126	0.054	0.180
		Right Touch	0.077	0.227	0.304
		Left Tilt	0.051	0.024	0.075
		Right Tilt	0.060	0.046	0.106
	WCDMA 1700	Left Touch	0.358	0.054	0.412
		Right Touch	0.180	0.227	0.407
		Left Tilt	0.149	0.024	0.173
		Right Tilt	0.114	0.046	0.160
	WCDMA 1900	Left Touch	0.230	0.054	0.284
		Right Touch	0.092	0.227	0.319
		Left Tilt	0.131	0.024	0.155
		Right Tilt	0.088	0.046	0.134
	LTE Band 4	Left Touch	0.315	0.054	0.369
		Right Touch	0.143	0.227	0.370
		Left Tilt	0.143	0.024	0.167
		Right Tilt	0.103	0.046	0.149
	LTE Band 2	Left Touch	0.206	0.054	0.260
		Right Touch	0.126	0.227	0.353
		Left Tilt	0.080	0.024	0.104
		Right Tilt	0.058	0.046	0.104

**Table 12.4.8 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth (Held to Ear)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Head SAR	GSM 1900	Left Touch	0.132	0.121	0.253
		Right Touch	0.073	0.300	0.373
		Left Tilt	0.051	0.055	0.106
		Right Tilt	0.059	0.096	0.155
	GPRS 1900	Left Touch	0.126	0.121	0.247
		Right Touch	0.077	0.300	0.377
		Left Tilt	0.051	0.055	0.106
		Right Tilt	0.060	0.096	0.156
	WCDMA 1700	Left Touch	0.358	0.121	0.479
		Right Touch	0.180	0.300	0.480
		Left Tilt	0.149	0.055	0.204
		Right Tilt	0.114	0.096	0.210
	WCDMA 1900	Left Touch	0.230	0.121	0.351
		Right Touch	0.092	0.300	0.392
		Left Tilt	0.131	0.055	0.186
		Right Tilt	0.088	0.096	0.184
	LTE Band 4	Left Touch	0.315	0.121	0.436
		Right Touch	0.143	0.300	0.443
		Left Tilt	0.143	0.055	0.198
		Right Tilt	0.103	0.096	0.199
	LTE Band 2	Left Touch	0.206	0.121	0.327
		Right Touch	0.126	0.300	0.426
		Left Tilt	0.080	0.055	0.135
		Right Tilt	0.058	0.096	0.154

**Table 12.4.9 Simultaneous Transmission Scenario : Bluetooth + 5 GHz W-LAN (Held to Ear)**

Exposure Condition	Mode	Configuration	Bluetooth SAR (W/kg)	5G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Head SAR	5.3G W-LAN	Left Touch	0.121	0.033	0.154
		Right Touch	0.300	0.133	0.433
		Left Tilt	0.055	0.017	0.072
		Right Tilt	0.096	0.033	0.129
	5.6G W-LAN	Left Touch	0.121	0.038	0.159
		Right Touch	0.300	0.186	0.486
		Left Tilt	0.055	0.021	0.076
		Right Tilt	0.096	0.038	0.134
	5.8G W-LAN	Left Touch	0.121	0.054	0.175
		Right Touch	0.300	0.227	0.527
		Left Tilt	0.055	0.024	0.079
		Right Tilt	0.096	0.046	0.142

## 12.5 Body-Worn Simultaneous Transmission Analysis

**Table 12.5.1 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth + 5.3 GHz W-LAN (Body-Worn at 15 mm)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)		Bluetooth SAR (W/kg)		5.3G W-LAN SAR (W/kg)		ΣSAR (W/kg)		
			1	2	3	1+2	1+3	1+2+3			
Body-Worn SAR	GSM 1900	Front	0.089	0.025	0.015	0.114	0.104	0.129			
		Rear	0.349	0.176	0.317	0.525	0.666	0.842			
	GPRS 1900	Front	0.098	0.025	0.015	0.123	0.113	0.138			
		Rear	0.351	0.176	0.317	0.527	0.668	0.844			
	WCDMA 1700	Front	0.323	0.025	0.015	0.348	0.338	0.363			
		Rear	0.447	0.176	0.317	0.623	0.764	0.940			
	WCDMA 1900	Front	0.126	0.025	0.015	0.151	0.141	0.166			
		Rear	0.554	0.176	0.317	0.730	0.871	1.047			
	LTE Band 4	Front	0.304	0.025	0.015	0.329	0.319	0.344			
		Rear	0.362	0.176	0.317	0.538	0.679	0.855			
	LTE Band 2	Front	0.146	0.025	0.015	0.171	0.161	0.186			
		Rear	0.597	0.176	0.317	0.773	0.914	1.090			

**Table 12.5.2 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth + 5.6 GHz W-LAN (Body-Worn at 15 mm)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)		Bluetooth SAR (W/kg)		5.6G W-LAN SAR (W/kg)		ΣSAR (W/kg)		
			1	2	3	1+2	1+3	1+2+3			
Body-Worn SAR	GSM 1900	Front	0.089	0.025	0.019	0.114	0.108	0.133			
		Rear	0.349	0.176	0.364	0.525	0.713	0.889			
	GPRS 1900	Front	0.098	0.025	0.019	0.123	0.117	0.142			
		Rear	0.351	0.176	0.364	0.527	0.715	0.891			
	WCDMA 1700	Front	0.323	0.025	0.019	0.348	0.342	0.367			
		Rear	0.447	0.176	0.364	0.623	0.811	0.987			
	WCDMA 1900	Front	0.126	0.025	0.019	0.151	0.145	0.170			
		Rear	0.554	0.176	0.364	0.730	0.918	1.094			
	LTE Band 4	Front	0.304	0.025	0.019	0.329	0.323	0.348			
		Rear	0.362	0.176	0.364	0.538	0.726	0.902			
	LTE Band 2	Front	0.146	0.025	0.019	0.171	0.165	0.190			
		Rear	0.597	0.176	0.364	0.773	0.961	1.137			

**Table 12.5.3 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth + 5.8 GHz W-LAN (Body-Worn at 15 mm)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)		Bluetooth SAR (W/kg)		5.8G W-LAN SAR (W/kg)		ΣSAR (W/kg)		
			1	2	3	1+2	1+3	1+2+3			
Body-Worn SAR	GSM 1900	Front	0.089	0.025	0.022	0.114	0.111	0.136			
		Rear	0.349	0.176	0.338	0.525	0.687	0.863			
	GPRS 1900	Front	0.098	0.025	0.022	0.123	0.120	0.145			
		Rear	0.351	0.176	0.338	0.527	0.689	0.865			
	WCDMA 1700	Front	0.323	0.025	0.022	0.348	0.345	0.370			
		Rear	0.447	0.176	0.338	0.623	0.785	0.961			
	WCDMA 1900	Front	0.126	0.025	0.022	0.151	0.148	0.173			
		Rear	0.554	0.176	0.338	0.730	0.892	1.068			
	LTE Band 4	Front	0.304	0.025	0.022	0.329	0.326	0.351			
		Rear	0.362	0.176	0.338	0.538	0.700	0.876			
	LTE Band 2	Front	0.146	0.025	0.022	0.171	0.168	0.193			
		Rear	0.597	0.176	0.338	0.773	0.935	1.111			

**Table 12.5.4 Simultaneous Transmission Scenario : 2G/3G/4G + 2.4 GHz W-LAN (Body-Worn at 15 mm)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)		2.4G W-LAN SAR (W/kg)		ΣSAR (W/kg)	
			1	2	1+2			
Body-Worn SAR	GSM 1900	Front	0.089	0.021	0.110			
		Rear	0.349	0.087	0.436			
	GPRS 1900	Front	0.098	0.021	0.119			
		Rear	0.351	0.087	0.438			
	WCDMA 1700	Front	0.323	0.021	0.344			
		Rear	0.447	0.087	0.534			
	WCDMA 1900	Front	0.126	0.021	0.147			
		Rear	0.554	0.087	0.641			
	LTE Band 4	Front	0.304	0.021	0.325			
		Rear	0.362	0.087	0.449			
	LTE Band 2	Front	0.146	0.021	0.167			
		Rear	0.597	0.087	0.684			

**Table 12.5.5 Simultaneous Transmission Scenario : 2G/3G/4G + 5.3 GHz W-LAN (Body-Worn at 15 mm)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)		5.3G W-LAN SAR (W/kg)		ΣSAR (W/kg)	
			1	2	1+2			
Body-Worn SAR	GSM 1900	Front	0.089	0.015	0.104			
		Rear	0.349	0.317	0.666			
	GPRS 1900	Front	0.098	0.015	0.113			
		Rear	0.351	0.317	0.668			
	WCDMA 1700	Front	0.323	0.015	0.338			
		Rear	0.447	0.317	0.764			
	WCDMA 1900	Front	0.126	0.015	0.141			
		Rear	0.554	0.317	0.871			
	LTE Band 4	Front	0.304	0.015	0.319			
		Rear	0.362	0.317	0.679			
	LTE Band 2	Front	0.146	0.015	0.161			
		Rear	0.597	0.317	0.914			

**Table 12.5.6 Simultaneous Transmission Scenario : 2G/3G/4G + 5.6 GHz W-LAN (Body-Worn at 15 mm)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)		5.6G W-LAN SAR (W/kg)		ΣSAR (W/kg)	
			1	2	1+2			
Body-Worn SAR	GSM 1900	Front	0.089	0.019	0.108			
		Rear	0.349	0.364	0.713			
	GPRS 1900	Front	0.098	0.019	0.117			
		Rear	0.351	0.364	0.715			
	WCDMA 1700	Front	0.323	0.019	0.342			
		Rear	0.447	0.364	0.811			
	WCDMA 1900	Front	0.126	0.019	0.145			
		Rear	0.554	0.364	0.918			
	LTE Band 4	Front	0.304	0.019	0.323			
		Rear	0.362	0.364	0.726			
	LTE Band 2	Front	0.146	0.019	0.165			
		Rear	0.597	0.364	0.961			

**Table 12.5.7 Simultaneous Transmission Scenario : 2G/3G/4G + 5.8 GHz W-LAN (Body-Worn at 15 mm)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)		5.8G W-LAN SAR (W/kg)		ΣSAR (W/kg)	
			1	2	1+2			
Body-Worn SAR	GSM 1900	Front	0.089	0.022	0.111			
		Rear	0.349	0.338	0.687			
	GPRS 1900	Front	0.098	0.022	0.120			
		Rear	0.351	0.338	0.689			
	WCDMA 1700	Front	0.323	0.022	0.345			
		Rear	0.447	0.338	0.735			
	WCDMA 1900	Front	0.126	0.022	0.148			
		Rear	0.554	0.338	0.892			
	LTE Band 4	Front	0.304	0.022	0.326			
		Rear	0.362	0.338	0.700			
	LTE Band 2	Front	0.146	0.022	0.168			
		Rear	0.597	0.338	0.935			

**Table 12.5.8 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth (Body-Worn at 15 mm)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Body-Worn SAR	GSM 1900	Front	0.089	0.025	0.114
		Rear	0.349	0.176	0.525
	GPRS 1900	Front	0.098	0.025	0.123
		Rear	0.351	0.176	0.527
	WCDMA 1700	Front	0.323	0.025	0.348
		Rear	0.447	0.176	0.623
	WCDMA 1900	Front	0.126	0.025	0.151
		Rear	0.554	0.176	0.730
	LTE Band 4	Front	0.304	0.025	0.329
		Rear	0.362	0.176	0.538
	LTE Band 2	Front	0.146	0.025	0.171
		Rear	0.597	0.176	0.773

**Table 12.5.9 Simultaneous Transmission Scenario : Bluetooth + 5 GHz W-LAN (Body-Worn at 15 mm)**

Exposure Condition	Mode	Configuration	Bluetooth SAR (W/kg)	5G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Body-Worn SAR	5.3G W-LAN	Front	0.025	0.015	0.040
		Rear	0.176	0.317	0.493
	5.6G W-LAN	Front	0.025	0.019	0.044
		Rear	0.176	0.364	0.540
	5.8G W-LAN	Front	0.025	0.022	0.047
		Rear	0.176	0.338	0.514

## 12.6 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v02r01, the device edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR ("").

**Table 12.6.1 Simultaneous Transmission Scenario : 2G/3G/4G + 2.4 GHz W-LAN (Hotspot at 10 mm)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	2.4G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Hotspot SAR	GPRS 1900	Top	-	0.011	0.011
		Bottom	0.448	-	0.448
		Front	0.185	0.046	0.231
		Rear	0.788	0.243	1.031
		Right	0.005	-	0.005
		Left	0.182	0.181	0.363
	WCDMA 1700	Top	-	0.011	0.011
		Bottom	0.336	-	0.336
		Front	0.679	0.046	0.725
		Rear	0.735	0.243	0.978
		Right	0.068	-	0.068
		Left	0.439	0.181	0.620
	WCDMA 1900	Top	-	0.011	0.011
		Bottom	0.889	-	0.889
		Front	0.288	0.046	0.334
		Rear	1.183	0.243	1.426
		Right	0.011	-	0.011
		Left	0.304	0.181	0.485
	LTE Band 4	Top	-	0.011	0.011
		Bottom	0.253	-	0.253
		Front	0.456	0.046	0.502
		Rear	0.590	0.243	0.833
		Right	0.032	-	0.032
		Left	0.316	0.181	0.497
	LTE Band 2	Top	-	0.011	0.011
		Bottom	0.838	-	0.838
		Front	0.322	0.046	0.368
		Rear	1.116	0.243	1.359
		Right	0.011	-	0.011
		Left	0.276	0.181	0.457

**Table 12.6.2 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth (Hotspot at 10 mm)**

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Hotspot SAR	GPRS 1900	Top	-	0.026	0.026
		Bottom	0.448	-	0.448
		Front	0.185	0.055	0.240
		Rear	0.788	0.407	1.195
		Right	0.005	-	0.005
		Left	0.182	0.311	0.493
	WCDMA 1700	Top	-	0.026	0.026
		Bottom	0.336	-	0.336
		Front	0.679	0.055	0.734
		Rear	0.735	0.407	1.142
		Right	0.068	-	0.068
		Left	0.439	0.311	0.750
	WCDMA 1900	Top	-	0.026	0.026
		Bottom	0.889	-	0.889
		Front	0.288	0.055	0.323
		Rear	1.183	0.407	1.590
		Right	0.011	-	0.011
		Left	0.304	0.311	0.615
	LTE Band 4	Top	-	0.026	0.026
		Bottom	0.253	-	0.253
		Front	0.456	0.055	0.511
		Rear	0.590	0.407	0.997
		Right	0.032	-	0.032
		Left	0.316	0.311	0.627
	LTE Band 2	Top	-	0.026	0.026
		Bottom	0.838	-	0.838
		Front	0.322	0.055	0.377
		Rear	1.116	0.407	1.523
		Right	0.011	-	0.011
		Left	0.276	0.311	0.587

## 12.7 Phablet SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 648474 D04 Handset SAR, Phablet SAR tests were not required of Hotspot 1g SAR (scaled to maximum output power, including tolerance)  $< 1.2$  W/kg. Therefore no further analysis was required to for Phablet Simultaneous Transmission Analysis.

## 12.8 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2.

## 13. SAR MEASUREMENT VARIABILITY

### 13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

1. When the original highest measured SAR is  $\geq 0.80$  W/kg, the measurement was repeated once.
2. A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was  $> 1.20$  or when the original or repeated measurement was  $\geq 1.45$  W/kg (~10% from the 1-g SAR limit).
3. A third repeated measurement was performed only if the original, first or second repeated measurement was  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .
4. Repeated measurements are not required when the original highest measured SAR is  $< 0.80$  W/kg
5. The same procedures should be adapted for measurements according to extremity exposure limits by applying a factor of 2.5 for extremity exposure to the corresponding SAR thresholds.

**Table 13.1 Hotspot SAR Measurement Variability Results**

Frequency		Mode	Service	# of Time Slots	Spacing [Side]	Measured SAR (1g)	1st Repeated SAR(1g)	Ratio	2nd Repeated SAR(1g)	Ratio	3rd Repeated SAR(1g)	Ratio
MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1852.4	9262	WCDMA 1900	RMC	-	10 mm [Rear]	0.935	0.932	1.00	-	-	-	-
1900.0	19100	LTE B2	-	-	10 mm [Rear]	0.882	0.880	1.00	-	-	-	-
ANSI / IEEE C95.1-1992- SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure						Body 1.6 W/kg (mW/g) averaged over 1 gram						

### 13.2 Measurement Uncertainty

The measured SAR was  $< 1.5$  W/kg for 1g and  $< 3.75$  W/kg for 10g for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.



# 14. EQUIPMENT LIST

**Table 14.1.1 Test Equipment Calibration**

Type	Manufacturer	Model	Cal.Date	Next.Cal.Date	S/N
☑ SEMITEC Engineering	SEMITEC	N/A	N/A	N/A	Shield Room
☑ SEMITEC Engineering	SEMITEC	N/A	N/A	N/A	Shield Room
☑ SEMITEC Engineering	SEMITEC	N/A	N/A	N/A	Shield Room
☑ Robot	SPEAG	TX90XL	N/A	N/A	F13/5P9GA1/A/01
☑ Robot	SPEAG	TX90XL	N/A	N/A	F13/5RR2A1/A/01
☑ Robot	SPEAG	TX60L	N/A	N/A	F15/50NHA1/A/01
☑ Robot Controller	SPEAG	CS8C	N/A	N/A	F13/5P9GA1/C/01
☑ Robot Controller	SPEAG	CS8C	N/A	N/A	F13/5RR2A1/C/01
☑ Robot Controller	SPEAG	CS8C	N/A	N/A	F15/50NHA1/C/01
☑ Joystick	SPEAG	N/A	N/A	N/A	S-12450905
☑ Joystick	SPEAG	N/A	N/A	N/A	S-13200990
☑ Joystick	SPEAG	N/A	N/A	N/A	D21142605A
☑ Intel Core i7-3 770 3.40 GHz Windows 7 Professional	N/A	N/A	N/A	N/A	N/A
☑ Intel Core i7-3 770 3.40 GHz Windows 7 Professional	N/A	N/A	N/A	N/A	N/A
☑ Intel Core i7-8 700K 3.70 GHz Window 10 Pro	N/A	N/A	N/A	N/A	N/A
☑ Probe Alignment Unit LB	N/A	N/A	N/A	N/A	SE UKS 030 AA
☑ Probe Alignment Unit LB	N/A	N/A	N/A	N/A	SE UKS 030 AA
☑ Probe Alignment Unit LB	N/A	N/A	N/A	N/A	SE UKS 030 AA
☑ Device Holder	SPEAG	SD000H01HA	N/A	N/A	N/A
☑ Device Holder	SPEAG	SD000H01HA	N/A	N/A	N/A
☑ Device Holder	SPEAG	SD000H01HA	N/A	N/A	N/A
☑ Twin SAM Phantom	SPEAG	QD000P40CD	N/A	N/A	1782
☑ Twin SAM Phantom	SPEAG	QD000P40CD	N/A	N/A	1785
☑ Twin SAM Phantom	SPEAG	QD000P40CD	N/A	N/A	1786
☑ Twin SAM Phantom	SPEAG	QD000P40CD	N/A	N/A	1895
☑ Data Acquisition Electronics	SPEAG	DAE4V1	2021-04-26	2022-04-26	1485
☑ Data Acquisition Electronics	SPEAG	DAE3V1	2020-11-24	2021-11-24	520
☑ Data Acquisition Electronics	SPEAG	DAE4V1	2021-07-27	2022-07-27	1335
☑ Dosimetric E-Field Probe	SPEAG	EX3DV4	2020-11-27	2021-11-27	7368
☑ Dosimetric E-Field Probe	SPEAG	ES3DV3	2021-01-27	2022-01-27	3327
☑ Dosimetric E-Field Probe	SPEAG	EX3DV4	2021-06-23	2022-06-23	7337
☑ 1 800MHz SAR Dipole	SPEAG	D1800V2	2021-04-23	2023-04-23	2047
☑ 1 900MHz SAR Dipole	SPEAG	D1900V2	2021-07-23	2023-07-23	50209
☑ 2 450MHz SAR Dipole	SPEAG	D2450V2	2021-09-22	2023-09-22	726
☑ 5GHz SAR Dipole	SPEAG	D5GHZV2	2021-02-23	2023-02-23	1103
☑ Network Analyzer	Agilent	E5071C	2021-06-24	2022-06-24	MY46106970
☑ Signal Generator	Agilent	E4438C	2021-06-24	2022-06-24	US41461520
☑ Amplifier	EMPOWER	BBS3Q7ELU	2021-06-24	2022-06-24	1020
☑ High Power RF Amplifier	EMPOWER	BBS3Q8CCJ	2021-06-24	2022-06-24	1005
☑ Power Meter	HP	EPM-442A	2020-12-16	2021-12-16	GB37170267
☑ Power Meter	HP	EPM-442A	2020-12-16	2021-12-16	GB37170413
☑ Power Sensor	HP	8481A	2020-12-16	2021-12-16	US37294267
☑ Power Sensor	HP	8481A	2020-12-16	2021-12-16	2702A61707
☑ Power Sensor	HP	8481A	2020-12-16	2021-12-16	2702A65976
☑ Dual Directional Coupler	Agilent	778D-012	2020-12-16	2021-12-16	50228
☑ Directional Coupler	HP	772D	2021-06-24	2022-06-24	2889A01064
☑ Low Pass Filter 3.0GHz	Micro LAB	LA-30N	2021-06-24	2022-06-24	2
☑ Low Pass Filter 6.0GHz	Micro LAB	LA-60N	2020-12-16	2021-12-16	03942
☑ Attenuators(10 dB)	WEINSCHIEL	23-10-34	2020-12-16	2021-12-16	BP4387
☑ Step Attenuator	HP	8494A	2021-06-24	2022-06-24	3308A33341
☑ Dielectric Probe kit	SPEAG	DAK-3.5	2020-11-25	2021-11-25	1092
☑ 8960 Series 10 Wireless Comms. Test Set	Agilent	E5515C	2021-06-24	2022-06-24	GB41321164
☑ Wideband Radio Communication Tester	Rohde Schwarz	CMW500	2020-12-16	2021-12-16	101414
☑ Wideband Radio Communication Tester	Rohde Schwarz	CMW500	2021-04-23	2022-04-23	166448
☑ Power Splitter	Anritsu	K241B	2020-12-16	2021-12-16	1301183
☑ Bluetooth Tester	TESCOM	TC-3000C	2021-06-24	2022-06-24	3000C000563

**NOTE(S):**  
 1. The E-field probe was calibrated by SPEAG, by temperature measurement procedure. Dipole Verification measurement is performed by DT&C before each test. The brain and muscle simulating material are calibrated by DT&C using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the brain and muscle-equivalent material. Each equipment item was used solely within its respective calibration period.  
 2. CBT(Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

## 15. MEASUREMENT UNCERTAINTIES

### 1 800 MHz Head (SN: 3327)

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1 g	(Ci) 10 g	Standard 1 g (± %)	Standard 10 g (± %)	vi 2 or Veff
<b>Measurement System</b>								
Probe calibration	6.0	Normal	1	1	1	6.0	6.0	∞
Axial isotropy	4.7	Rectangular	√3	1	1	2.7	2.7	∞
Hemispherical isotropy	9.6	Rectangular	√3	1	1	5.5	5.5	∞
Boundary Effects	0.8	Rectangular	√3	1	1	0.46	0.46	∞
Probe Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	∞
Probe modulation response	2.4	Rectangular	√3	1	1	1.4	1.4	∞
Detection limits	0.25	Rectangular	√3	1	1	0.14	0.14	∞
Readout Electronics	1.0	Normal	1	1	1	1.0	1.0	∞
Response time	0.8	Rectangular	√3	1	1	0.46	0.46	∞
Integration time	2.6	Rectangular	√3	1	1	1.5	1.5	∞
RF Ambient Conditions – Noise	3.0	Rectangular	√3	1	1	1.7	1.7	∞
RF Ambient Conditions – Reflections	3.0	Rectangular	√3	1	1	1.7	1.7	∞
Probe Positioner	0.4	Rectangular	√3	1	1	0.23	0.23	∞
Probe Positioning	2.9	Rectangular	√3	1	1	1.7	1.7	∞
Algorithms for Max. SAR Eval.	1.0	Rectangular	√3	1	1	0.58	0.58	∞
<b>Test Sample Related</b>								
Device Positioning	2.9	Normal	1	1	1	2.9	2.9	145
Device Holder	3.6	Normal	1	1	1	3.6	3.6	5
Power Drift	5.0	Rectangular	√3	1	1	2.9	2.9	∞
SAR Scaling	2.0	Rectangular	√3	1	1	1.2	1.2	∞
<b>Physical Parameters</b>								
Phantom Shell	7.6	Rectangular	√3	1	1	4.4	4.4	∞
Liquid conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	1.8	1.2	∞
Liquid conductivity (Meas.)	3.9	Normal	1	0.78	0.71	3.0	2.8	10
Liquid permittivity (Target)	5.0	Rectangular	√3	0.60	0.49	1.7	1.4	∞
Liquid permittivity (Meas.)	4.0	Normal	1	0.23	0.26	0.92	1.0	10
Temp. unc. - Conductivity	1.9	Rectangular	√3	0.78	0.71	0.86	0.78	∞
Temp. unc. - Permittivity	1.8	Rectangular	√3	0.23	0.26	0.24	0.27	∞
<b>Combined Standard Uncertainty</b>						<b>13</b>	<b>13</b>	<b>330</b>
<b>Expanded Uncertainty (k=2)</b>						<b>26</b>	<b>26</b>	

$$U(1\text{ g}) = k \cdot u_c$$

$$= 2 \cdot 13\%$$

$$= 26\% \text{ (The confidence level is about 95\% } k=2)$$

$$U(10\text{ g}) = k \cdot u_c$$

$$= 2 \cdot 13\%$$

$$= 26\% \text{ (The confidence level is about 95\% } k=2)$$

**1 900 MHz Head (SN: 3327)**

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1 g	(Ci) 10 g	Standard 1 g (± %)	Standard 10 g (± %)	vi 2 or Veff
<b>Measurement System</b>								
Probe calibration	6.0	Normal	1	1	1	6.0	6.0	∞
Axial isotropy	4.7	Rectangular	√3	1	1	2.7	2.7	∞
Hemispherical isotropy	9.6	Rectangular	√3	1	1	5.5	5.5	∞
Boundary Effects	0.8	Rectangular	√3	1	1	0.46	0.46	∞
Probe Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	∞
Probe modulation response	2.4	Rectangular	√3	1	1	1.4	1.4	∞
Detection limits	0.25	Rectangular	√3	1	1	0.14	0.14	∞
Readout Electronics	1.0	Normal	1	1	1	1.0	1.0	∞
Response time	0.8	Rectangular	√3	1	1	0.46	0.46	∞
Integration time	2.6	Rectangular	√3	1	1	1.5	1.5	∞
RF Ambient Conditions – Noise	3.0	Rectangular	√3	1	1	1.7	1.7	∞
RF Ambient Conditions – Reflections	3.0	Rectangular	√3	1	1	1.7	1.7	∞
Probe Positioner	0.4	Rectangular	√3	1	1	0.23	0.23	∞
Probe Positioning	2.9	Rectangular	√3	1	1	1.7	1.7	∞
Algorithms for Max. SAR Eval.	1.0	Rectangular	√3	1	1	0.58	0.58	∞
<b>Test Sample Related</b>								
Device Positioning	2.9	Normal	1	1	1	2.9	2.9	145
Device Holder	3.6	Normal	1	1	1	3.6	3.6	5
Power Drift	5.0	Rectangular	√3	1	1	2.9	2.9	∞
SAR Scaling	2.0	Rectangular	√3	1	1	1.2	1.2	∞
<b>Physical Parameters</b>								
Phantom Shell	7.6	Rectangular	√3	1	1	4.4	4.4	∞
Liquid conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	1.8	1.2	∞
Liquid conductivity (Meas.)	4.0	Normal	1	0.78	0.71	3.1	2.8	10
Liquid permittivity (Target)	5.0	Rectangular	√3	0.60	0.49	1.7	1.4	∞
Liquid permittivity (Meas.)	3.8	Normal	1	0.23	0.26	0.87	1.0	10
Temp. unc. - Conductivity	1.9	Rectangular	√3	0.78	0.71	0.86	0.78	∞
Temp. unc. - Permittivity	2.0	Rectangular	√3	0.23	0.26	0.27	0.30	∞
<b>Combined Standard Uncertainty</b>						<b>13</b>	<b>13</b>	<b>330</b>
<b>Expanded Uncertainty (k=2)</b>						<b>26</b>	<b>26</b>	

$$U(1\text{ g}) = k \cdot u_c$$

$$= 2 \cdot 13\%$$

= 26 % (The confidence level is about 95 %  $k = 2$ )

$$U(10\text{ g}) = k \cdot u_c$$

$$= 2 \cdot 13\%$$

= 26 % (The confidence level is about 95 %  $k = 2$ )

**750 ~ 2 600 MHz Head (SN: 7337)**

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1 g	(Ci) 10 g	Standard 1 g (± %)	Standard 10 g (± %)	vi 2 or Veff
<b>Measurement System</b>								
Probe calibration	6.0	Normal	1	1	1	6.0	6.0	∞
Axial isotropy	4.7	Rectangular	√3	1	1	2.7	2.7	∞
Hemispherical isotropy	9.6	Rectangular	√3	1	1	5.5	5.5	∞
Boundary Effects	0.8	Rectangular	√3	1	1	0.46	0.46	∞
Probe Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	∞
Probe modulation response	2.4	Rectangular	√3	1	1	1.4	1.4	∞
Detection limits	0.25	Rectangular	√3	1	1	0.14	0.14	∞
Readout Electronics	1.0	Normal	1	1	1	1.0	1.0	∞
Response time	0.8	Rectangular	√3	1	1	0.46	0.46	∞
Integration time	2.6	Rectangular	√3	1	1	1.5	1.5	∞
RF Ambient Conditions – Noise	3.0	Rectangular	√3	1	1	1.7	1.7	∞
RF Ambient Conditions – Reflections	3.0	Rectangular	√3	1	1	1.7	1.7	∞
Probe Positioner	0.4	Rectangular	√3	1	1	0.23	0.23	∞
Probe Positioning	2.9	Rectangular	√3	1	1	1.7	1.7	∞
Algorithms for Max. SAR Eval.	1.0	Rectangular	√3	1	1	0.58	0.58	∞
<b>Test Sample Related</b>								
Device Positioning	2.9	Normal	1	1	1	2.9	2.9	145
Device Holder	3.6	Normal	1	1	1	3.6	3.6	5
Power Drift	5.0	Rectangular	√3	1	1	2.9	2.9	∞
SAR Scaling	2.0	Rectangular	√3	1	1	1.2	1.2	∞
<b>Physical Parameters</b>								
Phantom Shell	7.6	Rectangular	√3	1	1	4.4	4.4	∞
Liquid conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	1.8	1.2	∞
Liquid conductivity (Meas.)	4.0	Normal	1	0.78	0.71	3.1	2.8	10
Liquid permittivity (Target)	5.0	Rectangular	√3	0.60	0.49	1.7	1.4	∞
Liquid permittivity (Meas.)	4.0	Normal	1	0.23	0.26	0.92	1.0	10
Temp. unc. - Conductivity	2.0	Rectangular	√3	0.78	0.71	0.90	0.82	∞
Temp. unc. - Permittivity	2.0	Rectangular	√3	0.23	0.26	0.27	0.30	∞
<b>Combined Standard Uncertainty</b>						<b>13</b>	<b>13</b>	<b>330</b>
<b>Expanded Uncertainty (k=2)</b>						<b>26</b>	<b>26</b>	

$$U(1\text{ g}) = k \cdot u_c$$

$$= 2 \cdot 13\%$$

= 26 % (The confidence level is about 95 %  $k = 2$ )

$$U(10\text{ g}) = k \cdot u_c$$

$$= 2 \cdot 13\%$$

= 26 % (The confidence level is about 95 %  $k = 2$ )

**2 450 MHz Head (SN: 7368)**

Error Description	Uncertainty value $\pm\%$	Probability Distribution	Divisor	(Ci) 1 g	(Ci) 10 g	Standard 1 g ( $\pm\%$ )	Standard 10 g ( $\pm\%$ )	vi 2 or Veff
<b>Measurement System</b>								
Probe calibration	6.5	Normal	1	1	1	6.5	6.5	$\infty$
Axial isotropy	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	$\infty$
Hemispherical isotropy	9.6	Rectangular	$\sqrt{3}$	1	1	5.5	5.5	$\infty$
Boundary Effects	0.8	Rectangular	$\sqrt{3}$	1	1	0.46	0.46	$\infty$
Probe Linearity	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	$\infty$
Probe modulation response	2.4	Rectangular	$\sqrt{3}$	1	1	1.4	1.4	$\infty$
Detection limits	0.25	Rectangular	$\sqrt{3}$	1	1	0.14	0.14	$\infty$
Readout Electronics	1.0	Normal	1	1	1	1.0	1.0	$\infty$
Response time	0.8	Rectangular	$\sqrt{3}$	1	1	0.46	0.46	$\infty$
Integration time	2.6	Rectangular	$\sqrt{3}$	1	1	1.5	1.5	$\infty$
RF Ambient Conditions – Noise	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	$\infty$
RF Ambient Conditions – Reflections	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	$\infty$
Probe Positioner	0.4	Rectangular	$\sqrt{3}$	1	1	0.23	0.23	$\infty$
Probe Positioning	2.9	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	$\infty$
Algorithms for Max. SAR Eval.	1.0	Rectangular	$\sqrt{3}$	1	1	0.58	0.58	$\infty$
<b>Test Sample Related</b>								
Device Positioning	2.9	Normal	1	1	1	2.9	2.9	145
Device Holder	3.6	Normal	1	1	1	3.6	3.6	5
Power Drift	5.0	Rectangular	$\sqrt{3}$	1	1	2.9	2.9	$\infty$
SAR Scaling	2.0	Rectangular	$\sqrt{3}$	1	1	1.2	1.2	$\infty$
<b>Physical Parameters</b>								
Phantom Shell	7.6	Rectangular	$\sqrt{3}$	1	1	4.4	4.4	$\infty$
Liquid conductivity (Target)	5.0	Rectangular	$\sqrt{3}$	0.64	0.43	1.8	1.2	$\infty$
Liquid conductivity (Meas.)	4.2	Normal	1	0.78	0.71	3.3	3.0	10
Liquid permittivity (Target)	5.0	Rectangular	$\sqrt{3}$	0.60	0.49	1.7	1.4	$\infty$
Liquid permittivity (Meas.)	4.0	Normal	1	0.23	0.26	0.92	1.0	10
Temp. unc. - Conductivity	1.9	Rectangular	$\sqrt{3}$	0.78	0.71	0.86	0.78	$\infty$
Temp. unc. - Permittivity	1.9	Rectangular	$\sqrt{3}$	0.23	0.26	0.25	0.29	$\infty$
<b>Combined Standard Uncertainty</b>						<b>13</b>	<b>13</b>	<b>330</b>
<b>Expanded Uncertainty (k=2)</b>						<b>26</b>	<b>26</b>	

$$U(1\text{ g}) = k \cdot u_c$$

$$= 2 \cdot 13\%$$

= 26 % (The confidence level is about 95 %  $k = 2$ )

$$U(10\text{ g}) = k \cdot u_c$$

$$= 2 \cdot 13\%$$

= 26 % (The confidence level is about 95 %  $k = 2$ )

**5 300 MHz Head (SN: 7368)**

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1 g	(Ci) 10 g	Standard 1 g (± %)	Standard 10 g (± %)	vi 2 or Veff
<b>Measurement System</b>								
Probe calibration	6.5	Normal	1	1	1	6.5	6.5	∞
Axial isotropy	4.7	Rectangular	√3	1	1	2.7	2.7	∞
Hemispherical isotropy	9.6	Rectangular	√3	1	1	5.5	5.5	∞
Boundary Effects	0.8	Rectangular	√3	1	1	0.46	0.46	∞
Probe Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	∞
Probe modulation response	2.4	Rectangular	√3	1	1	1.4	1.4	∞
Detection limits	0.25	Rectangular	√3	1	1	0.14	0.14	∞
Readout Electronics	1.0	Normal	1	1	1	1.0	1.0	∞
Response time	0.8	Rectangular	√3	1	1	0.46	0.46	∞
Integration time	2.6	Rectangular	√3	1	1	1.5	1.5	∞
RF Ambient Conditions – Noise	3.0	Rectangular	√3	1	1	1.7	1.7	∞
RF Ambient Conditions – Reflections	3.0	Rectangular	√3	1	1	1.7	1.7	∞
Probe Positioner	0.4	Rectangular	√3	1	1	0.23	0.23	∞
Probe Positioning	2.9	Rectangular	√3	1	1	1.7	1.7	∞
Algorithms for Max. SAR Eval.	1.0	Rectangular	√3	1	1	0.58	0.58	∞
<b>Test Sample Related</b>								
Device Positioning	2.9	Normal	1	1	1	2.9	2.9	145
Device Holder	3.6	Normal	1	1	1	3.6	3.6	5
Power Drift	5.0	Rectangular	√3	1	1	2.9	2.9	∞
SAR Scaling	2.0	Rectangular	√3	1	1	1.2	1.2	∞
<b>Physical Parameters</b>								
Phantom Shell	7.6	Rectangular	√3	1	1	4.4	4.4	∞
Liquid conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	1.8	1.2	∞
Liquid conductivity (Meas.)	4.0	Normal	1	0.78	0.71	3.1	2.8	10
Liquid permittivity (Target)	5.0	Rectangular	√3	0.60	0.49	1.7	1.4	∞
Liquid permittivity (Meas.)	4.0	Normal	1	0.23	0.26	0.92	1.0	10
Temp. unc. - Conductivity	1.9	Rectangular	√3	0.78	0.71	0.86	0.78	∞
Temp. unc. - Permittivity	2.0	Rectangular	√3	0.23	0.26	0.27	0.30	∞
<b>Combined Standard Uncertainty</b>						<b>13</b>	<b>13</b>	<b>330</b>
<b>Expanded Uncertainty (k=2)</b>						<b>26</b>	<b>26</b>	

$$U(1\text{ g}) = k \cdot u_c$$

$$= 2 \cdot 13\%$$

= 26 % (The confidence level is about 95 %  $k = 2$ )

$$U(10\text{ g}) = k \cdot u_c$$

$$= 2 \cdot 13\%$$

= 26 % (The confidence level is about 95 %  $k = 2$ )



**5 600 MHz Head (SN: 7368)**

Error Description	Uncertainty value $\pm\%$	Probability Distribution	Divisor	(Ci) 1 g	(Ci) 10 g	Standard 1 g ( $\pm\%$ )	Standard 10 g ( $\pm\%$ )	vi 2 or Veff
<b>Measurement System</b>								
Probe calibration	6.5	Normal	1	1	1	6.5	6.5	$\infty$
Axial isotropy	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	$\infty$
Hemispherical isotropy	9.6	Rectangular	$\sqrt{3}$	1	1	5.5	5.5	$\infty$
Boundary Effects	0.8	Rectangular	$\sqrt{3}$	1	1	0.46	0.46	$\infty$
Probe Linearity	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	$\infty$
Probe modulation response	2.4	Rectangular	$\sqrt{3}$	1	1	1.4	1.4	$\infty$
Detection limits	0.25	Rectangular	$\sqrt{3}$	1	1	0.14	0.14	$\infty$
Readout Electronics	1.0	Normal	1	1	1	1.0	1.0	$\infty$
Response time	0.8	Rectangular	$\sqrt{3}$	1	1	0.46	0.46	$\infty$
Integration time	2.6	Rectangular	$\sqrt{3}$	1	1	1.5	1.5	$\infty$
RF Ambient Conditions – Noise	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	$\infty$
RF Ambient Conditions – Reflections	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	$\infty$
Probe Positioner	0.4	Rectangular	$\sqrt{3}$	1	1	0.23	0.23	$\infty$
Probe Positioning	2.9	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	$\infty$
Algorithms for Max. SAR Eval.	1.0	Rectangular	$\sqrt{3}$	1	1	0.58	0.58	$\infty$
<b>Test Sample Related</b>								
Device Positioning	2.9	Normal	1	1	1	2.9	2.9	145
Device Holder	3.6	Normal	1	1	1	3.6	3.6	5
Power Drift	5.0	Rectangular	$\sqrt{3}$	1	1	2.9	2.9	$\infty$
SAR Scaling	2.0	Rectangular	$\sqrt{3}$	1	1	1.2	1.2	$\infty$
<b>Physical Parameters</b>								
Phantom Shell	7.6	Rectangular	$\sqrt{3}$	1	1	4.4	4.4	$\infty$
Liquid conductivity (Target)	5.0	Rectangular	$\sqrt{3}$	0.64	0.43	1.8	1.2	$\infty$
Liquid conductivity (Meas.)	4.0	Normal	1	0.78	0.71	3.1	2.8	10
Liquid permittivity (Target)	5.0	Rectangular	$\sqrt{3}$	0.60	0.49	1.7	1.4	$\infty$
Liquid permittivity (Meas.)	4.0	Normal	1	0.23	0.26	0.92	1.0	10
Temp. unc. - Conductivity	1.9	Rectangular	$\sqrt{3}$	0.78	0.71	0.86	0.78	$\infty$
Temp. unc. - Permittivity	2.0	Rectangular	$\sqrt{3}$	0.23	0.26	0.27	0.30	$\infty$
<b>Combined Standard Uncertainty</b>						<b>13</b>	<b>13</b>	<b>330</b>
<b>Expanded Uncertainty (k=2)</b>						<b>26</b>	<b>26</b>	

$$U(1\text{ g}) = k \cdot u_c$$

$$= 2 \cdot 13\%$$

= 26 % (The confidence level is about 95 %  $k = 2$ )

$$U(10\text{ g}) = k \cdot u_c$$

$$= 2 \cdot 13\%$$

= 26 % (The confidence level is about 95 %  $k = 2$ )

**5 800 MHz Head (SN: 7368)**

Error Description	Uncertainty value $\pm\%$	Probability Distribution	Divisor	(Ci) 1 g	(Ci) 10 g	Standard 1 g ( $\pm\%$ )	Standard 10 g ( $\pm\%$ )	vi 2 or Veff
<b>Measurement System</b>								
Probe calibration	6.5	Normal	1	1	1	6.5	6.5	$\infty$
Axial isotropy	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	$\infty$
Hemispherical isotropy	9.6	Rectangular	$\sqrt{3}$	1	1	5.5	5.5	$\infty$
Boundary Effects	0.8	Rectangular	$\sqrt{3}$	1	1	0.46	0.46	$\infty$
Probe Linearity	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	$\infty$
Probe modulation response	2.4	Rectangular	$\sqrt{3}$	1	1	1.4	1.4	$\infty$
Detection limits	0.25	Rectangular	$\sqrt{3}$	1	1	0.14	0.14	$\infty$
Readout Electronics	1.0	Normal	1	1	1	1.0	1.0	$\infty$
Response time	0.8	Rectangular	$\sqrt{3}$	1	1	0.46	0.46	$\infty$
Integration time	2.6	Rectangular	$\sqrt{3}$	1	1	1.5	1.5	$\infty$
RF Ambient Conditions – Noise	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	$\infty$
RF Ambient Conditions – Reflections	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	$\infty$
Probe Positioner	0.4	Rectangular	$\sqrt{3}$	1	1	0.23	0.23	$\infty$
Probe Positioning	2.9	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	$\infty$
Algorithms for Max. SAR Eval.	1.0	Rectangular	$\sqrt{3}$	1	1	0.58	0.58	$\infty$
<b>Test Sample Related</b>								
Device Positioning	2.9	Normal	1	1	1	2.9	2.9	145
Device Holder	3.6	Normal	1	1	1	3.6	3.6	5
Power Drift	5.0	Rectangular	$\sqrt{3}$	1	1	2.9	2.9	$\infty$
SAR Scaling	2.0	Rectangular	$\sqrt{3}$	1	1	1.2	1.2	$\infty$
<b>Physical Parameters</b>								
Phantom Shell	7.6	Rectangular	$\sqrt{3}$	1	1	4.4	4.4	$\infty$
Liquid conductivity (Target)	5.0	Rectangular	$\sqrt{3}$	0.64	0.43	1.8	1.2	$\infty$
Liquid conductivity (Meas.)	4.0	Normal	1	0.78	0.71	3.1	2.8	10
Liquid permittivity (Target)	5.0	Rectangular	$\sqrt{3}$	0.60	0.49	1.7	1.4	$\infty$
Liquid permittivity (Meas.)	4.1	Normal	1	0.23	0.26	0.94	1.1	10
Temp. unc. - Conductivity	1.9	Rectangular	$\sqrt{3}$	0.78	0.71	0.86	0.78	$\infty$
Temp. unc. - Permittivity	1.9	Rectangular	$\sqrt{3}$	0.23	0.26	0.25	0.29	$\infty$
<b>Combined Standard Uncertainty</b>						<b>13</b>	<b>13</b>	<b>330</b>
<b>Expanded Uncertainty (k=2)</b>						<b>26</b>	<b>26</b>	

$$U(1\text{ g}) = k \cdot u_c$$

$$= 2 \cdot 13\%$$

= 26 % (The confidence level is about 95 %  $k = 2$ )

$$U(10\text{ g}) = k \cdot u_c$$

$$= 2 \cdot 13\%$$

= 26 % (The confidence level is about 95 %  $k = 2$ )

## 16. CONCLUSION

---

### Measurement Conclusion

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the FCC. These measurements are taken to simulate the RF effects exposure under the worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters subject to the test. The test results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are every complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role impossible biological effect are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease).

Because innumerable factors may interact to determine the specific biological outcome of an exposure to electromagnetic fields, any protection guide shall consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables.

## 17. REFERENCES

---

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radiofrequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radiofrequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for Radio Frequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid& Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct.1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bio electromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computer mathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.

- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300MHz to 3 GHz), Feb. 2005.
- [21] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radio communication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225,D01-D07
- [24] SAR Measurement procedures for IEEE 802.11a/b/g KDB Publication 248227 D01v02
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474D02-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] 615223 D01 802 16e WI-Max SAR Guidance v01, Nov. 13, 2009
- [30] Anexo à Resolução No. 533, de 10 de September de 2009.
- [31] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body(frequency range of 30 MHz to 6 GHz), Mar. 2010.

## APPENDIX A. – Probe Calibration Data



**Calibration Laboratory of  
 Schmid & Partner  
 Engineering AG**  
 Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**S** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108



Client **DT&C (Dymstec)**

Certificate No: ES3-3327\_Jan21

## CALIBRATION CERTIFICATE

Object	ES3DV3 - SN:3327
Calibration procedure(s)	QA CAL-01.v9, QA CAL-14.v6, QA CAL-23.v5, QA CAL-25.v7 Calibration procedure for dosimetric E-field probes
Calibration date:	January 27, 2021
This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.	
All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.	
Calibration Equipment used (M&TE critical for calibration)	

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	01-Apr-20 (No. 217-03100/03101)	Apr-21
Power sensor NRP-Z91	SN: 103244	01-Apr-20 (No. 217-03100)	Apr-21
Power sensor NRP-Z91	SN: 103245	01-Apr-20 (No. 217-03101)	Apr-21
Reference 20 dB Attenuator	SN: CC2552 (20x)	31-Mar-20 (No. 217-03106)	Apr-21
DAE4	SN: 660	23-Dec-20 (No. DAE4-660_Dec20)	Dec-21
Reference Probe ES3DV2	SN: 3013	30-Dec-20 (No. ES3-3013_Dec20)	Dec-21
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-20)	In house check: Jun-22
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-20)	In house check: Jun-22
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-20)	In house check: Jun-22
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-20)	In house check: Jun-22
Network Analyzer E8358A	SN: US41080477	31-Mar-14 (in house check Oct-20)	In house check: Oct-21

	Name	Function	Signature
Calibrated by:	Jeffrey Katzman	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	
			Issued: January 28, 2021
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			

**Calibration Laboratory of  
 Schmid & Partner  
 Engineering AG**  
 Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**S** Service suisse d'étalonnage  
**C** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: SCS 0108

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

### Glossary:

TSL	tissue simulating liquid
NORM <sub>x,y,z</sub>	sensitivity in free space
ConvF	sensitivity in TSL / NORM <sub>x,y,z</sub>
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization $\varphi$	$\varphi$ rotation around probe axis
Polarization $\vartheta$	$\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).



ES3DV3 – SN:3327

January 27, 2021

## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3327

### Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup>	1.15	1.09	1.03	± 10.1 %
DCP (mV) <sup>B</sup>	103.6	106.2	107.2	

### Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Max dev.	Unc <sup>E</sup> (k=2)
0	CW	X	0.0	0.0	1.0	0.00	193.6	± 2.5 %	± 4.7 %
		Y	0.0	0.0	1.0		202.9		
		Z	0.0	0.0	1.0		195.9		

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

ES3DV3– SN:3327

January 27, 2021

## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3327

### Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-125.9
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm

**Note:** Measurement distance from surface can be increased to 3-4 mm for an *Area Scan* job.

ES3DV3- SN:3327

January 27, 2021

## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3327

### Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) <sup>c</sup>	Relative Permittivity <sup>f</sup>	Conductivity (S/m) <sup>f</sup>	ConvF X	ConvF Y	ConvF Z	Alpha <sup>g</sup>	Depth <sup>g</sup> (mm)	Unc (k=2)
750	41.9	0.89	6.49	6.49	6.49	0.80	1.26	± 12.0 %
835	41.5	0.90	6.26	6.26	6.26	0.77	1.23	± 12.0 %
900	41.5	0.97	6.08	6.08	6.08	0.40	1.75	± 12.0 %
1750	40.1	1.37	5.41	5.41	5.41	0.73	1.31	± 12.0 %
1900	40.0	1.40	5.13	5.13	5.13	0.68	1.32	± 12.0 %
2450	39.2	1.80	4.68	4.68	4.68	0.80	1.40	± 12.0 %
2600	39.0	1.96	4.47	4.47	4.47	0.80	1.37	± 12.0 %
3500	37.9	2.91	4.23	4.23	4.23	0.90	1.40	± 13.1 %
3700	37.7	3.12	4.13	4.13	4.13	0.90	1.40	± 13.1 %

<sup>c</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4-9 MHz, and ConvF assessed at 13 MHz is 9-19 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>f</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>g</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

ES3DV3- SN:3327

January 27, 2021

## DASY/EASY - Parameters of Probe: ES3DV3 - SN:3327

### Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) <sup>c</sup>	Relative Permittivity <sup>F</sup>	Conductivity (S/m) <sup>F</sup>	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth <sup>G</sup> (mm)	Unc (k=2)
750	55.5	0.96	6.51	6.51	6.51	0.43	1.58	± 12.0 %
835	55.2	0.97	6.34	6.34	6.34	0.80	1.18	± 12.0 %
900	55.0	1.05	6.23	6.23	6.23	0.57	1.39	± 12.0 %
1750	53.4	1.49	5.26	5.26	5.26	0.48	1.59	± 12.0 %
1900	53.3	1.52	5.01	5.01	5.01	0.48	1.64	± 12.0 %
2450	52.7	1.95	4.49	4.49	4.49	0.80	1.28	± 12.0 %
2600	52.5	2.16	4.34	4.34	4.34	0.80	1.25	± 12.0 %
3500	51.3	3.31	3.81	3.81	3.81	0.80	1.60	± 13.1 %
3700	51.0	3.55	3.71	3.71	3.71	0.80	1.60	± 13.1 %

<sup>c</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4-9 MHz, and ConvF assessed at 13 MHz is 9-19 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.


<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

ES3DV3- SN:3327

January 27, 2021

### Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  (k=2)



ES3DV3-SN:3327

January 27, 2021

### Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$





Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )

ES3DV3- SN:3327

January 27, 2021

### Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell, $f_{\text{eval}} = 1900 \text{ MHz}$ )




Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )


ES3DV3-SN:3327

January 27, 2021

### Conversion Factor Assessment



### Deviation from Isotropy in Liquid Error ( $\phi, \theta$ ), f = 900 MHz



**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
 Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**S** Service suisse d'étalonnage  
**C** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108



Client DT&amp;C (Dymstec)

Certificate No: EX3-7368\_Nov20

## CALIBRATION CERTIFICATE

Object	EX3DV4 - SN:7368
Calibration procedure(s)	QA CAL-01.v9, QA CAL-14.v6, QA CAL-23.v5, QA CAL-25.v7 Calibration procedure for dosimetric E-field probes
Calibration date:	November 27, 2020
This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.	
All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.	
Calibration Equipment used (M&TE critical for calibration)	

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	01-Apr-20 (No. 217-03100/03101)	Apr-21
Power sensor NRP-Z91	SN: 103244	01-Apr-20 (No. 217-03100)	Apr-21
Power sensor NRP-Z91	SN: 103245	01-Apr-20 (No. 217-03101)	Apr-21
Reference 20 dB Attenuator	SN: CC2552 (20x)	31-Mar-20 (No. 217-03106)	Apr-21
DAE4	SN: 660	27-Dec-19 (No. DAE4-660_Dec19)	Dec-20
Reference Probe ES3DV2	SN: 3013	31-Dec-19 (No. ES3-3013_Dec19)	Dec-20
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-20)	In house check: Jun-22
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-20)	In house check: Jun-22
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-20)	In house check: Jun-22
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-20)	In house check: Jun-22
Network Analyzer E8358A	SN: US41080477	31-Mar-14 (in house check Oct-20)	In house check: Oct-21

	Name	Function	Signature
Calibrated by:	Jeton Kastrati	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	
			Issued: December 1, 2020
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



**Calibration Laboratory of**  
 Schmid & Partner  
 Engineering AG  
 Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**S** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: SCS 0108

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

### Glossary:

TSL	tissue simulating liquid
NORM <sub>x,y,z</sub>	sensitivity in free space
ConvF	sensitivity in TSL / NORM <sub>x,y,z</sub>
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization $\varphi$	$\varphi$ rotation around probe axis
Polarization $\vartheta$	$\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).

EX3DV4 – SN:7368

November 27, 2020

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:7368

### Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup>	0.48	0.56	0.42	± 10.1 %
DCP (mV) <sup>B</sup>	100.7	97.7	102.2	

### Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Max dev.	Max Unc <sup>E</sup> (k=2)
0	CW	X	0.00	0.00	1.00	0.00	160.3	± 3.0 %	± 4.7 %
		Y	0.00	0.00	1.00		150.0		
		Z	0.00	0.00	1.00		153.7		
10352-AAA	Pulse Waveform (200Hz, 10%)	X	3.59	70.12	12.21	10.00	60.0	± 3.6 %	± 9.6 %
		Y	7.31	77.83	15.34		60.0		
		Z	2.34	65.07	9.45		60.0		
10353-AAA	Pulse Waveform (200Hz, 20%)	X	8.27	79.42	14.40	6.99	80.0	± 2.5 %	± 9.6 %
		Y	20.00	89.19	17.66		80.0		
		Z	1.05	62.05	7.32		80.0		
10354-AAA	Pulse Waveform (200Hz, 40%)	X	20.00	90.35	16.92	3.98	95.0	± 1.6 %	± 9.6 %
		Y	20.00	92.58	17.99		95.0		
		Z	1.31	67.09	8.70		95.0		
10355-AAA	Pulse Waveform (200Hz, 60%)	X	20.00	100.56	20.68	2.22	120.0	± 0.9 %	± 9.6 %
		Y	20.00	98.82	19.84		120.0		
		Z	20.00	90.18	15.38		120.0		
10387-AAA	QPSK Waveform, 1 MHz	X	1.76	66.72	15.53	1.00	150.0	± 1.7 %	± 9.6 %
		Y	1.70	65.34	14.63		150.0		
		Z	1.89	69.82	16.78		150.0		
10388-AAA	QPSK Waveform, 10 MHz	X	2.32	68.49	16.16	0.00	150.0	± 1.1 %	± 9.6 %
		Y	2.23	67.27	15.31		150.0		
		Z	2.39	70.02	17.05		150.0		
10396-AAA	64-QAM Waveform, 100 kHz	X	2.94	71.30	19.25	3.01	150.0	± 0.9 %	± 9.6 %
		Y	2.70	69.06	18.13		150.0		
		Z	2.46	69.81	18.76		150.0		
10399-AAA	64-QAM Waveform, 40 MHz	X	3.59	67.39	16.00	0.00	150.0	± 0.8 %	± 9.6 %
		Y	3.40	66.17	15.27		150.0		
		Z	3.50	67.50	16.15		150.0		
10414-AAA	WLAN CCDF, 64-QAM, 40MHz	X	4.93	65.84	15.67	0.00	150.0	± 1.3 %	± 9.6 %
		Y	4.80	65.05	15.20		150.0		
		Z	4.73	65.78	15.70		150.0		

Note: For details on UID parameters see Appendix

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4– SN:7368

November 27, 2020

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:7368

### Sensor Model Parameters

	C1 fF	C2 fF	$\alpha$ V <sup>-1</sup>	T1 ms.V <sup>-2</sup>	T2 ms.V <sup>-1</sup>	T3 ms	T4 V <sup>-2</sup>	T5 V <sup>-1</sup>	T6
X	45.0	330.78	34.68	8.53	0.00	4.98	1.90	0.05	1.01
Y	48.5	362.65	35.59	7.00	0.00	5.00	1.12	0.18	1.01
Z	35.0	255.74	34.42	6.18	0.00	4.95	1.32	0.00	1.00

### Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	155.8
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

**Note:** Measurement distance from surface can be increased to 3-4 mm for an *Area Scan* job.



EX3DV4– SN:7368

November 27, 2020

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:7368

### Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) <sup>C</sup>	Relative Permittivity <sup>F</sup>	Conductivity (S/m) <sup>F</sup>	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth (mm) <sup>G</sup>	Unc (k=2)
750	41.9	0.89	9.90	9.90	9.90	0.51	0.80	± 12.0 %
835	41.5	0.90	9.68	9.68	9.68	0.43	0.80	± 12.0 %
900	41.5	0.97	9.59	9.59	9.59	0.46	0.80	± 12.0 %
1750	40.1	1.37	8.52	8.52	8.52	0.41	0.80	± 12.0 %
1900	40.0	1.40	8.27	8.27	8.27	0.29	0.80	± 12.0 %
2450	39.2	1.80	7.89	7.89	7.89	0.36	0.80	± 12.0 %
2600	39.0	1.96	7.53	7.53	7.53	0.37	0.80	± 12.0 %
3500	37.9	2.91	7.03	7.03	7.03	0.35	1.30	± 13.1 %
3700	37.7	3.12	6.92	6.92	6.92	0.35	1.30	± 13.1 %
5200	36.0	4.66	5.65	5.65	5.65	0.40	1.80	± 13.1 %
5300	35.9	4.76	5.39	5.39	5.39	0.40	1.80	± 13.1 %
5500	35.6	4.96	5.04	5.04	5.04	0.40	1.80	± 13.1 %
5600	35.5	5.07	4.84	4.84	4.84	0.40	1.80	± 13.1 %
5800	35.3	5.27	5.03	5.03	5.03	0.40	1.80	± 13.1 %

<sup>C</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4-9 MHz, and ConvF assessed at 13 MHz is 9-19 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4– SN:7368

November 27, 2020

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:7368

### Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) <sup>C</sup>	Relative Permittivity <sup>F</sup>	Conductivity (S/m) <sup>F</sup>	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth (mm) <sup>G</sup>	Unc (k=2)
6500	34.5	6.07	5.50	5.50	5.50	0.20	2.50	± 18.6 %

<sup>C</sup> Frequency validity above 6GHz is ± 700 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.


<sup>F</sup> At frequencies 6-10 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz; below ± 2% for frequencies between 3-6 GHz; and below ± 4% for frequencies between 6-10 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:7368

November 27, 2020

### Frequency Response of E-Field (TEM-Cell: ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  (k=2)



EX3DV4- SN:7368

November 27, 2020

### Receiving Pattern ( $\phi$ ), $\vartheta = 0^\circ$

f=600 MHz,TEM

f=1800 MHz,R22





Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  (k=2)

EX3DV4- SN:7368

November 27, 2020

### Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell, $f_{\text{eval}} = 1900 \text{ MHz}$ )




Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )




EX3DV4- SN:7368

November 27, 2020

### Conversion Factor Assessment



### Deviation from Isotropy in Liquid Error ( $\phi, \theta$ ), f = 900 MHz



EX3DV4- SN:7368

November 27, 2020

**Appendix: Modulation Calibration Parameters**

UID	Rev	Communication System Name	Group	PAR (dB)	Unc <sup>E</sup> (k=2)
0		CW	CW	0.00	± 4.7 %
10010	CAA	SAR Validation (Square, 100ms, 10ms)	Test	10.00	± 9.6 %
10011	CAB	UMTS-FDD (WCDMA)	WCDMA	2.91	± 9.6 %
10012	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	WLAN	1.87	± 9.6 %
10013	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	WLAN	9.46	± 9.6 %
10021	DAC	GSM-FDD (TDMA, GMSK)	GSM	9.39	± 9.6 %
10023	DAC	GPRS-FDD (TDMA, GMSK, TN 0)	GSM	9.57	± 9.6 %
10024	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	GSM	6.56	± 9.6 %
10025	DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	GSM	12.62	± 9.6 %
10026	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	GSM	9.55	± 9.6 %
10027	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	GSM	4.80	± 9.6 %
10028	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	GSM	3.55	± 9.6 %
10029	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	GSM	7.78	± 9.6 %
10030	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH1)	Bluetooth	5.30	± 9.6 %
10031	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	Bluetooth	1.87	± 9.6 %
10032	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	Bluetooth	1.16	± 9.6 %
10033	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	Bluetooth	7.74	± 9.6 %
10034	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH3)	Bluetooth	4.53	± 9.6 %
10035	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)	Bluetooth	3.83	± 9.6 %
10036	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	Bluetooth	8.01	± 9.6 %
10037	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	Bluetooth	4.77	± 9.6 %
10038	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	Bluetooth	4.10	± 9.6 %
10039	CAB	CDMA2000 (1xRTT, RC1)	CDMA2000	4.57	± 9.6 %
10042	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Halfrate)	AMPS	7.78	± 9.6 %
10044	CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	AMPS	0.00	± 9.6 %
10048	CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	DECT	13.80	± 9.6 %
10049	CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	DECT	10.79	± 9.6 %
10056	CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	TD-SCDMA	11.01	± 9.6 %
10058	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	GSM	6.52	± 9.6 %
10059	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	WLAN	2.12	± 9.6 %
10060	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	WLAN	2.83	± 9.6 %
10061	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	WLAN	3.60	± 9.6 %
10062	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)	WLAN	8.68	± 9.6 %
10063	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)	WLAN	8.63	± 9.6 %
10064	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)	WLAN	9.09	± 9.6 %
10065	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)	WLAN	9.00	± 9.6 %
10066	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	WLAN	9.38	± 9.6 %
10067	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)	WLAN	10.12	± 9.6 %
10068	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)	WLAN	10.24	± 9.6 %
10069	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	WLAN	10.56	± 9.6 %
10071	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	WLAN	9.83	± 9.6 %
10072	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	WLAN	9.62	± 9.6 %
10073	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)	WLAN	9.94	± 9.6 %
10074	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)	WLAN	10.30	± 9.6 %
10075	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)	WLAN	10.77	± 9.6 %
10076	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)	WLAN	10.94	± 9.6 %
10077	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	WLAN	11.00	± 9.6 %
10081	CAB	CDMA2000 (1xRTT, RC3)	CDMA2000	3.97	± 9.6 %
10082	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Fullrate)	AMPS	4.77	± 9.6 %
10090	DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)	GSM	6.56	± 9.6 %
10097	CAC	UMTS-FDD (HSDPA)	WCDMA	3.98	± 9.6 %
10098	DAC	UMTS-FDD (HSUPA, Subtest 2)	WCDMA	3.98	± 9.6 %