

Report on the RF Testing of:

KYOCERA Corporation
Mobile Phone, Model: EB1157
FCC ID: JOYEB1157

In accordance with FCC Part 15 Subpart C
(15.249)

Prepared for: KYOCERA Corporation
Yokohama Office 2-1-1 Kagahara, Tsuzuki-ku
Yokohama-shi, Kanagawa, Japan
Phone: +81-45-943-6253 Fax: +81-45-943-6314



Japan

Add value.
Inspire trust.

COMMERCIAL-IN-CONFIDENCE

Document Number: JPD-TR-23079-0

SIGNATURE

NAME	JOB TITLE	RESPONSIBLE FOR	ISSUE DATE
Hiroaki Suzuki	Deputy Manager of RF Group	Approved Signatory	2023.08.18

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD Japan Ltd. document control rules.

EXECUTIVE SUMMARY – Result: Complied

A sample of this product was tested and the result above was confirmed in accordance with FCC Part 15 Subpart C (15.249).



DISCLAIMER AND COPYRIGHT

The results in this report are applicable only to the equipment tested.
This report shall not be re-produced except in full without the written approval of TÜV SÜD Japan Ltd.

We assume no responsibility for damage occurred from error in the information provided by the applicant.

ACCREDITATION

This test report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the U.S. Government.

TÜV SÜD Japan Ltd.
Yonezawa Testing Center
5-4149-7 Hachimanpara,
Yonezawa-shi, Yamagata,
992-1128 Japan

Phone: +81 (0) 238 28 2881
www.tuv-sud.jp

Contents

1	Summary of Test	3
1.1	Modification history of the test report.....	3
1.2	Standards.....	3
1.3	Test methods.....	3
1.4	Deviation from standards.....	3
1.5	List of applied test(s) of the EUT.....	3
1.6	Test information.....	3
1.7	Test set up.....	3
1.8	Test period.....	3
2	Equipment Under Test	4
2.1	EUT information.....	4
2.2	Modification to the EUT.....	5
2.3	Variation of family model(s).....	5
2.4	Operating channels and frequencies.....	5
2.5	Operating mode.....	6
2.6	Operating flow.....	6
3	Configuration of Equipment	7
3.1	Equipment used.....	7
3.2	Cable(s) used.....	7
3.3	System configuration.....	7
4	Test Result	8
4.1	Occupied Bandwidth.....	8
4.2	Spurious Emissions - Radiated -.....	11
4.3	Restricted Band of Operation.....	19
4.4	AC Power Line Conducted Emissions.....	23
5	Antenna requirement	26
6	Measurement Uncertainty	27
7	Laboratory Information	28
	Appendix A. Test Equipment	29
	Appendix B. Duty Cycle	30

1 Summary of Test

1.1 Modification history of the test report

Document Number	Modification History	Issue Date
JPD-TR-23079-0	First Issue	Refer to the cover page

1.2 Standards

CFR47 FCC Part 15 Subpart C (15.249)

1.3 Test methods

ANSI C63.10-2013

1.4 Deviation from standards

None

1.5 List of applied test(s) of the EUT

Test item section	Test item	Condition	Result	Remark
2.1049 RSS-Gen 6.7	Occupied Bandwidth	Conducted	PASS	-
15.249(a), (b), (c), (d), (e) RSS-210 B.10(a), (b)	Spurious Emissions - Field Strength of Fundamental and Harmonics -	Radiated	PASS	-
15.249(c), (d) RSS-210 B.10(b)	Restricted Bands of Operation	Radiated	PASS	-
15.207 RSS-Gen 8.8	AC Power Line Conducted Emissions	Conducted	PASS	-

1.6 Test information

None

1.7 Test set up

Table-top

1.8 Test period

26-June-2023 - 6-July-2023

2 Equipment Under Test

All information in this chapter was provided by the applicant.

2.1 EUT information

Applicant	KYOCERA Corporation	
	Yokohama Office 2-1-1 Kagahara, Tsuzuki-ku Yokohama-shi, Kanagawa, Japan	
	Phone: +81-45-943-6253 Fax: +81-45-943-6314	
Equipment Under Test (EUT)	Mobile Phone	
Model number	EB1157	
Serial number	358018240001198, 358018240001065	
Trade name	Kyocera	
Number of sample(s)	2	
EUT condition	Pre-Production	
Power rating	Battery: DC 3.87 V	
Size	(W) 75 mm x (D) 14.6 mm x (H) 154 mm	
Environment	Indoor and Outdoor use	
Terminal limitation	-20 °C to 60 °C	
Hardware version	Pre-Production	
Software version	0.130RI	
Firmware version	Not applicable	
RF Specification		
Protocol	ANT+	
Frequency range	2402 MHz-2480 MHz	
Number of RF Channels	79 Channels	
Modulation method/Data rate	GFSK (20 Kbps)	
Channel separation	1 MHz	
Output power	Peak:	101.9dBuV/m @ 3m
	Average:	81.9dBuV/m @ 3m
Antenna type	Internal antenna	
Antenna gain	Chain 0 : +1.0 dBi	
	Chain 1 : -1.1 dBi	

2.2 Modification to the EUT

The table below details modifications made to the EUT during the test project.

Modification State	Description of Modification	Modification fitted by	Date of Modification
Model: EB1157, Serial Number: 358018240001198, 358018240001065			
0	As supplied by the applicant	Not Applicable	Not Applicable

2.3 Variation of family model(s)

2.3.1 List of family model(s)

Not applicable

2.3.2 Reason for selection of EUT

Not applicable

2.4 Operating channels and frequencies

Channel	Frequency [MHz]	Channel	Frequency [MHz]	Channel	Frequency [MHz]
0	2402	27	2429	54	2456
1	2403	28	2430	55	2457
2	2404	29	2431	56	2458
3	2405	30	2432	57	2459
4	2406	31	2433	58	2460
5	2407	32	2434	59	2461
6	2408	33	2435	60	2462
7	2409	34	2436	61	2463
8	2410	35	2437	62	2464
9	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

2.5 Operating mode

The EUT had been tested under operating condition.
There are three channels have been tested as following:

Tested Channel	Frequency [MHz]
Low	2402
Middle	2441
High	2480

The pre-test has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates.

Tested Channel	Modulation Type	Data Rate
Low, Middle, High	GFSK	20 Kbps

The field strength of spurious emissions was measured at each position of all three axis X, Y and Z to compare the level, and the maximum noise.

The worst emission was found in X-axis, Chain 0 and the worst case recorded.

Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports.

2.6 Operating flow

[Tx mode]

- i) Test program setup to the DM tool
- ii) Select a Test mode
Operating frequency: Channel Low: 2402 MHz, Channel Middle: 2441 MHz, Channel High: 2480 MHz
- iii) Start test mode

[Rx mode]

- i) Test program setup to the DM tool
- ii) Select a Test mode
Operating frequency: Channel Low: 2402 MHz, Channel Middle: 2441 MHz, Channel High: 2480 MHz
- iii) Start test mode

3 Configuration of Equipment

Numbers assigned to equipment on the diagram in “3.3 System configuration” correspond to the list in “3.1 Equipment used” and “3.2 Cable(s) used”.

This test configuration is based on the manufacture’s instruction.

Cabling and setup(s) were taken into consideration and test data was taken under worse case condition.

3.1 Equipment used

No.	Equipment	Company	Model No.	Serial No.	FCC ID/DoC	Comment
1	Mobile Phone	KYOCERA	EB1157	358018240001198 358018240001065	JOYEB1157	EUT
2	AC Adapter	KDDI	0602PQA	N/A	N/A	*


*:AC power line Conducted Emission Test.

3.2 Cable(s) used

No.	Equipment	Length[m]	Shield	Connector	Comment
a	USB cable (for AC Adapter)	1.5	No	Plastic	*

*:AC power line Conducted Emission Test.

3.3 System configuration





4 Test Result

4.1 Occupied Bandwidth

4.1.1 Measurement procedure


[2.1049, RSS-Gen 6.7]

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99% bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

The spectrum analyzer is set to;

- a) RBW = 20 kHz
- b) VBW $\geq 3 \times$ RBW
- c) Sweep time = auto-couple
- d) Detector = peak
- e) Trace mode = max hold

- Test configuration



4.1.2 Limit

None

4.1.3 Measurement result

Date : 6-July-2023
 Temperature : 23.3 [°C]
 Humidity : 53.2 [%]
 Test place : Shielded room No.4


Test engineer : Kazunori Saito

Channel	Frequency [MHz]	Occupied Bandwidth [MHz]
Low [Chain 0]	2402	0.459
Middle [Chain 0]	2441	0.457
High [Chain 0]	2480	0.456
Low [Chain 1]	2402	0.463
Middle [Chain 1]	2441	0.457
High [Chain 1]	2480	0.457




4.1.4 Trace data


Channel Low [Chain 0]



Channel Middle [Chain 0]




Channel High [Chain 0]







Channel Low [Chain 1]



Channel Middle [Chain 1]



Channel High [Chain 1]



4.2 Spurious Emissions - Radiated -

4.2.1 Measurement procedure

[FCC 15.205, 15.209, 15.249(a), (b), (c), (d), (e), 15.35(b), RSS-210 B.10(a), (b), RSS-Gen 8.9]

Test was applied by following conditions.

Test method	:	ANSI C63.10
Frequency range	:	9kHz to 25GHz
Test place	:	3m Semi-anechoic chamber
EUT was placed on	:	Styrofoam table / (W)1.0m x (D)1.0m x (H)0.8m (below 1GHz) Styrofoam table / (W)0.6m x (D)0.6m x(H)1.5m (above 1GHz)
Antenna distance	:	3m
Test receiver setting	:	Below 1GHz
- Detector	:	Average (9kHz-90kHz, 110kHz-490kHz), Quasi-peak
- Bandwidth	:	200Hz, 120kHz
Spectrum analyzer setting	:	Above 1GHz
- Peak	:	RBW=1MHz, VBW=3MHz, Span=0Hz, Sweep=auto
- Average	:	Peak reading + DCF


Average Measurement Setting [VBW]

mode	Duty Cycle (%)	T _{on} (us)	T _{off} (us)	1/T _{on} (kHz)	100ms Window	Duty cycle factor 20log (Dc %) (dB)
ANT+	7.87	156	1827	6.410	50	-22.16

Radiated emission measurements are performed at 3m distance with the broadband antenna (Loop antenna, Biconical antenna, Log periodic antenna, Double ridged guide antenna and Broad-band horn Antenna). The antenna is positioned both the horizontal and vertical planes of polarization and height is varied 1m to 4m and stopped at height producing the maximum emission. As for the Loop antenna, it is positioned with its plane vertical, and the center of the Loop antenna is 1m above the ground plane.

The EUT is Placed on a turntable, which is 0.8m/1.5m above ground plane. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. The test results represent the worst case emission for each emission with manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation. Sufficient time for the EUT, support equipment, and test equipment are allowed in order for them to warm up to their normal operating condition.

- Test configuration



4.2.2 Calculation method

[9kHz to 150kHz]

Emission level = Reading + (Ant factor + Cable system loss)

Margin = Limit – Emission level

[150kHz to 25GHz]

Emission level = Reading + (Ant factor + Cable system loss - Amp. Gain)

Margin = Limit – Emission level

Example:

Limit @ 4804.0MHz : 74.0dBuV/m (Peak Limit)

S.A Reading = 39.9dBuV Cable system loss = 8.3dB

Result = 39.9 + 8.3 = 48.2dBuV/m

Margin = 74.0 - 48.2 = 25.8dB

4.2.3 Limit

Fundamental Frequency [MHz]	Field strength of fundamental		Field strength of harmonics		Distance [m]
	[mV/m]	[dBuV/m]	[mV/m]	[dBuV/m]	
2400-2483.5	50	20logE [uV/m]	500	20logE [uV/m]	3

Frequency [MHz]	Field strength		Distance [m]
	[uV/m]	[dBuV/m]	
0.009-0.490	2400 / F [kHz]	20logE [uV/m]	300
0.490-1.705	24000 / F [kHz]	20logE [uV/m]	30
1.705-30	30	29.5	30
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level [dBuV/m] = 20log Emission [uV/m]
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition modulation.



Japan

4.2.4 Test data

Date : 26-June-2023
Temperature : 23.5 [°C]
Humidity : 62.2 [%]
Test place : 3m Semi-anechoic chamber

Test engineer : Chiaki Kanno

Date : 27-June-2023
Temperature : 23.5 [°C]
Humidity : 62.2 [%]
Test place : 3m Semi-anechoic chamber

Test engineer : Chiaki Kanno

Date : 29-June-2023
Temperature : 23.5 [°C]
Humidity : 62.2 [%]
Test place : 3m Semi-anechoic chamber

Test engineer : Chiaki Kanno

Channel Low Peak

(P)	Frequency [MHz]	Reading [dB μ V/m]	c.f [dB(1/m)]	Duty cycle factor [dB(1/m)]	Result [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
H	2402	93.9	6.4	-	100.3	114	13.7
V	2402	87.1	6.4	-	93.5	114	20.5
H	4804	49.8	10.7	-	60.5	74	13.5

Average

(P)	Frequency [MHz]	Reading [dB μ V/m]	c.f [dB(1/m)]	Duty cycle factor [dB(1/m)]	Result [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
H	2402	93.9	6.4	20.0	80.3	94	13.7
V	2402	87.1	6.4	20.0	73.5	94	20.5
H	4804	49.8	10.7	20.0	40.5	54	13.5

Channel Middle Peak

(P)	Frequency [MHz]	Reading [dB μ V/m]	c.f [dB(1/m)]	Duty cycle factor [dB(1/m)]	Result [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
H	2441	94.4	6.7	-	101.1	114	12.9
V	2441	86.3	6.7	-	93	114	21
H	4882	49.6	11	-	60.6	74	13.4

Average

(P)	Frequency [MHz]	Reading [dB μ V/m]	c.f [dB(1/m)]	Duty cycle factor [dB(1/m)]	Result [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
H	2441	94.4	6.7	20.0	81.1	94	12.9
V	2441	86.3	6.7	20.0	73.0	94	21.0
H	4882	49.6	11.0	20.0	40.6	54	13.4

Channel High Peak

(P)	Frequency [MHz]	Reading [dB μ V/m]	c.f [dB(1/m)]	Duty cycle factor [dB(1/m)]	Result [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
H	2480	95.0	6.9	-	101.9	114	12.1
V	2480	85.1	6.9	-	92.0	114	22.0
H	4960	49.7	11.5	-	61.2	74	12.8

Average

(P)	Frequency [MHz]	Reading [dB μ V/m]	c.f [dB(1/m)]	Duty cycle factor [dB(1/m)]	Result [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
H	2480	95.0	6.9	20.0	81.9	94	12.1
V	2480	85.1	6.9	20.0	72.0	94	22.0
H	4960	49.7	11.5	20.0	41.2	54	12.8


Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.
3. No emission was detected in the receive mode.

[Transmission mode]
Channel: Low
BELOW 1 GHz(Worst)

Company name : KYOCERA Corporation
 EUT : Mobile Phone
 Model No. : EB1157
 Serial No. : N/A
 Test mode : ANT+_Tx_CH:Low

Sheet No. : 04
 Standard : FCC Part15 subpart C
 Operator : T.Seino
 Temp,Hum,Atm : 22.8 [° C], 67.8 [%]
 Note1 :



Final Result

Note:


1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 30MHz at the 3 meters distance.



**Channel: Low
ABOVE 1 GHz**

Company name : KYOCERA Corporation
 EUT : Mobile Phone
 Model No. : EB1157
 Serial No. : N/A
 Test mode : ANT+_Tx_Ch:Low

Standard : FCC Part.15 subpart C
 Operator : C.Kanno
 Temp,Hum,Atm : 22.8 [°C] 55.0 [%]
 Note1 :
 Note2 :



Final Result

No.	Frequency [MHz]	Pol	Reading PK [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	2402.000	H	93.9	6.4	100.3	114.0	13.7	100.0	86.0	
2	2402.000	V	87.1	6.4	93.5	114.0	20.5	388.0	348.0	
3	4804.000	H	49.8	10.7	60.5	74.0	13.5	155.0	321.0	

Note:


1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.



**Channel: Middle
ABOVE 1 GHz**

Company name : KYOCERA Corporation
 EUT : Mobile Phone
 Model No. : EB1157
 Serial No. : N/A
 Test mode : ANT+_Tx_Ch:Mid

Standard : FCC Part.15 subpart C
 Operator : C.Kanno
 Temp,Hum,Atm : 23.3 [°C] 58.7 [%]
 Note1 :
 Note2 :



Final Result

No.	Frequency [MHz]	Pol	Reading PK [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	2441.000	H	94.4	6.7	101.1	114.0	12.9	100.0	78.0	
2	2441.000	V	86.3	6.7	93.0	114.0	21.0	363.0	215.0	
3	4882.000	H	49.6	11.0	60.6	74.0	13.4	158.0	297.0	

Note:


1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.



**Channel: High
ABOVE 1 GHz**

Company name : KYOCERA Corporation
 EUT : Mobile Phone
 Model No. : EB1157
 Serial No. : N/A
 Test mode : ANT+_Tx_Ch:High

Standard : FCC Part.15 subpart C
 Operator : C.Kanno
 Temp,Hum,Atm : 23.3 [°C] 58.7 [%]
 Note1 :
 Note2 :



Final Result

No.	Frequency [MHz]	Pol	Reading PK [dB(μV)]	c. f [dB(1/m)]	Result PK [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	2480.000	H	95.0	6.9	101.9	114.0	12.1	100.0	79.0	
2	2480.000	V	85.1	6.9	92.0	114.0	22.0	100.0	239.0	
3	4960.000	H	49.7	11.5	61.2	74.0	12.8	170.0	231.0	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

4.3 Restricted Band of Operation

4.3.1 Measurement procedure

[FCC 15.205, 15.209, 15.249(c), (d), RSS-210 B.10(b)]

Test was applied by following conditions.

Test method : ANSI C63.10
 Test place : 3m Semi-anechoic chamber
 EUT was placed on : Styrofoam table / (W)0.6m x (D)0.6m x(H)1.5m
 Antenna distance : 3m

Spectrum analyzer setting
 - Peak : RBW=1MHz, VBW=3MHz, Span=Arbitrary setting, Sweep=auto
 - Average : RBW=1MHz, VBW=10kHz, Span=Arbitrary setting, Sweep=auto
 Display mode=Linear


Average Measurement Setting [VBW]

mode	Duty Cycle (%)	T _{on} (us)	T _{off} (us)	1/T _{on} (kHz)	Determined VBW Setting
ANT+	7.87	156	1827	6.410	10kHz

Radiated emission measurements are performed at 3m distance with the broadband antenna (Double ridged guide antenna). The antenna is positioned both the horizontal and vertical planes of polarization and height is varied 1m to 4m and stopped at height producing the maximum emission.

The EUT is Placed on a turntable, which is 1.5m above ground plane. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. The test results represent the worst case emission for each emission with manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation. Sufficient time for the EUT, support equipment, and test equipment are allowed in order for them to warm up to their normal operating condition.

- Test configuration





4.3.2 Limit

Emission at the boundary of the restricted band provided by 15.205 shall be lower than 15.209 limit.

4.3.3 Measurement result

Channel	Frequency [MHz]	Results Chart	Result
Low	2402	See the Trace Data	Pass
High	2480	See the Trace Data	Pass

4.3.4 Test data

Date : 29-June-2023

Temperature : 22.8 [°C]

Humidity : 67.8 [%]


Test place : 3m Semi-anechoic chamber

Test engineer :


Chiaki Kanno




**Channel: Low
Horizontal
Peak**




Average



**Vertical
Peak**




Average







**Channel: High
Horizontal
Peak**




Average



**Vertical
Peak**



Average



4.4 AC Power Line Conducted Emissions

4.4.1 Measurement procedure

[FCC 15.207, RSS-Gen 8.8]

Test was applied by following conditions.


Test method	: ANSI C63.10
Frequency range	: 0.15 MHz to 30 MHz
Test place	: 3 m Semi-anechoic chamber
EUT was placed on	: FRP table / (W)2.0 m × (D)1.0 m × (H)0.8 m
Vertical Metal Reference Plane	: (W)2.0 m × (H)2.0 m 0.4 m away from EUT
Test receiver setting	
- Detector	: Quasi-peak, Average
- Bandwidth	: 9 kHz

EUT and peripherals are connected to 50Ω/50μH Line Impedance Stabilization Network (LISN) which are connected to reference ground plane, and are placed 80cm away from EUT. Excess of AC power cable is bundled in center.

LISN for peripheral is terminated in 50Ω.

EUT operating mode is selected to emit the maximum noise. Overall frequency range is investigated with spectrum analyzer using peak detector. Maximum emission configuration is determined by manipulating the EUT, peripherals, interconnecting cables. Then, emission measurements are performed with test receiver in above setting to each current-carrying conductor of the mains port. Sufficient time for EUT, peripherals and test equipment is provided in order for them to warm up to their normal operating condition. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits.

- Test configuration



4.4.2 Calculation method

Emission level = Reading + (LISN. Factor + Cable system loss)

Margin = Limit – Emission level

Example:

Limit @ 6.770 MHz : 60.0 dB μ V(Quasi-peak)

: 50.0 dB μ V(Average)

(Quasi peak) Reading = 41.2 dB μ V c.f = 10.3 dB

Emission level = 41.2 + 10.3 = 51.5 dB μ V

Margin = 60.0 – 51.5 = 8.5 dB

(Average) Reading = 35.0 dB μ V c.f = 10.3 dB

Emission level = 35.0 + 10.3 = 45.3 dB μ V

Margin = 50.0 – 45.3 = 4.7 dB

4.4.3 Limit

Frequency [MHz]	Limit	
	QP [dBuV]	AV [dBuV]
0.15-0.5	66-56*	56-46*
0.5-5	56	46
5-30	60	50

*: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.




4.4.4 Test data

Date : 30-June-2023
 Temperature : 23.5 [°C]
 Humidity : 62.2 [%]
 Test place : 3m Semi-anechoic chamber

Test engineer : Chiaki Kanno

Company name : KYOCERA Corporation
 EUT : Mobile Phone
 Model No. : EB1157
 Serial No. : N/A
 Test mode : ANT_Tx

Standard : FCC Part 15 Subpart C
 Operator : C.Kanno
 Temp,Hum,Atm : 23.5 [°C], 62.2 [%]
 Note1 :
 Note2 :



Final Result

--- L1 ---

No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading CAV [dB(μV)]	c. f [dB]	Result QP [dB(μV)]	Result CAV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin CAV [dB]
1	0.154	26.3	7.2	10.5	36.8	17.7	65.8	55.8	29.0	38.1
2	0.689	29.5	20.4	10.3	39.8	30.7	56.0	46.0	16.2	15.3
3	1.058	19.5	10.7	10.4	29.9	21.1	56.0	46.0	26.1	24.9
4	4.966	20.5	7.4	10.7	31.2	18.1	56.0	46.0	24.8	27.9
5	5.645	19.2	5.7	10.7	29.9	16.4	60.0	50.0	30.1	33.6
6	7.216	17.4	6.6	10.9	28.3	17.5	60.0	50.0	31.7	32.5

--- L2 ---

No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading CAV [dB(μV)]	c. f [dB]	Result QP [dB(μV)]	Result CAV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin CAV [dB]
1	0.154	27.0	8.1	10.5	37.5	18.6	65.8	55.8	28.3	37.2
2	0.693	29.8	21.0	10.3	40.1	31.3	56.0	46.0	15.9	14.7
3	1.058	17.5	11.0	10.3	27.8	21.3	56.0	46.0	28.2	24.7
4	4.450	17.8	6.5	10.6	28.4	17.1	56.0	46.0	27.6	28.9
5	5.671	21.8	7.2	10.7	32.5	17.9	60.0	50.0	27.5	32.1
6	8.252	16.6	7.7	11.0	27.6	18.7	60.0	50.0	32.4	31.3



Japan





5 Antenna requirement

According to FCC section 15.203, an intentional radiator shall be designed to ensure that no antenna other than furnished by the responsible party shall be used with the device. The antenna is a special antenna mounted inside of the EUT. Therefore, the EUT complies with the antenna requirement of FCC section 15.203.

6 Measurement Uncertainty

Expanded uncertainties stated are calculated with a coverage Factor $k=2$.
 Please note that these results are not taken into account when measurement uncertainty considerations contained in ETSI TR 100 028 Parts 1 and 2 determining compliance or non-compliance with test result.

Test item	Measurement uncertainty
Conducted emission, AMN (9 kHz – 150 kHz)	± 3.7 dB
Conducted emission, AMN (150 kHz – 30 MHz)	± 3.3 dB
Radiated emission (9 kHz – 30 MHz)	± 3.8 dB
Radiated emission (30 MHz – 1000 MHz)	± 5.4 dB
Radiated emission (1 GHz – 6 GHz)	± 4.6 dB
Radiated emission (6 GHz – 18 GHz)	± 4.7 dB
Radiated emission (18 GHz – 40 GHz)	± 6.4 dB
Radio Frequency	$\pm 1.3 \cdot 10^{-8}$
RF power, conducted	± 0.7 dB
Adjacent channel power	± 1.5 dB
Temperature	± 0.6 °C
Humidity	± 1.2 %
Voltage (DC)	± 0.4 %
Voltage (AC, <10kHz)	± 0.2 %

Judge	Measured value and standard limit value
PASS	Case1  <p>Standard limit value</p> <p>+Uncertainty -Uncertainty</p> <p>Measured value</p> <p>Even if it takes uncertainty into consideration, a standard limit value is fulfilled.</p>
	Case2  <p>Although measured value is in a standard limit value, a limit value won't be fulfilled if uncertainty is taken into consideration.</p>
FAIL	Case3  <p>Although measured value exceeds a standard limit value, a limit value will be fulfilled if uncertainty is taken into consideration.</p>
	Case4  <p>Even if it takes uncertainty into consideration, a standard limit value isn't fulfilled.</p>



Japan

7 Laboratory Information

Testing was performed and the report was issued at:

TÜV SÜD Japan Ltd. Yonezawa Testing Center

Address: 5-4149-7 Hachimanpara, Yonezawa-shi, Yamagata, 992-1128 Japan

Phone: +81-238-28-2881

Accreditation and Registration

A2LA

Certificate #3686.03

VLAC

Accreditation No.: VLAC-013

BSMI

Laboratory Code: SL2-IN-E-6018, SL2-A1-E-6018

Innovation, Science and Economic Development Canada

ISED#: 4224A

VCCI Council

Registration number: A-0166

Appendix A. Test Equipment

Antenna port conducted test

Equipment	Company	Model No.	Serial No.	Cal. Due	Cal. Date
Spectrum analyzer	Agilent Technologies	E4440A	US44302655	30-Sep-2023	05-Sep-2022
Attenuator	HUBER+SUHNER	6810.19.A	N/A(S450)	31-Dec-2023	19-Dec-2022

Radiated emission

Equipment	Company	Model No.	Serial No.	Cal. Due	Cal. Date
EMI receiver	ROHDE&SCHWARZ	ESW44	103171	30-Sep-2023	20-Sep-2022
Spectrum analyzer	ROHDE&SCHWARZ	FSV40	101731	31-Jul-2023	19-Jul-2022
Preamplifier	SONOMA	310	372170	30-Sep-2023	28-Sep-2022
Loop antenna	ROHDE&SCHWARZ	HFH2-Z2	100515	30-Apr-2024	21-Apr-2023
Attenuator	TOYO Connector	NA-PJ-6	N/A(S507)	31-Mar-2024	15-Mar-2023
Biconical antenna	Schwarzbeck	VHBB9124/BBA9106	1145	30-Jun-2023	28-Jun-2022
Log periodic antenna	Schwarzbeck	VUSLP9111B	346	30-Nov-2023	16-Nov-2022
Attenuator	TOYO Connector	NA-PJ-6/dB	N/A(S541)	30-Sep-2023	28-Sep-2022
Attenuator	TAMAGAWA.ELEC	CFA-10/3dB	N/A(S503)	31-Jul-2023	14-Jul-2022
Preamplifier	TSJ	MLA-100M18-B02-40	1929118	31-Dec-2023	22-Dec-2022
Attenuator	AEROFLEX	26A-10	081217-08	31-Dec-2023	19-Dec-2022
Double ridged guide antenna	ETS LINDGREN	3117	00052315	30-Jun-2024	22-Jun-2023
Attenuator	HUBER+SUHNER	6803.17.B	N/A(2340)	31-Dec-2023	22-Dec-2022
Double ridged guide antenna	A.H.Systems Inc.	SAS-574	469	31-Aug-2023	19-Aug-2022
Preamplifier	TSJ	MLA-1840-B03-35	1240332	31-Aug-2023	19-Aug-2022
Notch Filter	Micro-Tronics	BRM50702	G433	30-Sep-2023	28-Sep-2022
Microwave cable	HUBER+SUHNER	SUCOFLEX104/9m	800690/4	31-Oct-2023	26-Oct-2022
		SUCOFLEX104/1m	my24610/4	31-Dec-2023	19-Dec-2022
		SUCOFLEX104/9m	2001099/4	31-Dec-2023	22-Dec-2022
		SUCOFLEX104/1m	MY32976/4	31-Dec-2023	22-Dec-2022
		SUCOFLEX104/2m	SN MY28404/4	31-Dec-2023	19-Dec-2022
SUCOFLEX104/7m	41625/6	31-Dec-2023	22-Dec-2022		
PC	DELL	OPTIPLEX9010	00186-228-073-851	N/A	N/A
Software	TOYO Technica	ES10/RE-AJ	Ver.2021.10.001	N/A	N/A
Absorber	RIKEN	PPF30	N/A	N/A	N/A
3m Semi an-echoic Chamber	TOKIN	N/A	N/A(9002-NSA)	31-May-2024	28-May-2023
3m Semi an-echoic Chamber	TOKIN	N/A	N/A(9002-SVSWR)	31-May-2024	28-May-2023



Conducted emission at mains port

Equipment	Company	Model No.	Serial No.	Cal. Due	Cal. Date
EMI receiver	ROHDE&SCHWARZ	ESW44	103171	30-Sep-2023	20-Sep-2022
Attenuator	HUBER+SUHNER	6810.01.A	N/A (S411)	31-Dec-2023	20-Dec-2022
Line impedance stabilization network	Kyoritsu Electrical Works, Ltd.	TNW-407F2	12-17-110-2	30-Jun-2024	22-Jun-2023
Microwave cable	HUBER+SUHNER	SUCOFLEX104/5m	MY33601/4	31-Oct-2023	27-Oct-2022
Microwave cable	HUBER+SUHNER	SUCOFLEX104/2m	MY37268/4	31-Oct-2023	27-Oct-2022
Coaxial cable	HUBER+SUHNER	RG214/U/10m	N/A (S194)	31-Dec-2023	22-Dec-2022
PC	DELL	OPTIPLEX9010	00186-228-073-851	N/A	N/A
Software	TOYO Technica	ES10/RE-AJ	Ver.2021.10.001	N/A	N/A

*: The calibrations of the above equipment are traceable to NIST or equivalent standards of the reference organizations.

Appendix B. Duty Cycle

[Plot & Calculation]



Duty Cycle Factor Calculation

RF duty cycle factor: Calculation according to RF burst Para 15.35 (c)

Pulse width is 0.156ms

There are 50 pulses in 100ms window

$0.155\text{ms} \times 50 = 7.8\text{ms}$, It is 7.8ms in 100ms

Duty cycle: $7.8/100 = 0.078$

Duty cycle factor: $20\log(0.078) = -22.16\text{dB}$

Maximum is used duty cycle according to Para 15.35 (b): 20dB