



Zacta

TEST REPORT

Report number : Z071C-13469

Issue date : December 27, 2013

The device, as described herewith, was tested pursuant to applicable test procedure and complies with the requirements of;

FCC Part15 Subpart E

The test results are traceable to the international or national standards.

Applicant	: KYOCERA Corporation
Equipment under test (EUT)	: Mobile Phone
Model number	: KYY22
FCC ID	: JOYKYY22

Date of test : December 17, 20, 21, 2013
 Test place : TÜV SÜD Zacta Ltd. Yonezawa Testing Center
 4149-7 Hachimanpara 5-chome
 Yonezawa-shi Yamagata 992-1128 Japan
 Phone: +81-238-28-2880 Fax: +81-238-28-2888
 Test results : Complied

The results in this report are applicable only to the equipment tested.
 This report shall not be re-produced except in full without the written approval of TÜV SÜD Zacta Ltd.
 This test report must not be used by client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Tested by : Taiki Watanabe
 Taiki Watanabe

Authorized by : Hiroaki Suzuki
 Hiroaki Suzuki
 Manager of EMC Technical Department



Table of contents

	Page
1. Summary of Test	3
1.1 Purpose of test	3
1.2 Standards	3
1.3 List of applied test to the EUT	3
1.4 Modification to the EUT by laboratory	3
2. Equipment Under Test	4
2.1 General Description of equipment	4
2.2 EUT information	4
2.3 Variation of the family model(s)	5
2.4 Operating channels and frequencies	5
2.5 Description of Test mode	6
2.6 Operating mode	6
3. Configuration of equipment	7
3.1 Equipment(s) used	7
3.2 System configuration	7
4. Radiated Emissions (Restricted Bands of Operation)	8
4.1 Measurement procedure	8
4.2 Calculation method	9
4.3 Limit	9
4.4 Test data	10
5. Antenna requirement	13
6. Uncertainty of measurement	14
7. Laboratory description	15
Appendix A. Test equipment	16

1. Summary of Test

1.1 Purpose of test

It is the original test in order to verify conformance to FCC Part 15 Subpart E.

1.2 Standards

CFR47 FCC Part 15 Subpart E

1.2.1 Test Methods

ANSI C63.4-2003, KDB789033

1.2.2 Deviation from standards

None

1.3 List of applied test to the EUT

Test items Section	Test items	Condition	Result
15.407(d) 15.205 15.209	Radiated emissions (Restricted Bands of Operation)	Radiated	PASS

*: Conducted test was to proceed at FCCID:JOYKYY21.
FCCID:JOYKYY22 was measured by applying only Radiated test.

1.3.1 Test set up

Table-Top

1.4 Modification to the EUT by laboratory

None



Zacta

2. Equipment Under Test

2.1 General Description of equipment

EUT is the Mobile Phone.

2.2 EUT information

Applicant	:	KYOCERA Corporation Yokohama Office 2-1-1 Kagahara, Tsuzuki-ku Yokohama-shi, Kanagawa, Japan Phone: +81-45-943-6253 Fax: +81-45-943-6314
Equipment under test	:	Mobile Phone
Trade name	:	Kyocera
Model number	:	KYY22
Serial number	:	N/A
EUT condition	:	Pre-Production
Max. frequency	:	1.5GHz
Power ratings	:	Battery: DC 3.8V
Size	:	(W) 65.0 × (D) 11.0 × (H) 134.0 mm
Environment	:	Indoor and Outdoor use
Terminal limitation	:	-20°C to 60°C
RF Specification Protocol	:	IEEE802.11a, IEEE802.11n (HT20), IEEE802.11n (HT40)
Frequency range	:	IEEE802.11a/n (HT20): 5180MHz-5320MHz, 5500MHz-5700MHz IEEE802.11n (HT40): 5190MHz-5310MHz, 5510MHz-5670MHz
Number of RF Channels	:	IEEE802.11a/n (HT20): 16 Channels IEEE802.11n (HT40): 7 Channels
Modulation type	:	IEEE802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Data rate	:	IEEE802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE802.11n (HT20 LGI): 6.5, 13, 19.5, 26, 39, 52, 58.5, 65Mbps IEEE802.11n (HT20 SGI): 7.2, 14.4, 21.7, 28.9, 43.3, 57.8, 65, 72.2Mbps IEEE802.11n (HT40 LGI): 13.5, 27, 40.5, 54, 81, 108, 121.5, 135Mbps IEEE802.11n (HT40 LGI): 15, 30, 45, 60, 90, 120, 135, 150Mbps
Channel separation	:	IEEE802.11a/n (HT20): 20MHz IEEE802.11n (HT40): 40MHz
Antenna type	:	Internal antenna
Antenna gain	:	0dBi



2.3 Variation of the family model(s)

Not applicable

2.4 Operating channels and frequencies

[IEEE802.11a/n (HT20)]

Channel	Frequency [MHz]
36	5180
40	5200
44	5220
48	5240
52	5260
56	5280
60	5300
64	5320
100	5500
104	5520
108	5540
112	5560
116	5580
132	5660
136	5680
140	5700

[IEEE802.11n (HT40)]

Channel	Frequency [MHz]
38	5190
46	5230
54	5270
62	5310
102	5510
110	5550
134	5670

2.5 Description of Test mode

The EUT had been tested under operating condition.
There are three channels have been tested as following:

Band	IEEE802.11a/n (HT20)		IEEE802.11n (HT40)	
	Channel	Frequency [MHz]	Channel	Frequency [MHz]
5.2GHz Band	36	5180	38	5190
	40	5200	-	-
	48	5240	46	5230
5.3GHz Band	52	5260	54	5270
	56	5280	-	-
	64	5320	62	5310
5.6GHz Band	100	5500	102	5510
	116	5580	110	5550
	140	5700	134	5670

The pre-test has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates.

Band	Modulation Type	Data Rate
5.2GHz Band	IEEE802.11a: OFDM	6Mbps
	IEEE802.11n (HT20): OFDM	MCS0
	IEEE802.11n (HT40): OFDM	MCS0
5.3GHz Band	IEEE802.11a: OFDM	6Mbps
	IEEE802.11n (HT20): OFDM	MCS0
	IEEE802.11n (HT40): OFDM	MCS0
5.6GHz Band	IEEE802.11a: OFDM	6Mbps
	IEEE802.11n (HT20): OFDM	MCS0
	IEEE802.11n (HT40): OFDM	MCS0

The field strength of spurious emissions was measured at each position of all three axis X, Y and Z to compare the level, and the maximum noise.

The worst emission was found in Z axis and the worst case recorded.

2.6 Operating mode

[Tx mode]

- i) Test program setup to the DM tool
- ii) Select a Test mode
Operating frequency: 5.2GHz Band, 5.3GHz Band, 5.6GHz Band
- iii) Start test mode

[Rx mode]

- i) Test program setup to the DM tool
- ii) Select a Test mode
Operating frequency: 5.2GHz Band, 5.3GHz Band, 5.6GHz Band
- iii) Start test mode



Zacta

3. Configuration of equipment

3.1 Equipment(s) used

No.	Equipment	Company	Model No.	Serial No.	FCC ID / DoC	Comment
1	Mobile Phone	KYOCERA	KYY22	N/A	JOYKYY22	EUT

3.2 System configuration

1. Mobile Phone
(EUT)

Note1: Numbers assigned to equipment or cables on this diagram correspond to the list in "3.1 Equipment(s) used".

4. Radiated Emissions (Restricted Bands of Operation)

4.1 Measurement procedure

[FCC 407(d), 15.205, 15.209, KDB789033]

Test was applied by following conditions.

Frequency range	:	30MHz to 40GHz
Test place	:	3m Semi-anechoic chamber
EUT was placed on	:	FRP table / (W)2.0m × (D)1.0m × (H)0.8m
Antenna distance	:	3m
Test receiver setting	:	Below 1GHz
- Detector	:	Quasi-peak
- Bandwidth	:	120kHz
Spectrum analyzer setting	:	Above 1GHz
- Peak	:	RBW=1MHz, VBW=1MHz, Span=0Hz, Sweep=auto
- Average	:	RBW=1MHz, VBW=10Hz, Span=0Hz, Sweep=auto
	:	Display mode=Linear

Radiated emission measurements are performed at 3m distance with the broadband antenna (Biconical antenna, Log periodic antenna and Double ridged guide antenna). The antenna is positioned both the horizontal and vertical planes of polarization and height is varied 1m to 4m and stopped at height producing the maximum emission.

The EUT is Placed on a turntable, which is 0.8m above ground plane. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. The test results represent the worst case emission for each emission with manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation. Sufficient time for the EUT, support equipment, and test equipment are allowed in order for them to warm up to their normal operating condition.


The EUT was set to operate with following conditions.

- 5.2GHz Band, 5.3GHz Band, 5.6GHz Band

The test mode of EUT is as follows.

- Tx mode, Rx mode

- Test configuration



4.2 Calculation method

Emission level = Reading + (Ant. factor + Cable system loss – Amp. Gain)

Margin = Limit – Emission level

4.3 Limit

- (1) For transmitters operating in the 5.15-5.25GHz band: all emissions outside of the 5.15-5.35GHz band shall not exceed an EIRP of -27dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35GHz band: all emissions outside of the 5.15-5.35GHz band shall not exceed an EIRP of -27dBm/MHz.
Devices operating in the 5.25-5.35GHz band that generate emissions in the 5.15-5.25GHz band must meet all applicable technical requirements for operation in the 5.15-5.25GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27dBm/MHz in the 5.15-5.25GHz band.
- (3) For transmitters operating in the 5.47-5.725GHz band: all emissions outside of the 5.47 5-5.725GHz band shall not exceed an EIRP of -27dBm/MHz.
- (4) For transmitters operating in the 5.725-5.825GHz band: all emissions within the frequency range from the band edge to 10MHz above or below the band edge shall not exceed an EIRP of -17dBm/MHz; for frequencies 10MHz or greater above or below the band edge, emissions shall not exceed an EIRP of -27dBm/MHz.

Frequency [MHz]	Field strength		Distance [m]
	[uV/m]	[dBuV/m]	
0.009-0.490	2400 / F [kHz]	20logE [uV/m]	300
0.490-1.705	24000 / F [kHz]	20logE [uV/m]	30
1.705-30	30	29.5	30
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	300	54.0	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level [dBuV/m] = 20log Emission [uV/m]
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition modulation.



Zacta

4.4 Test data

Date : Dec. 17, 2013 Test personnel :
 Temperature : 23.6 [°C]
 Humidity : 22.6 [%] Tested by :
 Test place : 3m Semi-anechoic chamber Taiki Watanabe

Date : Dec. 20, 2013 Test personnel :
 Temperature : 21.1 [°C]
 Humidity : 23.6 [%] Tested by :
 Test place : 3m Semi-anechoic chamber Taiki Watanabe

Date : Dec. 21, 2013 Test personnel :
 Temperature : 21.1 [°C]
 Humidity : 23.4 [%] Tested by :
 Test place : 3m Semi-anechoic chamber Taiki Watanabe

[IEEE802.11a] (5.2GHz Band)

Mode	Channel	Frequency (MHz)	Frequency (MHz)	ANT H/V	Detector PK/AV	Reading (dBμV)	C.F (dB)	DCF (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11a	36	5180	10360.00	V	PK	42.2	18.5		60.7	68.2	7.5
			5147.52	V	PK	46.5	9.9		56.4	74.0	17.6
	40	5200	5147.52	V	AV	33.4	9.9	0.09	43.4	54.0	10.6
			10400.00	V	PK	42.1	18.6		60.7	68.2	7.5
	48	5240	10480.00	V	PK	43.6	18.7		62.3	68.2	5.9

(5.3GHz Band)

Mode	Channel	Frequency (MHz)	Frequency (MHz)	ANT H/V	Detector PK/AV	Reading (dBμV)	C.F (dB)	DCF (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11a	52	5260	10520.00	V	PK	42.8	18.8		61.6	68.2	6.6
	56	5280	10560.00	V	PK	41.8	18.9		60.7	68.2	7.5
	64	5320	10640.00	V	PK	42.7	19.0		61.7	74.0	12.3

(5.6GHz Band)

Mode	Channel	Frequency (MHz)	Frequency (MHz)	ANT H/V	Detector PK/AV	Reading (dBμV)	C.F (dB)	DCF (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11a	100	5500	5447.55	V	PK	48.5	10.4		58.9	74.0	15.1
			5447.55	V	AV	38.3	10.4	0.09	48.8	54.0	5.2
			11000.00	V	PK	40.7	19.8		60.5	68.2	7.7
	116	5580	11160.00	V	PK	41.9	19.8		61.7	68.2	6.5
			5726.11	V	PK	58.5	10.4		68.9	74.0	5.1
	140	5700	5726.11	V	AV	35.2	10.4	0.09	45.7	54.0	8.3
			11400.00	V	PK	41.1	20.3		61.4	68.2	6.8

Note:

- Emission Level (Margin) = Limit - [Reading + C.F (Antenna + Cable – Amp)] + DCF (If transmit duty cycle < 98 percent)
- DCF = 20log (1/x), x = On time / (On + Off time)
- No emission were detected in frequency range 30MHz to 1000MHz at the 3 meters distance.
- No emission was detected in the receive mode.

[IEEE802.11n (HT20)]**(5.2GHz Band)**

Mode	Channel	Frequency (MHz)	Frequency (MHz)	ANT H/V	Detector PK/AV	Reading (dBμV)	C.F (dB)	DCF (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11n (20MHz)	36	5180	5128.18	V	PK	47.0	9.9		56.9	74.0	17.1
			5128.18	V	AV	35.0	9.9	0.09	45.0	54.0	9.0
			10360.00	V	PK	44.4	18.5		62.9	68.2	5.3
	40	5200	5147.96	V	PK	47.4	9.9		57.3	74.0	16.7
			5147.96	V	AV	35.6	9.9	0.09	45.6	54.0	8.4
			10400.00	V	PK	42.1	18.6		60.7	68.2	7.5
48	5240	10480.00	V	PK	42.9	18.7		61.6	68.2	6.6	

(5.3GHz Band)

Mode	Channel	Frequency (MHz)	Frequency (MHz)	ANT H/V	Detector PK/AV	Reading (dBμV)	C.F (dB)	DCF (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11n (20MHz)	52	5260	10520.00	V	PK	41.4	18.8		60.2	68.2	8.0
	56	5280	10560.00	V	PK	41.9	18.9		60.8	68.2	7.4
	64	5320	5372.00	V	PK	47.0	10.3		57.3	74.0	16.7
			5372.00	V	AV	34.7	10.3	0.09	45.1	54.0	8.9
			10640.00	V	PK	42.2	19.0		61.2	68.2	7.0

(5.6GHz Band)

Mode	Channel	Frequency (MHz)	Frequency (MHz)	ANT H/V	Detector PK/AV	Reading (dBμV)	C.F (dB)	DCF (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11n (20MHz)	100	5500	5447.90	V	PK	48.2	10.4		58.6	74.0	15.4
			5447.90	V	AV	36.4	10.4	0.09	46.9	54.0	7.1
			11000.00	V	PK	41.1	19.8		60.9	68.2	7.3
	116	5580	11160.00	V	PK	42.4	19.8		62.2	68.2	6.0
	140	5700	5726.11	V	PK	60.5	10.4		70.9	74.0	3.1
			5726.11	V	AV	36.0	10.4	0.09	46.5	54.0	7.5
11400.00			V	PK	40.7	21.0		61.7	68.2	6.5	

Note:

1. Emission Level (Margin) = Limit - [Reading + C.F (Antenna + Cable – Amp)] + DCF (If transmit duty cycle < 98 percent)
2. DCF = 20log (1/x) , x = On time / (On + Off time)
3. No emission were detected in frequency range 30MHz to 1000MHz at the 3 meters distance.
4. No emission was detected in the receive mode.

**[IEEE802.11n (HT40)]
(5.2GHz Band)**

Mode	Channel	Frequency (MHz)	Frequency (MHz)	ANT H/V	Detector PK/AV	Reading (dBμV)	C.F (dB)	DCF (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11n (40MHz)	38	5190	5148.92	V	PK	55.2	9.9		65.1	74.0	8.9
			5148.92	V	AV	32.1	9.9	0.05	42.1	54.0	12.0
			10380.00	V	PK	42.8	18.6		61.4	68.2	6.8
	46	5230	5145.05	V	PK	53.5	9.9		63.4	74.0	10.6
			5145.05	V	AV	30.1	9.9	0.05	40.1	54.0	14.0
			10460.00	V	PK	43.3	18.7		62.0	68.2	6.2

(5.3GHz Band)

Mode	Channel	Frequency (MHz)	Frequency (MHz)	ANT H/V	Detector PK/AV	Reading (dBμV)	C.F (dB)	DCF (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11n (40MHz)	54	5270	5149.30	V	PK	51.0	9.9		60.9	74.0	13.1
			5149.30	V	AV	29.9	9.9	0.05	39.9	54.0	14.2
			10540.00	V	PK	41.3	18.8		60.1	68.2	8.1
	62	5310	5351.30	V	PK	55.6	10.3		65.9	74.0	8.1
			5351.30	V	AV	30.6	10.3	0.05	41.0	54.0	13.1
			10620.00	V	PK	42.0	19.0		61.0	68.2	7.2

(5.6GHz Band)

Mode	Channel	Frequency (MHz)	Frequency (MHz)	ANT H/V	Detector PK/AV	Reading (dBμV)	C.F (dB)	DCF (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11n (40MHz)	102	5510	5467.18	V	PK	53.2	10.5		63.7	74.0	10.3
			5467.18	V	AV	32.3	10.5	0.05	42.9	54.0	11.2
			11020.00	V	PK	41.5	19.8		61.3	68.2	6.9
	110	5550	5469.00	V	PK	49.4	10.5		59.9	74.0	14.1
			5469.00	V	AV	29.8	10.5	0.05	40.4	54.0	13.7
			1110.00	V	PK	41.8	19.8		61.6	68.2	6.6
	134	5670	5728.32	V	PK	49.5	10.4		59.9	74.0	14.1
			5728.32	V	AV	29.6	10.4	0.05	40.1	54.0	14.0
			11340.00	V	PK	41.4	20.3		61.7	68.2	6.5

Note:

1. Emission Level (Margin) = Limit - [Reading + C.F (Antenna + Cable – Amp)] + DCF (If transmit duty cycle < 98 percent)
2. DCF = 20log (1/x) , x = On time / (On + Off time)
3. No emission were detected in frequency range 30MHz to 1000MHz at the 3 meters distance.
4. No emission was detected in the receive mode.



Zacta

5. Antenna requirement

According to FCC section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The antenna is a special antenna mounted inside of the EUT. Therefore, the EUT complies with the antenna requirement of FCC section 15.203.

6. Uncertainty of measurement

Expanded uncertainties stated are calculated with a coverage Factor $k=2$.

Please note that these results are not taken into account when determining compliance or non-compliance with test result.

Test item	Measurement uncertainty
Conducted emission at mains port	$\pm 3.0\text{dB}$
Radiated emission (9kHz – 30MHz)	$\pm 4.4\text{dB}$
Radiated emission (30MHz – 1000MHz)	$\pm 4.5\text{dB}$
Radiated emission (1000MHz – 26GHz)	$\pm 3.9\text{dB}$



Zacta

7. Laboratory description

1. Location:

TÜV SÜD Zacta Ltd. Yonezawa Testing Center
 4149-7 Hachimanpara 5-chome Yonezawa-shi Yamagata 992-1128 Japan
 Phone: +81-238-28-2880 Fax: +81-238-28-2888

2. Facility filing information:

1) NVLAP accreditation: NVLAP Lab. code: 200306-0

2) VLAC accreditation: Lab. code: VLAC-013

Site name	Radiated emission	Conducted emission for mains port	Conducted emission for telecom port	Radiated emission (CMAD)	Expiry Date
3m Semi-anechoic chamber	VLAC-013	-	-	-	Jul. 3, 2015
10m Semi-anechoic chamber				VLAC-013	
Shielded room No.1	-	VLAC-013	-	-	

3) FCC filing:

Site name	Registration Number	Expiry Date
Site 2	91065	Oct.31, 2014
Site 3		
3m Semi-anechoic chamber	540072	Jan. 9, 2016
10m Semi-anechoic chamber		
Shielded room No.1		

4) Industry Canada Oats site filing:

Site name	Sites on file: Oats 3m/10m	Expiry Date
Site 2	4224A-2	Jan. 23, 2015
Site 3	4224A-3	
3m Semi-anechoic chamber	4224A-4	
10m Semi-anechoic chamber	4224A-5	

5) VCCI site filing:

Site name	Radiated emission	Conducted emission for mains port	Conducted emission for telecom port	Expiry Date
Site 2	R-137	C-133	T-1221	Nov. 16, 2014 Nov. 28, 2014* (*:Telecom port)
Site 3	R-138	C-134	T-1222	
3m Semi-anechoic chamber	-	A-0166	-	Jul. 3, 2015
10m Semi-anechoic chamber				
Shielded room No.1				

6) TÜV SÜD PS authorization:

Authorized as an EMC test laboratory

7) TÜV Rheinland authorization:

Authorized as an EMC test laboratory



Zacta

Appendix A. Test equipment

Radiated emission

Equipment	Company	Model No.	Serial No.	Cal. Due	Cal. Date
EMI Receiver	ROHDE&SCHWARZ	ECSI	100451	Nov. 2014	Nov. 16, 2013
Preamplifier	ANRITSU	MH648A	M96057	Jun. 2014	Jun. 12, 2013
Biconical antenna	Schwarzbeck	VHA9103/BBA9106	2155	May 2014	May 1, 2013
Log periodic antenna	Schwarzbeck	UHALP9108A	0560	May 2014	May 1, 2013
Attenuator	TME	CFA-01NPJ-6	N/A (S275)	Jun. 2014	Jun. 6, 2013
Attenuator	TME	CFA-01NPJ-3	N/A (S272)	Jun. 2014	Jun. 6, 2013
Spectrum analyzer	Agilent Technologies	E4440A	US4432655	May 2014	May 14, 2013
Preamplifier	Agilent Technologies	8449B	3008A1008	Dec. 2014	Dec. 9, 2013
Double ridged guide antenna	EMCO	3115	4328	Jan. 2014	Jan. 21, 2013
Attenuator	AEROFLEX	40A-03	081217-20	Feb. 2014	Feb. 23, 2013
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	BBHA9170189	May 2015	May 2, 2013
Preamplifier	TSJ	MLA-1840-B03-35	1240332	May 2015	May 2, 2013
Notch filter	Micro-Tronics	BRM50716	006	Jul. 2014	Jul. 12, 2013
Microwave cable	SUHNER	SUCOFLEX104/9m	322083/4	May 2014	May 14, 2013
		SUCOFLEX104/9m	346316/4	Oct. 2014	Oct. 6, 2013
		SUCOFLEX104/1m	322084/4	Oct. 2014	Oct. 6, 2013
		SUCOFLEX104/1.5m	317226/4	Oct. 2014	Oct. 6, 2013
		SUCOFLEX104/7m	41625/6	Oct. 2014	Oct. 6, 2013
PC	DELL	DIMENSION E521	75465BX	N/A	N/A
Software	TOYO Corporation	EP5/RE-AJ	0611193/V5.3.61	N/A	N/A
3m Semi-anechoic chamber	TOKIN	N/A	N/A (9002-NSA)	May 2014	May 6, 2013
3m Semi-anechoic chamber	TOKIN	N/A	N/A (9002-SVSWR)	May 2014	May 6, 2013

*: The calibrations of the above equipment are traceable to NIST or equivalent standards of the reference organizations.