


Attestation letter for FCCID: JOYYAKF-1

We hereby declares this device supports below information,

- a) Submit a channel/frequency plan for this device showing the channels that have active scanning or passive scanning. Active scanning is where the device can transmit a probe (beacon) and passive scanning is where the device is can listen only with no probes.
⇒ **Please refer to device description table on the attached page.**
- b) Verify that this device does not have ad-hoc mode
⇒ **Please refer to device description table on the attached page.**
- c) Can this device act as an access point on the non-DFS legacy frequencies (5.15-5.25 MHz)
⇒ **Please refer to device description table on the attached page.**
- d) For client devices that have software configuration control to operate in different modes (active scanning in some and passive scanning in others) in different bands (devices with multiple equipment classes or those that operate on non-DFS frequencies) or modular devices which configure the modes of operations through software, the application must provide software and operations description on how the software and / or hardware is implemented to ensure that proper operations modes cannot be modified by end user or an installer.
⇒ **Please refer to device description table on the attached page and for NII frequencies, this device can operate as a client only.**
The client software and associated drivers will not initiate any transmissions on DFS frequencies, which includes the transmissions for beacons, ad-hoc and peer-to-peer modes.
The software is locked by the manufacturer, so the settings cannot be changed or modified by the end user of the device.
- e) The Felica transmitter operation
⇒ **The Felica transmitter is disabled from operating in USA and cannot be enabled by any users. The Felica transmitter is only operated when Japanese system is connected.**

Sincerely,

Signature



Responsible Name

Yoshikazu Yamamoto

Title

Manager of Quality Assurance Dept.

Freq. (MHz)	CH.	Support IEEE802.11 and BW	Active Scan	Passive Scan	Client Only	DFS	Mobile Hop spot	Wi-Fi Direct	Peer to Peer	Ad-hoc	Radar Detection														
2412	1	802.11b/g/n(HT20) & BW = 20MHz	Yes	No	No	No	Yes	Yes	Yes	Yes	No														
2417	2																								
2422	3																								
2427	4																								
2432	5																								
2437	6																								
2442	7																								
2447	8																								
2452	9																								
2457	10																								
2462	11																								
5180	36	802.11a/n(HT20) & BW=20MHz	Yes	No	Yes	No	No	No	No	No	No														
5200	40																								
5220	44																								
5240	48																								
5260	52		802.11a/n(HT20) & BW=20MHz	No	Yes	Yes	Yes	No	No	No	No	No													
5280	56																								
5300	60																								
5320	64																								
5500	100			802.11a/n(HT20) & BW=20MHz	No	Yes	Yes	Yes	No	No	No	No	No												
5520	104																								
5540	108																								
5560	112																								
5580	116				802.11a/n(HT20) & BW=20MHz	N/A This device does not support these channel.																			
5600	120					802.11a/n(HT20) & BW=20MHz	No	Yes	Yes	Yes	No	No	No	No	No										
5620	124																								
5640	128																								
5660	132																								
5680	136	802.11a/n(HT20) & BW=20MHz					No	Yes	Yes	Yes	No	No	No	No	No										
5700	140																								
5190	38															802.11a/n(HT40) & BW=40MHz	Yes	No	Yes	No	No	No	No	No	No
5230	46																								
5270	54																								
5310	62		802.11a/n(HT40) & BW=40MHz				No	Yes	Yes	Yes	No	No	No	No	No										
5510	102																								
5550	110																								
5590	118			802.11a/n(HT40) & BW=40MHz			N/A This device does not support these channel.																		
5630	126						802.11a/n(HT40) & BW=40MHz	No	Yes	Yes	Yes	No	No	No	No		No								
5670	134																								
5670	134																								