



Unit Label

LUTRON®
Coopersburg, PA 18036 USA
RadioRA2
RRD-6CL
120 V~ 50 / 60 Hz

For control of permanently installed fixtures using Dimmable bulbs only. 150 W CFL/LED or 600 W Incandescent/Halogen.

Para instalaciones permanentes usando lámparas regulables solamente 150 W LFCA/LED ó 600 W Incandescente/Halogeno.

Pour installations permanentes montées avec des lampes à intensité variable seulement 150 W AFC/DEL ou 600 W Incandescent/Halogène

Pat./Brevets: 5,637,930; 5,798,581;
5,838,216; 5,848,054; 5,905,442; 5,982,103; 6,169,377;
6,687,487; 6,803,728; 6,969,959; 7,190,125; 7,365,282;
7,365,285; 7,408,525; 7,548,216; 7,719,817
FCC ID: J-PZ0092
Model/Modele: 6DCL IC: 2851A-JP Z0092

Pat./Brevets: 5,637,930; 5,798,581;
5,838,216; 5,848,054; 5,905,442; 5,982,103; 6,169,377;
6,687,487; 6,803,728; 6,969,959; 7,190,125; 7,365,282;
7,365,285; 7,408,525; 7,548,216; 7,719,817
FCC ID: J-PZ0092
Model/Modele: 6DCL IC: 2851A-JP Z0092

Unit Label