

50019898B

Shvole QS  
**PALLADIOM**

Model | Modelo | Modelé QSFC-EDU-BP-C  
 4.5-9.0 V== 5 W 6 in-lb (0,68 N•m)



IEC PELV/  
 NEC CLASS 2

**CE**  
**NOM**

This device complies with part 15 of the FCC Rules.  
 Operation is subject to the following conditions:

- (1) This device may not cause harmful interference, and  
 (2) This device must accept any interference received,  
 including interference that may cause undesired operation.

FCC ID : JP20137  
 IC: 2851A-JP20137  
 SCT: RCPLUS09-0944  
 HWN: RFB-A

Pol./Brevets:  
[betron.com/galients](http://betron.com/galients)



DAVEN INSTRUMENTS  
 CAN/US-100-1989-030

DIMENSIONS: 1.67" x 2.20" DR. # 3028

SHAPE: Special Shape

**PRODUCT INFORMATION**  
**THERMBlue SELECT® 21900**

**Product Description:**

THERMBlue SELECT 21900 is a UL-recognized CSA-accepted, 20-watt glow-in-the-dark emergency lighting device. This polymer-coated, self-assembling, pressure-curable reflector, and reflector with lens, please see:

- THERMBlue SELECT 21900: 2-hand glow-in-the-dark emergency lighting device designed for high performance, shock applications.
- 21900: Specialized emergency lighting device, often painted into steel and aluminum structural assemblies. Typical applications include: emergency lighting, exit signs, emergency preparedness, and location for lighting.
- 21900: Appropriate high performance pressure sensitive adhesive.
- 21900: 20-watt, standard 20-watt reflector lens.