



**BEC INCORPORATED**

**MAXIMUM PERMISSABLE EXPOSURE (MPE) REPORT**

**TEST STANDARDS:**

**U.S. Title 47 Chapter 1 Subchapter A Part 2 Subpart J**

**Lutron Models DS-5ANS / DVRF-5NS  
Vogelkop In-wall Lighting Switch**

**FCC ID: JPZ0140**

**REPORT# BEC-2197-02**

**CUSTOMER:**

**Lutron Electronics Company Incorporated  
7200 Suter Road  
Coopersburg, PA 18036**

**PREPARED BY:** \_\_\_\_\_

*Paul Banker*  
Paul Banker, Test Engineer

**REVIEWED and APPROVED BY:** \_\_\_\_\_

*Steve Fanella*  
Steve Fanella, Quality Manager

The results described in this report relate only to the item(s) tested. This document shall not be reproduced except in full without prior written permission of BEC Incorporated





## TABLE OF CONTENTS

<b>Notice To Customer .....</b>	<b>3</b>
<b>Revision History .....</b>	<b>3</b>
<b>1.0 Administrative Information.....</b>	<b>4</b>
1.1 General Information Table .....	4
1.2 Maximum Permissible Exposure Calculation .....	5
1.3 Maximum Permissible Exposure (MPE) 04/25/2022 .....	7



## Notice To Customer

This report and any recommendations it contains represent the result of BEC's testing and assessment on behalf of your company. Testing has been conducted according to accepted engineering standards and practices. This report reflects testing and assessment of product samples provided by your company and may not reflect the characteristics of other samples, especially those produced at different times. Therefore this report and its findings and recommendations, if implemented, should not be construed as an assurance or implied warranty for the continuing electromagnetic compatibility (EMC) of the product. **BEC shall not be liable for incidental or consequential damages, even if advised of the possibility thereof.**

BEC will not disseminate this report to other parties without your express permission. You may reproduce this report in its entirety including this notice and the entireties of any supplemental test reports on the same product (e.g. reports on additional testing following modification). However 'you may not reproduce portions of the report (except for the entirety of the summary section) or quote from it for any purpose without specific prior written permission from BEC'.

## Revision History

Revision #	Description of Changes	Date of Changes	Date Released
0	Test Report Initial Release	N/A	04/25/2022



## 1.0 Administrative Information

### 1.1 General Information Table

<b>Project Number</b>	BEC-2197
<b>Manufacturer</b>	Lutron Electronics
<b>Model Numbers Tested</b>	DS-5ANS / DVRF-5NS
<b>EUT Sample Type</b>	FCC Test Code Radiated Sample
<b>EUT Serial Number</b>	030A5E8
<b>EUT Sample Number</b>	2197-01
<b>EUT Firmware Version</b>	2.01
<b>Frequency of Operation</b>	431 MHz to 437 MHz
<b>Antenna Gain</b>	-14.85 dBi
<b>Antenna Type</b>	Loop
<b>Modulation</b>	FSK
<b>FCC Classification</b>	DSR, Part 15 Remote Control/Security Device Transceiver
<b>Date Samples Received</b>	03/16/2022
<b>Sample Type and Condition Received</b>	Production Unit Suitable for Test
<b>EUT Description</b>	Vogelkop Wireless RF In-wall Lighting Switch
<b>FCC ID</b>	JPZ0140
<b>Applicable FCC Rules</b>	47 CFR Part 2.1091, OET Bulletin 65



## 1.2 Maximum Permissible Exposure Calculation

### **§1.1307 Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.**

(b)(1) *Requirements.* (i) With respect to the limits on human exposure to RF provided in §1.1310 of this chapter, applicants to the Commission for the grant or modification of construction permits, licenses or renewals thereof, temporary authorities, equipment authorizations, or any other authorizations for radiofrequency sources must either:

(A) Determine that they qualify for an exemption pursuant to §1.1307(b)(3);

(B) Prepare an evaluation of the human exposure to RF radiation pursuant to §1.1310 and include in the application a statement confirming compliance with the limits in §1.1310; or

(C) Prepare an Environmental Assessment if those RF sources would cause human exposure to levels of RF radiation in excess of the limits in §1.1310

### **§1.1310 Radiofrequency radiation exposure limits.**

(2) At operating frequencies less than or equal to 6 GHz, the limits for maximum permissible exposure (MPE), derived from whole-body Specific Absorption Rate (SAR) limits and listed in Table 1 of paragraph (e) of this section, may be used instead of whole-body SAR limits as set forth in paragraph (a) through (c) of this section to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b), except for portable devices as defined in §2.1093 as these evaluations shall be performed according to the SAR provisions in §2.1093 of this chapter.

(4) Both the MPE limits listed in Table 1 of paragraph (e) of this section and the SAR limits as set forth in paragraph (a) through (c) of this section and in §2.1093 of this chapter are for continuous exposure, that is, for indefinite time periods. Exposure levels higher than the limits are permitted for shorter exposure times, as long as the average exposure over the specified averaging time in Table 1 is less than the limits. Detailed information on our policies regarding procedures for evaluating compliance with all of these exposure limits can be found in the FCC's *OET Bulletin 65*, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields," and in supplements to *Bulletin 65*, all available at the FCC's Internet Web site: <http://www.fcc.gov/oet/rfsafety>.



**§2.1091 Radiofrequency radiation exposure evaluation: mobile devices.**

(b) For purposes of this section, the definitions in §1.1307(b)(2) of this chapter shall apply. A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and the body of the user or nearby persons. In this context, the term “fixed location” means that the device is physically secured at one location and is not able to be easily moved to another location while transmitting. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal desktop computer, are considered to be mobile devices if they meet the 20-centimeter separation requirement.

The Lutron Model DS-5ANS / DVRF-5NS is categorized as a fixed RF source as defined by 47 CFR Part 1.1307. Although the device is not mobile or portable, the fixed RF source will be evaluated at a distance of 20 cm. This distance is much less than probable exposure distance. The device will be mounted at the top of a window or door. Therefore, the limits of Section 1.1310, Table 1 “Limits for Maximum Permissible Exposure (MPE)” Section (ii) “Limits for General Population / Uncontrolled Exposure are applicable.

The use of OET Bulletin 65 was used to calculate the Power Density based upon EIRP levels of the QSFC-EDU-BP-C device measured and reported by this laboratory during testing for compliance to 47 CFR Part 15C.

**From: OET Bulletin 65 Edition 97-02, page 19.**

$$S = \frac{PG}{4\pi R^2} \quad (3)$$

where: S = Power Density (in appropriate units, e.g., mW/cm<sup>2</sup>)  
P = Power input to the antenna (in appropriate units, e.g., mW)  
G = Power Gain of the antenna in the direction of interest to an isotropic radiator  
R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

or: 
$$S = \frac{EIRP}{4\pi R^2} \quad (4)$$

where: EIRP = equivalent (or effective) isotropically radiated power (mw)



### 1.3 Maximum Permissible Exposure (MPE) 04/25/2022

Antenna power is the highest measured level among the low and high frequencies of the transmitter contained in each model identified above. The measurements below were taken from a test sample of the Lutron Models DS-5ANS / DVRF-5NS. The maximum radiated field strength level of the two fundamental transmit frequencies were converted from dBμV/m to dBm. The table below identifies the transmitter output level to achieve the EIRP level. The Power Density is then calculated using Formula (4) of OET Bulletin 65.

#### EIRP Measurement (04/06/2022) and Calculation

Effective Isotropic Radiated Power (EIRP) =

Antenna Power Output (dBm) + antenna gain (dBi)

Modulation	Frequency (MHz)	Transmitter Output Total		Antenna Gain		EIRP	
		dBm	Watts	Isotropic	Numeric	Total	
						dBm	Watts
FSK	431.5	-1.790	0.000662	-14.85	0.033	-16.64	0.0000217
	436.6	-3.470	0.000450	-14.85	0.033	-18.32	0.0000147

#### Power Spectral Density Calculation

Formula (4) above: S or Power Density =  $\frac{\text{EIRP}}{4\pi R^2}$

Modulation	Frequency (MHz)	EIRP		Spectral Density S=EIRP/4πd <sup>2</sup>			Result
		Total		@ 20 cm	Limit	Margin	
		dBm	Watts	mW/cm <sup>2</sup>	mW/cm <sup>2</sup>	mW/cm <sup>2</sup>	
FSK	431.5	-16.64	0.0000217	0.00000431	0.288	-0.288	Pass
	436.6	-18.32	0.0000147	0.00000293	0.291	-0.291	Pass

**Results:** The highest calculated Power Density, 0.00000431 mW/cm<sup>2</sup>, is based upon the EIRP measurements for the Lutron Models DS-5ANS / DVRF-5NS. This level complies with the limit Table 1(B) of 47 CFR Part 1.1310 at a separation distance of 20 cm. Therefore, the SAR exposure evaluation is not required.