



**BEC INCORPORATED**

**MAXIMUM PERMISSABLE EXPOSURE (MPE) REPORT**

**TEST STANDARDS:**

**U.S. Title 47 Chapter 1 Subchapter A Part 2 Subpart J**

**Lutron Model QSERJ-EDU  
Wireless Battery-Operated Motor Drive**

**FCC ID: JPZ0147**

**REPORT# BEC-2312-02**

**CUSTOMER:**

**Lutron Electronics Company Incorporated  
7200 Suter Road  
Coopersburg, PA 18036**

**PREPARED BY:**

\_\_\_\_\_  
JR Fanella, Test Engineer

**REVIEWED and APPROVED BY:**

\_\_\_\_\_  
Steve Fanella, Quality Manager

The results described in this report relate only to the item(s) tested. This document shall not be reproduced except in full without prior written permission of BEC Incorporated





## TABLE OF CONTENTS

<b>Notice to Customer .....</b>	<b>3</b>
<b>Revision History .....</b>	<b>3</b>
<b>1.0 Administrative Information.....</b>	<b>4</b>
1.1 General Information Table .....	4
<b>2.0 Product Description.....</b>	<b>5</b>
2.1 Test Configuration.....	5
2.2 Test Configuration Rationale. ....	5
2.3 Test Configuration Diagram Radiated Measurements.....	5
2.4 EUT Information, Interconnection Cabling and Support Equipment .....	6
<b>3.0 MPE (Maximum Permissible Exposure) .....</b>	<b>7</b>
3.1 Minimum Separation Distance.....	7
3.2 Maximum Permissible Exposure Calculation .....	7
3.3 Maximum Permissible Exposure (MPE) 03/29/2024 .....	10
Appendix A – Test Equipment .....	11



## Notice to Customer

This report and any recommendations it contain represent the result of BEC's testing and assessment on behalf of your company. Testing has been conducted according to accepted engineering standards and practices. This report reflects testing and assessment of product samples provided by your company and may not reflect the characteristics of other samples, especially those produced at different times. This report and its findings and recommendations, if implemented, should not be construed as an assurance or implied warranty for the continuing electromagnetic compatibility (EMC) of the product. **BEC shall not be liable for incidental or consequential damages, even if advised of the possibility thereof.**

BEC will not disseminate this report to other parties without your express permission. You may reproduce this report in its entirety including this notice and the entireties of any supplemental test reports on the same product (e.g. reports on additional testing following modification). However, 'you may not reproduce portions of the report (except for the entirety of the summary section) or quote from it for any purpose without specific prior written permission from BEC'.

The BEC Decision Rule: Measurement Uncertainty is not applied to any testing measurements or test results provided to the customer by BEC Incorporated at this time.

## Revision History

Revision #	Description of Changes	Date of Changes	Date Released
0	Test Report Initial Release	N/A	04/01/2024
1	Clarified the measurement method and data for MPE calculation in Section 3.3 of this report	06/10/2024	06/10/2024
2	Updated the measurement data for MPE calculation in Section 3.3. using the Radiated Measurements	06/11/2024	06/11/2024



## 1.0 Administrative Information

### 1.1 General Information Table

<b>Project Number</b>	BEC-2312
<b>Manufacturer</b>	Lutron Electronics Company, Inc.
<b>Model Numbers Tested</b>	QSERJ-EDU
<b>EUT Description</b>	Wireless Battery-operated Motor Drive
<b>EUT Sample Type</b>	Antenna Conducted Sample with Test Code
<b>EUT Serial Number</b>	04BC03EB
<b>EUT Sample Number</b>	2312-02
<b>Date Samples Received</b>	03/18/2024
<b>Condition of Sample Received</b>	Suitable for test
<b>Sample Version</b>	Prototype Unit
<b>Frequency of Operation</b>	431 MHz to 437 MHz
<b>Antenna Gain</b>	-6 dBi (-8.15 dBd)
<b>Antenna Type</b>	Monopole Antenna
<b>EUT Firmware Version</b>	Basenji 2.0 RF Test Code
<b>FCC ID</b>	JPZ0147
<b>FCC Classification</b>	DSR, Part 15 Remote Control / Security Device Transceiver
<b>Applicable FCC Rules</b>	47 CFR Part 2.1091, OET Bulletin 65



## 2.0 Product Description

The Lutron Model QSERJ-EDU Wireless Battery-operated Motor Drive is a battery-powered shade solution. The Lutron Model QSERJ-EDU Wireless Battery-operated Motor Drive uses a Lutron Designed Transceiver Radio which operates momentarily in the 431 MHz to 437 MHz frequency range.

### 2.1 Test Configuration

The Lutron Model QSERJ-EDU Wireless Battery-operated Motor Drive samples were programmed to provide control of the radio to enable transmission at Low Channel Frequency of 431.5 MHz or at High Channel Frequency of 436.6 MHz in multiple modes. Available transmission modes in the Basenji 2.0 RF Test Code were Constant Wave, Constant Packet or Continuous Constant Packet when transmitting.

Basenji 2.0 RF Test Code, Standard Mode 2, State 3. Continuous Constant Packet was used during the measurement of the fundamental frequency transmitter output.


### 2.2 Test Configuration Rationale.

The tested configurations are based on the signal types required to make proper measurements for the testing to RSS-210.

### 2.3 Test Configuration Diagram Radiated Measurements

Block diagram of the EUT configuration showing interconnection cables are illustrated below.

Fundamental Radiated Test Setup Diagram





## 2.4 EUT Information, Interconnection Cabling and Support Equipment

### EUT Hardware and Software/Firmware

Description	Manufacturer	Model	Serial Number	Software Firmware Version	Sample Number
QSERJ-EDU Wireless Battery-operated Motor Drive Antenna Conducted Test Sample with Basenji 2.0 RF Test Code	Lutron	QSERJ-EDU	04BC03EB	2.010	2312-02



## **3.0 MPE (Maximum Permissible Exposure)**

### **3.1 Minimum Separation Distance**

The manufacturer declares a minimum separation distance of 20 cm between user and device. This device is designed to be mounted on a wall at a height for traditional window blinds. The highest output power, based upon the measurements below, is used to compute the exemption limit for Routine Evaluation.

### **3.2 Maximum Permissible Exposure Calculation**

**§1.1307 Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.**

(b)(1) *Requirements.* (i) With respect to the limits on human exposure to RF provided in §1.1310 of this chapter, applicants to the Commission for the grant or modification of construction permits, licenses or renewals thereof, temporary authorities, equipment authorizations, or any other authorizations for radiofrequency sources must either:

(A) Determine that they qualify for an exemption pursuant to §1.1307(b)(3);

(B) Prepare an evaluation of the human exposure to RF radiation pursuant to §1.1310 and include in the application a statement confirming compliance with the limits in §1.1310; or

(C) Prepare an Environmental Assessment if those RF sources would cause human exposure to levels of RF radiation in excess of the limits in §1.1310



### **§1.1310 Radiofrequency radiation exposure limits.**

(2) At operating frequencies less than or equal to 6 GHz, the limits for maximum permissible exposure (MPE), derived from whole-body Specific Absorption Rate (SAR) limits and listed in Table 1 of paragraph (e) of this section, may be used instead of whole-body SAR limits as set forth in paragraph (a) through (c) of this section to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b), except for portable devices as defined in §2.1093 as these evaluations shall be performed according to the SAR provisions in §2.1093 of this chapter.

(4) Both the MPE limits listed in Table 1 of paragraph (e) of this section and the SAR limits as set forth in paragraph (a) through (c) of this section and in §2.1093 of this chapter are for continuous exposure, that is, for indefinite time periods. Exposure levels higher than the limits are permitted for shorter exposure times, as long as the average exposure over the specified averaging time in Table 1 is less than the limits. Detailed information on our policies regarding procedures for evaluating compliance with all of these exposure limits can be found in the FCC's *OET Bulletin 65*, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields," and in supplements to *Bulletin 65*, all available at the FCC's Internet Web site: <http://www.fcc.gov/oet/rfsafety>.

### **§2.1091 Radiofrequency radiation exposure evaluation: mobile devices.**

(b) For purposes of this section, the definitions in §1.1307(b)(2) of this chapter shall apply. A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location while transmitting. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal desktop computer, are considered to be mobile devices if they meet the 20-centimeter separation requirement.

The Lutron Model QSERJ-EDU is categorized as a fixed RF source as defined by 47 CFR Part 1.1307. Although the device is not mobile or portable, the fixed RF source will be evaluated at a distance of 20 cm. This distance is much less than probable exposure distance. The device will be mounted at the top of a window or door. Therefore, the limits of Section 1.1310, Table 1 "Limits for Maximum Permissible Exposure (MPE)" Section (ii) "Limits for General Population / Uncontrolled Exposure are applicable.





The use of OET Bulletin 65 was used to calculate the Power Density based upon EIRP levels of the QSERJ-EDU device measured and reported by this laboratory during testing for compliance to 47 CFR Part 15C.

**From: OET Bulletin 65 Edition 97-02, page 19.**

$$S = \frac{PG}{4\pi R^2} \quad (3)$$

where: S = Power Density (in appropriate units, e.g., mW/cm<sup>2</sup>)  
P = Power input to the antenna (in appropriate units, e.g., mW)  
G = Power Gain of the antenna in the direction of interest to an isotropic radiator  
R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

or: 
$$S = \frac{\text{EIRP}}{4\pi R^2} \quad (4)$$

where: EIRP = equivalent (or effective) isotropically radiated power (mw)



### 3.3 Maximum Permissible Exposure (MPE) 03/29/2024

Antenna power is the highest measured level among the low and high frequencies of the transmitter contained in each model identified above. The Radiated Emissions measurements below were taken from a test sample of the Lutron QSERJ-EDU. The maximum radiated emissions field strength level of the two fundamental transmit frequencies were converted from dBuV/m to dBm. The table below identifies the transmitter output level to achieve the EIRP level. The Power Density is then calculated using Formula (4) of OET Bulletin 65.

#### EIRP Measurement and Calculation

**Effective Isotropic Radiated Power (EIRP) =**

**Antenna Power Output (dBm) + antenna gain (dBi)**

Modulation	Frequency (MHz)	Transmitter Output Total		Antenna Gain		EIRP Total	
		dBm	Watts	Isotropic	Numeric	dBm	Watts
FSK	431.5	-13.269	0.000047	-6.00	0.251	-19.27	0.0000118
	436.6	-10.079	0.000098	-6.00	0.251	-16.08	0.0000247

#### Power Density Calculation

**Formula (4) above: S or Power Density =  $\frac{\text{EIRP}}{4\pi R^2}$**

Frequency	Peak Level @ 3M	EIRP	Power Density @ 20 cm	47 CFR Part 1.1310 Limit	Margin
MHz	dBuV/m	dBm	mW/cm <sup>2</sup>	mW/cm <sup>2</sup>	mW/cm <sup>2</sup>
431.5	75.96	-19.27	0.00000235	0.288	-0.2877
436.6	79.15	-16.08	0.00000491	0.291	-0.2911

**Results:** The calculated Power Density closest to the limit, based upon the measurements for the Lutron Model QSERJ-EDU is 0.00000235 mW/cm<sup>2</sup>. This complies with the limit of 0.288 mW/cm<sup>2</sup> from Table 1(B) of 47 CFR Part 1.1310 at a separation distance of 20 cm. Therefore, the SAR exposure evaluation is not required.



## Appendix A – Test Equipment

Equipment	Manufacturer	Model #	Serial #	BEC #	Calibration Date	Calibration Cycle	Calibration Due Date
EMI Receiver (20 Hz – 26.5 GHz)	Rohde & Schwarz	ESIB 26	836119/006	1010	12/09/2022	3 Years	12/09/2025