

## MPE CALCULATION

FCC ID: JQ6-ICLASSU90 / IC ID: 2236B-ICLASSU90

RF Exposure Requirements:	47 CFR §1.1307(b)
RF Radiation Exposure Limits:	47 CFR §1.1310
RF Radiation Exposure Guidelines:	FCC OST/OET Bulletin Number 65
EUT Frequency Band:	902.75-927.25 MHz
Limits for General Population/Uncontrolled Exposure in the band of:	300-1500 MHz
Power Density Limit:	0.62 mW / cm <sup>2</sup> (300-1500 MHz)

Equation:  $S = PG / 4\pi R^2$  or  $R = \sqrt{PG / 4\pi S}$

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain

R = distance to the center of radiated antenna

---

Prediction distance 20cm

UHF RFID (902.75-927.25MHz): Power = 28.81 dBm, Antenna gain= 5.37dBi, Power density=0.521 mW/cm<sup>2</sup>

Maximum MPE is 0.521mW/cm<sup>2</sup>, which is less than 0.62 mW/ cm<sup>2</sup>.

The Above Result had shown that Device complied with MPE requirement.

Completed By: David Zhang

Date : July 25th, 2014