

OMNIKEY®

Smart Card Readers

3121-906-ENEN, A.7

Installation Guide

Base Models: 1021, 3021, 3121, 4040, 4121, 4321, 5121, 5125, 5127, 5321, 5325, 5326, 6121, 6221, 6321.

Drivers and Manuals:
<http://www.hidglobal.com/omnikey>



North America
15370 Barranca Parkway
Irvine, CA 92618
USA

Asia Pacific
19/F 625 King's Road
North Point, Island East
Hong Kong

Europe, Middle East & Africa
Phoenix Road
Haverhill, Suffolk CB9 7AE
England

support.hidglobal.com

© 2010 – 2011 HID Global Corporation - All rights reserved.





Introduction

This guide describes physical behavior and conformities of the OMNIKEY® Smart Card Reader family.

1021 USB – Desktop smart card reader in a small form factor for desktop and mobile usage.

3021 USB – High-performance smart card reader, with a USB interface and small form factor for desktop and mobile usage.

3121 USB – High-performance smart card reader for desktop use with multiple standing base options in a robust housing.

4040 Mobile PCMCIA – High-performance smart card reader for mobile use in laptops and PDAs with PCMCIA interface.

4121 CL - Mobile ExpressCard 34mm – Contactless Reader with ExpressCard™ interface for Laptops and mobile devices that reads/writes to 13.56 MHz smart cards.

4321 Mobile ExpressCard 54 – High-performance smart card reader for mobile use in laptops and mobile devices with the ExpressCard™ interface.

5125 / 5325 USB Prox – Dual interface PC-linked reader that reads contactless (125kHz) HID Prox cards and reads/writes virtually any contact smart card.

5121 / 5321 USB – Dual interface PC-linked reader that reads/writes to both 13.56 MHz contactless cards and virtually any contact smart card.

5127 CK USB – Contactless 13.56MHz/125kHz reader with CCID/Keyboard wedge interface.

5321 CL USB – Contactless Reader with USB interface for desktop use that reads/writes to 13.56 MHz smart cards.

5321 CL SAM USB – Dual interface PC-linked reader that reads/writes to both 13.56 MHz contactless cards and virtually any SIM-sized contact smart card.

5326 DFR USB – Contactless Dual Frequency (13.56MHz/125kHz) Reader with CCID interface.

6121 Mobile USB – Dongle-sized smart card reader for SIM-sized smart cards, especially well suited for use with mobile devices.

6221 USB – Dongle-sized reader for SIM-sized smart cards and Micro-SD cards, especially well suited for use with mobile devices.

6321 Mobile USB – Dongle-sized Dual interface PC linked reader that reads/writes to 13.56 MHz contactless smart card and virtually any SIM-sized contact smart card.

Parts

- Smart Card Reader
- Installation Guide

Find drivers, reader documentation supporting various operating systems at

<http://www.hidglobal.com/omnikey>.

See the application note for card loading and handling instructions at

<http://www.hidglobal.com/omnikey>.



Specifications and Installation

For further information, contact HID support: <http://support.hidglobal.com/>.

For driver setup, consult the OMNIKEY Smart Card User Guide (http://www.hidglobal.com/documents/ok3121_userguide_ins_en.pdf).

CAUTION: Install the drivers prior to attaching the OMNIKEY reader with the computer.

USB Connected Reader Specifications

Operating Temperature	0°-55°C / 32°-131°F
PC Connector Cable	180 cm / 70.9 in (150 cm / 59.1 in - Models 1021 & 3021)
Meantime between Failure (MTBF)	500,000 Hours
Host Interface	USB 2.0 CCID (USB 1.1 Compatible)
Host Data Transmission Speed	12 Mbps (USB 2.0 Full Speed)
Power Supply	Bus Powered

USB Connected Reader Installation

1. Connect the reader with your computer; plug the USB connector into your computers USB port.
2. When the reader is operational, the LED illuminates.
3. For contactless operation, hold the card next to the reader logo. For contact smart cards, insert the card into the reader with contacts facing up.
4. When the reader is exchanging data with a card (reading/writing), the LED blinks.

PCMCIA and ExpressCard Reader Specifications

	4321	4121 CL	4040
Operating Temperature	0°-55°C / 32°-131°F		
Meantime between Failure (MTBF)	500,000 Hours		
Host Interface	ExpressCard 54 mm	ExpressCard 34mm	PCMCIA
Host Data Transmission Speed	12 Mbps		16 Mbps
Power Supply	Bus Powered		PCMCIA

PCMCIA and ExpressCard Reader Installation

1. Insert the reader into the compatible interface slot of your Notebook or mobile device.
2. If the reader is operational, observe the reader in your operating system's **Device Manager**.
3. For contactless operation, hold the card next to the logo on the reader. For contact smart cards, insert the card into the reader with contacts facing up.



Regulatory

FCC / Canada Radio Certification

CAUTION: Any changes or modifications to this device not explicitly approved by manufacturer could void your authority to operate this equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This device complies with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions:

- (1) This device may not cause interference, and
- (2) This device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

CE Marking

HID Global hereby declares that these products are in compliance with the essential requirements and other relevant provisions of the applicable Directives. A DoC copy can be found at <http://certifications.hidglobal.com>.

Nur in Verbindung mit zertifiziertem PC.

Taiwan

According to "Administrative Regulations on Low Power Radio Waves Radiated Devices" Without permission granted by the DGT, any company, enterprise, or user is not allowed to change frequency, enhance transmitting power or alter original characteristic as well as performance to a approved low power radio-frequency devices. The low power radio-frequency devices shall not influence aircraft security and interfere legal communications; If found, the user shall cease operating immediately until no interference is achieved. The said legal communications means radio communications is operated in compliance with the Telecommunications Act. The low power radio-frequency devices must be susceptible with the interference from legal communications or ISM radio wave radiated devices.

Singapore

Approved by IDA for use in Singapore. DA103548

Japan ITE

この装置は総務省の型式指定を受けています。

本製品は電波を使用したRFID機器の読み取り・書き込み装置です。

そのため使用する用途・場所によっては、医療機器に影響を与える恐れがあります。

Korean

이 기기는 가정용(비급)으로 전자파 적합 등록을 한 기기로서 주로 가정에서 사용하는 것을 목적으로 하며, 모든 지역에서 사용할 수 있습니다.

