

RF TEST REPORT



Report No.: RF_SL15102901-HID-029_FCC-IC
Supersede Report No.: None

Applicant	:	HID Global Corporation
Product Name	:	USB Contactless Smart Card Reader
Model No.	:	OMNIKEY 5022 CL
Test Standard	:	FCC 15.225 RSS-210 Issue 8: 2010
Test Method	:	FCC 15.225 ANSI C63.10 2013 RSS Gen Issue 4 2014
FCC ID	:	JQ6-OK5022CL
IC ID	:	2236B-OK5022CL
Dates of test	:	November 16 th , 17 th , 18 th , 19 th and 23 th of 2015
Issue Date	:	12/14/2015
Test Result	:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
Equipment complied with the specification		[X]
Equipment did not comply with the specification		[]

This Test Report is Issued Under the Authority of:	
Rachana Khanduri	Nima Molaei
Test Engineer	Engineer Reviewer
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only	

Issued By:
SIEMIC Laboratories
775 Montague Expressway, Milpitas, CA 95035



775 Montague Expressway, Milpitas, CA 95035, USA • Phone: (+1) 408 526 1188 • Facsimile (+1) 408 526 1088

Visit us at: www.siemic.com; Follow us at:

Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Accreditation Body	Scope
USA	FCC, A2LA	EMC, RF/Wireless, Telecom
Canada	IC, A2LA, NIST	EMC, RF/Wireless, Telecom
Taiwan	BSMI, NCC, NIST	EMC, RF, Telecom, Safety
Hong Kong	OFTA, NIST	RF/Wireless, Telecom
Australia	NATA, NIST	EMC, RF, Telecom, Safety
Korea	KCC/RRA, NIST	EMI, EMS, RF, Telecom, Safety
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom
Mexico	NOM, COFETEL, Caniety	EMC, RF/Wireless, Telecom, Safety
Europe	A2LA, NIST	EMC, RF, Telecom, Safety
Israel	MOC, NIST	EMC, RF, Telecom, Safety

Accreditations for Product Certifications

Country	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC, RF, Telecom
Canada	IC FCB, NIST	EMC, RF, Telecom
Singapore	iDA, NIST	EMC, RF, Telecom
EU	NB	EMC & R&TTE Directive
Japan	MIC (RCB 208)	RF, Telecom
Hong Kong	OFTA (US002)	RF, Telecom

CONTENTS

1	REPORT REVISION HISTORY	4
2	EXECUTIVE SUMMARY	5
3	CUSTOMER INFORMATION	5
4	TEST SITE INFORMATION	5
5	MODIFICATION	5
6	EUT INFORMATION	6
6.1	EUT Description	6
6.2	Radio Description	6
6.3	EUT test modes/configuration Description.....	7
6.4	EUT Photos – External	8
6.6	EUT Test Setup Photos	10
7	SUPPORTING EQUIPMENT/SOFTWARE AND CABLING DESCRIPTION.....	11
7.1	Supporting Equipment	11
7.2	Cabling Description	11
7.3	Test Software Description	11
8	TEST SUMMARY.....	12
9	MEASUREMENT UNCERTAINTY	13
10	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	14
10.1	Antenna Requirement.....	14
10.2	Conducted Emissions Test Result	15
10.3	Radiated Measurements.....	20
10.3.1	Radiated Measurements below 1GHz.....	20
10.3.2	Radiated Measurements below 30MHz (Field Strength)	22
10.3.3	Frequency Stability	26
10.3.4	Occupied bandwidth	28
	ANNEX A. TEST INSTRUMENT.....	30
	ANNEX B. SIEMIC ACCREDITATION	31

1 Report Revision History

Report No.	Report Version	Description	Issue Date
RF_SL15102901-HID-029_RFID FCC-IC	-	Original	12/14/2015

2 Executive Summary

The purpose of this test program was to demonstrate compliance of following product

Company: HID Global Corporation
Product: Smart Card Reader
Model: OMNIKEY 5022 CL

against the current Stipulated Standards. The specified model product stated above has demonstrated compliance with the Stipulated Standard listed on 1st page.

3 Customer information

Applicant Name	:	HID Global Corporation
Applicant Address	:	15370 Barranca Parkway, Irvine, CA 92618 USA
Manufacturer Name	:	HID Global Corporation
Manufacturer Address	:	10385 Westmoor Drive, Suite 300, Westminster, CO 80021

4 Test site information

Lab performing tests	:	SIEMIC Laboratories
Lab Address	:	775 Montague Expressway, Milpitas, CA 95035
FCC Test Site No.	:	881796
IC Test Site No.	:	4842D-2
VCCI Test Site No.	:	A0133

5 Modification

Index	Item	Description	Note
-	-	-	-

6 EUT Information

6.1 EUT Description

Product Name	:	USB Contactless Smart Card Reader
Model No.	:	OMNIKEY 5022 CL
Trade Name	:	HID
Serial No.	:	N/A
Input Power	:	5VDC/USB
Software version	:	N/A
Hardware version	:	N/A
Date of EUT received	:	19/05/2015
Equipment Class/ Category	:	RFID
Working Frequencies	:	13.56MHz
Port/Connectors	:	USB

6.2 Radio Description

Specifications for Radio:

Radio Type	RFID
Operating Frequency	13.56MHz
Modulation	ASK (13.56MHz)
Channel Spacing	None
Antenna Type	Mag Integrated Loop Antenna
Antenna Gain	1 dBi
Antenna Connector Type	N/A

Channel List:

Type	Mode	Channel No.	Frequency (MHz)	Available (Y/N)
RFID	13.56MHz	1	13.56	Y

6.3 EUT test modes/configuration Description

Mode	Note
RF test	EUT is set to continuously transmit at 13.56MHz when powered on.
Note: None	

Test Item	Operating mode	Tested antenna port	Test frequencies
Antenna Requirement	N/A	-	13.56MHz
Conducted Emissions Voltage	Continuous Transmit	-	
Limit in the band of 13.553 – 13.567 MHz	Continuous Transmit	-	
Limit in the band of 13.410 – 13.553 MHz and 13.567 – 13.710 MHz	Continuous Transmit	-	
Limit in the band of 13.110 – 13.410 MHz and 13.710 – 14.010 MHz	Continuous Transmit	-	
Limit outside the band of 13.110 – 14.010 MHz	Continuous Transmit	-	
Frequency Stability	Continuous Transmit	-	
Occupied Bandwidth	Continuous Transmit	-	

Note: EUT uses a PCB trace antenna attached to the PCB board. Only radiated measurements were performed during the test.

6.4 EUT Photos – External



Top Side



Bottom Side



Front Side



Rear Side




Left Side




Right Side

6.5 EUT Photos - Internal




6.6 EUT Test Setup Photos




AC Line Conducted Emissions– Front View




AC Line Conducted Emissions– Rear View




Radiated Emissions (<1GHz) – Front View



Radiated Emissions (<1GHz) – Rear View



Radiated Emissions (<30MHz) – Front View



Radiated Emissions (<30MHz) – Rear View

7 Supporting Equipment/Software and cabling Description

7.1 Supporting Equipment

Index	Supporting Equipment Description	Model	Serial No	Manu	Note
1	Laptop	Lenovo	-	ThinkPad	-

7.2 Cabling Description

Name	Connection Start		Connection Stop		Length / shielding Info		Note
	From	I/O Port	To	I/O Port	Length (m)	Shielding	
USB	EUT	USB	Laptop	USB	2.0	Unshielded	-

7.3 Test Software Description

Test Item	Software	Description
Conducted Emissions	N/A	EUT is set to continuously transmit at 13.56MHz when powered on.
Radiated Spurious Emissions	N/A	
Frequency Stability	N/A	
Occupied Bandwidth	N/A	

8 Test Summary

Test Item	Test standard		Test Method/Procedure	Pass / Fail
Antenna Requirement	FCC	15.203	ANSI C63.10 – 2013	<input checked="" type="checkbox"/> Pass
	IC	-		<input type="checkbox"/> N/A
AC Conducted Emissions Voltage	FCC	15.225(a)	ANSI C63.10 2013 RSS Gen. 8.8	<input checked="" type="checkbox"/> Pass
	IC	RSS Gen (7.2.2)		<input type="checkbox"/> N/A
Remark	1. AC Line tests were performed on the support equipment's power adapter, laptop.			

Test Item	Test standard		Test Method/Procedure	Pass / Fail	
Limit in the band of 13.553 – 13.567 MHz	FCC	15.225(a)	FCC	ANSI C63.10 2013	<input checked="" type="checkbox"/> Pass
	IC	RSS210(A2.6)	IC	RSS Gen 6.13	<input type="checkbox"/> N/A
Limit in the band of 13.410 – 13.553 MHz and 13.567 – 13.710 MHz	FCC	15.225(b)	FCC	ANSI C63.10 2013	<input checked="" type="checkbox"/> Pass
	IC	RSS210(A2.6)	IC	RSS Gen 6.13	<input type="checkbox"/> N/A
Limit in the band of 13.110 – 13.410 MHz and 13.710 – 14.010 MHz	FCC	15.225(c)	FCC	ANSI C63.10 2013	<input checked="" type="checkbox"/> Pass
	IC	RSS210(A2.6)	IC	RSS Gen 6.13	<input type="checkbox"/> N/A
Limit outside the band of 13.110 – 14.010 MHz	FCC	15.225(d)	FCC	ANSI C63.10 2013	<input checked="" type="checkbox"/> Pass
	IC	RSS210(A2.6)	IC	RSS Gen 6.13	<input type="checkbox"/> N/A
Receiver Spurious Emission	IC	-	IC	RSS Gen 7.1	<input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A
Frequency Stability	FCC	15.225(e)	FCC	-	<input checked="" type="checkbox"/> Pass
	IC	RSS210(A2.6)	IC	RSS Gen 6.11	<input type="checkbox"/> N/A
Occupied Bandwidth	FCC	-	FCC	-	<input checked="" type="checkbox"/> Pass
	IC	RSS-210(5.9.1)	IC	RSS Gen 6.6	<input type="checkbox"/> N/A
Remark	<ol style="list-style-type: none"> All measurement uncertainties are not taken into consideration for all presented test result. The applicant shall ensure frequency stability by showing that an emission is maintained within the band of operation under all normal operating conditions as specified in the user's manual. 				

9 Measurement Uncertainty

Test Item	Description	Uncertainty
AC Conducted Emissions Voltage	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2	±3.5dB
Limit in the band of 13.553 – 13.567 MHz	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
Limit in the band of 13.410 – 13.553 MHz and 13.567 – 13.710 MHz		+5.6dB/-4.5dB
Limit in the band of 13.110 – 13.410 MHz and 13.710 – 14.010 MHz		+5.6dB/-4.5dB
Limit outside the band of 13.110 – 14.010 MHz		+5.6dB/-4.5dB
Radiated Spurious Emissions		+5.6dB/-4.5dB

10 Measurements, examination and derived results


10.1 Antenna Requirement

Spec	Requirement	Applicable
§15.203	<p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.</p> <p>Antenna requirement must meet at least one of the following:</p> <p>a) Antenna must be permanently attached to the device. b) The antenna must use a unique type of connector to attach to the device. c) Device must be professionally installed. The installer shall be responsible for ensuring that the correct antenna is employed by the device.</p>	☒
Remark	The RFID antenna is integral to the PCB board permanently to the device which meets the requirement (See Internal Photographs submitted as another Exhibit).	
Result	☒ PASS ☐ FAIL	

10.2 Conducted Emissions Test Result

Conducted Emission Limit

Section	Frequency ranges (MHz)	Limit (dBuV)	
		QP	Average
Class B devices	0.15 ~ 0.5	66 – 56	56 – 46
	0.5 ~ 5	56	46
	5 ~ 30	60	50


Spec	Item	Requirement	Applicable
§ 15.207, RSS Gen 8.8	a)	For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits set in § 15.207, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). AC Line conducted emission within the band 150kHz to 30MHz	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Note: 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes</p>		
Procedure	<ul style="list-style-type: none"> - The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B. - The power supply for the EUT was fed through a 50Ω/50μH EUT LISN, connected to filtered mains. - The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. - All other supporting equipment was powered separately from another main supply. 		
Test Date	18/11/2015	Environmental conditions	Temperature 21°C Relative Humidity 38 % Atmospheric Pressure 1025 mbar
Remark	The EUT was tested at 120VAC, 60Hz.		
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data Yes N/A


Test Plot Yes N/A

Test specification:	Conducted Emissions		
Mains Power:	120VAC, 60Hz		Result: <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
Tested by:	Rachana Khanduri		
Test Date:	18/11/2015		
Remarks:	Neutral		

Neutral Plot at V=120VAC, f=60



Antenna is terminated




Neutral Measurements

Frequency MHz	Raw dBuV	Cable Loss	Factors dB	Level dBuV	Measurement Type	Line	Limit dBuV	Margin dB	Pass /Fail
0.214367	33.00	10.00	1.23	44.24	Quasi Peak	Neutral	63.03	-18.8	Pass
21.68901	31.17	10.07	0.72	41.96	Quasi Peak	Neutral	60.00	-18.04	Pass
22.66888	29.90	10.07	0.74	40.71	Quasi Peak	Neutral	60.00	-19.29	Pass
21.9088	31.12	10.07	0.72	41.92	Quasi Peak	Neutral	60.00	-18.08	Pass
21.14476	31.15	10.07	0.71	41.93	Quasi Peak	Neutral	60.00	-18.07	Pass
19.72695	28.24	10.07	0.69	38.99	Quasi Peak	Neutral	60.00	-21.01	Pass
0.214367	19.47	10.00	1.23	30.7	Average	Neutral	53.03	-22.33	Pass
21.68901	26.97	10.07	0.72	37.77	Average	Neutral	50.00	-12.23	Pass
22.66888	26.53	10.07	0.74	37.34	Average	Neutral	50.00	-12.66	Pass
21.9088	25.55	10.07	0.72	36.34	Average	Neutral	50.00	-13.66	Pass
21.14476	25.84	10.07	0.71	36.63	Average	Neutral	50.00	-13.37	Pass
19.72695	22.12	10.07	0.69	32.88	Average	Neutral	50.00	-17.12	Pass


Test specification:	Conducted Emissions
---------------------	---------------------

Mains Power:	120VAC, 60Hz		Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
Tested by:	Rachana Khanduri			
Test Date:	18/11/2015			
Remarks:	Line			

Live Plot at V=120VAC, f=60Hz



Antenna is terminated




Live Measurements

Frequency MHz	Raw dB μ V	Cable Loss	Factors dB	Level dB μ V	Measurement Type	Line	Limit dB μ V	Margin dB	Pass /Fail
0.152861	8.58	10	1.76	20.34	Average	Live	55.84	-35.5	Pass
0.152861	26.46	10	1.76	38.22	Quasi Peak	Live	65.84	-27.62	Pass
0.217785	20.97	10	1.21	32.18	Average	Live	52.9	-20.72	Pass
0.217785	36.69	10	1.21	47.91	Quasi Peak	Live	62.9	-15	Pass
20.81727	23	10.07	0.7	33.77	Average	Live	50	-16.23	Pass
20.81727	27.48	10.07	0.7	38.25	Quasi Peak	Live	60	-21.75	Pass
21.14377	23.16	10.07	0.71	33.94	Average	Live	50	-16.06	Pass
21.14377	26.74	10.07	0.71	37.53	Quasi Peak	Live	60	-22.47	Pass
21.25274	26.35	10.07	0.71	37.13	Quasi Peak	Live	60	-22.87	Pass
21.25274	22.34	10.07	0.71	33.12	Average	Live	50	-16.88	Pass
21.36544	21.57	10.07	0.71	32.35	Average	Live	50	-17.65	Pass
21.36544	25.71	10.07	0.71	36.5	Quasi Peak	Live	60	-23.5	Pass

10.3 Radiated Measurements

10.3.1 Radiated Measurements below 1GHz

Requirement(s):


Spec	Requirement	Applicable										
47 CFR §15.225 RSS-210 (A2.6)	<p>Operation within the band 13.110–14.010 MHz:</p> <p>(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.</p> <p>(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.</p> <p>(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.</p> <p>(d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (uV/m)</th> </tr> </thead> <tbody> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216 960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>	Frequency range (MHz)	Field Strength (uV/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	☒
Frequency range (MHz)	Field Strength (uV/m)											
30 – 88	100											
88 – 216	150											
216 960	200											
Above 960	500											
Test Setup												
Procedure	<ol style="list-style-type: none"> The EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen. The EUT was then rotated to the direction that gave the maximum emission. Finally, the antenna height was adjusted to the height that gave the maximum emission. A Quasi-peak measurement was then made for that frequency point. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured. 											
Remark	The EUT was scanned up to 1GHz. Both horizontal and vertical polarities were investigated. The results show only the worst case.											
Result	☒ Pass ☐ Fail											

Test Data ☒ Yes (See below) ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test specification:	Radiated Emissions		
Mains Power:	120VAC, 60Hz		Result: <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
Tested by:	Rachana Khanduri		
Test Date:	23/11/2015		
Remarks:	below 1GHz		

f=30MHz – 1000MHz plot at V=120VAC, f=60Hz and 3 meter distance



f=30MHz – 1000MHz Measurements

Frequency MHz	Raw dBμV/m	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
39.537	30.86	0.92	-22.27	9.51	Quasi Max	V	304	13	40	-30.49	Pass
189.32	33.77	2.33	-27.41	8.7	Quasi Max	H	110	77	43.52	-34.82	Pass
30.00	36.14	0.81	-14.38	22.57	Quasi Max	H	255	67	40	-17.43	Pass
53.217	37.24	1.14	-29.5	8.88	Quasi Max	V	118	189	40	-31.12	Pass
66.947	38.94	1.29	-30.11	10.12	Quasi Max	V	173	80	40	-29.88	Pass
202.8	37.45	2.43	-26.14	13.74	Quasi Max	H	218	238	43.52	-29.78	Pass

10.3.2 Radiated Measurements below 30MHz (Field Strength)

Requirement(s):


Spec	Requirement	Applicable
47 CFR §15.225 RSS-210 (A2.6)	Operation within the band 13.110–14.010 MHz (a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters. (b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters. (c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters. (d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.	☒
Test Setup		
Procedure	For < 30MHz, Radiated emissions were measured according to ANSI C63.10. The EUT was set to transmit at the highest output power. The EUT was set 3 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the centre of the loop. The measuring bandwidth was set to 10 kHz. The limit is converted from microvolt/meter to decibel microvolt/meter.	
Test Date	17/11/2015	Environmental conditions Temperature 22°C Relative Humidity 40% Atmospheric Pressure 1026mbar
Remark	-	
Result	☒ Pass ☐ Fail	

Test Data ☒ Yes (See below) ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test specification:	Radiated Spurious Emissions		
Mains Power:	120VAC, 60Hz		Result: <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
Tested by:	Rachana Khanduri		
Test Date:	17/11//2015		
Remarks:	Below 30MHz		


f= 100kHz – 30MHz plot, and loop antenna at 0 degree



f=100kHz – 30MHz Measurements

Frequency MHz	Raw dBµV/m	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Degree	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
0.81	50.78	-0.20	14.28	64.86	Quasi Max	0	100.00	88.00	69.43	-4.57	Pass
1.39	38.87	-0.24	10.11	48.74	Quasi Max	0	100.00	118.00	64.75	-16.02	Pass
0.62	39.40	-0.19	16.44	55.65	Quasi Max	0	100.00	179.00	71.78	-16.13	Pass
1.93	39.32	-0.28	7.62	46.65	Quasi Max	0	100.00	352.00	69.54	-22.89	Pass
2.73	34.45	-0.31	5.18	39.33	Quasi Max	0	100.00	238.00	69.54	-30.22	Pass
3.81	31.55	-0.31	3.12	34.36	Quasi Max	0	100.00	262.00	69.54	-35.18	Pass


f= 100kHz – 30MHz plot, and loop antenna at 90 degree



f=100kHz – 30MHz Measurements


Frequency MHz	Raw dBµV/m	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Degree	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
0.81	50.25	-0.20	14.27	64.32	Quasi Max	90	100.00	356.00	69.42	-5.10	Pass
1.33	36.00	-0.23	10.44	46.21	Quasi Max	90	100.00	212.00	65.14	-18.92	Pass
1.77	36.61	-0.26	8.28	44.63	Quasi Max	90	100.00	81.00	69.54	-24.91	Pass
3.19	33.05	-0.31	4.16	36.90	Quasi Max	90	100.00	358.00	69.54	-32.64	Pass
0.46	47.67	-0.17	18.93	66.43	Quasi Max	90	100.00	150.00	94.38	-27.95	Pass
13.56	63.88	-0.62	-0.16	78.10	Quasi Max	90	100.00	171.00	124.92	-46.82	Pass

Loop Antenna at 0 degree @ 3meter distance



Frequency(MHz)	Amplitude(dBuV/m)
13.56	72.38


Loop Antenna at 90 degree @ 3meter distance



Frequency(MHz)	Amplitude(dBuV/m)
13.56	82.15

10.3.3 Frequency Stability

Requirement(s):

Spec	Requirement	Applicable									
47 CFR §15.225 (e) RSS-210 (A2.6)	Limit: $\pm 0.01\%$ of 13.56 MHz = 1356 Hz	<input checked="" type="checkbox"/>									
Test Setup	 <p>1. The EUT was set up inside an environmental chamber. 2. The EUT was placed in the centre of the environmental.</p>										
Procedure	Frequency Stability was measured according to 47 CFR §2.1055. Measurement was taken with spectrum analyzer. The spectrum analyzer bandwidth and span was set to read in hertz. A voltmeter was used to monitor when varying the voltage.										
Test Date	16/11/2015	<table border="1"> <tr> <td>Environmental conditions</td> <td>Temperature</td> <td>20°C</td> </tr> <tr> <td></td> <td>Relative Humidity</td> <td>41%</td> </tr> <tr> <td></td> <td>Atmospheric Pressure</td> <td>1026mbar</td> </tr> </table>	Environmental conditions	Temperature	20°C		Relative Humidity	41%		Atmospheric Pressure	1026mbar
Environmental conditions	Temperature	20°C									
	Relative Humidity	41%									
	Atmospheric Pressure	1026mbar									
Remark	None										
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail										

Test Data Yes (See below) N/A

Test Plot Yes (See below) N/A

Test results:

Frequency Stability versus Temperature: The Frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20°C to $+50^{\circ}\text{C}$ at normal supply voltage.

Reference Frequency: 13.55995792 MHz at 20°C at 5VDC

Temperature ($^{\circ}\text{C}$)	Measured Freq. (MHz)	Freq. Drift (Hz)	Freq. Deviation (Limit: 0.01%)	Pass/Fail
50	13.560335	40	<0.01	Pass
40	13.560345	30	<0.01	Pass
30	13.560365	10	<0.01	Pass
20	Reference (13.560375MHz)			
10	13.560410	-35	<0.01	Pass
0	13.560425	-50	<0.01	Pass
-10	13.560435	-60	<0.01	Pass
-20	13.560395	-20	<0.01	Pass

Frequency Stability versus Input Voltage: The Frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$, the frequency of the transmitter was measured at 85% and at 115% of the rated power supply voltage at a 20°C environmental temperature.

Carrier Frequency: 13.560375 MHz at 20°C at 5VDC

Measured Voltage $\pm 15\%$ of nominal (DC)	Measured Freq. (MHz)	Freq. Drift (Hz)	Freq. Deviation (Limit: 0.01%)	Pass/Fail
5.75	13.560083	2.92	<0.01	Pass
4.25	13.560383	-0.08	<0.01	Pass

10.3.4 Occupied bandwidth

Requirement(s):

Spec	Requirement	Applicable									
RSS-210(5.9.1)	The transmitter shall be operated at its maximum carrier power measured under normal test conditions. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used given that a peak or peak hold may produce a wider bandwidth than actual. The trace data points are recovered and directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.	<input checked="" type="checkbox"/>									
Test Setup	<ol style="list-style-type: none"> The EUT was set up inside a semi-anechoic chamber in accordance with the standard. The EUT was placed on top of a 0.8m high, non-metallic table in a typical configuration. 										
Procedure	<ol style="list-style-type: none"> The EUT was switched on and allowed to warm up to its normal operating condition. To measure conducted, a SMA cable was used to replace the EUT antenna. To measure radiated, an external antenna was used to detect EUT transmission signal. Measurement of the 99% Occupied Bandwidth of EUT transmission signal and make record. 										
Test Date	19/11/2015	<table border="1"> <tr> <td>Environmental conditions</td> <td>Temperature</td> <td>22°C</td> </tr> <tr> <td></td> <td>Relative Humidity</td> <td>39%</td> </tr> <tr> <td></td> <td>Atmospheric Pressure</td> <td>1025mbar</td> </tr> </table>	Environmental conditions	Temperature	22°C		Relative Humidity	39%		Atmospheric Pressure	1025mbar
Environmental conditions	Temperature	22°C									
	Relative Humidity	39%									
	Atmospheric Pressure	1025mbar									
Remark	-										
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail										

Test Data Yes (See below) N/A


Test Plot Yes (See below) N/A

Test specification:	Occupied Bandwidth		
Environmental Conditions:	Temp(°C):	20	Result:
	Humidity (%):	36	
	Atmospheric(mbar):	1021	
Mains Power:	5VDC	<input checked="" type="checkbox"/> Pass	
Tested by:	Rachana Khanduri	<input type="checkbox"/> Fail	
Test Date:	19/11/2015		
Remarks:	-		

Test results:

Radio	Channel Frequency (MHz)	99% Occupied BW (kHz)	Limit (MHz)
13.56MHz	13.56	1.155	N/A

13.56 MHz



















Annex A. TEST INSTRUMENT






Instrument	Model	Serial #	Cal Cycle	Cal Due	In use
Emissions Radiated					
EMI Test Receiver	ESL6	100178	1 Year	05/27/2016	<input checked="" type="checkbox"/>
ETS-Lindgren Loop Antenna	6512	00049120	1 Year	08/20/2016	<input checked="" type="checkbox"/>
Antenna – Bicon log (30 MHz – 2 GHz)	JB1	A030702	1 Year	08/15/2016	<input checked="" type="checkbox"/>
Double Ridged Waveguide Horn Antenna (1-18 GHz)	3115	10SL0059	1 Year	08/25/2016	<input type="checkbox"/>
Horn Antenna (18 GHz - 40 GHz)	AH-840	101013	1 Year	08/28/2016	<input type="checkbox"/>
RF Pre-Amplifier	LPA-6-30	11140711	1 Year	02/19/2016	<input checked="" type="checkbox"/>
Microwave Preamplifier (18 GHz - 40 GHz)	PA-840	181251	1 Year	02/19/2016	<input type="checkbox"/>
3 Meters SAC	3M	N/A	1 Year	10/30/2016	<input type="checkbox"/>
10 Meters SAC	10M	N/A	1 Year	05/06/2016	<input checked="" type="checkbox"/>
Frequency tolerance					
Spectrum Analyzer	N9010A	MY50210206	1 Year	08/20/2016	<input checked="" type="checkbox"/>
Test Equity Environment Chamber	1007H	61201	1 Year	07/28/2016	<input checked="" type="checkbox"/>
RF Conducted Measurement					
Spectrum Analyzer	N9010A	MY50210206	1 Year	08/20/2016	<input checked="" type="checkbox"/>

Test Software Version

Test Item	Vendor	Software	Version
Radiated Emission	EMISoft	EMISoft Vasona	V5.0
Conducted Emission	EMISoft	EMISoft Vasona	V5.0

Annex B. SIEMIC Accreditation

Accreditations	Document	Scope / Remark
ISO 17025 (A2LA)		Please see the documents for the detailed scope
ISO Guide 65 (A2LA)		Please see the documents for the detailed scope
TCB Designation		A1, A2, A3, A4, B1, B2, B3, B4, C
FCC DoC Accreditation		FCC Declaration of Conformity Accreditation
FCC Site Registration		3 meter site
FCC Site Registration		10 meter site
IC Site Registration		3 meter site
IC Site Registration		10 meter site
EU NB		Radio & Telecommunications Terminal Equipment: EN45001 – EN ISO/IEC 17025
		Electromagnetic Compatibility: EN45001 – EN ISO/IEC 17025
Singapore iDA CB(Certification Body)	 	Phase I, Phase II
Vietnam MIC CAB Accreditation		Please see the document for the detailed scope
Hong Kong OFCA		(Phase II) OFCA Foreign Certification Body for Radio and Telecom
		(Phase I) Conformity Assessment Body for Radio and Telecom
Industry Canada CAB		Radio: Scope A – All Radio Standard Specification in Category I
		Telecom: CS-03 Part I, II, V, VI, VII, VIII

Japan Recognized Certification Body Designation		<p>Radio: A1. Terminal equipment for purpose of calling</p> <p>Telecom: B1. Specified radio equipment specified in Article 38-2, Paragraph 1, Item 1 of the Radio Law</p>
Korea CAB Accreditation		<p>EMI: KCC Notice 2008-39, RRL Notice 2008-3: CA Procedures for EMI KN22: Test Method for EMI</p> <p>EMS: KCC Notice 2008-38, RRL Notice 2008-4: CA Procedures for EMS KN24, KN61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11: Test Method for EMS</p>
		<p>Radio: RRL Notice 2008-26, RRL Notice 2008-2, RRL Notice 2008-10, RRL Notice 2007-49, RRL Notice 2007-20, RRL Notice 2007-21, RRL Notice 2007-80, RRL Notice 2004-68</p> <p>Telecom: President Notice 20664, RRL Notice 2007-30, RRL Notice 2008-7 with attachments 1, 3, 5, 6; President Notice 20664, RRL Notice 2008-7 with attachment 4</p>
Taiwan NCC CAB Recognition		LP0002, PSTN01, ADSL01, ID0002, IS6100, CNS14336, PLMN07, PLMN01, PLMN08
Taiwan BSMI CAB Recognition		CNS 13438
Japan VCCI		<p>R-3083: Radiation 3 meter site</p> <p>C-3421: Main Ports Conducted Interference Measurement</p> <p>T-1597: Telecommunication Ports Conducted Interference Measurements</p>
Australia CAB Recognition		<p>EMC: AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR22, AS/NZS 61000.6.3, AS/NZS 61000.6.4</p>
		<p>Radio communications: AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1, AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS 4769.2, AS/NZS 4770, AS/NZS 4771</p>
		<p>Telecommunications: AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06 AS/ACIF S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01, AS/ACIF S041:05, AS/ACIF S043.2:06, AS/ACIF S60950.1</p>
Australia NATA Recognition		AS/ACIF S002, AS/ACIF S003, AS/ACIF S004, AS/ACIF S006, AS/ACIF S016, AS/ACIF S031, AS/ACIF S038, AS/ACIF S040, AS/ACIF S041, AS/ACIF S043.2