



Canada

# RF Test Report

As per

## RSS-137 Issue 2:2009 & FCC Part 90 Subpart M:2015

Location and Monitoring Service (LMS)  
Operation in the 902 -928 MHz Band  
on the

### JANUS™ Interior OBU Family Model: 801660B-TAB

Issued by: **TÜV SÜD Canada Inc.**  
11 Gordon Collins Dr,  
Gormley, ON, L0H 1G0  
Canada  
Ph: (905) 883-7255

Testing produced for



Prepared by

Min Xie,  
Sr. EMC Engineer

See Appendix A for full client &  
EUT details.

Reviewed by

Amir Emami,  
Project Engineer



Registration #  
6844A-3




Testing Laboratory  
Certificate #2955.02



R-4023, G-506  
C-4498, T-1246




Registration #  
CA6844

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

## Table of Contents

Table of Contents .....	2
Report Scope .....	3
Summary .....	4
Test Results Summary .....	5
Notes, Justifications, or Deviations .....	6
Sample Calculation(s) .....	7
Applicable Standards, Specifications and Methods .....	8
Document Revision Status .....	9
Definitions and Acronyms .....	10
Testing Facility .....	11
Calibrations and Accreditations .....	11
Testing Environmental Conditions and Dates .....	12
Detailed Test Results Section .....	13
Output Power and Antenna Heights .....	14
Occupied Bandwidth .....	17
Emission Mask .....	20
Transmitter Spurious Radiated Emissions .....	25
Temperature Frequency Stability .....	32
Appendix A – EUT Summary .....	34

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

## Report Scope

This report addresses the EMC verification testing and test results of the Kapsch TrafficCom Canada Inc.'s **JANUS™ Interior OBU Family, Model: 801660B-TAB**, and is herein referred to as EUT (Equipment Under Test). The EUT was tested for compliance against the following standards:

RSS-137 Issue 2:2009


FCC Part 90 Subpart M:2015

Test procedures, results, justifications, and engineering considerations, if any, follow later in this report.

The results contained in this report relate only to the item(s) tested.

This report does not imply product endorsement by any government, accreditation agency, or TÜV SÜD Canada Inc.

Opinions or interpretations expressed in this report, if any, are outside the scope of TÜV SÜD Canada Inc. accreditations. Any opinions expressed do not necessarily reflect the opinions of TÜV SÜD Canada Inc., unless otherwise stated.


Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

## Summary

The results contained in this report relate only to the item(s) tested.

EUT:	JANUS™ OBU Family, Model: 801660B-TAB
FCC Certification #, FCC ID:	JQU801660B
Industry Canada Certification #, IC:	2665A-801660B
EUT passed all tests performed	Yes
Tests conducted by	Min Xie


For testing dates, see "Testing Environmental Conditions and Dates".

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

## Test Results Summary

Standard/Method	Description	Limit	Result
FCC 90.205 RSS-137 Clause 6.4	Output Power	30 W	Pass
FCC 90.207 RSS-137 Clause 6.2	Types of Modulation	--	Pass See Justifications
FCC 90.209 RSS-137 Clause 6.1.2	Occupied Bandwidth	902 - 904 MHz: 2 MHz 909.75 – 921.75 MHz 12 MHz	Pass
FCC 90.210 (K) RSS-137 Clause 6.5.3	Spurious antenna port conducted emissions	Attenuation By: $55 + 10 \log_{10}(P_{max})$ dB.	Pass
FCC 90.210 RSS-137 Clause 6.5.3	Spurious radiated emissions	Attenuation By: $55 + 10 \log_{10}(P_{max})$ dB.	Pass
FCC 90.213 RSS-137 Clause 6.3	Frequency stability	2.5 PPM	N/A See Justification
FCC 90.214	Transient Behavior	--	N/A See Justifications
<b>Overall Result</b>			<b>Pass</b>

If the product as tested or otherwise complies with the specification, the EUT is deemed to comply with the requirement and is deemed a 'PASS' grade. If not 'FAIL' grade will be issued. Note that 'PASS' / 'FAIL' grade is independent of any measurement uncertainties. A 'PASS' / 'FAIL' grade within measurement uncertainty is marked with a '\*'.

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

### ***Notes, Justifications, or Deviations***

The following notes, justifications for tests not performed or deviations from the above listed specifications apply:

JANUS™ Interior OBU Family, Model: 801660B-TAB have the following model variance:

1. 801970B-TAB
2. 801990B-TAB
3. 802001B-TAB
4. 802690B-TAB
5. 802700B-TAB

See model-difference exhibit for description and additional information.

Models 801660B-TAB and 801970B-TAB are tested. Worst case results are reported in this report.

The EUT uses Shaped ON-OFF Keying to transmit information. According to FCC 90.207, the EUT is classified as K1D type of emission.

For FCC 90.214, the EUT operates in the 902-928 MHz band, and this requirement is not applicable.

For FCC 90.213, the EUT is an intermittently operated mobile transponder and therefore is not subject to frequency tolerance restrictions. The test was performed for information purpose.

For the requirements of FCC 90.210 (K) and FCC 2.1053 Measurements required: Field strength of spurious radiation. Spurious radiated emissions of the EUT was performed at 3 meters. The limit specified in FCC 90.210 (K) is: On any frequency outside the licensee's sub-band edges, the peak power of any emission shall be attenuated by  $55 + 10 \log(P)$  where P is the highest emission (Watts) of the transmitter. For all intents and purposes, the limit is -25 dBm ERP. The 3 meter field strength limit for the EUT is given below:


$$E(\text{dB}\mu\text{V/m}) = \text{EIRP}(\text{dBm}) + 95.2$$

$$\text{Where EIRP} = \text{ERP} + 2.15$$

$$E(\text{dB}\mu\text{V/m}) = \text{ERP}(\text{dBm}) + 97.35$$

$$E(\text{dB}\mu\text{V/m}) = -25 \text{ dBm} + 97.35 = 72.35 \text{ dB}\mu\text{V}$$

This limit is applicable to all emission at 3 meter measurement distance.

Client	<b>Kapsch TrafficCom Canada Inc</b>	 Canada
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	


### **Sample Calculation(s)**

#### **Radiated Emission Test**

Margin = Limit – (Received Signal + Antenna Factor + Cable Loss – Pre-Amp Gain)

Margin = 50.5dB $\mu$ V/m – (50dB $\mu$ V + 10dB + 2.5dB – 20dB)


Margin = 8.0 dB (pass)

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

## Applicable Standards, Specifications and Methods

ANSI C63.4:2009	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
ANSI/TIA-603-E	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
CFR 47 FCC Part 2 Subpart J	Code of Federal Regulations – Equipment Authorization Procedure
CFR 47 FCC Part 90	Code of Federal Regulations – Private Land Mobile Radio Services
FCC KDB 412172	D01 Determining ERP and EIRP v01
RSS 137 Issue 2:2009	Spectrum Management and Telecommunications. Radio Standards Specification, Location and Monitoring Service in the Band 902-928 MHz.
RSS-GEN Issue 5 2018	General Requirements and Information for the Certification of Radio Apparatus
ISO 17025:2005	General Requirements for the Competence of Testing and Calibration Laboratories




Client	<b>Kapsch TrafficCom Canada Inc</b>	 Canada
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

## Document Revision Status

Revision 000 - Aug 9, 2018  
Initial Release

Revision 001 Sept 4, 2018  
Capitalize ppm on pages 9 and 32.  
This revision replaces the previous revision in its entirety.

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

## Definitions and Acronyms

The following definitions and acronyms are applicable in this report.  
See also ANSI C63.14.

**AE** – Auxiliary Equipment. A digital accessory that feeds data into or receives data from another device (host) that in turn, controls its operation.

**BW** – Bandwidth. Unless otherwise stated, this refers to the 6 dB bandwidth.

**EMC** – Electro-Magnetic Compatibility. The ability of an equipment or system to function satisfactorily in its electromagnetic environment without introducing intolerable electromagnetic disturbances to anything in that environment.

**EMI** – Electro-Magnetic Immunity. The ability to maintain a specified performance when the equipment is subjected to disturbance (unwanted) signals of specified levels.


**EUT** – Equipment Under Test. A device or system being evaluated for compliance that is representative of a product to be marketed.

**ITE** – Information Technology Equipment with a primary function(s) of entry, storage, display, retrieval, transmission, processing, switching, or control, of data.

**LISN** – Line Impedance Stabilization Network

**NCR** – No Calibration Required

**RF** – Radio Frequency


Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

## Testing Facility

Testing for EMC on the EUT was carried out at TÜV SÜD Canada testing lab near Toronto, Ontario. The testing lab has a calibrated 3m semi-anechoic chamber which allows measurements on a EUT that has a maximum width or length of up to 2m and a height of up to 3m. The chamber is equipped with a turntable that is capable of testing devices up to 3300lb in weight. This facility is capable of testing products that are rated for 120Vac and 240Vac single phase, or devices that are rated for a 208Vac 3 phase input. DC capability is also available for testing. The chamber is equipped with a mast that controls the polarization and height of the antenna. Control of the mast occurs in the control room adjoining the shielded chamber. Radiated emission measurements are performed using a BiLog antenna and a Horn antenna where applicable. Conducted emissions, unless otherwise stated, are performed using a LISN and using the Vertical Ground plane if applicable.

### **Calibrations and Accreditations**


The 3m semi-anechoic chamber is registered with Federal Communications Commission (FCC, CA6844), Industry Canada (IC, 6844A-3) and Voluntary Control Council for Interference (VCCI, R-4023, G-506, C-4498, and T-1246). This chamber was calibrated for Normalized Site Attenuation (NSA) using test procedures outlined in ANSI C63.4 "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". The chamber is lined with ferrite tiles and absorption cones to minimize any undesired reflections. The NSA data is kept on file at TÜV SÜD Canada. For radiated susceptibility testing, a 16 point field calibration has been performed on the chamber. The field uniformity data is kept on file at TÜV SÜD Canada. TÜV SÜD Canada Inc. is accredited to ISO 17025 by A2LA with Testing Certificate #2955.02. The laboratory's current scope of accreditation listing can be found as listed on the A2LA website. All measuring equipment is calibrated on an annual or bi-annual basis as listed for each respective test.

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	


### ***Testing Environmental Conditions and Dates***

Following environmental conditions were recorded in the facility during time of testing

<b>Date</b>	<b>Test</b>	<b>Initials</b>	<b>Temperature (°C)</b>	<b>Humidity (%)</b>	<b>Pressure (kPa)</b>
2018/6/1,13	Radiated Emissions	MX	23.7 – 24.5	35.8 – 55.0	101.3 – 1021.
2018/6/4	Antenna Conducted Emissions	MX	23.7	52.8	100.6

Client	<b>Kapsch TrafficCom Canada Inc</b>	 Canada
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

## Detailed Test Results Section

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

## **Output Power and Antenna Heights**

### **Purpose**

The purpose of this test is to ensure that the maximum power conducted to the radiating element does not exceed the limits specified.

### **Limits**

The limits are defined in FCC Part 90.205 (l) and RSS 137 Clause 6.4 as per the following paragraph:

902-928 MHz. LMS systems operating pursuant to subpart M of this part in the 902-927.25 MHz band will be authorized a maximum of 30 watts ERP. LMS equipment operating in the 927.25-928 MHz band will be authorized a maximum of 300 watts ERP. ERP must be measured as peak envelope power. Antenna heights will be as specified in §90.353(h).

### **Results**

The EUT passed.

The EUT supports one protocols and operates only on a single channel. The EUT has a PCB antenna. Thus antenna height is not applicable.

Radiated measurements were performed because the antenna is a PCB trace; the antenna gain is not accurately known and due to the impedance mismatch between the spectrum analyzer and the modified unit with antenna connector. KDB 412172 is used to determine the ERP of the EUT from a measured field.

$$P = \frac{(E*d)^2}{30}$$

Where:

P is the EIRP in Watts


E is the Electric Field in V/m

d is distance is meters

$P(\text{dBm}) = E (\text{dBuV/m}) - 95.23$  for a measurement distance of 3 m.

and


$ERP = EIRP - 2.15$

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	


Frequency	Raw Reading (dBuV)	Antenna Factor (dB)	Attenuator Factor (dB)	Cable Factor (dB)	E-Field (dBuV/m)	ERP (dBm)	ERP (mW)
915	52.3	23.4	16.0	2.5	94.2	-3.2	0.5

### Graph(s)

The graph shown below are maximized peak measurement graphs measured with a resolution bandwidth greater OBW of the EUT over a full 0-360° and the polarity of the measuring antenna in the same polarity as the EUT’s antenna.



Date: 13.JUN.2018 20:35:39


Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

Note: See ‘Appendix B – EUT & Test Setup Photographs’ for photos showing the test set-up.

### Test Equipment List

Equipment	Model No.	Manufacturer	Last Calibration Date	Next Calibration Date	Asset #
Spectrum Analyzer	ESU 40	Rohde & Schwarz	Jan. 12, 2018	Jan. 12, 2020	GEMC 233
BiLog Antenna	3142-C	ETS	Oct. 5, 2016	Oct. 5, 2018	GEMC 8
Attenuator 10 dB	612-10-1	Meca Electronics, Inc	NCR	NCR	GEMC 224
Attenuator 6 dB	612-6-1	Meca Electronics, Inc	NCR	NCR	GEMC 286
RF Cable 10m	LMR-400-10M-50Ω-MN-MN	LexTec	NCR	NCR	GEMC 274
RF Cable 2m	Sucoflex 104A	Huber+Suhner	NCR	NCR	GEMC 271



Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

## **Occupied Bandwidth**

### **Purpose**

The purpose of this test is to ensure that the bandwidth occupied exceeds a stated minimum. This helps ensure the utilization of the frequency allocation is sufficiently wide. This also helps prevent corruption of data by ensuring adequate data separation to distinguish the reception of the intended information.

### **Limits**


The Limit is as specified in FCC Part 90.209 and RSS-137 Clause 6.1.2.

The maximum authorized bandwidth shall be 12 MHz for non-multilateration LMS operations in the band 909.75-921.75 MHz and 2 MHz in the band 902.00-904.00 MHz. The maximum authorized bandwidth for multilateration LMS operations shall be 5.75 MHz in the 904.00-909.75 MHz band; 2 MHz in the 919.5-921.75 MHz band; 5.75 MHz in the 921.75-927.25 MHz band and its associated 927.25-927.50 MHz narrowband forward link; and 8.00 MHz if the 919.75-921.75 MHz and 921.75-927.25 MHz bands and their associated 927.25-927.50 MHz and 927.50-927.75 MHz narrowband forward links are aggregated.

### **Results**

The EUT passed


Frequency (MHz)	99% Bandwidth (MHz)	20 dB BW (MHz)
915.0	7.67	5.10

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	


**Graph(s)**

The graphs showed below shows the OBW during the operation of the device. This is measured by a max hold on the spectrum analyzer and the highest resolution bandwidth that is sufficiently low to exhibit the 99% bandwidth of a channel during operation of the EUT. This measurement is a peak measurement. Max hold is performed for a duration of not less than 1 minute


**99 % Bandwidth**



Date: 4.JUN.2018 12:01:19

Client	<b>Kapsch TrafficCom Canada Inc</b>	 TÜV SÜD Canada
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

### 20 dB Bandwidth




Date: 4.JUN.2018 10:49:12

Note: See 'Appendix B – EUT & Test Setup Photographs' for photos showing the test set-up.

### Test Equipment List

Equipment	Model No.	Manufacturer	Last Calibration Date	Next Calibration Date	Asset #
Spectrum Analyzer	FSU26	Rohde & Schwarz	Feb 15, 2017	Feb 15, 2019	GEMC 232
Attenuator 10 dB	612-10-1	Meca Electronics, Inc	NCR	NCR	GEMC 224

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

## **Emission Mask**

### **Purpose**

The purpose of this test is to ensure that the maximum power conducted to the radiating element at frequencies outside of the authorized spectrum does not exceed the limits specified. This ensures that the only the intended signal is delivered to the radiating element.

### **Limits**

The Limit is as specified in FCC Part 90.210 (K) and RSS-137 Clause 6.5.3

Emission Mask K—(1) Wideband multilateration transmitters. For transmitters authorized under subpart M to provide forward or reverse links in a multilateration system in the subbands 904-909.75 MHz, 921.75-927.25 MHz and 919.75-921.75 MHz, and which transmit an emission occupying more than 50 kHz bandwidth: in any 100 kHz band, the center frequency of which is removed from the center of authorized sub-band(s) by more than 50 percent of the authorized bandwidth, the power of emissions shall be attenuated below the transmitter output power, as specified by the following equation, but in no case less than 31 dB:

$$A=16+0.4 (D-50)+10 \log B \text{ (attenuation greater than 66 dB is not required)}$$


Where:

- A = attenuation (in decibels) below the maximum permitted output power level
- D = displacement of the center frequency of the measurement bandwidth from the center frequency of the authorized sub-band, expressed as a percentage of the authorized bandwidth B
- B = authorized bandwidth in megahertz.

(2) Narrowband forward link transmitters. For LMS multilateration narrowband forward link transmitters operating in the 927.25-928 MHz frequency band the power of any emission shall be attenuated below the transmitter output power (P) in accordance with following schedule:

On any frequency outside the authorized sub-band and removed from the edge of the authorized sub-band by a displacement frequency ( $f_d$  in kHz): at least  $116 \log ((f_d+10)/6.1)$  dB or  $50 + 10 \log (P)$  dB or 70 dB, whichever is the lesser attenuation.

(3) Other transmitters. For all other transmitters authorized under subpart M that operate in the 902-928 MHz band, the peak power of any emission shall be attenuated below the power of the highest emission contained within the licensee's sub-band in accordance with the following schedule:

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

- (i) On any frequency within the authorized bandwidth: Zero dB.
- (ii) On any frequency outside the licensee's sub-band edges:  $55 + 10 \log(P)$  dB, where (P) is the highest emission (watts) of the transmitter inside the licensee's sub-band.

(4) In the 902-928 MHz band, the resolution bandwidth of the instrumentation used to measure the emission power shall be 100 kHz, except that, in regard to paragraph (2) of this section, a minimum spectrum analyzer resolution bandwidth of 300 Hz shall be used for measurement center frequencies with 1 MHz of the edge of the authorized subband. The video filter bandwidth shall not be less than the resolution bandwidth.

(5) Emission power shall be measured in peak values.

(6) The LMS sub-band edges for non-multilateration systems for which emissions must be attenuated are 902.00, 904.00, 909.5 and 921.75 MHz.

Note: The EUT is a non- multilateration LMS transmitter. Emission limit (3) applies to the EUT. A  $55 + 10 \log(P)$  dB attenuation (or -25 dBm absolute emission level) was applied all frequency from the outside authorized band.


Test procedure is as per eCFR 47 Part 2 Clause 2.1051.

## Results

The EUT passed; it meets attenuation requirement at the antenna port.

The worst case is presented as a graph for the spectrum. Band edge requirements were shown for the lower band edge at 909.5 MHz in the low band where applicable. Band edge requirements were also shown for the higher band edge at 921.75 MHz in the high band where applicable.


Note: All measurements were made with an attenuator as appropriate to the measurement. The insertion loss were adjusted with Reference Level Offset function in the spectrum analyzer.

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	


### Graph(s)

The graphs shown below shows the peak power output of the device during the antenna conducted measurement during transmit operation of the EUT.


#### 30 MHz – 10 GHz



Date: 4.JUN.2018 11:43:30


Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

### Band Edge



Date: 4.JUN.2018 12:58:52


See 'Appendix B – EUT & Test Setup Photographs' for photos showing the test set-up.

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

### Test Equipment List

Equipment	Model No.	Manufacturer	Last Calibration Date	Next Calibration Date	Asset #
Spectrum Analyzer	FSU26	Rohde & Schwarz	Feb 15, 2017	Feb 15, 2019	GEMC 232
Attenuator 10 dB	612-10-1	Meca Electronics, Inc	NCR	NCR	GEMC 224



Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

## ***Transmitter Spurious Radiated Emissions***

### **Purpose**

The purpose of this test is to ensure that the RF energy unintentionally emitted from the EUT does not exceed the limits listed below as defined in the applicable test standard, as measured from a receiving antenna. This helps protect broadcast radio services such as television, FM radio, pagers, cellular telephones, emergency services, and so on, from unwanted interference.

### **Limit(s) and Method**

The method is as defined in FCC 2.1053 and the limits are as defined in FCC Part 90.210(K).

(3) *Other transmitters.* For all other transmitters authorized under subpart M that operate in the 902-928 MHz band, the peak power of any emission shall be attenuated below the power of the highest emission contained within the licensee's sub-band in accordance with the following schedule:

(i) On any frequency within the authorized bandwidth: Zero dB.

(ii) On any frequency outside the licensee's sub-band edges:  $55 + 10 \log(P)$  dB, where (P) is the highest emission (watts) of the transmitter inside the licensee's sub-band.

Spurious radiated emissions of the EUT was performed at 3 meters. The limit specified in FCC 90.210 (K) is  $55 + 10 \log(P)$  dBc. For all intensive purpose, the limit is -25 dBm. The field strength limit for the EUT is give in the below:

$$E(\text{dB}\mu\text{V/m}) = \text{ERIP}(\text{dBm}) + 95.2$$


$$\text{Where EIRP} = \text{ERP} + 2.15$$

$$E(\text{dB}\mu\text{V/m}) = \text{ERP} (\text{dBm}) + 97.35$$


$$E(\text{dB}\mu\text{V/m}) = -25 \text{ dBm} + 97.35 = 72.35 \text{ dBuV}$$

This limit is applicable all emission at 3 meter measurement distance.

The Limit is with 100 kHz measurement bandwidth and using a Peak detector.

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

### Typical Radiated Emissions Setup



### Measurement Uncertainty


The expanded measurement uncertainty is calculated in accordance with CISPR 16-4-2 and is +/-4.4 dB with a 'k=2' coverage factor and a 95% confidence level.

### Preliminary Graphs


Note the graphs shown below are for graphical illustration only. For final measurements with the appropriate detector, please refer to the final measurement table where applicable. The graph shown below is a maximized peak measurement graph, measured with a resolution bandwidth greater than the final required detector and over a full 0-360 rotation. This peaking process is done as a worst case measurement. This process enables the detection of frequencies of concern for final measurement, and provides considerable time savings.


The device was scanned to the 10<sup>th</sup> harmonic (a minimum of a 10 GHz).

The measured radiation includes the emissions from the reader being used to control the EUT.


Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

### Vertical – Peak Emission Graph 30 MHz – 1 GHz




Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	


**Vertical – Peak Emission Graph  
1 GHz – 10 GHz**




© TÜV SÜD Canada Inc. This test report shall not be reproduced except in full, without written approval of TÜV SÜD Canada Inc


Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	


### Horizontal – Peak Emission Graph 30 MHz – 1 GHz



Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

### Horizontal – Peak Emission Graph 1 GHz – 10 GHz



Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

## Results


Pass.

The EUT meets the Transmitter Spurious Radiated Emissions requirements.

All scan were perform with a measurement bandwidth greater than the required bandwidth.  
No peak emissions were above the limit.

## Test Equipment List

Equipment	Model No.	Manufacturer	Last Calibration Date	Next Calibration Date	Asset #
Spectrum Analyzer	ESU 40	Rohde & Schwarz	Jan. 12, 2018	Jan. 12, 2020	GEMC 233
BiLog Antenna	3142-C	ETS	Oct. 5, 2016	Oct. 5, 2018	GEMC 8
Horn Antenna 1 – 18 GHz	AH-118	Com-Power Corporation	July 12, 2017	July 12, 2019	GEMC 214
Band Reject Filter	BRC50722	Micro-Tronics	Apr 9, 2016	Apr 9, 2017	GEMC 186
1.2 GHz High pass filter	5IH30-1078	K & L Microwave	NCR	NCR	GEMC 118
Attenuator 10 dB	612-10-1	Meca Electronics, Inc	NCR	NCR	GEMC 224
Attenuator 6 dB	612-6-1	Meca Electronics, Inc	NCR	NCR	GEMC 286
Pre-Amp 9 kHz – 1 GHz	CPA9231A	Chase	Oct 12, 2016	Oct 12, 2018	GEMC 6403
Pre-Amp 1 – 26.5 GHz	HP 8449B	HP	Jun. 12, 2018	Jun. 12, 2020	GEMC 312
RF Cable 10m	LMR-400-10M-50Ω-MN-MN	LexTec	NCR	NCR	GEMC 274
RF Cable 2m	Sucoflex 104A	Huber+Suhner	NCR	NCR	GEMC 271
Emissions Software	0.1.97	TUV SUD Canada, Inc	NCR	NCR	GEMC 58

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

## ***Temperature Frequency Stability***

### **Purpose**

The purpose of this test is to ensure that the RF energy unintentionally emitted from the EUT does not exceed the permitted bandwidth during extreme temperature variations. This helps protect radio broadcasts and receivers with spectrum nearby to the equipment under test from unwanted interference. This also helps ensure proper reception of the intended signal by ensuring the transmit frequency is correct in any temperature.

### **Limit(s) and Method**

The methods are given in FCC Part 2.1055. There limits given in FCC Part 90.213.

However, the device meets the following condition:

Fixed non-multilateration transmitters with an authorized bandwidth that is more than 40 kHz from the band edge, intermittently operated hand-held readers, and mobile transponders are not subject to frequency tolerance restrictions.

The EUT is an intermittently operated hand-held reader and therefore is not subject to frequency tolerance restrictions. The test was performed for information purpose.


Frequency tolerances measurements are taken for information purpose. Frequency must be maintained from -30 C to +50 C. The EUT is monitored at each 10 degree increment. At each temperature, the device is checked after a stabilization period required for the device to reach the temperature.

### **Measurements**

The worst case results are presented, with the frequency shown. The device was checked at each 10 degree increment of temperature


Temperature	Measured Frequency	Frequency Drift (PPM)
-30	915.118509615	-100.16
-20	915.135336538	-81.77
-10	915.153285256	-62.16
0	915.166185897	-48.07
10	915.181923077	-30.87
20	915.210176282	0.00
30	915.197804487	-13.52
40	915.194150641	-17.51
50	915.190625000	-21.36




Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

### Test Equipment List

Equipment	Model No.	Manufacturer	Last Calibration Date	Next Calibration Date	Asset #
Spectrum Analyzer	FSU26	Rohde & Schwarz	Feb 15, 2017	Feb 15, 2019	GEMC 232
Attenuator 10 dB	612-10-1	Meca Electronics, Inc	NCR	NCR	GEMC 224
Environmental Chamber	SM-32-7800	Thermotron	NCR	NCR	GEMC 153

Client	<b>Kapsch TrafficCom Canada Inc</b>	 Canada
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	


## Appendix A – EUT Summary

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

For further details for filing purposes, refer to filing package.

### General EUT Description

Client Details	
Organization / Address	Kapsch TrafficCom Canada Inc 6020 Ambler Drive, Mississauga, Ontario, Canada, L4W 1P1
Contact	Alastair Malarky
Phone	905-624-3020, x 1203
Email	alastair.malarky@kapsch.net
EUT (Equipment Under Test) Details	
EUT Name (for report title)	JANUS™ Interior OBU Family
EUT Model / SN (if known)	2 models 8021660B-TAB and 801970B-TAB  see "801660B Model Differences" for full family
EUT revision	New product
Software version	N/A
Equipment category	902-928 MHz, LMS Non-multilateration, mobile transponder
EUT is powered using	Battery 3.6V Internal to EUT
Transmits RF energy? (describe)	Yes 902-928 MHz, LMS Non-multilateration Listen before Talk - Triggered by part 90 licensed reader Transmits fixed frequency 915 +/- 0.6 MHz Transmits burst OOK Manchester, 500 kbps Internal antenna Rated -3 dBm ERP max
Testing is required for the following standards	FCC 90 LMS Non-multi-lateration, RSS-137
Basic EUT functionality description	Devicer responds to specific RF free-space signal (receive) signal and radiates (transmits) short burt of 915 MHz manchester encoded RF free-space signal.

Client	<b>Kapsch TrafficCom Canada Inc</b>	
Product	<b>JANUS™ Interior OBU Family</b>	
Standard(s)	RSS 137 Issue 2:2009 FCC Part 90 Subpart M:2015	

High level block diagram of EUT (attachment)	See 801660B - Exhibit 04 - Block Diagram
Step by step instructions for setup and operation	see "801660B Test Article Modifications and Instructions" attached
Customer to setup EUT on site?	Yes The EUT requires no setup. The EUT triggering requires setup - see "801660B Test Article Modifications and Instructions" attached
Frequency of all clocks present in EUT	See 801660B - Exhibit 12 - Operating Description
Peripherals required to exercise EUT Ex. Signal generator	Signal generator capable of 20us RF pulses, 133 Hz rate, at 915.75 MHz, Conducted Level $\geq -8$ dBm Radiated source level $\sim +40$ dBm at 3m
Dimensions of product	L 93 mm W 49 mm H 24 mm

Note the EUT is considered to have been received the date of the commencement of the first test, unless otherwise stated. For a close-up picture of the EUT, see ‘Appendix B – EUT and Test Setup Photos’.