

ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT

INTENTIONAL RADIATOR CERTIFICATION TO FCC PART 15 SUBPART C REQUIREMENT

OF

Product name: Car Alarm System

Model Name: JRMTX306

FCC ID: JRMTX306

REPORT NO: ER/2004/80009

ISSUE DATE: Aug. 16, 2004

FCC Rule Part: §15.231

Prepared for Micro Alarm System

4825 Soto Street, Vernon California, CA
90058, U.S.A.

Prepared by SGS Taiwan Ltd.

No. 134, Wu Kung Rd., Wuku Industrial
Zone, Taipei County, Taiwan.

Note: This report shall not be reproduced except in full, without the written approval of SGS Taiwan Ltd. This document may be altered or revised by SGS Taiwan Ltd. personnel only, and shall be noted in the revision section of the document.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Taiwan Ltd. No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei Country, Taiwan. / 台北縣五股工業區五工路136之1號
台灣檢驗科技股份有限公司 t (886-2) 2299-3939 f (886-2) 2298-2698 www.sgs.com.tw

VERIFICATION OF COMPLIANCE

Applicant: Micro Alarm System
4825 Soto Street, Vernon California, CA 90058, U.S.A.

Product Description: Car Alarm System

FCC ID Number: JRMTX306

Brand Name: MICRO INTERNET

Model No.: JRMTX306

Model Difference: N/A

File Number: ER/2004/80009

Date of test: Aug 01, 2004 ~ Aug 10, 2004


Date of receive: Aug 01, 2004

We hereby certify that:

The above equipment was tested by SGS Taiwan Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2001) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.231.

The test results of this report relate only to the tested sample identified in this report.

Test By:



Date

Aug. 26, 2004

Alex Hsieh

Approved By



Date

Aug. 26, 2004

Vincent Su

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Version

| Version No. | Date |
|-------------|---------------|
| 00 | Aug. 26, 2004 |
| | |
| | |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Table of Contents

| | |
|--------------------------------------------------------------------|-----------|
| 1. GENERAL INFORMATION | 6 |
| 1.1 PRODUCT DESCRIPTION | 6 |
| 1.2 RELATED SUBMITTAL(S) / GRANT (S) | 6 |
| 1.3 TEST METHODOLOGY..... | 6 |
| 1.4 TEST FACILITY | 6 |
| 2. SYSTEM TEST CONFIGURATION | 7 |
| 2.1 EUT CONFIGURATION..... | 7 |
| 2.2 EUT EXERCISE | 7 |
| 2.3 TEST PROCEDURE..... | 7 |
| 2.4 LIMITATION | 8 |
| 2.5 CONFIGURATION OF TESTED SYSTEM | 10 |
| 3. SUMMARY OF TEST RESULTS | 11 |
| 4. DESCRIPTION OF TEST MODES | 11 |
| 5. CONDUCTED EMISSIONS TEST (NOT APPLY IN THE REPORT) | 12 |
| 5.1 MEASUREMENT PROCEDURE: | 12 |
| 5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 12 |
| 5.3 MEASUREMENT EQUIPMENT USED: | 12 |
| 5.4 MEASUREMENT RESULT: | 12 |
| 6. RADIATED EMISSION TEST | 13 |
| 6.1 MEASUREMENT PROCEDURE..... | 13 |
| 6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 13 |
| 6.3 MEASUREMENT EQUIPMENT USED: | 14 |
| 6.4 FIELD STRENGTH CALCULATION | 14 |
| 6.5 MEASUREMENT RESULT | 15 |
| 7. OCCUPIED BANDWIDTH..... | 19 |
| 7.1 MEASUREMENT PROCEDURE..... | 19 |
| 7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 19 |
| 7.3 MEASUREMENT EQUIPMENT USED: | 19 |
| 7.4 MEASUREMENT RESULTS..... | 19 |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

| | | |
|-----------|----------------------------------------------------|-----------|
| 8. | DUTY CYCLE MEASUREMENT | 21 |
| 8.1 | MEASUREMENT PROCEDURE..... | 21 |
| 8.2 | TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 21 |
| 8.3 | MEASUREMENT EQUIPMENT USED: | 21 |
| 8.4 | MEASUREMENT RESULTS:..... | 21 |
| 9. | RELEASE TIME MEASUREMENT: | 24 |
| 9.1 | MEASUREMENT PROCEDURE..... | 24 |
| 9.2 | TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 24 |
| 9.3 | MEASUREMENT EQUIPMENT USED: | 24 |
| 9.4 | MEASUREMENT RESULTS..... | 24 |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1. GENERAL INFORMATION

1.1 Product Description

The Micro Alarm System, Model: JRMTX306 (referred to as the EUT in this report) is a Car Alarm System.

A major technical descriptions of EUT is described as following:

- A). Operation Frequency: 310 MHz
- B). Modulation: Pulse Modulation
- C). Antenna Designation: Non-User Replaceable (Fixed)
- D). Power Supply: 12 Vdc from battery.
- E). Transmitting Time: Periodic \leq 5 seconds

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **JRMTX306** filing to comply with Section 15.231 of the FCC Part 15, Subpart C Rules. The composite system (receiver) is compliance with Subpart B is authorized under a DoC procedure.

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (2001). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the address of SGS Taiwan Ltd. No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei Country, Taiwan. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2001 and CISPR 22/EN 55022 requirements. Site No. 1(3 &10 meters) Registration Number: 94644, Anechoic chamber (3 meters) Registration Number: 573967

1.5 Special Accessories

Not available for this EUT intended for grant.

1.6 Equipment Modifications

Not available for this EUT intended for grant.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. the Tx frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions (Not apply in the report)

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4-2001. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2001.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.4 Limitation

(1) Conducted Emission (Not applicable in this report)

According to section 15.207(a) Conducted Emission Limits is as following.

| Frequency range MHz | Limits dB (uV) | |
|------------------------|-------------------|----------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

Note

- 1.The lower limit shall apply at the transition frequencies
- 2.The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

(2) Radiated Emission

According to 15.231(b), the field strength of emissions from Intentional Radiators operated under this section shall not exceed the following:

| Fundamental Frequency (MHz) | Field Strength of Fundamental | | Field Strength of Spurious | |
|-----------------------------|-------------------------------|------------------|----------------------------|--------------|
| | (dBuV/m) | (uV/m) | (dBuV/m) | (uV/m) |
| 40.66 - 40.70 | 67.04 | 2,250 | 40 | 100 |
| 70 - 130 | 61.94 | 1,250 | 34 | 50 |
| 130 - 174 | * 61.94 - 71.48 | * 1,250 - 3,750 | * 34 - 43.5 | * 50 to 150 |
| 174 - 260 | 71.48 | 3,750 | 43.5 | 150 |
| 260 - 470 | * 71.48 - 81.94 | * 3,750 - 12,500 | * 43.5 - 54 | * 150 to 500 |
| above 470 | 81.94 | 12,500 | 74 | 500 |

Remark: 1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of ξ 15.205
4. Emission spurious frequency which appearing within the Restricted Bands specified in provision of ξ 15.205, then the general radiated emission limits in ξ 15.209 apply.
5. For the band 130-174MHz, uV/m at 3meters = $56.81818(F) - 6136.3636$;
For the band 260-470MHz uV/m at 3meters = $41.6667(F) - 7083.3333$;
Where F is the frequency in MHz.
6. $310\text{MHz limit} = 41.6667 * 310 - 7083.3333 = 5833.3437 \text{ uV/m}$
 $= 75.3\text{dBuV/m}$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.5 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

| Item | Equipment | Mfr/Brand | Model/ Type No. | FCC ID | Series No. | Data Cable | Power Cord |
|------|-----------|-----------|--------------------|--------|------------|------------|------------|
| 1. | | | | | | | |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

3. Summary Of Test Results

| FCC Rules | Description Of Test | Result |
|---------------|------------------------------------|-----------|
| §15.207 | Conducted Emission | N/A |
| §15.231 | Radiated Emission | Compliant |
| §15.231(c) | 20dB Bandwidth | Compliant |
| | Duty Cycle Test (Pulse Modulation) | Compliant |
| §15.231(a)(1) | Release Time Measurement | Compliant |

4. Description of test modes

The EUT has been tested under engineering test mode condition. and the EUT staying in continuous transmitting mode.

The Frequency 310MHz is chosen for testing.

The X, Y and Z-axis of EUT were pre-test; X and Y mode were the worse case and report.


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

5. Conducted Emissions Test (Not apply in the report)

5.1 Measurement Procedure:

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

5.2 Test SET-UP (Block Diagram of Configuration)



5.3 Measurement Equipment Used:

| Conducted Emission Test Site | | | | | |
|------------------------------|------------|-------------------------|--------------------------|----------------------|-----------------|
| EQUIPMENT TYPE | MFR | MODEL NUMBER | SERIAL NUMBER | LAST CAL. | CAL DUE. |
| EMC Analyzer | HP | 8594EM | 3624A00203 | 12/31/2003 | 12/30/2004 |
| EMI Test Receiver | R&S | ESCS30 | 828985/004 | 01/15/2004 | 01/14/2005 |
| LISN | Rolf-Heine | NNB-2/16Z | 99012 | 12/30/2003 | 12/29/2004 |
| LISN | Rolf-Heine | NNB-2/16Z | 99013 | 11/06/2003 | 11/05/2004 |

5.4 Measurement Result:

N/A

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


6. Radiated Emission Test

6.1 Measurement Procedure


1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured were complete.

6.2 Test SET-UP (Block Diagram of Configuration)

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

6.3 Measurement Equipment Used:

| 966 Chamber | | | | | |
|-------------------|---------------|---------------------|---------------|------------|------------|
| EQUIPMENT TYPE | MFR | MODEL NUMBER | SERIAL NUMBER | LAST CAL. | CAL DUE. |
| Spectrum Analyzer | R&S | FSP 40 | 100034 | 05/27/2004 | 05/26/2005 |
| Spectrum Analyzer | Agilent | E7405A | US41160416 | 08/27/2003 | 08/27/2004 |
| Bilog Antenna | SCHWAZBECK | VULB9163 | 152 | 06/03/2004 | 06/02/2005 |
| Bilog Antenna | SCHWAZBECK | VULB9160 | | 06/03/2004 | 06/02/2005 |
| Horn Antenna | SCHWAZBECK | BBHA 9120D | 309/320 | 08/16/2003 | 08/15/2004 |
| Pre-Amplifier | HP | 8447D | 2944A09469 | 07/19/2004 | 07/18/2005 |
| Pre-Amplifier | HP | 8449B | 3008A00578 | 02/26/2004 | 02/25/2005 |
| Turn Table | HD | DT420 | N/A | N.C.R | N.C.R |
| Antenna Tower | HD | MA240-N | 240/657 | N.C.R | N.C.R |
| Controller | HD | HD100 | N/A | N.C.R | N.C.R |
| Low Loss Cable | HUBER+SUHNE R | SUCOFLEX 104PEA-10M | 10m | 10/9/2003 | 10/08/2004 |
| Low Loss Cable | HUBER+SUHNE R | SUCOFLEX 104PEA-3M | 3m | 10/9/2003 | 10/08/2004 |
| Site NSA | SGS | 966 chamber | N/A | 11/17/2003 | 11/16/2004 |
| Site NSA | SGS | 10m Open-Site | N/A | 10/02/2003 | 10/01/2004 |

6.4 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Average Value = Peak Value + 20 Log (Ton/Tp) Pulse Modulation

| | | |
|-------|------------------------|--------------------------------------------|
| Where | FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| | RA = Reading Amplitude | AG = Amplifier Gain |
| | AF = Antenna Factor | |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

6.5 Measurement Result

Operation Mode: Transmitting Mode

Test Date: Aug. 10, 2004

Fundamental Frequency: 310 MHz X mode

Test By: Alex

Temperature : 25

Pol: Vertical

Humidity : 65 %

Judgement : Passed by -22.94 dB at 1860 MHz Ant.Pol. Ver EUT Axis X

| Freq. (MHz) | F (MHz) | Ant.Pol. /S | Reading (dBuV) | Peak | | AV | | Peak | | AV | | Margin (dB) |
|----------------|------------|----------------|-------------------|--------------------------|--------|-------------------|-------------------|-------------------|-------------------|--------|----|----------------|
| | | | | Correct Ant./CL dB | CF(dB) | Level (dBuV/m) | Level (dBuV/m) | Limit (dBuV/m) | Limit (dBuV/m) | | | |
| 310.0 | F | V | 60.30 | - 6.38 | -13.09 | 47.21 | 40.83 | 95.30 | 75.30 | -34.47 | AV | |
| 620.0 | S | V | 42.25 | - 6.38 | -7.16 | 35.09 | 28.71 | 75.30 | 55.30 | -26.59 | AV | |
| 930.0 | S | V | -- | - 6.38 | -- | -- | -- | 75.30 | 55.30 | | | |
| 1240.0 | *S | V | -- | - 6.38 | -- | -- | -- | 74.00 | 54.00 | | | |
| 1550.0 | *S | V | -- | - 6.38 | -- | -- | -- | 74.00 | 54.00 | | | |
| 1860.0 | S | V | 44.46 | - 6.38 | - 5.72 | 38.74 | 32.36 | 75.30 | 55.30 | -22.94 | AV | |
| 2170.0 | S | V | -- | - 6.38 | -- | -- | -- | 75.30 | 55.30 | | | |
| 2480.0 | S | V | -- | - 6.38 | -- | -- | -- | 75.30 | 55.30 | | | |
| 2790.0 | *S | V | -- | - 6.38 | -- | -- | -- | 74.00 | 54.00 | | | |
| 3100.0 | S | V | -- | - 6.38 | -- | -- | -- | 75.30 | 55.30 | | | |

Remark :

- (1) + F/S F : denotes Fundamental Frequency ; S : denotes Spurious Frequency
- (2) EUT Orthogonal Axes : X denotes Laid on Table ; Y denotes Vertical Stand .
- (3) Measuring frequencies from 30 MHz to the 10th harmonic of fundamental frequency of 310 MHz.
- (4) Dates of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) * Denotes spurious frequency, which falls within the Restricted Bands specified in provision of $\xi 15.205$, then the general radiated emission limits in $\xi 15.209$ apply.
- (6) Peak Setting: 30MHz – 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.
1GHz- 5GHz, RBW= 1MHz, VBW= 1MHz, Sweep time= 200 ms

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operation Mode: Transmitting Mode

Test Date: Aug. 10, 2004

Fundamental Frequency: 310MHz X mode

Test By: Alex

Temperature : 25

Pol: Horizontal

Humidity : 65 %

Judgement : Passed by -5.11 dB at 1860 MHz Ant.Pol. Hor EUT Axis X

| Freq. (MHz) | F /S | Ant.Pol. (H/V) | Reading (dBuV) | Peak | | AV | | Peak | | AV | | Peak | | AV | |
|----------------|---------|-------------------|-------------------|---------------|-------------------|-------------------|-------------------|-------------------|-------------------|----------------|----|------|--|----|--|
| | | | | Correct dB | Ant./CL CF(dB) | Level (dBuV/m) | Level (dBuV/m) | Limit (dBuV/m) | Limit (dBuV/m) | Margin (dB) | | | | | |
| 310.0 | F | H | 78.25 | - 6.38 | -13.09 | 65.16 | 58.78 | 95.30 | 75.30 | -16.52 | AV | | | | |
| 620.0 | S | H | 55.59 | - 6.38 | -7.16 | 48.43 | 42.05 | 75.30 | 55.30 | -13.25 | AV | | | | |
| 930.0 | S | H | 36.38 | - 6.38 | - 1.92 | 34.46 | 28.08 | 75.30 | 55.30 | -27.22 | AV | | | | |
| 1240.0 | *S | H | 47.77 | - 6.38 | - 8.42 | 39.35 | 32.97 | 74.00 | 54.00 | -21.03 | AV | | | | |
| 1550.0 | *S | H | 58.24 | - 6.38 | - 7.02 | 51.22 | 44.84 | 74.00 | 54.00 | -9.16 | AV | | | | |
| 1860.0 | S | H | 62.29 | - 6.38 | - 5.72 | 56.57 | 50.19 | 75.30 | 55.30 | -5.11 | AV | | | | |
| 2170.0 | S | H | 56.16 | - 6.38 | - 4.39 | 51.77 | 45.39 | 75.30 | 55.30 | -9.91 | AV | | | | |
| 2480.0 | S | H | -- | - 6.38 | -- | -- | -- | 75.30 | 55.30 | | | | | | |
| 2790.0 | *S | H | -- | - 6.38 | -- | -- | -- | 74.00 | 54.00 | | | | | | |
| 3100.0 | S | H | -- | - 6.38 | -- | -- | -- | 75.30 | 55.30 | | | | | | |

Remark :

(1) + F/S F : denotes Fundamental Frequency ; S : denotes Spurious Frequency

(2) EUT Orthogonal Axes : X denotes Laid on Table ; Y denotes Vertical Stand .

(3) Measuring frequencies from 30 MHz to the 10th harmonic of fundamental frequency of 310 MHz.

(4) Dates of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

(5) * Denotes spurious frequency, which falls within the Restricted Bands specified in provision of $\xi 15.205$, then the general radiated emission limits in $\xi 15.209$ apply.

(6) Peak Setting: 30MHz – 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.
1GHz- 5GHz, RBW= 1MHz, VBW= 1MHz, Sweep time= 200 ms

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operation Mode: Transmitting Mode Test Date: Aug. 10, 2004
 Fundamental Frequency: 310MHz Y mode Test By: Alex
 Temperature : 25 Pol: Vertical
 Humidity : 65 %
 Judgement : Passed by -5.14 dB at 1860 MHz Ant.Pol. Ver EUT Axis Y

| Freq. (MHz) | F /S | Ant.Pol. (H/V) | Reading (dBuV) | Peak | AV | Peak | AV | Peak | AV | Margin (dB) |
|----------------|---------|-------------------|-------------------|---------------|-------------------|-------------------|-------------------|-------------------|-------------------|----------------|
| | | | | Correct dB | Ant./CL CF(dB) | Level (dBuV/m) | Level (dBuV/m) | Limit (dBuV/m) | Limit (dBuV/m) | |
| 310.0 | F | V | 77.30 | - 6.38 | -13.09 | 64.21 | 57.83 | 95.30 | 75.30 | -17.47 |
| 620.0 | S | V | 55.11 | - 6.38 | -7.16 | 47.95 | 41.57 | 75.30 | 55.30 | -13.73 |
| 930.0 | S | V | 35.65 | - 6.38 | - 1.92 | 33.73 | 27.35 | 75.30 | 55.30 | -27.95 |
| 1240.0 | *S | V | -- | - 6.38 | -- | -- | -- | 74.00 | 54.00 | |
| 1550.0 | *S | V | 51.79 | - 6.38 | - 7.02 | 44.77 | 38.39 | 74.00 | 54.00 | -15.61 |
| 1860.0 | S | V | 62.26 | - 6.38 | - 5.72 | 56.54 | 50.16 | 75.30 | 55.30 | -5.14 |
| 2170.0 | S | V | 58.31 | - 6.38 | - 4.39 | 53.92 | 47.54 | 75.30 | 55.30 | -7.76 |
| 2480.0 | S | V | -- | - 6.38 | -- | -- | -- | 75.30 | 55.30 | |
| 2790.0 | *S | V | -- | - 6.38 | -- | -- | -- | 74.00 | 54.00 | |
| 3100.0 | S | V | -- | - 6.38 | -- | -- | -- | 75.30 | 55.30 | |

Remark :

- (1) + F/S F : denotes Fundamental Frequency ; S : denotes Spurious Frequency
- (2) EUT Orthogonal Axes : X denotes Laid on Table ; Y denotes Vertical Stand .
- (3) Measuring frequencies from 30 MHz to the 10th harmonic of fundamental frequency of 310 MHz.
- (4) Dates of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) * Denotes spurious frequency, which falls within the Restricted Bands specified in provision of ξ15.205, then the general radiated emission limits in ξ 15.209 apply.
- (6) Peak Setting: 30MHz – 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.
1GHz- 5GHz, RBW= 1MHz, VBW= 1MHz, Sweep time= 200 ms

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operation Mode: Transmitting Mode

Test Date: Aug. 10, 2004

Fundamental Frequency: 310 MHz Y mode

Test By: Alex

Temperature : 25

Pol: Horizontal

Humidity : 65 %

Judgement : Passed by -7.3 dB at 1860 MHz Ant.Pol. Hor EUT Axis Y

| Freq. (MHz) | F /S | Ant.Pol. (H/V) | Reading (dBuV) | Peak | AV | Peak | AV | Peak | AV | Margin (dB) |
|----------------|---------|-------------------|-------------------|---------------|-------------------|-------------------|-------------------|-------------------|-------------------|----------------|
| | | | | Correct dB | Ant./CL CF(dB) | Level (dBuV/m) | Level (dBuV/m) | Limit (dBuV/m) | Limit (dBuV/m) | |
| 310.0 | F | H | 65.67 | - 6.38 | -13.09 | 52.58 | 46.20 | 95.30 | 75.30 | -29.10 AV |
| 620.0 | S | H | 46.15 | - 6.38 | -7.16 | 38.99 | 32.61 | 75.30 | 55.30 | -22.69 AV |
| 930.0 | S | H | -- | - 6.38 | -- | -- | -- | 74.00 | 54.00 | |
| 1240.0 | *S | H | 47.11 | - 6.38 | -8.42 | 38.69 | 32.31 | 74.00 | 54.00 | -21.69 AV |
| 1550.0 | *S | H | 55.67 | - 6.38 | -8.42 | 47.25 | 40.87 | 74.00 | 54.00 | -13.13 AV |
| 1860.0 | S | H | 62.80 | - 6.38 | -8.42 | 54.38 | 48.00 | 75.30 | 55.30 | -7.30 AV |
| 2170.0 | S | H | 57.77 | - 6.38 | -8.42 | 49.35 | 42.97 | 75.30 | 55.30 | -12.33 AV |
| 2480.0 | S | H | -- | - 6.38 | -- | -- | -- | 75.30 | 55.30 | |
| 2790.0 | *S | H | -- | - 6.38 | -- | -- | -- | 74.00 | 54.00 | |
| 3100.0 | S | H | -- | - 6.38 | -- | -- | -- | 75.30 | 55.30 | |

Remark :

- (1) + F/S F : denotes Fundamental Frequency ; S : denotes Spurious Frequency
- (2) EUT Orthogonal Axes : X denotes Laid on Table ; Y denotes Vertical Stand .
- (3) Measuring frequencies from 30 MHz to the 10th harmonic of fundamental frequency of 310 MHz.
- (4) Dates of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) * Denotes spurious frequency, which falls within the Restricted Bands specified in provision of $\xi 15.205$, then the general radiated emission limits in $\xi 15.209$ apply.
- (6) Peak Setting: 30MHz – 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.
1GHz- 5GHz, RBW= 1MHz, VBW= 1MHz, Sweep time= 200 ms

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

7. Occupied Bandwidth

7.1 Measurement Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Set EUT as normal operation
3. Set SPA Center Frequency = fundamental frequency, RBW, VBW= 10KHz, Span =1MHz.
4. Set SPA Max hold. Mark peak, -20dB.

7.2 Test SET-UP (Block Diagram of Configuration)

Same as 6.3 Radiated Emission Measurement.

7.3 Measurement Equipment Used:

Same as 6.3 Radiated Emission Measurement.

7.4 Measurement Results

Refer to attached data chart.

The center frequency **f_c is 310Mhz**, according to the Rules, section 15.231(C), the Bandwidth of Center Frequency at-20dB should be calculated as following:

$$310 \times 0.0025 = 775\text{KHz}$$

So, the Up/Lower frequencies limit should be specified as:

$$f_{(U)} = f_c + \Delta f/2 = 310 + 0.3875 = 310.3875(\text{MHz})$$


$$f_{(L)} = f_c - \Delta f/2 = 310 - 0.3875 = 309.6125 (\text{MHz})$$

Measurement Result:

-20dB bandwidth = 76.7 kHz within allowed frequency range.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

20dB Band Width Test Data



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

8. Duty Cycle Measurement

8.1 Measurement Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Set ETU normal operating mode.
3. Set SPA Center Frequency = fundamental frequency, RBW, VBW= 100KHz, Span =0 Hz. Adjacent sweep.
4. Set SPA View. Mark delta.

8.2 Test SET-UP (Block Diagram of Configuration)

Same as 6.3 Radiated Emission Measurement.

8.3 Measurement Equipment Used:

Same as 6.3 Radiated Emission Measurement.


8.4 Measurement Results:

$$Ton = 0.39(ms)*8 + 1.18(ms)*18 = 24.36(ms)$$


$$Tp = 50.8(ms)$$

$$\begin{aligned} \text{Average Correction Factory} &= 20\log(Ton/Tp) = 20\log(24.36/50.8) \\ &= -6.38 \end{aligned}$$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


Ton Measurement:

Date: 11.AUG.2004 18:20:54




Date: 11.AUG.2004 18:21:35

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Date: 11.AUG.2004 18:25:01

Tp Measurement:



Date: 11.AUG.2004 18:25:47

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Taiwan Ltd. No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei Country, Taiwan. / 台北市五股工業區五工路136號
台灣檢驗科技股份有限公司 | t (886-2) 2298-3939 | f (886-2) 2298-2698 | www.sgs.com.tw

9. Release Time Measurement:

15.231 (a) (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

9.1 Measurement Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Set SPA Center Frequency = fundamental frequency, RBW, VBW= 100KHz, Span =0Hz. Sweep Time= 5s.
3. Set EUT as normal operation and press Transmitter bottom for 2 s,
4. Set SPA Max hold. Delta Mark.

9.2 Test SET-UP (Block Diagram of Configuration)

Same as 6.3 Radiated Emission Measurement.

9.3 Measurement Equipment Used:


Same as 6.3 Radiated Emission Measurement.

9.4 Measurement Results

The release time less than 5 s.

Refer to attached data chart.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.