



# CONFORMANCE TEST REPORT FOR FCC 47 CFR, Part 15 Subpart C

**Report No.: 11-08-MAS-059**

Client: **Micro Alarm System Inc**  
Product: **transmitter**  
Model: **TX-D4A421**  
FCC ID: **JRMTXCR9**  
Manufacturer/supplier: **Micro Alarm System Inc**

Date test item received: **2011/08/08**  
Date test campaign completed: **2011/08/30**  
Date of issue: **2011/08/31**


**The test result only corresponds to the tested sample. It is not permitted to copy this report, in part or in full, without the permission of the test laboratory.**

*Total number of pages of this test report: 21 pages*

*Total number of pages of photos: External photos 1 pages*

*Internal photos 2 pages*

*Setup photos 2 pages*

Test Engineer	Checked By	Approved By
 John Li	 James Cheng	 Joe Hsieh

ELECTRONICS TESTING CENTER, TAIWAN  
NO.8, LANE 29, WENMING RD.,  
LESHAN TSUEN, GUISHAN SHIANG,  
TAOYUAN COUNTY, TAIWAN 33383, R.O.C.

TEL: (03) 3276170~4  
INT: +886-3-3276170~4  
FAX: (03) 3276188  
INT: +886-3-3276188



Client : Micro Alarm System Inc  
Address : 4825 South Soto street Vernon, ca 90058  
Manufacturer : Micro Alarm System Inc  
Address : 4825 South Soto street Vernon, ca 90058  
EUT : transmitter  
Trade name : MICRO  
Model No. : TX-D4A421  
Power Source : DC 6V (Lithium Battery)  
Regulations applied : FCC 47 CFR, Part 15 Subpart C

The testing described in this report has been carried out to the best of our knowledge and ability, and our responsibility is limited to the exercise of reasonable care. This certification is not intended to relieve the sellers from their legal and/or contractual obligations.

The compliance test is only certified for the test equipment and the results of the testing report relate only to the item tested. The compliance test of this report was conducted in accordance with the appropriate standards. It's not intention to assure the quality and performance of the product. This report shall not be reproduced except in full, without the approval of ETC. This report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

Laboratory Introduction: Electronics Testing Center, Taiwan is recognized, filed and mutual recognition arrangement as following:

- ① ISO9001: TÜV Product Service
- ② ISO/IEC 17025: BSMI, CNLA, NCC, NVLAP, CCIBLAC, UL, Compliance
- ③ Filing: FCC, Industry Canada, VCCI
- ④ MRA: Australia, Hong Kong, New Zealand, Singapore, USA, Japan, Korea, China, APLAC through TAF
- ⑤ FCC Registration Number: 90588, 91094, 91095
- ⑥ Industry Canada Site Registration number: IC 2949A



NVLAP Lab Code 200133-0

# Table of Contents

	<i>Page</i>
<b>1. GENERAL INFORMATION .....</b>	<b>4</b>
1.1 PRODUCT DESCRIPTION.....	4
1.2 CHARACTERISTICS OF DEVICE.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY .....	4
<b>2. DEFINITION AND LIMITS .....</b>	<b>5</b>
2.1 DEFINITION .....	5
2.2 RESTRICTED BANDS OF OPERATION .....	5
2.3 LIMITATION.....	6
2.4 LABELING REQUIREMENT.....	7
2.5 USER INFORMATION .....	7
<b>3. RADIATED EMISSION MEASUREMENT .....</b>	<b>8</b>
3.1 APPLICABLE STANDARD.....	8
3.2 MEASUREMENT PROCEDURE.....	8
3.3 TEST DATA.....	10
3.4 FIELD STRENGTH CALCULATION.....	12
3.5 RADIATED TEST EQUIPMENT.....	12
3.6 MEASURING INSTRUMENT SETUP .....	16
<b>4. BANDWIDTH OF EMISSION.....</b>	<b>17</b>
4.1 APPLICABLE STANDARD PLOT GRAPHIC OF BANDWIDTH .....	17
4.2 TEST EQUIPMENT .....	17
4.3 TEST RESULT .....	17
<b>5. CONDUCTED EMISSION MEASUREMENT.....</b>	<b>19</b>
<b>6. LIMIT OF TRANSMISSION TIME .....</b>	<b>20</b>
6.1 APPLICABLE STANDARD .....	20
6.2 TEST EQUIPMENT .....	20
6.3 TEST RESULT .....	20

## 1. GENERAL INFORMATION

### 1.1 Product Description

- a) Type of EUT : transmitter
- b) Model No. : TX-D4A421
- c) Serial No. : ----
- d) FCC ID : JRMTXCR9
- e) Working Frequency : 433.92 MHz

### 1.2 Characteristics of Device:

The EUT is a remote controller operates at 433.92 MHz.

### 1.3 Test Methodology

Both Conducted and radiated testing were performed according to the procedures in chapter 13 of ANSI C63.4 (2003).

The equipment under test was operated continuously in its normal operating mode for the purpose of the measurements. In order to secure the continuous operation of the device under test, the circuit rewired by the manufacturer to affect its intended operation. The receiving antenna was varied from 1 to 4 meters and the wooden turntable was rotated through 360 degrees to obtain the highest reading on the field strength meter or on the display of the spectrum analyzer. And also, each emission was to be maximized by changing the orientation of the equipment transmitter under test.

### 1.4 Test Facility

The semi-anechoic chamber and conducted measurement facility used to collect the radiated and conducted data are located inside the Building at No.8, Lane 29, Wen-ming Road, Lo-shan Tsun, Kweishan Hsiang, Taoyuan, Taiwan, R.O.C.

This site has been accreditation as a FCC filing site.

## 2. DEFINITION AND LIMITS

### 2.1 Definition

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

### 2.2 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.25
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

Remark “\*\*” : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

## 2.3 Limitation

### (1) Conducted Emission Limits :

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the conducted limit is the following:

Frequency MHz	Quasi Peak dB $\mu$ V	Average dB $\mu$ V
0.15 - 0.5	66-56	56-46
0.5 - 5.0	56	46
5.0 - 30.0	60	50

### (2) Radiated Emission Limits :

According to 15.231 (b) , in addition to the provisions of section 15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Frequency Band (MHz)	Field strength of Fundamental (uV/m)	Field strength of Spurious (uV/m)
40.66-40.70	2250	225
70-130	1250	125
130-174	*1,250 to 3,750	*125 to 375
174-260	3750	375
260-470	*3,750 to 12,500	*375 to 1250
Above 470	12500	1250

\* Linear interpolations.

According to 15.231(e) ,Periodic operation in the band 40.66-40.70 MHz and above 70 MHz, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Frequency Band (MHz)	Field strength of Fundamental (uV/m)	Field strength of Spurious (uV/m)
40.66-40.70	1000	100
70-130	500	50
130-174	*500-1500	*50-150
174-260	1500	150
260-470	*1500-5000	*150-500
Above 470	5000	500

\* Linear interpolations.

According to 15.205 (b), the field strength of emissions appearing within the Restricted Bands shield not exceed. The general radiated limits in 15.209, as following table:

Frequency (MHz)	Field Strength μV/meter	Field Strength dBμV/meter	Measurement Distance (meters)
30 - 88	100	40.0	3
88 - 216	150	43.5	3
216 - 960	200	46.0	3
Above 960	500	54.0	3

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

### (3) Limit of transmission time

According to 15.231(a)(1), a manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

According to 15.231(e) , devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

## 2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

## 2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

To comply with the FCC RF exposure compliance requirement, this device and its antenna must not be co-located or operating to conjunction with any other antenna or transmitter.

### 3. RADIATED EMISSION MEASUREMENT

#### 3.1 Applicable Standard

For periodic operation intentional radiator, the radiated emission shall comply with § 15.231(b).

#### 3.2 Measurement Procedure

##### A. Preliminary Measurement For Portable Devices.

For portable devices, the following procedure was performed to determine the maximum emission axis of EUT:

1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

##### B. Final Measurement

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively. Turn on EUT and make sure that it is in continuous operating function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a semi-anechoic chamber to determine the accurate frequencies of higher emissions and then each selected frequency is precisely measured. As the same purpose, for emission measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission measured below and above 1 GHz, set the spectrum analyzer on a 120 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



### 3.3 Test Data

#### 3.3.1 Fundamental and Harmonic of Transmitter

Operated mode : Transmitting

Frequency (MHz)	Ant Pol H/V	Reading (dBuV) @3m		Correct Factor (dB/m)	Duty Factor (dB)	Result (dBuV) @3m			Limit (dBuV/m) @3m			Margin (dB)
		Peak	QP			Peak	QP	AVG	Peak	QP	AVG	
<b>Fundamental</b>												
433.9200	H	59.4	----	19.58	-9.62	79.0	----	69.4	100.8	----	80.8	-11.4
433.9200	V	45.2	----	19.58	-9.62	64.8	----	55.2	100.8	----	80.8	-25.6
<b>Harmonic</b>												
867.8400	H	36.2	----	25.30	-9.62	61.5	----	51.9	80.8	----	60.8	-8.9
867.8400	V	29.5	----	25.30	-9.62	54.8	----	45.2	80.8	----	60.8	-15.6
*1301.7600	H	59.6	----	-13.10	-9.62	46.5	----	36.9	74.0	----	54.0	-17.1
*1301.7600	V	62.6	----	-13.10	-9.62	49.5	----	39.9	74.0	----	54.0	-14.1
1735.6800	H	62.8	----	-10.92	-9.62	51.9	----	42.3	80.8	----	60.8	-18.5
1735.6800	V	60.5	----	-10.92	-9.62	49.6	----	40.0	80.8	----	60.8	-20.8
2169.6000	H	55.8	----	-9.10	-9.62	46.7	----	37.1	80.8	----	60.8	-23.7
2169.6000	V	57.9	----	-9.10	-9.62	48.8	----	39.2	80.8	----	60.8	-21.6
2603.5200	H	----	----	-7.75	-9.62	----	----	----	80.8	----	60.8	----
2603.5200	V	----	----	-7.75	-9.62	----	----	----	80.8	----	60.8	----
3037.4400	H	54.5	----	-6.30	-9.62	48.2	----	38.6	80.8	----	60.8	-22.2
3037.4400	V	61.2	----	-6.30	-9.62	54.9	----	45.3	80.8	----	60.8	-15.5
3471.3600	H	55.0	----	-5.09	-9.62	49.9	----	40.3	80.8	----	60.8	-20.5
3471.3600	V	54.8	----	-5.09	-9.62	49.7	----	40.1	80.8	----	60.8	-20.7
*3905.2800	H	----	----	-3.47	-9.62	----	----	----	74.0	----	54.0	----
*3905.2800	V	----	----	-3.47	-9.62	----	----	----	74.0	----	54.0	----
*4339.2000	H	----	----	-3.17	-9.62	----	----	----	74.0	----	54.0	----
*4339.2000	V	----	----	-3.17	-9.62	----	----	----	74.0	----	54.0	----

**Note:**

1. Peak Result = Peak Reading + Correct Factor
2. AVG Result = Peak Result + Duty Factor
3. If the result of peak value is under the limit of average, the average value doesn't need to be measured.
4. "\*" means the frequency is in the Restricted Bands.

### 3.3.2 Other Emission

### 3.3.2.1 Transmitter

Operated mode : Transmitting Mode

### A. below 1GHz

**File: N**      **Data: #20**      **Date: 2011/8/16**      **Temperature: 28 °C**  
**Time: PM 02:51:53**      **Humidity: 55 %**

**Condition:** EUTY **Polarization:** Horizontal  
**EUT:** EUTY **Distance:** 3m  
**Model:**  
**Test Mode:**

No.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	31.9438	14.05	peak	18.90	32.95	40.00	-7.05
2	37.7755	19.10	peak	15.72	34.82	40.00	-5.18
3	45.5510	19.98	peak	11.75	31.73	40.00	-8.27
4	181.6231	18.05	peak	12.14	30.19	43.50	-13.31
5	201.0620	12.56	peak	15.77	28.33	43.50	-15.17
6	304.0881	14.98	peak	17.59	32.57	46.00	-13.43

**Condition:** **Polarization:** **Vertical**

No.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	30.0000	13.16	peak	19.97	33.13	40.00	-6.87
2	37.7754	17.97	peak	15.72	33.69	40.00	-6.31
3	45.5510	20.58	peak	11.75	32.33	40.00	-7.67
4	152.4650	14.90	peak	13.09	27.99	43.50	-15.51
5	224.3888	17.11	peak	13.93	31.04	46.00	-14.96
6	304.0881	14.46	peak	17.59	32.05	46.00	-13.95

## B. above 1GHz

### Note:

1. Place of Measurement: Measuring site of the ETC.
2. If the data table appeared symbol of "\*\*\*" means the value was too low to be measured.
3. The estimated measurement uncertainty of the result measurement is
  - ±4.6dB (30MHz  $\leq$  f < 300MHz).
  - ±4.4dB (300MHz  $\leq$  f < 1000MHz).
  - ±4.1dB (1GHz  $\leq$  f  $\leq$  18GHz).

### 3.4 Field Strength Calculation

(a) Field Strength:

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$\text{RESULT} = \text{READING} + \text{CORR. FACTOR}$$

where CORR. FACTOR = Antenna FACTOR + Cable FACTOR

(b) Duty Factor:

$$20\log \frac{2.0084 \times 8(\text{ms}) + 0.6833 \times 17(\text{ms})}{83.8(\text{ms})} = -9.62 \text{ dB}$$

The plotted graph of Duty Factor please see page 13 ~ 15.

### 3.5 Radiated Test Equipment


The following instrument are used for radiated emissions measurement :

Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
EMI Receiver	R&S	ESIB7	13054414-001	07/25/2012
BiLog Antenna	Schaffner	CBL 6112B	2927	09/02/2011
Horn Antenna	EMCO	3115	9107-3729	07/21/2012
PRE-Amplifier	Agilent	8449B	3008A01648	10/25/2011
Spectrum Analyzer	R&S	FSU46	13040904-001	11/25/2011
Spectrum Analyzer	Agilent	E4446A	MY48250073	09/26/2011

Note: The standards used to perform this calibration are traceable to NML/ROC, NIST/USA and NPL.

File: N

Data: #48

Date: 2011/8/30  
Time: PM 03:19:05Temperature: 27 °C  
Humidity: 53 %**Condition:**

EUT: EUTY

**RF Conducted**

Sweep Time: 5ms Att.: 0dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note:

No.	Sweep time(ms)	Level(dBm)
1	0.3083	-101.61
2	2.3167	-102.79
3	2.9500	-98.89
4	3.6333	-98.86

No.		ΔTime(ms)	ΔLevel(dB)
1	mk2-mk1	2.0084	-1.18
2	mk4-mk3	0.6833	0.03

File: N


Data: #50

Date: 2011/8/30

Time: PM 03:17:59

Temperature: 27 °C

Humidity: 53 %

**Condition:**

EUT: EUTY

**RF Conducted**

Sweep Time: 120ms Att.: 0dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:


Note:

No.	Sweep time(ms)	Level(dBm)
1	10.0000	-95.91
2	29.8000	-96.68
3	93.8000	-95.82

No.		△Time(ms)	△Level(dB)
1	mk3-mk1	83.8	0.09
2	mk3-mk2	64	0.86

File: N

Data: #45

Date: 2011/8/30  
Time: PM 03:15:11Temperature: 27 °C  
Humidity: 53 %

Condition:

EUT:

EUTY

Model:

Test Mode:

Note:

RF Conducted

Sweep Time: 200ms Att.: 0dB

RBW: 100 KHz VBW: 300 KHz

### 3.6 Measuring Instrument Setup

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution Bandwidth	Video Bandwidth
30 to 1000	EMI Test Receiver	Peak	120 kHz	300 kHz
1000 to 4500	EMI Test Receiver	Peak	1 MHz	1 MHz

## 4. BANDWIDTH OF EMISSION

### 4.1 Applicable Standard Plot Graphic of Bandwidth

Per FCC rule §15.231(c), the permitted emission bandwidth is no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the centre frequency.

### 4.2 Test Equipment

Equipment	Manufacturer	Model No.	Next Cal. Date
Spectrum Analyzer	Agilent	E4446A	09/26/2011

### 4.3 Test Result

Test Date : Aug. 30, 2011Temperature : 27°CHumidity : 53%

Center Frequency	433.8933 MHz
Limit	433.8933 MHz $\times 0.25\% = 1084.7$ kHz
20dB Bandwidth of Emission	490 kHz
Chart	Page 18
Result	PASS

File: N


Data: #58

Date: 2011/8/30

Time: PM 04:51:01

Temperature: 27 °C

Humidity: 53 %

**Condition:**

EUT: EUTY

Model:

Test Mode:

Note:

**RF Conducted**

Sweep Time: 200ms Att.: 0dB

RBW: 100 KHz VBW: 300 KHz

No.	Frequency(MHz)	Level(dBm)
1	433.6433	-52.31
2	433.8933	-31.90
3	434.1333	-52.58

No.	ΔFrequency(MHz)	ΔLevel(dB)
1	mk3-mk1	0.49

## 5. CONDUCTED EMISSION MEASUREMENT

This EUT is excused from investigation of conducted emission, for it is powered by battery only. According to §15.207 (d), measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

specification.

## 6. LIMIT OF TRANSMISSION TIME

### 6.1 Applicable Standard

According to 15.231(a)(1), a manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

### 6.2 Test Equipment

Equipment	Manufacturer	Model No.	Next Cal. Date
Spectrum Analyzer	Agilent	E4446A	09/26/2011

### 6.3 Test Result

Test Date : Aug. 30, 2011

Temperature : 27°C

Humidity : 53%

This transmitter is operated by manual and active time is 0.35 second after being released.

*Note : Please refer to page 21 for chart*

File: N


Data: #54

Date: 2011/8/30

Time: PM 03:52:33

Temperature: 27 °C

Humidity: 53 %



Condition:

RF Conducted

EUT:

EUTY

Sweep Time: 6000ms Att.: 0dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note:

No.	Sweep time(ms)	Level(dBm)
1	500.0000	-93.08
2	850.0000	-92.75

No.	△Time(ms)	△Level(dB)
1	mk2-mk1	350